

E DIN EN 61784-2:2018-02 (E)

Erscheinungsdatum: 2018-01-26

Industrial communication networks - Profiles - Part 2: Additional fieldbus profiles for real-time networks based on ISO/IEC 8802-3 (IEC 65C/863A/CDV:2017); English version prEN 61784-2:2017, only on CD-ROM

CONTENTS

FOREWORD.....	16
INTRODUCTION.....	18
1 Scope.....	19
2 Normative references	19
3 Terms, definitions, abbreviated terms, acronyms, and conventions.....	25
3.1 Terms and definitions.....	25
3.2 Abbreviated terms and acronyms	29
3.3 Symbols.....	31
3.3.1 CPF 2 symbols	31
3.3.2 CPF 3 symbols	32
3.3.3 CPF 4 symbols	33
3.3.4 CPF 6 symbols	33
3.3.5 CPF 10 symbols	34
3.3.6 CPF 11 symbols	34
3.3.7 CPF 12 symbols	35
3.3.8 CPF 13 symbols	35
3.3.9 CPF 14 symbols	36
3.3.10 CPF 15 symbols	36
3.3.11 CPF 16 symbols	37
3.3.12 CPF 17 symbols	37
3.3.13 CPF 18 symbols	38
3.3.14 CPF 20 symbols	39
3.3.15 CPF 21 symbols	40
3.4 Conventions.....	40
3.4.1 Conventions common to all layers	40
3.4.2 Physical layer	42
3.4.3 Data-link layer	42
3.4.4 Application layer.....	43
4 Conformance to communication profiles	43
5 RTE performance indicators	44
5.1 Basic principles of performance indicators	44
5.2 Application requirements.....	45
5.3 Performance indicators	45
5.3.1 Delivery time	45
5.3.2 Number of RTE end-stations.....	46
5.3.3 Basic network topology	46
5.3.4 Number of switches between RTE end-stations	46
5.3.5 Throughput RTE	46
5.3.6 Non-RTE bandwidth.....	46
5.3.7 Time synchronization accuracy.....	47
5.3.8 Non-time-based synchronization accuracy	47
5.3.9 Redundancy recovery time	47
6 Conformance tests	47
6.1 Concept.....	47
6.2 Methodology	48

6.3	Test conditions and test cases	48
6.4	Test procedure and measuring	48
6.5	Test report	49
7	Communication Profile Family 2 (CIP™) – RTE communication profiles	50
7.1	General overview	50
7.2	Profile 2/2	50
7.2.1	Physical layer	50
7.2.2	Data-link layer	50
7.2.3	Application layer	50
7.2.4	Performance indicator selection	50
7.3	Profile 2/2.1	54
7.3.1	Physical layer	54
7.3.2	Data-link layer	54
7.3.3	Application layer	56
7.3.4	Performance indicator selection	58
8	Communication Profile Family 3 (PROFIBUS & PROFINET) - RTE communication profiles	60
8.1	General overview	60
8.1.1	CPF 3 overview	60
8.1.2	Administrative numbers	60
8.1.3	Node Classes	61
8.1.4	Protocol and timing parameters	63
8.1.5	Communication classes	69
8.1.6	Media redundancy classes	72
8.1.7	Media classes	73
8.1.8	Application classes	73
8.1.9	Records	78
8.1.10	Communication feature list	86
8.1.11	Conformance class behaviors	86
8.2	Profile 3/4	93
8.2.1	Physical layer	93
8.2.2	Data link layer	93
8.2.3	Application layer	94
8.2.4	Performance indicator selection	100
8.3	Profile 3/5	107
8.3.1	Physical layer	107
8.3.2	Data link layer	107
8.3.3	Application layer	107
8.3.4	Performance indicator selection	113
8.4	Profile 3/6	114
8.4.1	Physical layer	114
8.4.2	Data link layer	114
8.4.3	Application layer	115
8.4.4	Performance indicator selection	120
9	Communication Profile Family 4 (P-NET) – RTE communication profiles	124
9.1	General overview	124
9.2	Profile 4/3, P-NET on IP	124
9.2.1	Physical layer	124
9.2.2	Data-link layer	124

9.2.3	Application layer	125
9.2.4	Performance indicator selection	126
10	Communication Profile Family 6 (INTERBUS®) – RTE communication profiles	130
10.1	General overview	130
10.2	Profile 6/4	131
10.2.1	Mapping	131
10.2.2	Type 10 service and protocol selection	132
10.2.3	Type 8 service and protocol selection	133
10.2.4	Performance indicator selection	133
10.3	Profile 6/5	134
10.3.1	Mapping	134
10.3.2	Type 10 service and protocol selection	134
10.3.3	Type 8 service and protocol selection	135
10.3.4	Performance indicator selection	135
10.4	Profile 6/6	135
10.4.1	Mapping	135
10.4.2	Type 10 service and protocol selection	135
10.4.3	Type 8 service and protocol selection	136
10.4.4	Performance indicator selection	136
11	Communication Profile Family 10 (Vnet/IP) – RTE communication profiles	137
11.1	General overview	137
11.2	Profile 10/1	138
11.2.1	Physical layer	138
11.2.2	Data link layer	138
11.2.3	Application layer	141
11.2.4	Performance indicator selection	141
12	Communication Profile Family 11 (TCnet) – RTE communication profiles	146
12.1	General overview	146
12.2	Profile 11/1	147
12.2.1	Physical layer	147
12.2.2	Data-link layer	147
12.2.3	Application layer	151
12.2.4	Performance indicator selection	151
12.3	Profile 11/2	157
12.3.1	Physical layer	157
12.3.2	Data-link layer	157
12.3.3	Application layer	161
12.3.4	Performance indicator selection	161
12.4	Profile 11/3	166
12.4.1	Physical layer	166
12.4.2	Data-link layer	166
12.4.3	Application layer	169
12.4.4	Performance indicator selection	170
13	Communication Profile Family 12 (EtherCAT®) – RTE communication profiles	176
13.1	General overview	176
13.2	Profile CP 12/1	176
13.2.1	Physical layer	176
13.2.2	Data-link layer	177

13.2.3	Application layer	181
13.2.4	Performance indicator selection	183
13.3	Profile CP 12/2	186
13.3.1	Physical layer	186
13.3.2	Data-link layer	186
13.3.3	Application layer	189
13.3.4	Performance indicator selection	192
14	Communication Profile Family 13 (Ethernet POWERLINK) – RTE communication profiles	194
14.1	General overview	194
14.2	Profile 13/1	194
14.2.1	Physical layer	194
14.2.2	Data-link layer	195
14.2.3	Application layer	195
14.2.4	Performance indicator selection	195
15	Communication Profile Family 14 (EPA)- RTE communication profiles	200
15.1	General overview	200
15.2	CPF 14 (EPA) communication concept	201
15.2.1	General	201
15.2.2	Network Topology	201
15.2.3	EPA devices	202
15.3	Profile 14/1	203
15.3.1	Physical layer	203
15.3.2	Data-link layer	203
15.3.3	Network Layer	203
15.3.4	Transport Layer	203
15.3.5	Application layer	203
15.3.6	Performance indicator selection	204
15.4	Profile 14/2	207
15.4.1	Physical layer	207
15.4.2	Data-link layer	207
15.4.3	Network Layer	208
15.4.4	Transport Layer	208
15.4.5	Application layer	208
15.4.6	Performance indicator selection	209
15.5	Profile 14/3	212
15.5.1	Physical layer	212
15.5.2	Data-link layer	212
15.5.3	Network Layer	213
15.5.4	Transport Layer	213
15.5.5	Application layer	213
15.5.6	Performance indicator selection	214
15.6	Profile 14/4	217
15.6.1	Physical layer	217
15.6.2	Data-link layer	217
15.6.3	Network layer	218
15.6.4	Transport layer	219
15.6.5	Application layer	219
15.6.6	Performance indicator selection	220

16	Communication Profile Family 15 (MODBUS-RTPS) – RTE communication profiles.....	222
16.1	General overview	222
16.2	Profile 15/1	223
16.2.1	Physical layer	223
16.2.2	Data-link layer	223
16.2.3	Application layer.....	223
16.2.4	Performance indicator selection.....	223
16.3	Profile 15/2	227
16.3.1	Physical layer	227
16.3.2	Data-link layer	227
16.3.3	Application layer.....	227
16.3.4	Performance indicator selection.....	228
17	Communication Profile Family 16 (SERCOS)- RTE communication profiles	232
17.1	General overview	232
17.2	Profile 16/3 (SERCOS III)	232
17.2.1	Physical layer	232
17.2.2	Data-link layer	233
17.2.3	Application layer.....	233
17.2.4	Performance indicator selection.....	234
18	Communication Profile Family 17 (RAPIEnet) – RTE communication profiles.....	240
18.1	General overview	240
18.2	Profile 17/1	240
18.2.1	Physical layer	240
18.2.2	Datalink layer	240
18.2.3	Application layer.....	241
18.2.4	Performance indicator selection.....	242
19	Communication Profile Family 18 (SafetyNET p) – RTE communication profiles	246
19.1	General overview	246
19.2	Profile 18/1	246
19.2.1	Physical layer	246
19.2.2	Data link layer	246
19.2.3	Application layer.....	249
19.2.4	Performance indicator selection.....	250
19.3	Profile 18/2	253
19.3.1	Physical layer	253
19.3.2	Data link layer	253
19.3.3	Application layer.....	255
19.3.4	Performance indicator selection.....	257
20	Communication Profile Family 8 (CC-Link) – RTE communication profiles	259
20.1	General overview	259
20.2	Profile 8/4	259
20.2.1	Physical layer	259
20.2.2	Data link layer	259
20.2.3	Application layer.....	260
20.2.4	Performance indicator selection.....	261
20.3	Profile 8/5	266
20.3.1	Physical layer	266
20.3.2	Data link layer	266

20.3.3	Application layer	266
20.3.4	Performance indicator selection	267
21	Communication Profile Family 20 (ADS-net) - RTE communication profiles	272
21.1	General overview	272
21.2	Profile 20/1	273
21.2.1	Physical layer	273
21.2.2	Data link layer	273
21.2.3	Application layer	273
21.2.4	Performance indicator selection	274
21.3	Profile 20/2	278
21.3.1	Physical layer	278
21.3.2	Data link layer	278
21.3.3	Application layer	278
21.3.4	Performance indicator selection	279
22	Communication Profile Family 21 (FL-net) - RTE communication profiles	283
22.1	General overview	283
22.2	Profile 21/1	283
22.2.1	Physical layer	283
22.2.2	Data-link layer	283
22.2.3	Application layer	286
22.2.4	Performance indicator selection	290
Annex A	(informative) Performance Indicator calculation	297
A.1	CPF 2 (CIP) – Performance indicator calculation	297
A.1.1	Profile 2/2 EtherNet/IP	297
A.1.2	Profile 2/2.1 EtherNet/IP with Time Synchronization	298
A.2	CPF 3 – PROFINET – Performance indicator calculation	299
A.2.1	Application Scenario	299
A.2.2	Structural examples used for calculation	299
A.2.3	Principles used for calculation	308
A.3	CPF 4/3 P-NET on IP – Performance indicator calculation	311
A.3.1	Application scenario	311
A.3.2	Delivery time calculation	311
A.3.3	Non-RTE throughput calculation	312
A.3.4	Non time-base synchronization accuracy	313
A.3.5	RTE throughput calculation	314
A.3.6	CPF 4/3, Derivation of delivery time formula	315
A.3.7	CPF 4/3, Ethernet characteristics	316
A.4	CPF 20 – Performance indicator calculation	317
A.4.1	Profile 20/1	317
A.4.2	Profile 20/2	318
Bibliography		320
Figure 1	– Example of graphical representation of consistent indicators	45
Figure 2	– Conformance test overview	47
Table 55	– Application class “isochronous application” AL protocol selection component	75
Table 57	– Application class “process automation” AL protocol selection component	76
Table 74	– Communication feature list	86

Table 75 – Conformance class behaviors.....	87
Table 84 – Conformance class behaviors for network components.....	91
Figure 3 – Example of network topology using CP 3/4, CP 3/5, and CP 3/6 components.....	93
Figure 4 – Example of network topology with wireless segment	96
Table 89 – CP 3/4: Additional AL protocol selection for an IO controller.....	96
Table 90 – CP 3/4: AL protocol selection for an IO device and Network component	97
Table 92 – CP 3/4, CP 3/5 and CP 3/6: performance indicator overview	101
Figure 5 – Calculation basis for delivery time and throughput RTE.....	103
Table 99 – CP 3/5: Additional AL protocol selection for an IO controller.....	109
Table 100 – CP 3/5: AL protocol selection for an IO device and Network component	109
Table 105 – CP 3/6: Additional AL protocol selection for an IO controller.....	116
Figure 6 – Linking-device communication profiles RTE-network context.....	130
Figure 7 – Linking-device mapping principle	131
Figure 8 – Data Mapping.....	132
Figure 9 – CP 11/1: Throughput RTE and non-RTE bandwidth.....	154
Figure 10 – CP 11/2: Throughput RTE and non-RTE bandwidth.....	164
Figure 11 – CP 11/3: Throughput RTE and non-RTE bandwidth.....	173
Figure 12 – EPA system network topology example	202
Figure 13 – Protocol stack for Type 26 fieldbus	284
Figure A.1 – CP 3/4: Example of line structure.....	299
Figure A.2 – CP 3/4: Example of ring structure	300
Figure A.3 – CP 3/4: Example of a wireless segment	300
Figure A.4 – CP 3/4: Example of an integrated wireless client.....	301
Figure A.5 – CP 3/5: Example of line structure.....	301
Figure A.6 – CP 3/5: Example of ring structure	302
Figure A.7 – CP 3/6: Example of line structure.....	303
Figure A.8 – CP 3/6: Example of line structure.....	304
Figure A.9 – CP 3/6: Example of ring structure	305
Figure A.10 – CP 3/6: Example of tree structure	306
Figure A.11 – CP 3/6: Example of comb structure	307
Figure A.12 – CP 3/6: Example of comb structure (optional)	308
Figure A.13 – Definition of bridge delay	309
Figure A.14 – Example of a switch structure	310
Figure A.15 – Application configuration.....	311
Figure A.16 – Non-RTE throughput calculation	313
Figure A.17 – Non time-base synchronization accuracy	313
Table 1 – Layout of profile (sub)clause selection tables	40
Table 2 – Contents of (sub)clause selection tables	41
Table 3 – Layout of service selection tables.....	41
Table 4 – Contents of service selection tables	42
Table 5 – Layout of parameter selection tables	42
Table 6 – Contents of parameter selection tables	42

Table 7 – Layout of class attribute selection tables	43
Table 8 – Contents of class attribute selection tables.....	43
Table 9 – Basic network topology types	46
Table 10 – CP 2/2: PI overview.....	51
Table 11 – CP 2/2: PI dependency matrix	51
Table 12 – CP 2/2: Consistent set of PIs for factory automation	54
Table 13 – CP 2/2.1: DLL protocol selection	55
Table 14 – CP 2/2.1: DLL protocol selection of management objects	55
Table 15 – CP 2/2.1: AL service selection.....	56
Table 16 – CP 2/2.1: AL protocol selection	57
Table 17 – CP 2/2.1: PI overview.....	58
Table 18 – CP 2/2.1: PI dependency matrix	59
Table 19 – CP 2/2.1: Consistent set of PIs for motion control.....	59
Table 20 – Administrative numbers assignment	60
Table 21 – Maximum diagnosis data for one submodule	61
Table 22 – Maximum storage delay.....	62
Table 23 – Reporting system minimum storage size.....	62
Table 24 – Reporting system storage.....	62
Table 25 – IP layer parameters for IO controller.....	63
Table 26 – IP layer parameters for IO device	63
Table 27 – Timeout values for name resolution.....	63
Table 28 – Reaction time for an IO device	64
Table 29 – Maximum time values for MRP	65
Table 30 – Maximum packet size for MRP	65
Table 31 – Maximum time values for PTCP.....	65
Table 32 – Precision of timers used for PTCP.....	66
Table 33 – Maximum deviation values for time synchronization.....	66
Table 34 – Maximum time values for LLDP	66
Table 35 – Required RPC resources	67
Table 36 – Data Hold Time deviation	67
Table 37 – RTA Timeout deviation	68
Table 38 – Number of LogBookData entries.....	68
Table 39 – Community string	68
Table 40 – SNMP timeout values	68
Table 41 – DHCP client	69
Table 42 – Communication classes applicable in conformance classes.....	69
Table 43 – Communication performance parameters	70
Table 44 – Parameters for RT_CLASS_3 bridges.....	70
Table 45 – FrameSendOffset deviation	71
Table 46 – FrameSendOffset deviation for RT_CLASS_1 / RT_CLASS_UDP.....	71
Table 47 – Minimum FrameSendOffset	71
Table 48 – PTCP control loop	72
Table 49 – Maximum frame size	72

Table 50 – Media redundancy class applicable in conformance classes	73
Table 51 – Media redundancy startup mode.....	73
Table 52 – Application classes applicable in conformance classes for IO device and IO controller	74
Table 53 – Application classes applicable in conformance classes for network components	74
Table 54 – Application class “isochronous application” AL service selection	74
Table 56 – Application class “process automation” AL service selection.....	75
Table 58 – Application class “High performance” features supported	76
Table 59 – Application class “High performance” parameter values.....	76
Table 60 – Application class “Controller to Controller” features supported.....	77
Table 61 – Application class “Functional safety” features supported by IO device	77
Table 62 – Application class “Functional safety” features supported by IO controller.....	77
Table 63 – Application class “Energy saving” AL service selection	78
Table 64 – Application class “Energy saving” features supported by IO device	78
Table 65 – Application class “Energy saving” features supported by IO controller	78
Table 66 – Index (user specific)	78
Table 67 – Index (subslot specific).....	79
Table 68 – Index (slot specific)	81
Table 69 – Index (AR specific)	82
Table 70 – Index (API specific)	83
Table 71 – Index (device specific).....	84
Table 72 – PDPortDataAdjust (sub blocks)	85
Table 73 – PDPortDataCheck (sub blocks)	85
Table 76 – IETF RFC 1213-MIB (MIB-2) objects	88
Table 77 – LLDP-MIB objects – range 1	89
Table 78 – LLDP-MIB objects – range 2.....	89
Table 79 – LLDP-MIB objects – range 3.....	89
Table 80 – LLDP-EXT-PNO-MIB objects – range 1	90
Table 81 – LLDP-EXT-PNO-MIB objects – range 2	90
Table 82 – LLDP-EXT-DOT3-MIB objects – range 1.....	90
Table 83 – LLDP-EXT-DOT3-MIB objects – range 2.....	90
Table 85 – Buffering capacity @ 100 Mbit/s	92
Table 86 – Buffering capacity for less than eight ports @ 100 Mbit/s.....	92
Table 87 – Buffering capacity for eight and more ports @ 100 Mbit/s	93
Table 88 – CP 3/4: AL service selection for an IO device	94
Table 91 – CP 3/4: AL protocol selection for an IO controller	99
Table 93 – CP 3/4, CP 3/5 and CP 3/6: performance indicator dependency matrix.....	101
Table 94 – Manager parameters	104
Table 95 – Client parameters	105
Table 96 – CP 3/4: Consistent set of PI for MinDeviceInterval=128 ms	106
Table 97 – CP 3/4: Assumed values for consistent set of PI calculation	106
Table 98 – CP 3/5: AL service selection for an IO device	107
Table 101 – CP 3/5: AL protocol selection for an IO controller	111

Table 102 – CP 3/5: Consistent set of PI for MinDeviceInterval=128 ms	113
Table 103 – CP 3/5: Assumed values for consistent set of PI calculation	114
Table 104 – CP 3/6: AL service selection for an IO device	115
Table 106 – CP 3/6: AL protocol selection for an IO device and network component.....	117
Table 107 – CP 3/6: AL protocol selection for an IO controller	118
Table 108 – CP 3/6: Consistent set of PI for MinDeviceInterval=1 ms and NumberOfSwitches=20	120
Table 109 – CP 3/6: Consistent set of PI for MinDeviceInterval=1 ms and NumberOfSwitches=63	121
Table 110 – CP 3/6: Assumed values for consistent set of PI calculation	121
Table 111 – CP 3/6: Consistent set of PI for MinDeviceInterval=31.25 μ s and NumberOfSwitches=10	122
Table 112 – CP 3/6: Assumed values for consistent set of PI calculation	123
Table 113 – CP 4/3: DLL service selection.....	124
Table 114 – CP 4/3: DLL protocol selection	125
Table 115 – CP 4/3: AL service selection.....	125
Table 116 – CP 4/3: AL protocol selection	125
Table 117 – CP 4/3: PI overview	126
Table 118 – CP 4/3: PI dependency matrix	126
Table 119 – CP 4/3: Consistent set of PIs.....	129
Table 120 – Parameters for calculation of consistent set of PIs.....	129
Table 121 – CPF 6: device CP identifier assignment.....	131
Table 122 – Linking-device Type 10 network PI overview.....	133
Table 123 – OSI layers and CPF 10 layers	137
Table 124 – Overview of CPF 10 profile.....	138
Table 125 – CP 10/1: DLL service selection.....	139
Table 126 – CP 10/1: DLL protocol selection	139
Table 127 – Transport Layer Parameter selection	140
Table 128 – CP 10/1: AL service selection.....	141
Table 129 – CP 10/1: AL protocol selection	141
Table 130 – CP 10/1: PI overview	142
Table 131 – CP 10/1: PI dependency matrix	142
Table 132 – CP 10/1: Consistent set of PIs for the communication between two end-stations belonging to the same domain	145
Table 133 – CP 10/1: Consistent set of PIs for the communication between two end-stations belonging to different domains	145
Table 134 – CP 10/1: Consistent set of PIs for the communication between two end- stations belonging to the same domain with one lost frame	146
Table 135 – CP 10/1: Consistent set of PIs for the communication between two end-stations belonging to different domains with one lost frame.....	146
Table 136 – CPF 11: Overview of profile sets	147
Table 137 – CP 11/1: DLL service selection.....	147
Table 138 – CP 11/1: DLL protocol selection	148
Table 139 – CP 11/1: DLL protocol selection of Clause 5.....	149
Table 140 – CP 11/1: DLL protocol selection of Clause 6.....	149

Table 141 – CP 11/1: AL service selection	151
Table 142 – CP 11/1: AL protocol selection	151
Table 143 – CP 11/1: PI overview	152
Table 144 – CP 11/1: PI dependency matrix	152
Table 145 – CP 11/1: TCC data service selection	153
Table 146 – CP 11/1: Consistent set of PIs preferential for RTE communications	156
Table 147 – CP 11/1: Consistent set of PIs both for RTE and non-RTE communications.....	157
Table 148 – CP 11/2: DLL protocol selection	157
Table 149 – CP 11/2: DLL protocol selection of Clause 5.....	159
Table 150 – CP 11/2: DLL protocol selection of Clause 6.....	159
Table 151 – CP 11/2: PI overview	161
Table 152 – CP 11/2: PI dependency matrix	162
Table 153 – CP 11/2: TCC data service selection	162
Table 154 – CP 11/2: Consistent set of PIs preferential for RTE communications	165
Table 155 – CP 11/2: Consistent set of PIs both for RTE and non-RTE communications.....	166
Table 156 – CP 11/3: DLL protocol selection	166
Table 157 – CP 11/3: DLL protocol selection of Clause 5.....	167
Table 158 – CP 11/3: DLL protocol selection of Clause 6.....	168
Table 159 – CP 11/3: PI overview	170
Table 160 – CP 11/3: PI dependency matrix	171
Table 161 – CP 11/3: TCC data service selection	171
Table 162 – CP 11/3: Consistent set of PIs preferential for RTE communications	175
Table 163 – CP 11/3: Consistent set of PIs both for RTE and non-RTE communications.....	175
Table 164 – CP 12/1: PhL selection of preferred physical layer from IEEE 802.3-2008	176
Table 165 – CP 12/1: PhL selection of an optimized physical layer from IEC 61158-2.....	177
Table 166 – CP 12/1: DLL service selection.....	178
Table 167 – CP 12/1: DLL protocol selection	178
Table 168 – CP 12/1: DLL service selection.....	180
Table 169 – CP 12/1: DLL protocol selection	180
Table 170 – CP 12/1: AL service selection.....	181
Table 171 – CP 12/1: AL protocol selection	182
Table 172 – CP 12/1: AL service selection.....	182
Table 173 – CP 12/1: AL protocol selection	183
Table 174 – CP 12/1: PI overview	183
Table 175 – CP 12/1: PI dependency matrix	184
Table 176 – CP 12/1: PI ranges	184
Table 177 – CP 12/1: Consistent set of PIs for mid size automation systems	186
Table 178 – CP 12/2: DLL service selection.....	186
Table 179 – CP 12/2: DLL protocol selection	187
Table 180 – CP 12/2: DLL service selection.....	188
Table 181 – CP 12/2: DLL protocol selection	188
Table 182 – CP 12/2: AL service selection.....	190
Table 183 – CP 12/2: AL protocol selection	190

Table 184 – CP 12/2: AL service selection	191
Table 185 – CP 12/2: AL protocol selection	192
Table 186 – CP 12/2: PI overview	192
Table 187 – CP 12/2: PI dependency matrix	193
Table 188 – CP 12/2: Consistent set of PIs	194
Table 189 – CPF 13: Overview of profile sets	194
Table 190 – CP 13/1: DLL service selection	195
Table 191 – CP 13/1: DLL protocol selection	195
Table 192 – CP 13/1: AL service selection	195
Table 193 – CP 13/1: AL protocol selection	195
Table 194 – CP 13/1: PI overview	196
Table 195 – CP 13/1: PI dependency matrix	196
Table 196 – CP 13/1: Consistent set of PIs small size automation system	199
Table 197 – CP 13/1: Consistent set of PIs medium size automation system	199
Table 198 – CP 13/1: Consistent set of PIs large size automation system	200
Table 199 – CP 14/1: AL service selection	203
Table 200 – CP 14/1: AL protocol selection	204
Table 201 – CP 14/1: PI overview	204
Table 202 – CP 14/1: PI dependency matrix	205
Table 203 – CP 14/1: Consistent set of PIs	207
Table 204 – CP 14/2: DLL service selection	207
Table 205 – CP 14/2: DLL protocol selection	208
Table 206 – CP 14/2: AL service selection	208
Table 207 – CP 14/2: AL protocol selection	209
Table 208 – CP 14/2: PI overview	209
Table 209 – CP 14/2: PI dependency matrix	210
Table 210 – CP 14/2: Consistent set of PIs	211
Table 211 – CP 14/3: DLL service selection	212
Table 212 – CP 14/3: DLL protocol selection	212
Table 213 – CP 14/3: AL service selection	213
Table 214 – CP 14/3: AL protocol selection	213
Table 215 – CP 14/3: PI overview	214
Table 216 – CP 14/3: PI dependency matrix	214
Table 217 – CP 14/3: Consistent set of PIs	216
Table 218 – CP 14/3: Consistent set of PIs	217
Table 219 – CP 14/3: Consistent set of PIs	217
Table 220 – CP 14/4: DLL service selection	218
Table 221 – CP 14/4: DLL protocol selection	218
Table 222 – CP 14/4: AL service selection	219
Table 223 – CP 14/4: AL protocol selection	219
Table 224 – CP 14/4: PI overview	220
Table 225 – CP 14/4: PI dependency matrix	220
Table 226 – CP 14/4: Consistent set of PIs	222

Table 227 – CP 15/1: AL service selection	223
Table 228 – CP 15/1: AL protocol selection	223
Table 229 – CP 15/1: PI overview	224
Table 230 – CP 15/1: PI dependency matrix	224
Table 231 – CP 15/2: AL service selection	228
Table 232 – CP 15/2: AL protocol selection	228
Table 233 – CP 15/2: PI overview	228
Table 234 – CP 15/2: PI dependency matrix	229
Table 235 – CP 16/3: DLL service selection	233
Table 236 – CP 16/3: DLL protocol selection	233
Table 237 – CP 16/3: AL service selection	233
Table 238 – CP 16/3: AL protocol selection	233
Table 239 – CP 16/3: PI overview	234
Table 240 – CP 16/3: PI dependency matrix	234
Table 241 – CP 16/3: Consistent set of PIs with a minimum cycle time of 31,25 μ s	238
Table 242 – CP 16/3: Consistent set of PIs with a cycle time of 500 μ s (real-time only)	238
Table 243 – CP 16/3: Consistent set of PIs with a cycle time of 500 μ s (real-time and non-real-time)	239
Table 244 – CP 16/3: Consistent set of PIs with non symmetrical data throughput and a cycle time of 500 μ s (real-time and non-real-time)	239
Table 245 – CPF 17: Overview of profile sets	240
Table 246 – CP 17/1: DLL service selection	240
Table 247 – CP 17/1: DLL protocol selection	241
Table 248 – CP 17/1: AL service selection	241
Table 249 – CP 17/1: AL protocol selection	241
Table 250 – CP 17/1: PI overview	242
Table 251 – CP 17/1: PI dependency matrix	242
Table 252 – Consistent set of PIs small size automation system	245
Table 253 – Parameters for Calculation of Consistent set of PIs	245
Table 254 – CP 18/1: DLL service selection	246
Table 255 – CP 18/1: DLL protocol selection	248
Table 256 – CP 18/1: AL service selection	249
Table 257 – CP 18/1: AL protocol selection	250
Table 258 – CP 18/1: PI overview	250
Table 259 – CP 18/1: PI dependency matrix	251
Table 260 – CP 18/2: DLL service selection	253
Table 261 – CP 18/2: DLL protocol selection	254
Table 262 – CP 18/2: AL service selection	256
Table 263 – CP 18/2: AL protocol selection	257
Table 264 – CP 18/2: PI overview	257
Table 265 – CP 18/2: PI dependency matrix	258
Table 266 – CP 8/4: AL service selection	260
Table 267 – CP 8/4: AL protocol selection	261
Table 268 – CP 8/4: PI overview	261

Table 269 – CP 8/4: PI dependency matrix	262
Table 270 – CP 8/4: Consistent set of PIs (real-time only)	265
Table 271 – CP 8/4: Consistent set of PIs (real-time and non-real-time)	266
Table 272 – CP 8/5: AL service selection	266
Table 273 – CP 8/5: AL protocol selection	267
Table 274 – CP 8/5: PI overview	267
Table 275 – CP 8/5: PI dependency matrix	268
Table 276 – CP 8/5: Consistent set of PIs (real-time only)	272
Table 277 – CP 8/5: Consistent set of PIs (real-time and non-real-time)	272
Table 278 – CP 20/1: DLL service selection	273
Table 279 – CP 20/1: DLL protocol selection	273
Table 280 – CP 20/1: AL service selection	273
Table 281 – CP 20/1: AL protocol selection	274
Table 282 – CP 20/1: performance indicator overview	275
Table 283 – CP 20/1: Performance indicator dependency matrix	275
Table 284 – VLAN priority mapping of CP20/1 network	276
Table 285 – CP 20/1: Consistent set of performance indicators	278
Table 286 – CP 20/2: AL service selection	278
Table 287 – CP 20/2: AL protocol selection	279
Table 288 – CP 20/2: Performance indicator overview	279
Table 289 – CP 20/2: Performance indicator dependency matrix	280
Table 290 – CP 20/2: Consistent set of performance indicators	282
Table 291 – CPF 21: Overview of profile sets	283
Table 292 – DL-layer protocol / service suite selection	285
Table 293 – Data transmission service selection	285
Table 294 – Port number selection	286
Table 295 – IP address selection	286
Table 296 – CP 21/1: AL service selection	287
Table 297 – Service selection of subcluse 6.5.4 and 6.5.6	288
Table 298 – CP 21/1: AL protocol selection	289
Table 299 – Protocol selection of subclause 5.2	290
Table 300 – CP 21/1: Performance indicator overview	291
Table 301 – CP 21/1: Performance indicator dependency matrix	291
Table 302 – CP 21/1: Consistent set of PIs	296