ISO/IEC 14165-251:2008-01 (E)

Information technology_- Fibre Channel_- Part_251: Framing and Signaling (FC-FS)

Contents

FOREWORD - 37
INTRODUCTION - 40

1 Scope - 41
2 Normative references - 41
2.1 Approved references - 41
2.2 References under development - 41
2.3 Other references - 41
3 Definitions, abbreviations, conventions and keywords - 43
3.1 Definitions - 43
3.2 Editorial conventions - 50
3.3 Abbreviations, acronyms and symbols - 51
3.3.1 Data rate abbreviations - 51
3.3.2 Acronyms and other abbreviations - 51
3.3.3 Symbols - 55
3.4 Keywords - 55

4 Structure and Concepts - 57
4.1 Introduction - 57
4.2 FC-1 general description - 58
4.3 FC-2 general description - 59
4.4 FC-FS physical model - 60
4.5 Communication models - 60
4.5.1 Introduction - 60
4.5.2 Hunt Group - 61
4.5.3 Fractional bandwidth - 62
4.6 Bandwidth - 62
4.7 Topology - 62
4.7.1 Types - 62
4.7.2 Point-to-point topology - 62
4.7.3 Fabric topology - 62
4.7.4 Arbitrated Loop topology - 63
4.8 Classes of service - 63
4.8.1 General - 63
4.8.2 Class 1 service - dedicated connection - 64
4.8.3 Class 2 service - multiplex - 64
4.8.4 Class 3 service - datagram - 64
4.8.5 Class 4 service – fractional bandwidth - 65
4.8.6 Class 6 – multicast connection - 65
4.9 Intermixing other classes with Class 1 or Class 6 - 65
4.10 General Fabric model - 66
4.10.1 General - 66
4.10.2 Fabric Ports (F_Ports) - 66
4.10.3 Connection Service - 68
4.10.4 Connectionless Service - 68
4.11 Fibre Channel services - 69
4.12 Building Blocks - 69
4.12.1 Building block hierarchy - 69
4.12.2 Frame - 70
4.12.3 Sequence - 70
4.12.3.1 Introduction - 70
4.12.3.2 Sequence_Identifier (SEQ_ID) - 70
4.12.3.3 Sequence Status Blocks - 70
4.12.4 Exchange - 71
4.12.4.1 Introduction - 71

4.12.4.2 Exchange_Identifiers (OX_ID and RX_ID) - - - 71
4.12.4.3 Association_Header - - - 71
4.12.4.4 Exchange Status Blocks - - - 71
4.12.5 Exchange of service parameters - - - 71
4.13 Segmentation and reassembly - - - 72
4.13.1 General - - - 72
4.13.2 Application data mapping - - - 72
4.13.3 Relative offset - - - 72
4.13.4 Sending end mapping - - - 72
4.13.5 Capability - - - 72
4.13.6 FC-2 mapping - - - 73
4.13.7 Segmentation - - - 73
4.13.8 Reassembly - - - 73
4.14 Error detection and recovery - - - 73

5 FC-1 8B/10B transmission code - - - 74
5.1 Introduction - - - 74
5.2 Notation conventions - - - 74
5.3 Character encoding and decoding - - - 75
5.3.1 Introduction - - - 75
5.3.2 Transmission order - - - 75
5.3.3 Valid and invalid Transmission Characters - - - 75
5.3.3.1 Definitions - - - 75
5.3.3.2 Generating Transmission Characters - - - 81
5.3.3.3 Validity of received Transmission Characters - - - 81
5.4 Word encoding and decoding - - - 82
5.5 Ordered Sets - - - 82
5.5.1 General - - - 82
5.5.2 Frame delimiters - - - 83
5.5.3 Primitive Signals - - - 83
5.5.3.1 Introduction - - - 83
5.5.3.2 Idle - - - 83
5.5.3.3 Receiver_Ready (R_RDY) - - - 83
5.5.3.4 Virtual Circuit Ready (VC_RDY) - - - 85
5.5.3.5 BB_SCs - - - 85
5.5.3.6 BB_SCr - - - 86
5.5.3.7 SYNx, SYNy, SYNz - - - 86
5.5.3.8 ARByx, ARB(val)See [2] - - - 86
5.5.3.9 CLS - - - 86
5.5.3.10 DHD - - - 86
5.5.3.11 MRKtx - - - 86
5.5.3.12 OPNyx - - - 86
5.5.3.13 OPNyy - - - 86
5.5.3.14 OPNyr - - - 86
5.5.3.15 DHD - - - 86
5.5.4 Primitive Sequences - - - 86
5.5.4.1 Introduction - - - 86
5.5.4.2 Not_Operational (NOS) - - - 87

6 FC-1 Receiver and Transmitter State Diagrams - - - 88
6.1 Receiver - - - 88
6.1.1 Introduction - - - 88
6.1.2 State Diagram Overview - - - 88
6.1.3 Operational and Not Operational conditions - - - 88
6.1.4 Word Synchronization Procedure - - - 89
6.1.4.1 Bit Synchronization - - - 89
6.1.4.2 Transmission Word synchronization - - - 90
6.1.4.2.1 Introduction - - - 90

6.1.4.2.2 Achieving Word Synchronization - 90
6.1.4.2.3 Word alignment methods - 90
6.1.4.2.3.1 Continuous-mode alignment - 90
6.1.4.2.3.2 Explicit-mode alignment - 90
6.1.5 Loss of Word Synchronization - 90
6.1.5.1 Introduction - 90
6.1.5.2 Detection of loss of Signal - 91
6.1.5.3 Detection of an invalid Transmission Word - 91
6.1.6 State transitions - 91
6.1.6.1 Default State - 91
6.1.6.2 State A (Loss of Synchronization) - 91
6.1.6.3 State B (Word Synchronization Acquired) - 91
6.1.6.3.1 State B.1 (No Invalid Transmission Word Detected State) - 92
6.1.6.3.2 State B.2 (First Invalid Transmission Word Detected State) - 92
6.1.6.3.3 State B.3 (Second Invalid Transmission Word Detected State) - 92
6.1.6.3.4 State B.4 (Third Invalid Transmission Word Detection State) - 92
6.1.6.4 State C (Reset) - 92
6.2 Transmitter - 93
6.2.1 State Diagram - 93
6.2.2 Operational condition - 93
6.2.3 State Transitions - 93
6.2.3.1 Not Enabled State - 93
6.2.3.2 Working State - 94
6.2.3.3 Failure State - 94
7 FC_Port state machine - 95
7.1 State diagram - 95
7.2 Active State (AC) - 95
7.3 Link Recovery - 95
7.3.1 Link recovery hierarchy - 95
7.3.2 LR Transmit State (LR1) - 95
7.3.2.1 General (while in the LR1 state) - 95
7.3.2.2 Class 1 (while in the LR1 state) - 95
7.3.2.3 Class 2 and Class 3 (while in the LR1 state) - 96
7.3.2.4 Class 4 (while in the LR1 state) - 97
7.3.2.5 Class 6 (while in the LR1 state) - 97
7.3.3 LR Receive State (LR2) - 97
7.3.3.1 General (while in the LR2 state) - 97
7.3.3.2 Class 1 (while in the LR2 state) - 97
7.3.3.3 Class 4 (while in the LR2 state) - 97
7.3.3.4 Class 6 (while in the LR2 state) - 98
7.3.4 LRR Receive State (LR3) - 98
7.3.4.1 General (while in the LR3 state) - 98
7.3.4.2 Class 1 and Class 6 behavior (while in the LR3 state) - 98
7.3.4.3 Class 4 behavior (while in the LR2 state) - 98
7.4 Link Failure - 99
7.4.1 NOS Receive State (LF1) - 99
7.4.1.1 General - 99
7.4.1.2 Class 4 behavior - 99
7.4.2 NOS Transmit State (LF2) - 99
7.4.2.1 General - 99
7.4.2.2 Class 4 behavior - 99
7.5 Offline - 99
7.5.1 General - 99
7.5.2 OLS Transmit State (OL1) - 100
7.5.2.1 Actions applicable to all classes - 100
7.5.2.2 Class 4 behavior - 100
7.5.3 OLS Receive State (OL2) - 100

7.5.3.1 General - - - - - 100
7.5.3.2 Class 4 behavior - - - - - 100
7.5.4 Wait for OLS State (OL3) - - - - - 100
7.5.4.1 Actions applicable to all classes - - - - - 100
7.5.4.2 Class 4 behavior - - - - - 101
7.6 Primitive Sequence protocols - - - - - 101
7.6.1 Functions - - - - - 101
7.6.2 Link Initialization protocol - - - - - 101
7.6.3 Link Reset protocol - - - - - 101
7.6.4 Link Failure protocol - - - - - 101
7.6.5 Online-to-offline protocol - - - - - 102

8 Frame formats - - - - - 103
8.1 General frame format - - - - - 103
8.2 Frame transmission - - - - - 103
8.3 Start-of-Frame (SOF) delimiter - - - - - 103
8.3.1 Introduction - - - - - 103
8.3.2 SOF Connect Class 1 or 6 (SOFc1) - - - - - 104
8.3.3 SOF Circuit Activate Class 4 (SOFc4) - - - - - 104
8.3.4 SOF Initiate (SOFix) - - - - - 104
8.3.4.1 Applicability - - - - - 104
8.3.4.2 SOF Initiate Class 1 or 6 (SOFi1) - - - - - 104
8.3.4.3 SOF Initiate Class 2 (SOFi2) - - - - - 104
8.3.4.4 SOF Initiate Class 3 (SOFi3) - - - - - 104
8.3.4.5 SOF Initiate Class 4 (SOFi4) - - - - - 104
8.3.5 SOF Normal (SOFnx) - - - - - 104
8.3.5.1 Applicability - - - - - 104
8.3.5.2 SOF Normal Class 1 or 6 (SOFn1) - - - - - 104
8.3.5.3 SOF Normal Class 2 (SOFn2) - - - - - 104
8.3.5.4 SOF Normal Class 3 (SOFn3) - - - - - 104
8.3.5.5 SOF Normal Class 4 (SOFn4) - - - - - 105
8.3.6 SOF Fabric (SOFf) - - - - - 105
8.4 Frame_Header - - - - - 105
8.5 Data Field - - - - - 105
8.6 CRC - - - - - 105
8.7 End-of-Frame (EOF) delimiter - - - - - 106
8.7.1 Introduction - - - - - 106
8.7.2 Valid frame content - - - - - 106
8.7.2.1 EOF Normal (EOFn) - - - - - 106
8.7.2.2 EOF Terminate (EOFt) - - - - - 106
8.7.2.3 EOF Disconnect Terminate (EOFdt) (Class 1 or Class 6) - - - - - 106
8.7.2.4 EOF Deactivate Terminate (EOFdt) (Class 4) - - - - - 107
8.7.2.5 EOF Remove Terminate (EOFrt) - - - - - 107
8.7.3 Invalid frame content - - - - - 107
8.7.3.1 General - - - - - 107
8.7.3.2 End of Frame Abort (EOFa) - - - - - 107
8.7.3.3 EOF Disconnect Terminate Invalid (EOFdti) (Class 1 and Class 6) - - - - - 108
8.7.3.4 EOF Deactivate Terminate Invalid (EOFdti) (Class 4) - - - - - 108
8.7.3.5 EOF Remove Terminate Invalid (EOFrti) - - - - - 108
8.7.3.6 EOF Invalid (EOFni) - - - - - 108
8.8 Frame field order - - - - - 108
8.9 Frame reception - - - - - 110
8.9.1 Rules - - - - - 110
8.9.2 Frame validity - - - - - 110
8.9.3 Invalid frame processing - - - - - 110

9 Frame_Header - - - - - 111
9.1 Introduction - - - - - 111

9.2 Identification 111
9.2.1 Frame identification 111
9.2.2 Sequence identification 111
9.3 Routing Control (R_CTL) 112
9.3.1 Introduction 112
9.3.2 ROUTING Field 112
9.3.3 INFORMATION Field 112
9.4 Address identifiers (D_ID, S_ID) 114
9.4.1 General 114
9.4.2 Reserved address identifiers 114
9.4.3 Destination_ID (D_ID) 114
9.4.4 Source_ID (S_ID) 114
9.5 Class Specific Control (CS_CTL)/Priority 115
9.5.1 Introduction 115
9.5.2 CS_CTL 115
9.5.2.1 General 115
9.5.2.2 Class 1 and Class 6 115
9.5.2.3 Class 2 116
9.5.2.4 Class 3 116
9.5.2.5 Class 4 117
9.5.3 Priority 118
9.5.3.1 Introduction 118
9.5.3.2 Class 1 and Class 6 118
9.5.3.3 Class 2 and Class 3 119
9.5.3.4 Class 4 119
9.6 Data structure type (TYPE) 120
9.7 Frame Control (F_CTL) 122
9.7.1 Introduction 122
9.7.2 Exchange Context 122
9.7.3 Sequence Context 124
9.7.4 First_Sequence 125
9.7.5 Last_Sequence 125
9.7.6 End_Sequence 125
9.7.7 End_Connection (E_C) (Class 1 or 6) or Deactivate Class 4 circuit 125
9.7.8 CS_CTL/Priority Enable 125
9.7.9 Sequence Initiative 126
9.7.10 ACK_Form 126
9.7.11 Retransmitted Sequence 126
9.7.12 Unidirectional Transmit or Remove_Connection 126
9.7.13 Continue Sequence Condition 127
9.7.14 Abort Sequence Condition 127
9.7.15 Relative offset present 128
9.7.16 Exchange reassembly 129
9.7.17 Fill Data Bytes 129
9.7.18 F_CTL bits on Data frames 129
9.7.19 F_CTL bits on Link_Control frames 130
9.8 Sequence_ID (SEQ_ID) 132
9.9 Data Field Control (DF_CTL) 132
9.10 Sequence count (SEQ_CNT) 133
9.11 Originator Exchange_ID (OX_ID) 133
9.12 Responder Exchange_ID (RX_ID) 134
9.13 Parameter 134

10 Optional headers 135
10.1 Introduction 135
10.2 ESP_Header 136
10.3 Network_Header 138

10.4 Association_Header - - - 139
10.4.1 Introduction - - - 139
10.4.2 Process_Associators - - - 140
10.4.2.1 Originator and Responder Process_Associators - - - 140
10.4.2.2 Multicast Process_Associator - - - 140
10.4.2.3 Operation_Associators - - - 141
10.5 Device_Header - - - 141

11 Data frames and responses - - - 142
11.1 Data frames - - - 142
11.1.1 Introduction - - - 142
11.1.2 Frame Delimiters - - - 142
11.1.3 Addressing - - - 142
11.1.4 Data Field - - - 143
11.1.5 Payload size - - - 143
11.1.6 Responses - - - 143
11.1.6.1 R_RDY response - - - 143
11.1.6.2 Data frame responses - - - 143
11.1.6.2.1 Introduction - - - 143
11.1.6.2.2 ACK frames - successful Data frame delivery - - - 143
11.1.6.3 Link_Response frames - Unsuccessful Data frame delivery - - - 144
11.2 Link_Control Frames - - - 144
11.2.1 Introduction - - - 144
11.2.2 Link_Continue function - - - 146
11.2.2.1 Introduction - - - 146
11.2.2.2 Receiver Ready (R_RDY) - - - 146
11.2.2.3 Acknowledge (ACK) - - - 147
11.2.2.3.1 General - - - 147
11.2.2.3.2 ACK_1 - - - 148
11.2.2.3.3 ACK_0 - - - 148
11.2.2.3.4 Header definition for all ACK forms - - - 148
11.2.2.3.4.1 Addressing - - - 148
11.2.2.3.4.2 F_CTL - - - 148
11.2.2.3.4.3 SEQ_ID - - - 148
11.2.2.3.4.4 SEQ_CNT - - - 148
11.2.2.3.4.5 Parameter field - - - 149
11.2.2.3.5 Responses - - - 149
11.2.3 Link_Response - - - 149
11.2.3.1 Introduction - - - 149
11.2.3.2 Fabric Busy (F_BSY) - - - 149
11.2.3.2.1 Description - - - 149
11.2.3.2.2 Responses - - - 150
11.2.3.3 N_Port Busy (P_BSY) - - - 150
11.2.3.3.1 Description - - - 150
11.2.3.3.2 Responses - - - 152
11.2.3.4 Reject (P_RJT, F_RJT) - - - 152
11.2.3.4.1 Introduction - - - 152
11.2.3.4.2 Class 4 - - - 153
11.2.3.4.3 Parameter field - - - 153
11.2.3.4.3.1 Reject Code format - - - 153
11.2.3.4.3.2 Invalid D_ID - - - 156
11.2.3.4.3.3 Invalid S_ID - - - 156
11.2.3.4.3.4 Nx_Port not available, temporary - - - 156
11.2.3.4.3.5 Nx_Port not available, permanent - - - 156
11.2.3.4.3.6 Class not supported - - - 156
11.2.3.4.3.7 Delimiter usage error - - - 156
11.2.3.4.3.8 TYPE not supported - - - 157

11.2.3.4.3.9 Invalid Link_Control - 157
11.2.3.4.3.10 Invalid R_CTL field - 157
11.2.3.4.3.11 Invalid F_CTL field - 157
11.2.3.4.3.12 Invalid OX_ID - 157
11.2.3.4.3.13 Invalid RX_ID - 157
11.2.3.4.3.14 Invalid SEQ_ID - 157
11.2.3.4.3.15 Invalid DF_CTL - 157
11.2.3.4.3.16 Invalid SEQ_CNT - 157
11.2.3.4.3.17 Invalid Parameter field - 157
11.2.3.4.3.18 Exchange Error - 157
11.2.3.4.3.19 Protocol Error - 157
11.2.3.4.3.20 Incorrect length - 157
11.2.3.4.3.21 Unexpected ACK - 158
11.2.3.4.3.22 Class of service not supported by entity at hex ’FF FF FE’ - 158
11.2.3.4.3.23 Login Required - 158
11.2.3.4.3.24 Excessive Sequences attempted - 158
11.2.3.4.3.25 Unable to Establish Exchange - 158
11.2.3.4.3.26 Fabric path not available - 158
11.2.3.4.3.27 Invalid VC_ID (Class 4) - 158
11.2.3.4.3.28 Invalid CS_CTL Field - 158
11.2.3.4.3.29 Insufficient resources for VC (Class 4) - 158
11.2.3.4.3.30 Invalid class of service - 158
11.2.3.4.3.31 Preemption request rejected - 158
11.2.3.4.3.32 Preemption not enabled - 158
11.2.3.4.3.33 Multicast error - 159
11.2.3.4.3.34 Multicast error terminate - 159
11.2.3.4.3.35 Vendor Specific Reject - 159
11.2.3.4.3.36 Responses - 159
11.2.4 Link_Control commands - 159
11.2.4.1 Introduction - 159
11.2.4.2 Link Credit Reset (LCR) - 159
11.2.4.2.1 Description - 159
11.2.4.2.2 Protocol - 160
11.2.4.2.3 Request Sequence - 160
11.2.4.2.4 Responses - 160
11.2.4.3 End (END) - 160
11.2.4.3.1 Description - 160
11.2.4.3.2 Protocol - 161
11.2.4.3.3 Request Sequence - 161
11.2.4.3.4 Reply Sequence - 161
11.3 ACK generation assistance - 161
11.3.1 Introduction - 161
11.3.2 N_Port Login - 161
11.3.2.1 Capability Indicator - 161
11.3.3 Applicability - 161
11.3.4 F_CTL bits - 161
11.3.5 Login rules - 161
11.3.6 ACK_Form errors - 162

12 Link Services - 163
12.1 Sequence and Exchange management - 163
12.2 Basic Link Service commands - 163
12.2.1 Introduction - 163
12.2.2 Abort Sequence (ABTS) - 164
12.2.2.1 Overview - 164
12.2.2.2 Aborting Sequences using ABTS - 165
12.2.2.2.1 Introduction - 165

12.2.2.2.2 ABTS Initiator 165
12.2.2.2.3 ABTS Recipient 165
12.2.2.2.4 Recovery Qualifier 166
12.2.2.2.5 Protocol 166
12.2.2.2.6 Request Sequence 166
12.2.2.2.7 Reply Sequence 167
12.2.2.3 Aborting Exchanges using ABTS 167
12.2.2.3.1 Introduction 167
12.2.2.3.2 ABTS sent by the last Sequence Initiator in an open Sequence 168
12.2.2.3.3 ABTS sent by the last Sequence Initiator in a new Sequence 168
12.2.2.3.4 ABTS sent in an open or new Sequence 168
12.2.2.3.5 ABTS by the last Sequence Recipient 168
12.2.2.3.6 Request Sequence 168
12.2.2.3.7 Reply Sequence 169
12.2.3 Basic Accept (BA_ACC) 170
12.2.3.1 Description 170
12.2.3.2 Protocol 170
12.2.3.3 Request Sequence 170
12.2.3.4 Reply Sequence 170
12.2.4 Basic Reject (BA_RJT) 170
12.2.4.1 Description 170
12.2.4.2 Protocol 170
12.2.4.3 Request Sequence 170
12.2.4.4 Reply Sequence 171
12.2.5 No Operation (NOP) 172
12.2.5.1 Description 172
12.2.5.2 Protocol 172
12.2.5.3 Request Sequence 172
12.2.5.4 Reply Sequence 172
12.2.6 Remove Connection (RMC) 172
12.2.6.1 Description 172
12.2.6.2 Protocol: 173
12.2.6.3 Request Sequence 173
12.2.6.4 Reply Sequence 173
12.2.7 Dedicated connection preempted (PRMT) 173
12.2.7.1 Description 173
12.2.7.2 Protocol 173
12.2.7.3 Request Sequence 173
12.2.7.4 Reply Sequence 173
12.3 Extended Link Services 173
12.3.1 Introduction 173
12.3.2 Extended Link Service requests 174
12.3.2.1 Introduction 174
12.3.2.2 Abort Exchange (ABTX) 178
12.3.2.2.1 Description 178
12.3.2.2.2 Protocol 179
12.3.2.2.3 Request Sequence 179
12.3.2.2.4 Reply Sequence 180
12.3.2.3 Advise Credit (ADVC) 180
12.3.2.3.1 Description 180
12.3.2.3.2 Protocol 180
12.3.2.3.3 Request Sequence 180
12.3.2.3.4 Reply Sequence 181
12.3.2.4 Echo (ECHO) 182
12.3.2.4.1 Description 182
12.3.2.4.2 Protocol 182
12.3.2.4.3 Request Sequence 183

12.3.2.4.4 Reply Sequence - - - 183
12.3.2.5 Estimate Credit (ESTC) - - - 183
12.3.2.5.1 Description - - - 183
12.3.2.5.2 Protocol - - - 183
12.3.2.5.3 Request Sequence - - - 184
12.3.2.5.4 Reply Sequence - - - 184
12.3.2.6 Establish Streaming (ESTS) - - - 184
12.3.2.6.1 Description - - - 184
12.3.2.6.2 Protocol - - - 184
12.3.2.6.3 Request Sequence - - - 184
12.3.2.6.4 Reply Sequence - - - 185
12.3.2.7 Login (FLOGI/PLOGI) - - - 186
12.3.2.7.1 Description - - - 186
12.3.2.7.2 Protocol - - - 186
12.3.2.7.3 Request Sequence - - - 186
12.3.2.7.4 Reply Sequence - - - 186
12.3.2.8 Logout (LOGO) - - - 186
12.3.2.8.1 Description - - - 186
12.3.2.8.2 Protocol - - - 187
12.3.2.8.3 Request Sequence - - - 187
12.3.2.8.4 Reply Sequence - - - 187
12.3.2.9 Read Connection Status (RCS) - - - 187
12.3.2.9.1 Description - - - 187
12.3.2.9.2 Protocol - - - 187
12.3.2.9.3 Request Sequence - - - 188
12.3.2.9.4 Reply Sequence - - - 188
12.3.2.10 Read Exchange Status Block (RES) - - - 189
12.3.2.10.1 Description - - - 189
12.3.2.10.2 Protocol - - - 190
12.3.2.10.3 Request Sequence - - - 190
12.3.2.10.4 Reply Sequence - - - 190
12.3.2.11 Read Link Error Status Block (RLS) - - - 191
12.3.2.11.1 Description - - - 191
12.3.2.11.2 Protocol - - - 191
12.3.2.11.3 Request Sequence - - - 191
12.3.2.11.4 Reply Sequence - - - 191
12.3.2.12 Read Sequence Status Block (RSS) - - - 191
12.3.2.12.1 Description - - - 191
12.3.2.12.2 Protocol - - - 192
12.3.2.12.3 Request Sequence - - - 192
12.3.2.12.4 Reply Sequence - - - 192
12.3.2.13 Read Timeout Value (RTV) - - - 193
12.3.2.13.1 Description - - - 193
12.3.2.13.2 Protocol - - - 193
12.3.2.13.3 Request Sequence - - - 193
12.3.2.13.4 Reply Sequence - - - 193
12.3.2.14 Reinstate Recovery Qualifier (RRQ) - - - 194
12.3.2.14.1 Description - - - 194
12.3.2.14.2 Protocol - - - 194
12.3.2.14.3 Request Sequence - - - 194
12.3.2.14.4 Reply Sequence - - - 195
12.3.2.15 Request Sequence Initiative (RSI) - - - 195
12.3.2.15.1 Description - - - 195
12.3.2.15.2 Protocol - - - 196
12.3.2.15.3 Request Sequence - - - 196
12.3.2.15.4 Reply Sequence - - - 196
12.3.2.16 Test (TEST) - - - 196

12.3.2.16.1 Description - - - 196
12.3.2.16.2 Protocol - - - 197
12.3.2.16.3 Request Sequence - - - 197
12.3.2.16.4 Reply Sequence - - - 197
12.3.2.17 Report node Capability Information (RNC) - - - 197
12.3.2.18 Fabric Address Notification (FAN) - - - 197
12.3.2.18.1 Description - - - 197
12.3.2.18.2 Protocol - - - 198
12.3.2.18.3 Request Sequence - - - 198
12.3.2.18.4 Reply Sequence - - - 198
12.3.2.19 Loop Initialize (LINIT) - - - 198
12.3.2.19.1 Description - - - 198
12.3.2.19.2 Protocol - - - 198
12.3.2.19.3 Request Sequence - - - 198
12.3.2.19.4 Reply Sequence - - - 199
12.3.2.20 Loop Port Control (LPC) (Obsolete) - - - 200
12.3.2.21 Loop Status (LSTS) - - - 200
12.3.2.21.1 Description - - - 200
12.3.2.21.2 Protocol - - - 200
12.3.2.21.3 Request Sequence - - - 200
12.3.2.21.4 Reply Sequence - - - 200
12.3.2.22 Registered State Change Notification (RSCN) - - - 202
12.3.2.22.1 Introduction - - - 202
12.3.2.22.2 RSCNs issued by the Fabric Controller - - - 203
12.3.2.22.3 RSCN issued by the affected Nx_Port - - - 203
12.3.2.22.4 RSCN initiative - - - 203
12.3.2.22.5 RSCN registration - - - 203
12.3.2.22.6 Protocol - - - 203
12.3.2.22.7 Request Sequence - - - 204
12.3.2.22.8 Reply Sequence - - - 205
12.3.2.23 State Change Registration (SCR) - - - 206
12.3.2.23.1 Description - - - 206
12.3.2.23.2 Protocol - - - 206
12.3.2.23.3 Request Sequence - - - 206
12.3.2.23.4 Reply Sequence - - - 207
12.3.2.24 Process login (PRLI) - - - 207
12.3.2.24.1 Introduction - - - 207
12.3.2.24.2 Protocol - - - 207
12.3.2.24.3 Request Sequence - - - 207
12.3.2.24.4 Reply Sequence - - - 209
12.3.2.25 Process logout (PRLO) - - - 211
12.3.2.25.1 Description - - - 211
12.3.2.25.2 Protocol - - - 211
12.3.2.25.3 Request Sequence - - - 212
12.3.2.25.4 Reply sequence - - - 213
12.3.2.26 State change notification (SCN) - - - 216
12.3.2.27 Test Process Login State (TPLS) - - - 216
12.3.2.27.1 Description - - - 216
12.3.2.27.2 Protocol - - - 216
12.3.2.27.3 Request Sequence - - - 216
12.3.2.27.4 Reply sequence - - - 218
12.3.2.28 Fibre Channel Address Resolution Protocol Request (FARP_REQ) - - - 220
12.3.2.28.1 Description - - - 220
12.3.2.28.2 Protocol - - - 220
12.3.2.28.3 Request Sequence - - - 220
12.3.2.28.4 Reply Sequence - - - 224
12.3.2.29 Fibre Channel Address Resolution Protocol Reply (FARP_REPLY) - - - 224

12.3.2.29.1 Description - - - - 224
12.3.2.29.2 Protocol - - - - 225
12.3.2.29.3 Request Sequence - - - - 225
12.3.2.29.4 Reply Sequence - - - - 227
12.3.2.30 Request Node Identification Data (RNID) - - - - 227
12.3.2.30.1 Introduction - - - - 227
12.3.2.30.2 Protocol - - - - 228
12.3.2.30.3 Request Sequence - - - - 228
12.3.2.30.4 Reply Sequence: - - - - 229
12.3.2.31 Registered Link Incident Report (RLIR) - - - - 234
12.3.2.31.1 Description - - - - 234
12.3.2.31.2 Link Incident reporting procedure - - - - 234
12.3.2.31.3 Protocol - - - - 235
12.3.2.31.4 Request Sequence - - - - 235
12.3.2.31.5 Reply Sequence - - - - 241
12.3.2.32 Link Incident Record Registration (LIRR) - - - - 241
12.3.2.32.1 Description - - - - 241
12.3.2.32.2 Registration for Link Incident Records - - - - 241
12.3.2.32.3 Responsibilities of Valid-Registered Recipients - - - - 242
12.3.2.32.4 Protocol - - - - 242
12.3.2.32.5 Request Sequence - - - - 242
12.3.2.32.6 Reply Sequence - - - - 243
12.3.2.33 Get Alias_ID (GAID) - - - - 244
12.3.2.33.1 Description - - - - 244
12.3.2.33.2 Protocol - - - - 244
12.3.2.33.3 Request Sequence - - - - 244
12.3.2.33.4 Reply Sequence - - - - 245
12.3.2.34 Fabric Activate Alias_ID (FACT) - - - - 245
12.3.2.34.1 Description - - - - 245
12.3.2.34.2 Protocol - - - - 245
12.3.2.34.3 Request Sequence - - - - 245
12.3.2.34.4 Reply Sequence - - - - 246
12.3.2.35 Fabric Deactivate Alias_ID (FDACT) - - - - 246
12.3.2.35.1 Description - - - - 246
12.3.2.35.2 Protocol - - - - 246
12.3.2.35.3 Request Sequence - - - - 246
12.3.2.35.4 Reply Sequence - - - - 247
12.3.2.36 N_Port Activate Alias_ID (NACT) - - - - 247
12.3.2.36.1 Description - - - - 247
12.3.2.36.2 Protocol - - - - 247
12.3.2.36.3 Reply Sequence - - - - 248
12.3.2.36.4 Reply Sequence - - - - 248
12.3.2.37 N_Port Deactivate Alias_ID (NDACT) - - - - 249
12.3.2.37.1 Description - - - - 249
12.3.2.37.2 Protocol - - - - 249
12.3.2.37.3 Request Sequence - - - - 249
12.3.2.37.4 Reply Sequence - - - - 249
12.3.2.38 Quality of Service Request (QoSR) - - - - 250
12.3.2.38.1 Description - - - - 250
12.3.2.38.2 Protocol - - - - 250
12.3.2.38.3 Request Sequence - - - - 250
12.3.2.38.4 Reply Sequence - - - - 252
12.3.2.39 Read Virtual Circuit Status (RVCS) - - - - 254
12.3.2.39.1 Description - - - - 254
12.3.2.39.2 Protocol - - - - 254
12.3.2.39.3 Request Sequence - - - - 254
12.3.2.39.4 Reply Sequence - - - - 255

12.3.2.40 Discover N_Port/Service Parameters (PDISC) - 255
12.3.2.40.1 Description - 255
12.3.2.40.2 Protocol - 255
12.3.2.40.3 Request Sequence - 255
12.3.2.40.4 Reply Sequence - 256
12.3.2.41 Discover F_Port Service Parameters (FDISC) - 256
12.3.2.41.1 Description - 256
12.3.2.41.2 Protocol - 256
12.3.2.41.3 Request Sequence - 256
12.3.2.41.4 Reply Sequence - 256
12.3.2.42 Discover Address (ADISC) - 256
12.3.2.42.1 Description - 256
12.3.2.42.2 Protocol - 256
12.3.2.42.3 Request Sequence - 257
12.3.2.42.4 Reply Sequence - 257
12.3.2.43 Third Party Process Logout (TPRLO) - 258
12.3.2.43.1 Description - 258
12.3.2.43.2 Protocol - 258
12.3.2.43.3 Request Sequence - 258
12.3.2.44 Clock Synchronization Request (CSR) - 260
12.3.2.44.1 Description - 260
12.3.2.44.2 Protocol - 260
12.3.2.44.3 Request Sequence - 260
12.3.2.44.4 Reply Sequence - 260
12.3.2.45 Clock Synchronization Update (CSU) - 260
12.3.2.45.1 Description - 260
12.3.2.45.2 Protocol - 261
12.3.2.45.3 Request Sequence - 261
12.3.2.45.4 Reply Sequence - 261
12.3.2.46 Login Control List Management (LCLM) - 261
12.3.2.46.1 Description - 261
12.3.2.46.2 Protocol - 263
12.3.2.46.3 Request Sequence - 263
12.3.2.46.4 Reply sequence - 264
12.3.2.47 Read Port Status Block (RPS) - 266
12.3.2.47.1 Description - 266
12.3.2.47.2 Protocol - 266
12.3.2.47.3 Request Sequence - 266
12.3.2.47.4 Reply Sequence - 267
12.3.2.48 Read Port List (RPL) - 270
12.3.2.48.1 Description - 270
12.3.2.48.2 Protocol - 270
12.3.2.48.3 Request Sequence - 270
12.3.2.48.4 Reply Sequence - 271
12.3.2.49 Report Port Buffer Conditions (RPBC) - 271
12.3.2.49.1 Description - 271
12.3.2.49.2 Protocol - 272
12.3.2.49.3 Request Sequence - 272
12.3.2.49.4 Reply Sequence - 272
12.3.2.50 Report node FC-4 Types (RNFT) - 273
12.3.2.50.1 Description - 273
12.3.2.50.2 Protocol - 273
12.3.2.50.3 Request Sequence - 273
12.3.2.50.4 Reply Sequence - 274
12.3.2.51 Scan Remote Loop (SRL) - 275
12.3.2.51.1 Description - 275
12.3.2.51.2 Protocol - 275

12.3.2.51.3 Request Sequence - - - 275
12.3.2.51.4 Reply Sequence - - - 276
12.3.2.52 Set Bit-error Reporting Parameters (SBRP) - - - 276
12.3.2.52.1 Description - - - 276
12.3.2.52.2 Protocol - - - 277
12.3.2.52.3 Request Sequence - - - 277
12.3.2.52.4 Reply Sequence - - - 278
12.3.2.53 Report Port Speed Capabilities (RPSC) - - - 279
12.3.2.53.1 Description - - - 279
12.3.2.53.2 Protocol - - - 279
12.3.2.53.3 Request Sequence - - - 279
12.3.2.53.4 Reply Sequence - - - 280
12.3.2.54 Read Exchange Concise (REC) - - - 280
12.3.2.54.1 Description - - - 280
12.3.2.54.2 Protocol - - - 281
12.3.2.54.3 Request Sequence - - - 281
12.3.2.54.4 Reply Sequence - - - 281
12.3.3 Extended Link Service Reply Sequences - - - 282
12.3.3.1 Overview - - - 282
12.3.3.2 LS_ACC - - - 282
12.3.3.3 Reply Sequence - - - 283
12.3.3.4 Link Service Reject (LS_RJT) - - - 283
12.3.3.4.1 Description - - - 283
12.3.3.4.2 Payload - - - 283
12.3.3.4.3 Reply Sequence - - - 285
12.4 FC-4 Link Service - - - 286

13 Classes of service- - - 288
13.1 Introduction - - - 288
13.2 Class 1 - Dedicated connection - - - 288
13.2.1 Function - - - 288
13.2.2 Rules - - - 289
13.2.3 Delimiters - - - 290
13.2.4 Frame size - - - 290
13.2.5 Flow control - - - 290
13.2.6 Stacked connect-requests - - - 290
13.3 Class 2 - Multiplex - - - 290
13.3.1 Function - - - 290
13.3.2 Rules - - - 291
13.3.3 Delimiters - - - 292
13.3.4 Frame size - - - 292
13.3.5 Flow control - - - 292
13.4 Class 3 - Datagram - - - 292
13.4.1 Function - - - 292
13.4.2 Rules - - - 293
13.4.3 Delimiters - - - 293
13.4.4 Frame size - - - 294
13.4.5 Flow control - - - 294
13.4.6 Sequence integrity - - - 294
13.5 Intermix - - - 294
13.5.1 Introduction - - - 294
13.5.2 Rules - - - 294
13.5.3 Frame size - - - 295
13.5.4 Flow control - - - 295
13.6 Class 4 - Fractional - - - 295
13.6.1 Function - - - 295
13.6.2 Procedures - - - 296

13.6.3 Login - - - - - 297
13.6.4 Circuit Setup - - - - - 297
13.6.5 Circuit Activation - - - - - 297
13.6.6 Circuit Deactivation - - - - - 297
13.6.7 Circuit Removal - - - - - 298
13.6.8 Rules - - - - - 298
13.6.9 Interleaving other classes of service in Class 4 - - - - - 299
13.6.10 Class 4 delimiters - - - - - 299
13.6.11 Frame size - - - - - 300
13.6.12 End-to-end flow control - - - - - 300
13.6.13 Buffer-to-buffer flow control - - - - - 300
13.7 Class 6 - Connected Multicast - - - - - 301
13.7.1 Function - - - - - 301
13.7.2 Rules - - - - - 301
13.7.3 Delimiters - - - - - 303
13.7.4 Frame size - - - - - 303
13.7.5 Flow control - - - - - 303
13.7.6 Stacked Connect-requests - - - - - 303

14 Name_Identifier Formats - - - - - 304
14.1 Introduction - - - - - 304
14.2 IEEE 48-bit address - - - - - 304
14.3 IEEE extended - - - - - 305
14.4 Locally assigned - - - - - 305
14.5 32-bit IP address - - - - - 306
14.6 IEEE registered - - - - - 306
14.7 IEEE registered extended - - - - - 307
14.8 Other uses of IEEE registered Company_ID - - - - - 307
14.9 EUI-64 Mapped - - - - - 307
14.9.1 General - - - - - 307
14.9.2 EUI-64 to WWN Mapping Rules - - - - - 308
14.9.3 Encapsulated MAC-48 and EUI-48 translation - - - - - 308

15 Login and Service Parameters - - - - - 309
15.1 Introduction - - - - - 309
15.2 Default Login values - - - - - 309
15.3 Fabric Login - - - - - 310
15.3.1 Introduction - - - - - 310
15.3.2 Explicit Fabric Login - - - - - 310
15.3.2.1 Introduction - - - - - 310
15.3.2.2 Explicit Fabric Login Request - - - - - 310
15.3.2.3 Responses to Explicit Fabric Login - - - - - 310
15.3.2.4 Relogin with the Fabric - - - - - 311
15.3.3 SOF delimiters - - - - - 312
15.3.4 Frequency - - - - - 312
15.3.5 Fabric Login completion - Originator - - - - - 312
15.3.6 Fabric Login completion - Responder - - - - - 312
15.4 N_Port Login - - - - - 313
15.4.1 Introduction - - - - - 313
15.4.2 Explicit N_Port Login - - - - - 314
15.4.2.1 Introduction - - - - - 314
15.4.2.2 N_Port Login - Fabric present - - - - - 314
15.4.2.3 Responses to N_Port Login - Fabric present - - - - - 314
15.4.2.4 N_Port Login - No Fabric present - - - - - 315
15.4.2.5 Responses to N_Port Login - No Fabric present - - - - - 315
15.4.3 SOF delimiters - - - - - 316
15.4.4 Frequency - - - - - 316
15.4.5 N_Port Login completion - Originator - - - - - 316

15.4.6 N_Port Login completion - Responder ---- 316
15.4.7 N_Port Login frame flow ---- 316
15.5 Logout ---- 317
15.5.1 Introduction ---- 317
15.5.2 Explicit N_Port Logout ---- 317
15.5.3 Implicit Logout ---- 317
15.6 Service Parameters ---- 317
15.6.1 ELS and LS_ACC Payload ---- 317
15.6.2 Common Service Parameters ---- 319
15.6.2.1 Applicability ---- 319
15.6.2.2 Payload ---- 320
15.6.2.3 Buffer-to-buffer Credit ---- 321
15.6.2.4 Common Features ---- 321
15.6.2.4.1 Continuously increasing relative offset ---- 321
15.6.2.4.2 Clean Address ---- 322
15.6.2.4.3 Random relative offset ---- 322
15.6.2.4.4 Valid Vendor Version Level ---- 322
15.6.2.4.5 Multiple N_Port_ID Assignment ---- 322
15.6.2.4.6 N_Port/F_Port ---- 322
15.6.2.4.7 BB_Credit Management ---- 322
15.6.2.4.8 E_D_TOV Resolution ---- 323
15.6.2.4.9 Multicast ---- 323
15.6.2.4.10 Broadcast ---- 323
15.6.2.4.11 Hunt Group ---- 323
15.6.2.4.12 Query Buffer Conditions ---- 323
15.6.2.4.13 Clock Synchronization Primitive Capable ---- 323
15.6.2.4.14 R_T_TOV value ---- 324
15.6.2.4.15 Dynamic Half Duplex Supported ---- 324
15.6.2.4.16 SEQ_CNT ---- 324
15.6.2.4.17 Payload Bit ---- 324
15.6.2.5 BB_SC_N ---- 325
15.6.2.6 Buffer-to-buffer Receive Data_Field size ---- 325
15.6.2.7 Total Concurrent Sequences ---- 325
15.6.2.8 Relative offset by category ---- 325
15.6.2.9 R_A_TOV ---- 325
15.6.2.10 E_D_TOV ---- 325
15.6.3 N_Port_Name ---- 326
15.6.4 Node_ or Fabric_Name ---- 326
15.6.5 Class Service Parameters ---- 326
15.6.5.1 Applicability ---- 326
15.6.5.2 Payload ---- 328
15.6.5.3 Class validity ---- 329
15.6.5.4 Service options ---- 329
15.6.5.4.1 Introduction ---- 329
15.6.5.4.2 Intermix Mode ---- 329
15.6.5.4.3 Stacked Connect-requests ---- 330
15.6.5.4.4 Sequential delivery ---- 330
15.6.5.4.5 Priority/Preemption ---- 331
15.6.5.4.6 Preference ---- 331
15.6.5.4.6.1 Nx_Port ---- 331
15.6.5.4.6.2 Fx_Port ---- 332
15.6.5.4.7 DiffServ QoS ---- 333
15.6.5.4.7.1 N_Port Login ---- 333
15.6.5.4.7.2 F_Port Login ---- 333
15.6.5.5 Initiator control ---- 334
15.6.5.5.1 Introduction ---- 334
15.6.5.5.2 Initial Process_Associator ---- 334

15.6.5.5.3 ACK_0 capability - - - 334
15.6.5.5.4 ACK generation assistance - - - 335
15.6.5.5.5 Clock synchronization ELS capable - - - 335
15.6.5.6 Recipient control - - - 336
15.6.5.6.1 Introduction - - - 336
15.6.5.6.2 ACK_0 capability - - - 336
15.6.5.6.3 X_ID interlock - - - 337
15.6.5.6.4 Error policy supported - - - 337
15.6.5.6.5 Categories per Sequence - - - 338
15.6.5.6.6 Clock synchronization ELS capable - - - 338
15.6.5.7 Receive Data_Field Size - - - 338
15.6.5.8 Concurrent Sequences - - - 338
15.6.5.9 End-to-end Credit - - - 339
15.6.5.10 Open Sequences per Exchange - - - 340
15.6.5.11 CR_TOV - - - 340
15.6.6 Vendor Version Level - - - 340
15.6.7 Services Availability - - - 340
15.6.7.1 Introduction - - - 340
15.6.7.2 Multicast Server - - - 340
15.6.7.3 Clock Synchronization Server - - - 340
15.6.7.4 Security Key Distribution Server - - - 340
15.6.7.5 Alias Server - - - 340
15.6.7.6 Quality of Service Facilitator - - - 341
15.6.7.7 Management Server - - - 341
15.6.7.8 Time Server - - - 341
15.6.7.9 Directory Server - - - 341
15.6.8 Login Extension - - - 341
15.6.8.1 General - - - 341
15.6.8.2 Login Extension Data Length - - - 341
15.6.8.3 Login Extension format - - - 341
15.6.9 Clock Synchronization Quality of Service - - - 342
15.6.9.1 N_Port Login - - - 342
15.6.9.1.1 Applicability - - - 342
15.6.9.1.2 CS_QoS_Request - - - 343
15.6.9.1.3 CS_Accuracy (Mantissa and Exponent) - - - 343
15.6.9.1.4 Clock Synchronization Implemented MSB - - - 344
15.6.9.1.5 Clock Synchronization Implemented LSB - - - 344
15.6.9.1.6 Clock Synchronization Update Period - - - 344
15.6.9.2 Fabric Login - - - 344
15.6.9.2.1 Applicability - - - 344
15.6.9.2.2 CS_Transfer_Accuracy - - - 345
15.6.9.2.3 Clock Synchronization Implemented MSB - - - 345
15.6.9.2.4 Word 0, Bits 7 to 0 Clock Synchronization Implemented LSB - - - 346

16 Process Login/Logout- - - - 347
16.1 Process Login - - - 347
16.1.1 Introduction - - - 347
16.1.2 PRLI/PRLO Relationships - - - 349
16.1.2.1 Introduction - - - 349
16.1.2.2 PA not supported - - - 349
16.1.2.3 PA required by originator, supported by responder - - - 349
16.1.2.4 PA required by responder, supported by originator - - - 349
16.1.2.5 PA required by originator and responder - - - 350
16.1.3 Mode of operation - - - 350
16.1.3.1 Informative mode - - - 350
16.1.3.2 Binding mode - - - 350
16.1.4 Protocol - - - 350

16.1.4.1 PA required by originator and responder - - - 350
16.1.4.2 PA required by originator, supported by responder - - - 351
16.1.4.3 PA supported by originator, required by responder - - - 351
16.2 Process Logout - - - 351

17 Exchange, Sequence and sequence count management - - - 353
17.1 Introduction - - - 353
17.1.1 Data frame transfer - - - 353
17.1.2 Sequence - - - 353
17.1.3 Streamed Sequences - - - 353
17.1.4 SEQ_CNT - - - 353
17.1.5 Exchange - - - 353
17.1.6 Sequence Initiative - - - 355
17.2 Applicability - - - 355
17.3 Exchange rules - - - 356
17.3.1 Exchange management - - - 356
17.3.2 Exchange origination - - - 356
17.3.3 Sequence delimiters - - - 357
17.3.4 Sequence initiation - - - 357
17.3.5 Sequence management - - - 357
17.3.6 SEQ_CNT - - - 358
17.3.7 Normal ACK processing - - - 358
17.3.8 Normal Sequence completion - - - 359
17.3.9 Detection of missing frames - - - 360
17.3.10 Sequence errors - Class 1, 2, 4 and 6 - - - 361
17.3.10.1 Rules common to all Discard policies - - - 361
17.3.10.2 Discard multiple Sequences Error Policy - - - 362
17.3.10.3 Discard a single Sequence Error Policy - - - 363
17.3.10.4 Process with infinite buffers Error Policy - - - 363
17.3.11 Sequence errors - Class 3 - - - 364
17.3.11.1 Rules common to all discard policies - - - 364
17.3.11.2 Process with infinite buffers Error Policy - - - 364
17.3.12 Sequence Status Rules - - - 364
17.3.13 Exchange termination - - - 365
17.3.14 Exchange Status Rules - - - 365
17.4 Exchange management - - - 365
17.5 Exchange origination - - - 365
17.5.1 Introduction - - - 365
17.5.2 Exchange Originator - - - 366
17.5.3 Exchange Responder - - - 366
17.5.4 X_ID assignment - - - 367
17.5.5 X_ID interlock - - - 367
17.6 Sequence management - - - 367
17.6.1 Open and active Sequences - - - 367
17.6.2 Sequence_Qualifier management - - - 368
17.6.3 Sequence initiative and termination - - - 368
17.6.4 Transfer of Sequence Initiative - - - 368
17.6.5 Sequence Termination - - - 368
17.6.5.1 Introduction - - - 368
17.6.5.2 Class 1 and Class 6 - - - 369
17.6.5.3 Class 2 - - - 369
17.6.5.4 Class 3 - - - 369
17.6.5.5 Class 4 - - - 369
17.6.5.6 Continue Sequence Condition - - - 369
17.6.5.7 End_Sequence - - - 369
17.7 Exchange termination - - - 369
17.7.1 Normal termination - - - 369

17.7.2 Abnormal termination - - - 370
17.8 Status blocks - - - 370
17.8.1 Exchange Status Block - - - 370
17.8.2 Sequence Status Block - - - 371

18 Flow control management - - - 374
18.1 Introduction - - - 374
18.2 Physical flow control model for Classes 1, 2, 3 and 6 - - - 375
18.3 Credit and Credit_Count - - - 376
18.3.1 Introduction - - - 376
18.3.2 Credit_Count management - - - 376
18.3.3 Management by increasing the Credit_Count - - - 376
18.3.4 Management by decreasing the Credit_Count - - - 376
18.3.5 Credit_Count types - - - 376
18.3.6 Usage - - - 376
18.4 End-to-end flow control - - - 376
18.4.1 End-to-end management rules - - - 376
18.4.2 Sequence Initiator - - - 377
18.4.3 Sequence Recipient - - - 378
18.4.3.1 General - - - 378
18.4.3.2 ACK_0 - - - 378
18.4.3.3 ACK_1 - - - 378
18.4.3.4 Last ACK timeout - - - 378
18.4.3.5 Streamed Sequences - - - 379
18.4.4 EE_Credit - - - 379
18.4.5 EE_Credit_CNT - - - 379
18.4.6 EE_Credit management - - - 379
18.4.7 End-to-end flow control model - - - 380
18.4.8 End-to-end class dependency - - - 380
18.4.8.1 End-to-end Credit allocation - - - 380
18.4.8.2 EE_Credit_CNT management - - - 380
18.4.9 EE_Credit recovery - - - 381
18.4.10 Class 4 - - - 381
18.4.11 Procedure to estimate end-to-end Credit - - - 382
18.4.11.1 Introduction - - - 382
18.4.11.2 Procedure steps - - - 382
18.4.11.2.1 General - - - 382
18.4.11.2.2 Establish Streaming Sequence - - - 383
18.4.11.2.3 Estimate Credit Sequence - - - 384
18.4.11.2.4 Advise Credit Sequence - - - 384
18.5 Buffer-to-buffer flow control - - - 385
18.5.1 Introduction - - - 385
18.5.2 Buffer-to-buffer management rules - - - 385
18.5.3 BB_Credit - - - 386
18.5.4 BB_Credit_Count - - - 386
18.5.5 BB_Credit management - - - 386
18.5.6 Buffer-to-buffer flow control model - - - 386
18.5.7 Class dependent frame flow - - - 386
18.5.8 R_RDY - - - 386
18.5.9 BB_Credit_Count reset - - - 387
18.5.10 Alternate buffer-to-buffer Credit management - - - 391
18.5.11 BB_Credit Recovery - - - 391
18.6 VC_RDY - - - 392
18.7 BSY / RJT in flow control - - - 393
18.8 LCR in flow control - - - 393
18.9 Integrated Class 2 flow control - - - 393
18.10 Intermix - - - 393

18.11 Point-to-point topology - - - 394

19 Segmentation and reassembly - - - 398
19.1 Introduction - - - 398
19.2 Sending end - - - 398
19.2.1 Introduction - - - 398
19.2.2 Relative offset space - - - 398
19.2.3 Data block - - - 398
19.2.4 Sequence - - - 398
19.2.5 Relationship between Sequences - - - 398
19.3 FC-2 - - - 399
19.3.1 Mechanisms - - - 399
19.3.2 Relative offset - - - 399
19.3.3 SEQ_CNT - - - 399
19.4 Login - - - 399
19.5 Segmentation rules - - - 400
19.6 Reassembly rules - - - 400

20 Connection management - - - 402
20.1 Introduction - - - 402
20.1.1 Establishing a Connection - - - 402
20.1.2 Removing a Connection - - - 402
20.1.3 Preempting a dedicated connection - - - 402
20.1.4 Frame processing precedence - - - 403
20.2 Applicability - - - 403
20.3 Topology models - - - 404
20.3.1 Introduction - - - 404
20.3.2 Fabric model - - - 404
20.3.3 Point-to-point model - - - 404
20.4 Connect/disconnect rules - - - 405
20.4.1 Connect-request rules - - - 405
20.4.1.1 Source of connect-request - - - 405
20.4.1.2 Destination of connect-request - - - 406
20.4.2 Connection Rules - - - 406
20.4.3 Remove Connection rules - - - 407
20.5 Establishing a Connection - - - 407
20.5.1 Introduction - - - 407
20.5.2 Connection Initiator - - - 407
20.5.3 Stacked connect-requests - - - 409
20.5.4 Unidirectional dedicated connection - - - 410
20.5.5 Destination of connect-request - - - 410
20.6 Connected - - - 411
20.7 Removing a Connection - - - 411
20.7.1 Introduction - - - 411
20.7.2 When to remove a Connection - - - 411
20.7.3 End_Connection bit - - - 411
20.7.4 EOF***dt*** transmission - - - 412
20.8 Connection Recovery - - - 412
20.8.1 Introduction - - - 412
20.8.2 Link timeout - - - 412
20.8.3 Corrupted connect-request - - - 412
20.9 Connection Preemption - - - 413
20.9.1 Applicability - - - 413
20.9.2 Topology Model - - - 413
20.9.3 Rules for Preemption - - - 413
20.9.3.1 Preemptor - - - 413
20.9.3.2 Preempted Source - - - 413
20.9.3.3 Preempted Destination(s) - - - 414

20.9.3.4 Preemption Destination(s) - - - 414
20.10 Establishing a Connection Using Preemption - - - 414
20.10.1 Introduction - - - 414
20.10.2 Connection Initiator - - - 414
20.10.3 Preemption Destination - - - 416

21 Error detection/recovery - - - 417
21.1 Introduction - - - 417
21.2 Timeouts - - - 417
21.2.1 Timeout periods - - - 417
21.2.1.1 General - - - 417
21.2.1.2 R_T_TOV - - - 417
21.2.1.3 E_D_TOV - - - 417
21.2.1.4 R_A_TOV - - - 418
21.2.2 Link Failure timeouts - - - 418
21.2.3 Link timeout - - - 418
21.2.4 Sequence timeout - - - 419
21.2.4.1 Introduction - - - 419
21.2.4.2 Classes 1, 2 and 6 - - - 419
21.2.4.3 Class 3 - - - 419
21.2.4.4 End-to-end Class 2 Credit loss - - - 420
21.2.5 OLS transmit timeout - - - 420
21.2.6 Timer Enhancements for Classes 1 and 6 - - - 420
21.2.6.1 Introduction - - - 420
21.2.6.2 Applicability - - - 421
21.2.6.3 Login - - - 421
21.2.6.4 Value - - - 421
21.2.6.5 Stacked Connect-request - - - 421
21.2.6.6 Rules - - - 421
21.2.6.6.1 Connection Initiator - - - 421
21.2.6.6.2 Connection Recipient - - - 422
21.2.6.6.3 Fabric - - - 422
21.2.7 Bit-Error-Rate Thresholding - - - 422
21.2.7.1 Introduction - - - 422
21.2.7.2 Types of Link Errors Caused by Bit Errors - - - 422
21.2.7.3 Error Bursts - - - 422
21.2.7.4 Bit-Error-Rate-Thresholding Measurement - - - 422
21.3 Link error detection - - - 423
21.3.1 Link Failure - - - 423
21.3.2 Code violations - - - 423
21.3.3 Primitive Sequence protocol error - - - 423
21.4 Link error recovery - - - 423
21.5 Link recovery - secondary effects - - - 423
21.5.1 Class 1 and Class 6 - - - 423
21.5.2 Class 2 - - - 424
21.5.3 Class 3 - - - 425
21.5.4 Class 4 - - - 425
21.6 Exchange Integrity - - - 425
21.6.1 Applicability - - - 425
21.6.2 Exchange management - - - 425
21.6.3 Exchange Error Policies - - - 425
21.6.3.1 Introduction - - - 425
21.6.3.2 Discard multiple Sequences - - - 425
21.6.3.3 Discard a single Sequence - - - 426
21.6.3.4 Process with infinite buffering - - - 426
21.6.3.5 Discard multiple Sequences with retransmission - - - 426
21.6.4 Sequence integrity - - - 426

21.6.5 Sequence error detection - - - - 426
21.6.6 X_ID processing - - - - 427
21.7 Sequence recovery - - - - 427
21.7.1 Introduction - - - - 427
21.7.2 Abnormal Sequence termination - - - - 427
21.7.2.1 Introduction - - - - 427
21.7.2.2 Abort Sequence Protocol - - - - 427
21.7.2.2.1 General Case - - - - 427
21.7.2.2.2 Special case - new Exchange - - - - 428
21.7.2.3 Class 1 or 6 Sequence retransmission - - - - 428
21.7.2.4 Recipient abnormal termination - - - - 430
21.7.2.5 End_Sequence - - - - 430
21.7.3 Stop Sequence Protocol - - - - 430
21.7.4 End-to-end Credit loss - - - - 430
21.8 Link Error Status Block - - - - 431
21.9 Detailed Error Detection/Actions - - - - 431
21.9.1 Errors detected - - - - 431
21.9.2 Actions by Initiator or Recipient - - - - 432

22 Hunt Group - - - - 435
22.1 Introduction - - - - 435
22.2 Function - - - - 435
22.3 Communication Model - - - - 435
22.4 Applicability - - - - 435
22.4.1 Classes - - - - 435
22.4.2 Class 4 Addressing - - - - 435
22.5 Formation - - - - 436
22.5.1 General - - - - 436
22.5.2 Registration/deregistration - - - - 436
22.5.3 Inquiry - - - - 437
22.5.4 HG_ID Removal - - - - 437
22.6 N_Port Login - - - - 437
22.7 Addressing Protocol - - - - 437
22.7.1 address identifier Protocol - - - - 437
22.7.2 Originator - - - - 437
22.7.3 Responder - - - - 437
22.7.4 Address Resolution - - - - 438
22.7.5 Class - - - - 438
22.7.6 Class 4 - - - - 438
22.8 Resource management - - - - 438
22.8.1 Introduction - - - - 438
22.8.2 HG_ID use - - - - 439
22.8.3 N_Port_ID use - - - - 439
22.9 Rotary Group - - - - 439

23 Multicast - - - - 441
23.1 Applicability - - - - 441
23.2 Class 3 Multicast - - - - 441
23.2.1 Introduction - - - - 441
23.2.2 Registration and De-registration - - - - 441
23.2.3 Multicast Routing - - - - 441
23.2.4 Class 3 Multicast Rules - - - - 442
23.3 Class 6 Multicast - - - - 442
23.3.1 Introduction - - - - 442
23.3.2 Class 6 Multicast Routing - - - - 443
23.3.3 Class 6 Multicast Rules - - - - 443
23.3.4 Class 6 Multicast Server - - - - 444
23.3.5 Class 6 Multicast Recovery - - - - 444

23.4 Broadcast - 444
23.5 Other - 445

24 Alias_IDs - 446
24.1 Introduction - 446
24.2 Alias Server - 446
24.3 Alias Service protocol - 446
24.4 Alias_ID Routing - 446
24.5 Function Flow - 447
24.6 PA Considerations - 447
24.6.1 Hunt Groups - 447
24.6.2 Multicast Groups - 447
24.6.3 Broadcast - 448

25 Class 4 – Fractional - 449
25.1 Introduction - 449
25.2 Default N_Port Login service parameters - 450
25.3 Communication Model - 450
25.3.1 Introduction - 450
25.3.2 In-order delivery - 451
25.3.3 Guaranteed delivery - 451
25.3.4 Fractional bandwidth management - 452
25.3.5 Class 4 circuit - 452
25.3.5.1 Introduction - 452
25.3.5.2 Setup - 453
25.3.5.3 Activation - 456
25.3.5.4 Deactivation - 457
25.3.5.5 Removal - 458
25.4 Deactivation, removal contention and error recovery - 460
25.4.1 CTI has requested removal of Class 4 circuit - 460
25.4.2 CTR has requested removal of a Class 4 circuit - 460
25.4.3 CTI has requested deactivaton of a Class 4 circuit - 460
25.4.4 CTR has requested deactivaton of a Class 4 circuit - 461
25.4.5 CTI has no outstanding removal or deactivation request - 461
25.4.6 CTR has no outstanding removal or deactivation request - 461
25.5 Ordered Sets - 461
25.6 Quality of Service - 463

26 Stacked Connect-request - 465
26.1 Introduction - 465
26.2 FC-2 Mechanisms - 465
26.3 Applicability - 465
26.4 Communications Model - 465
26.5 Requirements - 465
26.5.1 Connection Initiator - 465
26.5.2 Connection Recipient - 465
26.5.3 Fabric - 466
26.6 Login - 466
26.7 Stacked Connect-request Invoked - 466
26.8 Timer - 466
26.8.1 General - 466
26.8.2 CR_TOV - 466
26.8.3 E_D_TOV - 466
26.9 Rules - 466
26.9.1 Connection Initiator - 466
26.9.2 Connection Recipient - 466
26.9.3 Fabric - 467

27 Clock synchronization service - 468

27.1 Introduction - - - - - 468
27.1.1 References - - - - - 468
27.1.2 Applicability - - - - - 468
27.1.3 Function - - - - - 468
27.1.4 Assumptions - - - - - 468
27.1.5 Clock Synchronization Quality of Service - - - - - 468
27.2 ELS Command Service - - - - - 468
27.2.1 ELS Commands - - - - - 468
27.2.2 Fabric Topology - - - - - 469
27.2.2.1 Model - - - - - 469
27.2.2.2 Clock Synchronization Server Rules - - - - - 469
27.2.2.3 Fabric Rules - - - - - 469
27.2.2.4 Fabric Options - - - - - 470
27.2.2.5 Client Rules - - - - - 470
27.2.2.6 Client Options - - - - - 470
27.2.3 Loop Topology - - - - - 470
27.2.3.1 Model - - - - - 470
27.2.3.2 L_Port Server Rules - - - - - 470
27.2.3.3 L_Port Server Options - - - - - 471
27.2.3.4 L_Port Client Rules - - - - - 471
27.2.3.5 Client Options - - - - - 471
27.2.4 Use of FC-FS Constructs - - - - - 471
27.2.4.1 Login/Logout - - - - - 471
27.2.4.2 Clock Synchronization Request (CSR) ELS - - - - - 472
27.2.4.2.1 Command Payload - - - - - 472
27.2.4.2.2 LS_ACC Payload - - - - - 473
27.2.4.3 Clock Synchronization Update (CSU) ELS Command - - - - - 474
27.3 Primitive Signal Service - - - - - 475
27.3.1 Topology compatibility - - - - - 475
27.3.2 Communication Model - - - - - 475
27.3.3 Requirements - - - - - 476
27.3.3.1 Introduction - - - - - 476
27.3.3.2 Clock Synchronization Server Rules - - - - - 478
27.3.3.3 Fabric Rules - - - - - 479
27.3.3.4 Client Rules - - - - - 479

28 Link Speed Negotiation - - - - - 480
28.1 Speed Negotiation overview - - - - - 480
28.2 Link physical architecture and requirements - - - - - 481
28.3 Speed Negotiation requirements on L_Ports - - - - - 481
28.4 State machines - - - - - 482
28.5 Primitives - - - - - 482
28.6 Speed Negotiation algorithm - - - - - 482
28.6.1 Algorithm overview - - - - - 482
28.6.2 Stage 1 - Wait_for_signal - - - - - 485
28.6.3 Stage 2 - Negotiate_master and Watchdog timer - - - - - 486
28.6.4 Stage 3 - Negotiate_follow - - - - - 488
28.6.5 Stage 4 - Normal operation - - - - - 490
28.6.6 Optional Stage 5 - Slow_wait - - - - - 490
28.6.7 Timing requirements - - - - - 492

Annex A (informative) CRC generation and checking - - - - - 494
A.1 Extract from FDDI - - - - - 494
A.2 Frame check sequence (FCS) - - - - - 494
A.3 Definitions - - - - - 494
A.3.1 FCS generation equations - - - - - 495
A.3.2 FCS checking - - - - - 495
A.4 CRC generation - - - - - 495

A.5 Transmit order of a word - 496
A.6 CRC generation example for ACK_1 frame - 496

Annex B (informative) Data transfer protocols and examples - 500
B.1 General - 500
B.2 Frame level protocol - 500
B.2.1 Class 1 and 6 frame level protocol - 500
B.2.2 Class 2 frame level protocol - 501
B.2.3 Class 3 Frame Level Protocol - 503
B.3 Sequence level protocol example - 505
B.4 Class 1 and 6 frame level protocol example - 507
B.5 Class 2 frame level protocol example - 508
B.6 Class 3 frame level protocol example - 509

Annex C (informative) Connection management applications - 511
C.1 Example cases - 511
C.1.1 Introduction - 511
C.1.2 Case 1 - 511
C.1.3 Case 2 - 511
C.1.4 Case 3 - 512
C.1.5 Case 4 - 512
C.2 Ending sequence and Connection - 512

Annex D (informative) Out of order characteristics - 514
D.1 Introduction - 514
D.2 Out of order Data frame delivery - 514
D.3 Out of order ACK transmission - 515

Annex E (informative) Link Error Status Block - 516
E.1 Introduction - 516
E.2 Link failure counters - 516
E.3 Invalid Transmission Word - 516
E.4 Invalid CRC Count - 516

Annex F (informative) Class 4 Examples - 518
F.1 Introduction - 518
F.2 Setup, activate and deactivate - 518
F.3 Activation collision and removal - 519

Annex G (informative) Priority and Preemption - 524
G.1 Overview - 524
G.2 Preemption Process - 524
G.3 Link Reset Protocol - 526

Annex H (informative) Clock Synchronization - 527
H.1 Introduction - 527
H.2 Discussion - 527
H.2.1 Introduction - 527
H.2.2 A Model of an NL_Port - 527
H.2.3 Hardware-Assisted Clock Synchronization - 528
H.2.4 A Point-to-Point System - 528
H.2.4.1 Introduction - 528
H.2.4.2 Discussion of Errors - 531
H.2.4.2.1 Introduction - 531
H.2.4.2.2 Client Oscillator Frequency Error - 531
H.2.4.2.3 Link Propagation Delay Error - 532
H.2.4.2.4 Unload Error - 533
H.2.4.2.5 Load Error - 534
H.2.4.2.6 R/T Clock Domain Error - 535
H.2.4.2.7 Server Oscillator Error - 536

H.2.4.3 Techniques for Reducing Deterministic Errors - 536
H.2.4.3.1 A Fix for Differences in Oscillator Frequencies - 536
H.2.4.3.2 A Fix for Link Propagation Delay Error - 537
H.2.4.3.3 A Fix for Load Error - 537
H.2.4.3.4 A Fix for Unload Error - 540
H.2.4.4 Dealing With Non-Deterministic Error - 540
H.2.4.5 Dealing With Non-Monotonicity - 540
H.2.5 Fabric Considerations - 541
H.2.5.1 Introduction - 541
H.2.5.2 Discussion of Errors - 542
H.2.5.2.1 Client Oscillator Frequency Error - 542
H.2.5.2.2 Link Propagation Delay Error - 544
H.2.5.2.3 Unload Error - 544
H.2.5.2.4 Load Error - 544
H.2.5.2.5 R/T Clock Domain Error - 544
H.2.5.2.6 Server Oscillator Error - 545
H.2.5.3 Fixes for Fabric Errors - 545
H.2.6 Loop Considerations - 545
H.2.6.1 Introduction - 545
H.2.6.2 Discussion of Errors - 545
H.2.6.3 Introduction - 545
H.2.6.3.1 Node Delay - 546
H.2.6.3.2 Client Oscillator Frequency Error - 547
H.2.6.3.3 Link Propagation Delay Error - 547
H.2.6.3.4 Unload Error - 547
H.2.6.3.5 Load Error - 547
H.2.6.3.6 R/T Clock Domain Error - 547
H.2.6.3.7 Server Oscillator Error - 547
H.2.6.4 Fixes for Loop Errors - 547
H.3 An Example - 547

Annex I (informative) Speed Negotiation details - 550
I.1 Scope - 550
I.2 Basic assumptions - 550
I.3 Supported configuration - 551
I.4 Derivation of timing requirements and characteristics - 551
I.4.1 Introduction and diagram conventions - 551
I.4.2 Receiver cycle time, t_rxcycl - 552
I.4.3 Master transmitter cycle time, t_txcycl - 552
I.4.4 Speed stability time, t_stbl - 552
I.4.5 Watchdog timer threshold, t_fail - 552
I.4.6 Watchdog Timer test delay, t_wddly - 553
I.4.7 Speed recording time, t_ncycl - 553
I.4.8 Speed recording time initial value, t_ncinit - 554
I.4.9 Parameters relating to the optional slow_wait stage: - 555
I.4.9.1 Low processing load sleep time, t_sleep - 555
I.4.9.2 Slow_wait cycle transmit cycle delay, t_txdly - 555
I.4.9.3 Periodic sync search wake time, t_wake - 555
I.4.10 Duration of disruption to single loops caused by connecting speed negotiating ports to hubs - - - - - - - - - - - - - - - - - - -

I.4.10.8 Maximum disruption group - Negotiate_master ---------- 561
I.4.10.9 Maximum disruption group - Negotiate_follow ---------- 562
I.4.10.10 Maximum single disruption overall ---------- 562
I.4.10.11 Maximum disruption group overall ---------- 563
I.4.10.12 Summary of loop disruption ---------- 563
I.4.11 Algorithm convergence time: ---------- 564
I.5 Ports using separate PMD components ---------- 564
I.6 Implementation notes ---------- 566

Annex J (informative) IEEE company_ID---------- 567

Annex K (informative) WWN-to-EUI-64 Mapping ---------- 568
K.1 Background ---------- 568
K.2 Solution ---------- 568
K.3 Case Study ---------- 569
Bibliography ---------- 571

Figure 1 - Fibre Channel Structure 57
Figure 2 - Node functional configuration 59
Figure 3 - FC-FS physical model 61
Figure 4 - Point-to-point topology 62
Figure 5 - Fabric topology 63
Figure 6 - Examples of the Arbitrated Loop Topology 64
Figure 7 - Informative general Fabric model 67
Figure 8 - FC-2 building block hierarchy 69
Figure 9 - Receiver State Diagram 89
Figure 10 - Transmitter State Diagram 93
Figure 11 - FC-2 frame format 103
Figure 12 - CIVC_ID and CRVC_ID management 118
Figure 13 - Frame structure when ESP_Header is not used 135
Figure 14 - Frame structure with ESP_Header and ESP_Trailer 136
Figure 15 - QoSR Sequence flow 250
Figure 16 - Illustration of parameters 277
Figure 17 - LS_RJT format 283
Figure 18 - Class 4 circuit – Management 296
Figure 19 - Image/Group of Related Processes 347
Figure 20 - Image pairs 348
Figure 21 - Exchange - Sequence relationship 354
Figure 22 - Exchange origination 366
Figure 23 - Physical flow control model for Classes 1, 2, 3 and 6 375
Figure 24 - End-to-end flow control model 381
Figure 25 - Procedure to estimate end-to-end Credit 383
Figure 26 - Buffer-to-buffer flow control model 387
Figure 27 - Class 1 or 6/SOFc1 frame flow with delivery or non-delivery to the fabric 388
Figure 28 - Class 1 or 6/SOFc1 frame flow with delivery or non-delivery to an Nx_Port 388
Figure 29 - Buffer-to-buffer - Class 2 frame flow with delivery or non-delivery to a Fabric 389
Figure 30 - Buffer-to-buffer - Class 2 frame flow with delivery or non-delivery to an Nx_Port 390
Figure 31 - Buffer-to-buffer - Class 3 frame flow 391
Figure 32 - LCR frame flow and possible responses 394
Figure 33 - LCR flow control model 395
Figure 34 - Integrated Class 2 flow control 397
Figure 35 - Frame Flow Timers 421
Figure 36 - Link recovery hierarchy 424
Figure 37 - Relationship of a Non-Participating to a Participating Nx_Port and switch 440
Figure 38 - Class 3 Multicast Routing 442
Figure 39 - Class 6 Multicast Routing 443
Figure 40 - Function Flow 447
Figure 41 - Class 4 Circuit hierarchy 449
Figure 42 - Basic Class 4 circuit 451
Figure 43 - Class 4 circuits – Example 451
Figure 44 - Class 4 circuit - Port level state diagram 453
Figure 45 - Class 4 circuit – Setup 455
Figure 46 - Class 4 circuit – Activation 457
Figure 47 - Class 4 - Example of frame flow 457
Figure 48 - Class 4 circuit - CTI or CTR initiated 458
Figure 49 - Class 4 circuit - Fabric initiated deactivation 458
Figure 50 - Class 4 circuit - CTI or CTR initiated removal 459
Figure 51 - Class 4 circuit - Fabric initiated removal 459
Figure 52 - Class 4 circuit - Data frame responses 463
Figure 53 - ELS Clock Sync Model – Fabric 469
Figure 54 - ELS Clock Sync Model – Loop 471

Figure 55 - Clock Synchronization Data Distribution 476
Figure 56 - Synchronization Primitive Substitution for IDLE Primitives in Inter-frame Interval 476
Figure 57 - Clock Synchronization Primitive Ordered Sets 477
Figure 58 - Physical architecture of the Speed Negotiating Link 481
Figure 59 - Delay / Test operations 483
Figure 60 - Overview of the Speed Negotiation algorithm 484
Figure 61 - Wait_for_signal flowchart 485
Figure 62 - Negotiate_master and Watchdog timer flowchart 487
Figure 63 - Negotiate_follow flowchart 489
Figure 64 - Normal operation flowchart 490
Figure 65 - Slow_wait flowchart 491
Figure A.1 - CRC coverage and bit ordering 496
Figure A.2 - Word transmit order 496
Figure B.1 - Class 1 and 6 frame level protocol 501
Figure B.2 - Class 2 frame level protocol 503
Figure B.3 - Class 3 frame level protocol 504
Figure B.4 - Sequence level protocol example 506
Figure B.5 - Class 1 and 6 frame level protocol - Login example 508
Figure B.6 - Class 2 frame level protocol - Login example 509
Figure B.7 - Class 3 frame level protocol - Login example 510
Figure F.1 - Class 4 setup, activation and deactivation 521
Figure F.2 - Class 4 activation collision and circuit removal 523
Figure G.1 - Preemption Request 524
Figure G.2 - Connection Rejection 525
Figure G.3 - Preemption Accepted 525
Figure G.4 - Connection Established 525
Figure G.5 - Link Reset Diagram 526
Figure H.1 - Generic NL_Port 528
Figure H.2 - Server NL_Port Clock Sync Context 529
Figure H.3 - Client NL_Port Clock Sync Context 529
Figure H.4 - Server Clock Sync Implementation (Basic Approach) 530
Figure H.5 - Client Clock Sync Implementation (Basic Approach) 530
Figure H.6 - ELS Clock Sync Model - Point-to-Point 530
Figure H.7 - Client Clock Drift 531
Figure H.8 - Client Clock Sync Logic Model (Rate Adjusted) 538
Figure H.9 - Rate Adjustment Hardware Assists for Client Clock Sync 539
Figure H.10 - Client Clock Sync Implementation (Link Delay Fix) 539
Figure H.11 - Server Clock Sync Implementation (Unload Error Fix) 540
Figure H.12 - Client Clock Drift (Monotonic) 541
Figure H.13 - ELS Clock Sync Model – Fabric 542
Figure H.14 - ELS Clock Sync Model – Loop 545
Figure H.15 - Application of Clock Synchronization to Tactical Avionics 548
Figure I.1 - Three configurations supported by the speed negotiation requirements 551
Figure I.2 - Example worst case timing for t_fail 553
Figure I.3 - Example worst case timing for t_ncycl using Rx_LOS 554
Figure I.4 - Example worst case timing for t_ncinit using Pass sync_test 555
Figure I.5 - Example worst case timing for t_wake 556
Figure I.6 - Example of maximum single disruption, Wait_for_signal 557
Figure I.7 - Example of maximum single disruption, Slow_wait 558
Figure I.8 - Example of maximum single disruption, Negotiate_master 559
Figure I.9 - Example where hub is at maximum port speed 559
Figure I.10 - Example of maximum disruption group - Wait_for_signal 560
Figure I.11 - Example of maximum disruption group - Slow_wait 561
Figure I.12 - Example of maximum disruption group - Negotiate_master 562
Figure I.13 - Example of maximum single disruption overall 563
Figure I.14 - Physical architecture of a port with a separate transceiver component 565
Figure K.1 - Case Study 570

Table 1 - Comparison of ISO and American numbering conventions 51
Table 2 - Data rate abbreviations 51
Table 3 - Symbols 55
Table 4 - Bit designations 74
Table 5 - Conversion Example 75
Table 6 - Valid Data Characters 77
Table 7 - Valid Special Characters 81
Table 8 - Delayed Code Violation example 82
Table 9 - Frame Delimiters 84
Table 10 - Primitive Signals 85
Table 11 - Primitive Sequences 87
Table 12 - FC_Port states 96
Table 13 - Frame byte order 109
Table 14 - Frame_Header 111
Table 15 - R_CTL - Type Code Summary 112
Table 16 - Device_Data Information Categories 113
Table 17 - Data Descriptor Payload 113
Table 18 - FC-4 Link_Data Information Categories 113
Table 19 - Video_Data Information Categories 114
Table 20 - Extended Routing Information Categories 114
Table 21 - Domain Controller and Well-known address identifiers 115
Table 22 - CS_CTL field - Class 1 116
Table 23 - CS_CTL field - Class 2 116
Table 24 - CS_CTL field - Class 3 116
Table 25 - CS_CTL field - Class 4 117
Table 26 - Priority Field - Class 1 and Class 6 118
Table 27 - Priority Field 119
Table 28 - TYPE codes - Link Service 120
Table 29 - TYPE codes - Video_Data 120
Table 30 - TYPE codes - FC-4 (Device_Data and Link_Data) 121
Table 31 - Exchange/Sequence Control (F_CTL) 123
Table 32 - Continue Sequence Condition Bits Definition 127
Table 33 - Abort Sequence Condition Bits Definition by Sequence Initiator 128
Table 34 - Abort Sequence Condition Bits Definition by Sequence Recipient 129
Table 35 - F_CTL bit interactions on Data frames 130
Table 36 - F_CTL bit interactions on ACK, BSY or RJT 131
Table 37 - DF_CTL bit definition 132
Table 38 - ESP_Header and ESP_Trailer in a frame 138
Table 39 - Network_Header 138
Table 40 - Association_Header 139
Table 41 - Association_Header Validity bits (Word 0, Bits 31 to 24) 140
Table 42 - Allowable Data frame delimiters 142
Table 43 - ACK Frames by Class 144
Table 44 - Link_Response Frames by Class 144
Table 45 - Link_Control Information Categories 145
Table 46 - Link_Control frame delimiters 146
Table 47 - ACK precedence 147
Table 48 - F_BSY Reason Codes 150
Table 49 - P_BSY code format 151
Table 50 - P_BSY action codes 151
Table 51 - P_BSY Reason Codes 152
Table 52 - Reject Code format 153
Table 53 - Reject Action Codes 154
Table 54 - Reject Reason Codes 154

Table 55 - Basic Link Service Information Categories 164
Table 56 - ABTS Parameter Field Definitions 164
Table 57 - BA_ACC Payload 169
Table 58 - BA_RJT Payload Format 171
Table 59 - BA_RJT reason codes 171
Table 60 - BA_RJT Reason Code Explanation 172
Table 61 - Extended Link Routing Bits and Information Categories 174
Table 62 - ELS_Command codes 175
Table 63 - Responses to Received ELSs 177
Table 64 - ABTX Payload 179
Table 65 - Recovery Qualifier Values 180
Table 66 - ABTX LS_ACC Payload 180
Table 67 - ADVC Payload 181
Table 68 - ADVC LS_ACC Payload 182
Table 69 - ECHO Payload 183
Table 70 - ECHO LS_ACC Payload 183
Table 71 - ESTC Payload 184
Table 72 - ESTS Payload 185
Table 73 - ESTS LS_ACC Payload 185
Table 74 - LOGO Payload 187
Table 75 - LOGO LS_ACC Payload 187
Table 76 - RCS Payload 188
Table 77 - RCS LS_ACC Payload 188
Table 78 - Connection Status Codes 189
Table 79 - RES Payload 190
Table 80 - RES LS_ACC Payload 190
Table 81 - RLS Payload 191
Table 82 - RLS LS_ACC Payload 191
Table 83 - RSS Payload 192
Table 84 - RSS LS_ACC Payload 192
Table 85 - RTV Payload 193
Table 86 - RTV LS_ACC Payload 193
Table 87 - RRQ Payload 195
Table 88 - RRQ LS_ACC Payload 195
Table 89 - RSI Payload 196
Table 90 - RSI LS_ACC Payload 196
Table 91 - TEST Payload 197
Table 92 - FAN Payload 198
Table 93 - LINIT Payload 199
Table 94 - Initialization Function 199
Table 95 - LINIT LS_ACC Payload 199
Table 96 - LINIT Status 199
Table 97 - LSTS Payload 200
Table 98 - LSTS LS_ACC Payload 200
Table 99 - FC-FLA Compliance Level 201
Table 100 - Loop State 202
Table 101 - RSCN Payload 204
Table 102 - Generic affected Port_ID page 204
Table 103 - RSCN Event Qualifier values 205
Table 104 - Address Format 205
Table 105 - RSCN LS_ACC Payload 206
Table 106 - SCR Payload 206
Table 107 - Registration Function 207
Table 108 - SCR LS_ACC Payload 207
Table 109 - PRLI Payload 208
Table 110 - PRLI service parameter page format 208
Table 111 - PRLI LS_ACC Payload 209

Table 112 - PRLI LS_ACC service parameter response page format 210
Table 113 - PRLI accept response code 211
Table 114 - PRLO Payload 212
Table 115 - PRLO logout parameter page format 213
Table 116 - PRLO LS_ACC Payload 214
Table 117 - PRLO LS_ACC logout parameter response page format 215
Table 118 - PRLO accept response code 216
Table 119 - TPLS Payload 217
Table 120 - TPLS image pair ID page format 217
Table 121 - TPLS LS_ACC Payload 218
Table 122 - TPLS response page format 219
Table 123 - TPLS accept response code 220
Table 124 - FARP_REQ Request Payload Item 221
Table 125 - FARP_REQ Match Address Code Points 223
Table 126 - FARP_REQ Address Fields 224
Table 127 - Responder Action 224
Table 128 - FARP_REPLY Request Payload 225
Table 129 - FARP_REPLY Address Fields 227
Table 130 - FARP_REPLY LS_ACC Payload 227
Table 131 - RNID Payload 228
Table 132 - Node Identification Data Format 228
Table 133 - RNID Accept Payload 229
Table 134 - Node Identification Data Format 229
Table 135 - Common Identification Data 230
Table 136 - General Topology Specific Identification Data 231
Table 137 - Associated Type 232
Table 138 - Multi-function device bit definitions 233
Table 139 - Node Management 233
Table 140 - IP Version 234
Table 141 - RLIR Payload 236
Table 142 - Link Incident Record Format 236
Table 143 - Common Link Incident Record Data 237
Table 144 - Time Stamp Format values 238
Table 145 - Incident Qualifier 239
Table 146 - Incident Code values 240
Table 147 - RLIR LS_ACC Payload 241
Table 148 - LIRR Payload 242
Table 149 - Registration Function 243
Table 150 - Link Incident Record-Registration Format 243
Table 151 - LIRR LS_ACC Payload 243
Table 152 - Get Alias_ID Payload 244
Table 153 - Get Alias_ID LS_ACC Payload 245
Table 154 - Fabric Activate Alias_ID Payload 246
Table 155 - Fabric Activate Alias_ID LS_ACC Payload 246
Table 156 - Fabric Deactivate Alias_ID Payload 247
Table 157 - Fabric Deactivate Alias_ID LS_ACC Payload 247
Table 158 - N_Port Activate Alias_ID Payload 248
Table 159 - N_Port Activate Alias_ID LS_ACC Payload 249
Table 160 - N_Port Deactivate Alias_ID Payload 249
Table 161 - N_Port Deactivate Alias_ID LS_ACC Payload 250
Table 162 - QoSR Payload 251
Table 163 - QoSR LS_ACC Payload 253
Table 164 - RVCS Payload 255
Table 165 - RVCS LS_ACC Payload 255
Table 166 - Class 4 VC Status Block entry 255
Table 167 - ADISC Payload 257
Table 168 - ADISC LS_ACC Payload 257

Table 169 - Response summary to FDISC/PDISC 258
Table 170 - TPRLO Payload 259
Table 171 - TPRLO logout parameter page format 259
Table 172 - TPRLO LS_ACC Payload 259
Table 173 - LCLM Payload 263
Table 174 - LCLM Commands 264
Table 175 - Global capabilities 264
Table 176 - N_Port and node Name Field Values 264
Table 177 - LCLM LS_ACC Payload 265
Table 178 - Global capabilities 265
Table 179 - RPS Payload 266
Table 180 - Flag field bit definitions 267
Table 181 - RPS LS_ACC Payload 267
Table 182 - Flag field bit definitions 267
Table 183 - Port Status 268
Table 184 - L_Port_Extension 268
Table 185 - L_Port Status 269
Table 186 - RPL Payload 270
Table 187 - Maximum Size values 270
Table 188 - RPL LS_ACC Payload 271
Table 189 - Port Number Block 271
Table 190 - RPBC Payload 272
Table 191 - ELS Buffer Parameters Field 272
Table 192 - RPL LS_ACC Payload 273
Table 193 - RNFT Payload 273
Table 194 - RNFT LS_ACC Payload 274
Table 195 - RNFT FC-4 Entry 274
Table 196 - SRL Payload 275
Table 197 - Flag field definitions 276
Table 198 - SRL LS_ACC Payload 276
Table 199 - SBRP Payload 277
Table 200 - SBRP LS_ACC Payload 279
Table 201 - RPSC Payload 280
Table 202 - RPSC LS_ACC Payload 280
Table 203 - REC Payload 281
Table 204 - REC LS_ACC Payload 282
Table 205 - LS_RJT Reason Codes 284
Table 206 - LS_RJT Reason Code Explanation 285
Table 207 - NAA identifiers 304
Table 208 - IEEE 48-bit address format 304
Table 209 - IEEE extended format 305
Table 210 - Locally assigned format 306
Table 211 - 32-bit IP address format 306
Table 212 - IEEE Registered 306
Table 213 - IEEE Registered Extended 307
Table 214 - EUI-64 Mapped Name_Identifier Format 308
Table 215 - Bit Position Map 308
Table 216 - FLOGI, PLOGI or LS_ACC Payload 318
Table 217 - Common Service Parameter applicability 319
Table 218 - Common Service Parameters - FLOGI 320
Table 219 - Common Service Parameters - PLOGI and PLOGI LS_ACC 321
Table 220 - Common Service Parameters - FLOGI LS_ACC 321
Table 221 - Clock Synchronization Applicability 324
Table 222 - Class Service Parameters Applicability 326
Table 223 - Class Service Parameters - FLOGI 328
Table 224 - Class Service Parameters - PLOGI and PLOGI LS_ACC 329
Table 225 - Class Service Parameters - FLOGI LS_ACC 329

Table 226 - Intermix Mode Support 330
Table 227 - Stacked Connect-request support Login Bits 330
Table 228 - Sequential delivery support 331
Table 229 - Fabric Login Priority and Preemption Support 331
Table 230 - Class 2 and 3 Preference Bit Function 332
Table 231 - Relationship between Preferred delivery and sequential delivery 333
Table 232 - DiffServ QoS bit definition 334
Table 233 - Initial Process_Associator Bits Definition 334
Table 234 - ACK_0 Support Conditions (Initiator Control) 335
Table 235 - ACK_0 Support Conditions (Recipient Control) 336
Table 236 - Error Policy Bits Definition 337
Table 237 - Categories per Sequence Bits Definition 338
Table 238 - Concurrent Sequences field meaning 339
Table 239 - End-to-end Credit Field Meaning 339
Table 240 - Login Extension Page format 342
Table 241 - Page Code Definitions 342
Table 242 - Vendor Specific Page format 342
Table 243 - N_Port Clock Synchronization QoS 343
Table 244 - FLOGI/PLOGI CS_QoS_Request 343
Table 245 - Fx_Port Clock Synchronization QoS 345
Table 246 - Exchange Status Block 370
Table 247 - Sequence Status Block 372
Table 248 - Flow control applicability 374
Table 249 - Buffer participation 375
Table 250 - End-to-end flow control management 377
Table 251 - Buffer-to-buffer flow control management 385
Table 252 - Integrated Class 2 flow control management 396
Table 253 - Segmentation and reassembly rules summary 401
Table 254 - Responses to connect-request (SOFc1) 408
Table 255 - Responses to Preemption Requests 415
Table 256 - Link Error Status Block format for RLS command 431
Table 257 - Detailed errors and actions 432
Table 258 - Address Resolution 438
Table 259 - Bandwidth Allocation Example 453
Table 260 - Frame delimiter usage 461
Table 261 - CSR Payload 472
Table 262 - CSR Clock Sync Mode Meaning 472
Table 263 - CSR LS_ACC Payload 473
Table 264 - CSU Clock Sync Mode Meaning 473
Table 265 - CSU Payload 474
Table 266 - Clock Count Field Meaning 475
Table 267 - Neutral Disparity Character Values 477
Table 268 - Timing parameters with a range 493
Table 269 - Constant timing parameters 493
Table A.1 - Sample FC-2 frame 497
Table A.2 - Sample ACK_1 without CRC 497
Table A.3 - F(x) 497
Table A.4 - X**32 F(x) + X**k L(x) 498
Table A.5 - R(x) 498
Table A.6 - L(x) + R(x) = R$(x) 498
Table A.7 - M(x) 498
Table A.8 - M(x) - (10B) 499
Table B.1 - F_CTL for Class 1, Class 2, and Class 6 frame level protocols 505
Table B.2 - F_CTL for Class 3 frame level protocol 505
Table B.3 - Sequence level protocol example 507
Table C.1 - Case 1 511
Table C.2 - Case 2 511

Table C.3 - Case 3 512
Table C.4 - Case 4 512
Table C.5 - F_CTL for example Exchange 513
Table E.1 - Link Failure Counters and management 517
Table H.1 - Parameters used in analysis 532
Table H.2 - Example of analysis results 532
Table H.3 - Parameters used in analysis 533
Table H.4 - Parameters used in analysis 534
Table H.5 - Parameters used in analysis 535
Table H.6 - Parameters used in analysis 536
Table H.7 - Parameters used in analysis 543
Table H.8 - Example of analysis results 543
Table H.9 - Parameters used in analysis 546
Table K.1 - IEEE 48 bit address WWN format 568
Table K.2 - Mapped EUI-64 address 568
Table K.3 - IEEE Extended WWN format 569
Table K.4 - Mapped EUI-64 address 569
Table K.5 - IEEE Registered WWN format 569
Table K.6 - Mapped EUI-64 address 569