ISO/IEC 29341-8-12:2008-11 (E)

Information technology_- UPnP Device Architecture_- Part_8-12: Internet Gateway Device Control Protocol_- Link Authentication Service

CONTENTS

FOREWORD 4
ORIGINAL UPNP DOCUMENTS (informative) 6
1. Overview and Scope 8
2. Service Modeling Definitions 9
2.1. ServiceType 9
2.2. State Variables 9
2.2.1. NumberOfEntries 9
2.2.2. Identifier 9
2.2.3. Secret 10
2.2.4. SecretType 10
2.2.5. AuthType 11
2.2.6. AuthState 11
2.2.7. CredentialState 12
2.2.8. Description 12
2.2.9. MACAddress 12
2.2.10. CredentialDuration 13
2.2.11. LinkedIdentifier 13
2.2.12. LastChange 13
2.2.13. LastError 14
2.3. Eventing and Moderation 14
2.3.1. Event Model 14
2.4. Actions 16
2.4.1. GetGenericEntry 17
2.4.2. GetSpecificEntry 18
2.4.3. AddEntry 19
2.4.4. UpdateEntry 20
2.4.5. DeleteEntry 21
2.4.6. GetNumberOfEntries 22
2.4.7. FactoryDefaultReset 22
2.4.8. ResetAuthentication 23
2.4.9. Common Error Codes 23
2.5. Theory of Operation 24
2.5.1. 802.1x introduction 24
2.5.2. High level intended operation 24
2.5.3. Detailed level operation 25
2.5.4. Record format 26
2.5.5. Example using client certificate credentials 27
2.5.6. Limitations on Pending Records 27
3. XML Service Description 28
4. Test 33

LIST OF TABLES

Table 1: State Variables 9
Table 1.1: allowedValueList for `SecretType` 10
Table 1.2: allowedValueList for `AuthType` 11
Table 1.3: allowedValueList for `AuthState` 11
Table 1.4: allowedValueList for `CredentialState` 12
Table 2: Event Moderation 14
Table 3: Actions 16
Table 4: Arguments for `GetGenericEntry` 17
Table 5: Arguments for `GetSpecificEntry` 18
Table 6: Arguments for `AddEntry` 19
Table 7: Arguments for `UpdateEntry` 20
Table 8: Arguments for `DeleteEntry` 21
Table 9: Arguments for `GetNumberOfEntries` 22
Table 10: Common Error Codes 23