

ISO/IEC 29341-8-12:2008-11 (E)

Information technology_ - UPnP Device Architecture_ - Part_8-12: Internet Gateway Device Control Protocol_ - Link Authentication Service

CONTENTS

FOREWORD	4
ORIGINAL UPNP DOCUMENTS (informative)	6
1. Overview and Scope	8
2. Service Modeling Definitions	9
2.1. ServiceType	9
2.2. State Variables	9
2.2.1. NumberOfEntries	9
2.2.2. Identifier	9
2.2.3. Secret	10
2.2.4. SecretType	10
2.2.5. AuthType	11
2.2.6. AuthState	11
2.2.7. CredentialState	12
2.2.8. Description	12
2.2.9. MACAddress	12
2.2.10. CredentialDuration	13
2.2.11. LinkedIdentifier	13
2.2.12. LastChange	13
2.2.13. LastError	14
2.3. Eventing and Moderation	14
2.3.1. Event Model	14
2.4. Actions	16
2.4.1. GetGenericEntry	17
2.4.2. GetSpecificEntry	18
2.4.3. AddEntry	19
2.4.4. UpdateEntry	20
2.4.5. DeleteEntry	21
2.4.6. GetNumberOfEntries	22
2.4.7. FactoryDefaultReset	22
2.4.8. ResetAuthentication	23
2.4.9. Common Error Codes	23
2.5. Theory of Operation	24
2.5.1. 802.1x introduction	24
2.5.2. High level intended operation	24
2.5.3. Detailed level operation	25
2.5.4. Record format	26
2.5.5. Example using client certificate credentials	27
2.5.6. Limitations on Pending Records	27
3. XML Service Description	28
4. Test	33

LIST OF TABLES

Table 1: State Variables	9
Table 1.1: allowedValueList for SecretType.....	10
Table 1.2: allowedValueList for AuthType.....	11
Table 1.3: allowedValueList for AuthState.....	11
Table 1.4: allowedValueList for CredentialState.....	12
Table 2: Event Moderation	14
Table 3: Actions	16
Table 4: Arguments for GetGenericEntry	17
Table 5: Arguments for GetSpecificEntry	18
Table 6: Arguments for AddEntry.....	19
Table 7: Arguments for UpdateEntry	20
Table 8: Arguments for DeleteEntry	21
Table 9: Arguments for GetNumberOfEntries.....	22
Table 10: Common Error Codes	23