

ISO/IEC 29341-8-13:2008-11 (E)

Information technology_ - UPnP Device Architecture_ - Part_8-13: Internet Gateway Device Control Protocol_ - Radius Client Service

CONTENTS

FOREWORD	3
ORIGINAL UPNP DOCUMENTS (informative)	5
1. Overview and Scope	7
2. Service Modeling Definitions	7
2.1. ServiceType	7
2.2. State Variables	7
2.2.1. NumberOfAuthServerEntries	7
2.2.2. AuthServerIPAddress	8
2.2.3. AuthServerPortNumber	8
2.2.4. AuthServerSharedSecret	8
2.3. Eventing and Moderation	8
2.3.1. Event Model	8
2.4. Actions	8
2.4.1. GetGenericAuthServerEntry	9
2.4.2. GetSpecificAuthServerEntry	9
2.4.3. AddAuthServerEntry	10
2.4.4. DeleteAuthServerEntry	11
2.4.5. FactoryDefaultReset	11
2.4.6. ResetAuthentication	11
2.4.7. Non-Standard Actions Implemented by a UPnP Device Vendor	12
2.4.8. Common Error Codes	12
2.5. Theory of Operation	12
2.5.1. Operation of the RADIUS Client	12
3. XML Service Description	13
4. Test	15

LIST OF TABLES

Table 1: State Variables	7
Table 2: Event Moderation	8
Table 3: Actions	8
Table 4: Arguments for GetGenericAuthServerEntry	9
Table 5: Arguments for GetSpecificAuthServerEntry	9
Table 6: Arguments for AddAuthServerEntry	10
Table 7: Arguments for DeleteAuthServerEntry	11
Table 8: Common Error Codes	12