

ISO/IEC 29341-8-13:2008-11 (E)

Information technology_ - UPnP Device Architecture_ - Part_8-13: Internet Gateway Device Control Protocol_ - Radius Client Service

CONTENTS

- FOREWORD 3
- ORIGINAL UPNP DOCUMENTS (informative) 5
- 1. Overview and Scope 7**
- 2. Service Modeling Definitions 7**
 - 2.1. ServiceType 7
 - 2.2. State Variables 7
 - 2.2.1. NumberOfAuthServerEntries 7
 - 2.2.2. AuthServerIPAddress 8
 - 2.2.3. AuthServerPortNumber 8
 - 2.2.4. AuthServerSharedSecret 8
 - 2.3. Eventing and Moderation 8
 - 2.3.1. Event Model 8
 - 2.4. Actions 8
 - 2.4.1. GetGenericAuthServerEntry 9
 - 2.4.2. GetSpecificAuthServerEntry 9
 - 2.4.3. AddAuthServerEntry 10
 - 2.4.4. DeleteAuthServerEntry 11
 - 2.4.5. FactoryDefaultReset 11
 - 2.4.6. ResetAuthentication 11
 - 2.4.7. Non-Standard Actions Implemented by a UPnP Device Vendor 12
 - 2.4.8. Common Error Codes 12
 - 2.5. Theory of Operation 12
 - 2.5.1. Operation of the RADIUS Client 12
- 3. XML Service Description 13**
- 4. Test 15**

LIST OF TABLES

- Table 1: State Variables 7
- Table 2: Event Moderation 8
- Table 3: Actions 8
- Table 4: Arguments for GetGenericAuthServerEntry 9
- Table 5: Arguments for GetSpecificAuthServerEntry 9
- Table 6: Arguments for AddAuthServerEntry 10
- Table 7: Arguments for DeleteAuthServerEntry 11
- Table 8: Common Error Codes 12