

ISO/IEC 29341-8-16:2008-11 (E)

Information technology_ - UPnP Device Architecture_ - Part_ 8-16: Internet Gateway Device Control Protocol_ - Wide Area Network Digital Subscriber Line Configuration Service

CONTENTS

FOREWORD	4
ORIGINAL UPNP DOCUMENTS (informative)	6
1. Overview and Scope	8
2. Service Modeling Definitions	9
2.1. ServiceType	9
2.2. State Variables	9
2.2.1. LinkType	10
2.2.2. LinkStatus	11
2.2.3. AutoConfig	11
2.2.4. ModulationType	11
2.2.5. DestinationAddress	11
2.2.6. ATMEncapsulation	11
2.2.7. FCSPreserved	11
2.2.8. Relationships Between State Variables	11
2.3. Eventing and Moderation	12
2.3.1. Event Model	12
2.4. Actions	13
2.4.1. SetDSLLinkType	13
2.4.2. GetDSLLinkInfo	14
2.4.3. GetAutoConfig	14
2.4.4. GetModulationType	15
2.4.5. SetDestinationAddress	15
2.4.6. GetDestinationAddress	16
2.4.7. SetATMEncapsulation	16
2.4.8. GetATMEncapsulation	17
2.4.9. SetFCSPreserved	17
2.4.10. GetFCSPreserved	18
2.4.11. Non-Standard Actions Implemented by a UPnP Vendor	18
2.4.12. Relationships Between Actions	18
2.4.13. Common Error Codes	18
2.5. Theory of Operation	19
3. XML Service Description	20
4. Test	23

LIST OF TABLES

Table 1: State Variables	9
Table 1.1: AllowedValueList for LinkType	10
Table 1.2: AllowedValueList for LinkStatus	10
Table 1.3: AllowedValueList for ModulationType	10
Table 1.4: AllowedValueList for ATMEncapsulation	10
Table 2: Event Moderation.....	12
Table 3: Actions	13
Table 4: Arguments for SetDSLLinkType.....	13
Table 5: Arguments for GetDSLLinkInfo.....	14
Table 6: Arguments for GetAutoConfig.....	14
Table 7: Arguments for GetModulationType	15
Table 8: Arguments for SetDestinationAddress	15
Table 9: Arguments for GetDestinationAddress	16
Table 10: Arguments for SetATMEncapsulation.....	16
Table 11: Arguments for GetATMEncapsulation.....	17
Table 12: Arguments for SetFCSPreserved	17
Table 13: Arguments for GetFCSPreserved	18
Table 14: Common Error Codes.....	18