ISO/IEC 14165-133:2010-02 (E)

Information technology – Fibre channnel – Part 133: Fibre channel switch fabric-3 (FC-SW-3)

Contents

FOREWORD 13

Introduction 15

1 Scope 16

2 Normative references 16

3 Terms and conventions. 17
3.1 Terms and definitions 17
3.2 Abbreviations, acronyms, and symbols 25
3.3 Editorial conventions 26
3.4 State machine notation. 27
3.5 Definition of Compliance Terms 27
3.6 Keywords 28

4 Structure and Concepts 30
4.1 Overview 30
4.2 E_Port Operation 30
4.3 Fabric Operation. 30
4.4 Fabric Definition 31
4.5 Switch. 31
4.6 Switching characteristics 33
4.6.1 Switching overview 33
4.6.2 Synchronous switching 33
4.6.3 Asynchronous switching 33
4.7 Switch Ports and Bridge Ports 34
4.7.1 General Characteristics 34
4.7.2 F_Port 34
4.7.3 FL_Port 34
4.7.4 E_Port 34
4.7.4 B_Port 35
4.7.5 G_Ports and GL_Ports 35
4.8 Fabric Addressing 35
4.9 Class F Service 36
4.10 FSPF-Backbone Fabric 37

5 Switch Ports and Bridge Ports 38
5.1 Overview 38
5.2 Model elements 38
5.2.1 FC Transports 38
5.2.2 Switch Transport 38
5.2.3 Control Facilities 38
5.2.4 Link Services 39
5.3 F_Port Operation 39
5.4 FL_Port Operation 40
5.5 E_Port Operation 41
5.6 B_Port operation 43
5.7 Inter-Switch Link Behavior 44
5.8 Class F Service 45
5.8.1 Class F Function 45
5.8.2 Class F Rules 45

5.8.3 Class F Frame Format 47
5.8.4 Class F Flow Control 48

6 Internal Link Services 49
6.1 Switch Fabric Internal Link Services (SW_ILS) 49
6.1.1 SW_ILS overview 49
6.1.2 Switch Fabric Internal Link Service Accept (SW_ACC) 50
6.1.3 Switch Fabric Internal Link Service Reject (SW_RJT) 51
6.1.4 Exchange Link Parameters (ELP) 54
6.1.5 Exchange Fabric Parameters (EFP) 60
6.1.6 Domain Identifier Assigned (DIA) 64
6.1.7 Request Domain_ID (RDI) 65
6.1.8 Hello (HLO) 67
6.1.8.1 HLO overview 67
6.1.8.2 FSPF Header Format 69
6.1.9 Link State Update (LSU) 70
6.1.9.1 LSU overview 70
6.1.9.2 Link-State Record (LSR) Format 71
6.1.9.3 Link State Header Format 72
6.1.9.4 Link Descriptor Format 74
6.1.9.5 Summary Descriptor Format 75
6.1.10 Link State Acknowledgement (LSA) 75
6.1.11 Build Fabric (BF) 76
6.1.12 Reconfigure Fabric (RCF) 77
6.1.13 Inter-Switch Registered State Change Notification (SW_RSCN) 78
6.1.14 Distribute Registered Link Incident Records (DRLIR) 81
6.1.15 Disconnect Class 1 Connection (DSCN) 82
6.1.16 Merge Request (MR) 83
6.1.16.1 MR overview 83
6.1.16.2 Merge Request Payload 84
6.1.16.2.1 Merge Request Payload overview 84
6.1.16.2.2 Merge Request Payload in Basic Zoning 85
6.1.16.2.3 Merge Request Payload in Enhanced Zoning 86
6.1.16.3 Merge Request Reply 87
6.1.17 Acquire Change Authorization Request (ACA) 87
6.1.18 Release Change Authorization (RCA) Request 89
6.1.19 Stage Fabric Configuration Update (SFC) Request 90
6.1.19.1 SFC overview 90
6.1.19.2 SFC in Basic Zoning 92
6.1.19.3 SFC in Enhanced Zoning 93
6.1.19.3.1 Overview 93
6.1.19.3.2 Operation Request ‘Activate Zone Set Enhanced’ 93
6.1.19.3.3 Operation Request ‘Deactivate Zone Set Enhanced’ 93
6.1.19.3.4 Operation Request ‘Distribute Zone Set Database’ 94
6.1.19.3.5 Operation Request ‘Activate Zone Set by Name’ 94
6.1.19.3.6 Operation Request ‘Set Zoning Policies’ 95
6.1.20 Update Fabric Configuration (UFC) Request 95
6.1.21 Exchange Switch Capabilities 96
6.1.22 Exchange Switch Support (ESS) 99
6.1.22.1 ESS overview 99
6.1.22.2 ESS Request Payload 99
6.1.22.3 Interconnect Element Information Object 100
6.1.22.4 Capability Object 100
6.1.22.5 Service Specific Capability Formats 100

6.1.22.5.1 Directory Server Capability 100
6.1.22.5.2 Fabric Controller Capability 101
6.1.22.5.3 ESS Fabric Configuration Server Capability Object 102
6.1.22.5.4 ESS Enhanced Zone Server Capability Object 102
6.1.22.5.5 ESS-Vendor Specific Capability Object 103
6.1.22.6 ESS Accept Payload 104
6.1.23 Merge Request Resource Allocation (MRRA) 104

7 Fabric Configuration 107
7.1 Fabric Configuration Summary 107
7.2 Switch Port Initialization 107
7.2.1 Basic Operation 107
7.2.2 Exchange Switch Capabilities Processing 116
7.3 Principal Switch Selection 117
7.4 Address Distribution 123
7.4.1 Address Distribution overview 123
7.4.2 Domain_ID Distribution by the Principal Switch 125
7.4.3 Domain_ID Requests by the Switches 127
7.5 E_Port and Fabric Isolation 130
7.6 B_Port Operation 131
7.6.1 Differences Between E_Ports and B_Ports 131
7.6.2 B_Port Internal Link Services 131
7.6.3 B_Port Initialization 132
7.6.4 Example B_Port Configuration 132

8 Fabric Shortest Path First (FSPF) 133
8.1 Overview 133
8.1.1 Basic Components 133
8.1.2 Fabric connectivity 133
8.1.3 Addressing 133
8.1.4 Path Selection and Routing 134
8.1.5 Hierarchical Path Selection 134
8.1.6 FSPF Path Selection Summary 134
8.2 FSPF Message Processing 134
8.2.1 Message transmission 134
8.2.2 Message Reception and Tests 135
8.3 Hello Protocol 135
8.3.1 Basic Functions 135
8.3.2 Hello Message Transmission 135
8.3.3 Hello Message Parameters 136
8.3.4 Hello Message Reception 136
8.4 The Topology Database 137
8.5 Usage of LSR Fields 137
8.5.1 LSR Age 137
8.5.2 LSR Incarnation Number 138
8.5.3 LSR Instance Rules 138
8.5.4 LSR Checksum 139
8.5.5 Link Cost 141
8.6 Topology Database Synchronization 141
8.6.1 Synchronization overview 141
8.6.2 Neighborhood and Adjacency 142
8.6.3 Continuous Topology Database Synchronization 143
8.6.4 Reliable Flooding 144
8.6.4.1 Basic Operation 144

8.6.4.2 The Flooding Procedure . . . 144
8.6.4.3 Generating a New LSR . . . 144
8.6.4.4 Transmitting an LSR . . . 145
8.6.4.5 Receiving an LSR . . . 145
8.7 Neighbor Finite State Machine (FSM) . . . 146
8.8 FSPF-Backbone . . . 149
8.8.1 FSPF-Backbone overview . . . 149
8.8.2 Multiple Switch Connections . . . 152
8.8.3 FSPF-Backbone Point-to-point Links . . . 154
8.8.4 FSPF-Backbone Routing Protocol . . . 154

9 Distributed Services . . . 156
9.1 Basic Model . . . 156
9.2 Distributed Services Framework . . . 156
9.2.1 Goals and Characteristics of the Distributed Services Framework . . . 156
9.2.2 Distributed Service Transport . . . 156
9.2.2.1 Required FC-2 Parameters . . . 156
9.2.2.2 FC-CT Header Usage . . . 157
9.2.2.3 Frame Distribution . . . 157
9.2.3 Common Characteristics . . . 157
9.2.4 Zoning Considerations . . . 158
9.2.5 Work Categories . . . 158
9.2.6 Frame Formats . . . 159
9.2.7 FC-CT Command Restrictions . . . 159
9.3 Distributed Name Server . . . 159
9.3.1 General Behavior . . . 159
9.3.2 FC-CT for Distributed Name Servers . . . 160
9.3.2.1 dNS Command Codes . . . 160
9.3.2.2 FC-CT Header usage for dNS . . . 164
9.3.3 Name Server Objects . . . 164
9.3.4 FC-CT requests for dNS . . . 167
9.3.4.1 Remove All . . . 167
9.3.4.2 Get Entry based on Port Identifier . . . 167
9.3.4.3 Get Entry based on Port_Name . . . 168
9.3.4.4 Get Entries based on Node_Name . . . 169
9.3.4.5 Get Entries based on IP address (Node) . . . 169
9.3.4.6 Get Entries based on FC-4 TYPEs . . . 170
9.3.4.7 Get Entries based on Port Type . . . 171
9.3.4.8 Get Entries based on Zone Member . . . 171
9.3.4.9 Get Entries based on Zone Name . . . 172
9.3.4.10 Get Entries based on Port IP Address . . . 173
9.3.4.11 Get Entries based on FC-4 Features . . . 173
9.3.4.12 Get Entries based on Fabric Port_Name . . . 174
9.4 Distributed Management Server . . . 175
9.4.1 General Behavior . . . 175
9.4.2 FC-CT Header . . . 175
9.4.2.1 FC-CT Header Parameters . . . 175
9.4.2.2 FC-CT Header Rule for Fabric Internal Requests . . . 175
9.4.3 Fabric Configuration Service . . . 176
9.4.4 Unzoned Name Service . . . 178
9.4.5 Fabric Zone Service . . . 178
9.4.6 Fabric-Device Management Service . . . 178
9.4.6.1 Operational Characteristics of the FDMI Server . . . 178
9.4.6.2 Registration Scenarios . . . 179

9.4.6.2.1 HBA Attached to a Single Switch . . . 179
9.4.6.2.2 HBA Attached to Multiple Switches . . . 179
9.4.6.2.3 Resolution of the Principal HBA Manager . . . 179
9.4.6.3 FDMI Inter-Switch Messages . . . 180
9.4.6.3.1 General Format . . . 180
9.4.6.3.2 FC-CT Header . . . 180
9.4.6.3.3 FDMI Header . . . 180
9.4.6.3.4 Payload . . . 181
9.4.6.4 FDMI Inter-Switch Requests . . . 181
9.4.6.5 FDMI Inter-Switch Responses . . . 182
9.4.6.5.1 Reject Response . . . 182
9.4.6.5.2 Accept Response . . . 182
9.4.6.6 FDMI Inter-Switch Operations . . . 182
9.4.6.6.1 Registration Notification (FRN) Operation . . . 182
9.4.6.6.2 De-Register Notification (FDRN) Operation . . . 182
9.4.6.6.3 Update Notification (FUN) Operation . . . 183
9.4.6.6.4 Update Forward (FUF) Operation . . . 183
9.4.6.6.5 De-Register Forward (FDRF) Operation . . . 183
9.4.6.6.6 Fetch . . . 183
9.4.6.7 GS Client Initiated FDMI Requests . . . 184
9.4.7 Other Fabric Internal Services . . . 185
9.4.7.1 Fabric Internal Requests . . . 185
9.4.7.2 Get Management Server Capabilities (GCAP) Operation . . . 186
9.4.7.2.1 Overview . . . 186
9.4.7.2.2 Capability Entry . . . 186
9.4.7.2.3 Subtype Capability Bit Masks . . . 187

10 Switch Zone Exchange and Merge . . . 188
10.1 Overview . . . 188
10.2 Joining Switches . . . 188
10.3 Enhanced Zoning Support Determination . . . 188
10.4 Zoning Framework and Data Structures . . . 189
10.4.1 Basic Zoning Framework . . . 189
10.4.2 Basic Zoning Data Structures . . . 193
10.4.2.1 Zoning Object List . . . 193
10.4.2.2 Zoning Object Format . . . 193
10.4.2.3 Name Entry Format . . . 194
10.4.2.4 Zone Member Format . . . 195
10.4.3 Enhanced Zoning Framework . . . 196
10.4.3.1 Introduction . . . 196
10.4.3.2 Zone Set Database . . . 196
10.4.3.3 Active Zone Set . . . 198
10.4.4 Enhanced Zoning Data Structures . . . 199
10.4.4.1 Zoning Object List . . . 199
10.4.4.2 Zoning Object Types . . . 199
10.4.4.3 Zone Set Object . . . 200
10.4.4.3.1 Zone Set Object in the Zone Set Database . . . 200
10.4.4.3.2 Zone Set Object in the Active Zone Set . . . 201
10.4.4.4 Zone Reference Object . . . 201
10.4.4.5 Zone Object in the Zone Set Database . . . 202
10.4.4.6 Zone Object in the Active Zone Set . . . 203
10.4.4.6.1 Overview . . . 203
10.4.4.6.2 Zone Member Format . . . 204
10.4.4.7 Zone Alias Object . . . 205

10.4.4.8 Zone Attribute Object . . . 206
10.4.4.8.1 Overview . . . 206
10.4.4.8.2 Zone Attribute Entry Format . . . 207
10.5 Merge Zone . . . 211
10.5.1 Example Merge Operation . . . 211
10.5.2 Merge Zone Rules . . . 213
10.5.2.1 Merge Rules in Basic Zoning . . . 213
10.5.2.2 Merge Rules in Enhanced Zoning . . . 214
10.6 Fabric Management Session Protocol . . . 215
10.6.1 Fabric Management Session Protocol overview . . . 215
10.6.2 Reserving Fabric Change Authorization . . . 216
10.6.3 Staging the Fabric Configuration . . . 216
10.6.4 Updating the Fabric Configuration . . . 217
10.6.5 Releasing Fabric Change Authorization . . . 217
10.6.6 Mapping of a GS Session to a Fabric Session . . . 217
10.6.7 Fabric Behavior to Handle the CT SFEZ Request . . . 219

11 Distributed broadcast . . . 220
11.1 Overview . . . 220
11.2 Spanning tree . . . 220
11.2.1 Overview . . . 220
11.2.2 Spanning tree example . . . 220

12 Timers and Constants . . . 222
12.1 General Timers and Constants . . . 222
12.2 SW_ILS Time-Out Values . . . 223

Annex A (informative) Examples of Switch Port Initialization . . . 224
A.1 Overview . . . 224
A.2 Example 1: two E/F/FL_Port-capable Switch Ports . . . 224
A.3 Example 2: two E/F/FL_Port-capable Switch Ports and one Nx_Port . . . 225
A.4 Example 3: one E/F/FL_Port-capable Port and one E/F_Port-capable Port . . . 226

Annex B (informative) ELP Negotiation Example . . . 227
B.1 Overview . . . 227
B.2 ELP Exchange Protocol . . . 227
B.2.1 General . . . 227
B.2.2 ELP Exchange without Parameter Negotiation . . . 227
B.2.3 ELP Exchange with Parameter Negotiation . . . 228
B.3 Summary of Responses to ELP . . . 231

Annex C (informative) Fabric Device Management interface-Sample Flows . . . 232
C.1 Overview . . . 232
C.2 Sample Flows . . . 232
C.2.1 HBA Registration - Single Switch . . . 232
C.2.2 HBA Registration - Multiple Switches - Caches Updated . . . 232
C.2.3 HBA Registration - Multiple Switches - Caches Not Updated . . . 233
C.2.4 HBA De-Registration - Primary HBA Manager . . . 235
C.2.5 HBA De-Registration - Non-Primary HBA Manager . . . 236

Bibliography . . . 237

Figures

Figure 1 State Machine Example . . . 27
Figure 2 Switch Model . . . 31
Figure 3 Multiple Switch Fabric Example . . . 32
Figure 4 Domain, Area, and Port Address Partitioning . . . 35
Figure 5 F_Port Model . . . 39
Figure 6 FL_Port Model . . . 41
Figure 7 E_Port Model . . . 42
Figure 8 B_Port Model . . . 43
Figure 9 Principal Inter-Switch Links . . . 45
Figure 10 Class F Frame Format . . . 47
Figure 11 Switch Port Mode Initialization State Machine . . . 108
Figure 12 Switch Port Mode Initialization State Machine - Continued . . . 109
Figure 13 Example of Simultaneous ELP Processing- Parameters Acceptable to Both Switches . . . 113
Figure 14 ESC Processing . . . 116
Figure 15 Principal Switch Selection State Machine . . . 118
Figure 16 Example Propagation of BF and RCF SW_ILS requests . . . 120
Figure 17 Address Distribution State Machines . . . 124
Figure 18 RDI Request Processing by Principal Switch . . . 126
Figure 19 RDI Request Processing by non-Principal Switch . . . 129
Figure 20 Example B_Port Configuration - Virtual ISL . . . 132
Figure 21 Neighbor Finite State Machine . . . 149
Figure 22 FSPF-Backbone Architecture . . . 150
Figure 23 Point-to-point FSPF-Backbone Links . . . 151
Figure 24 AR0 Consisting of Two ISW-0 Switching Devices . . . 151
Figure 25 Internal Service Supported By a BSW . . . 152
Figure 26 Dual BSW connectivity . . . 153
Figure 27 Physically Contiguous FSPF-Backbone with dual BSWs (Allowed) . . . 153
Figure 28 Physically Non-Contiguous FSPF-Backbone with dual BSWs (Disallowed) . . . 154
Figure 29 FSPF-Backbone Routing Protocol overview. . . . 155
Figure 30 Basic Zoning Framework . . . 190
Figure 31 Basic Zoning Hierarchy . . . 192
Figure 32 Basic Zoning Object Structure . . . 192
Figure 33 Logical Structure of the Zone Set Database . . . 197
Figure 34 Logical Structure of the Active Zone Set . . . 198
Figure 35 Merge Operation Between Two Switches . . . 211
Figure 36 Merge Operation Among Several Switches . . . 213
Figure 37 Broadcast path selection example . . . 221
Annex Figure A.1 Initialization example 1 . . . 224
Annex Figure A.2 Initialization example 2 . . . 225
Annex Figure A.3 Initialization example 3 . . . 226
Annex Figure B.1 Reference ELP Configuration . . . 227
Annex Figure B.2 A Successful and Complete ELP Exchange . . . 228
Annex Figure B.3 An Unsuccessful but Complete ELP Exchange . . . 228
Annex Figure B.4 A successful ELP Exchange Protocol Parameter Negotiation . . . 229
Annex Figure B.5 An Unsuccessful ELP Exchange Protocol Parameter Negotiation . . . 230
Annex Figure C.1 Registration of HBA Information - Single Switch . . . 232
Annex Figure C.2 Registration of HBA Information - Multiple Switches Caches Updated . . . 233
Annex Figure C.3 Registration of HBA Information - Multiple Switches Caches Not Updated . . . 234
Annex Figure C.4 HBA De-Registration - Primary HBA Manager . . . 235
Annex Figure C.5 HBA De-Registration - Non-Primary HBA Manager . . . 236

Tables

Table 1 ISO and American Conventions 26
Table 2 Address Identifier Values 36
Table 3 SW_ILS Command Codes 49
Table 4 SW_RJT Payload 51
Table 5 SW_RJT Reason Codes 52
Table 6 SW_RJT Reason Code Explanation 53
Table 7 ELP Request Payload 55
Table 8 Interconnect_Port Class F Service Parameters 56
Table 9 Class 1 Interconnect_Port Parameters 57
Table 10 Class 2 Interconnect_Port Parameters 58
Table 11 Class 3 Interconnect_Port Parameters 58
Table 12 ISL Flow Control Mode Values 59
Table 13 Flow Control Parameters 59
Table 14 ELP Accept Payload 60
Table 15 EFP Request Payload 61
Table 16 Switch_Priority Field Values 62
Table 17 Domain_ID_List Record Format 62
Table 18 Record_Type Field Values 63
Table 19 Multicast_ID_List Record Format 63
Table 20 EFP Accept Payload 64
Table 21 DIA Request Payload 65
Table 22 DIA Accept Payload 65
Table 23 RDI Request Payload 66
Table 24 RDI Accept Payload 67
Table 25 HLO Request Payload 68
Table 26 FSPF Header 69
Table 27 FSPF Command Codes 69
Table 28 LSU Request Payload 70
Table 29 Flags Field Bit Map 71
Table 30 Link State Record - Link Descriptor Format 71
Table 31 Link State Record - Summary Descriptor Format 72
Table 32 Link State Header Format 72
Table 33 Link State Record Type Field Values 73
Table 34 Link Descriptor Format 74
Table 35 Link Type Values 74
Table 36 Summary Descriptor Format 75
Table 37 LSA Request Payload 76
Table 38 BF Request Payload 77
Table 39 BF Accept Payload 77
Table 40 RCF Request Payload 78
Table 41 RCF Accept Payload 78
Table 42 SW_RSCN Request Payload 79
Table 43 Device Entry Format 80
Table 44 SW_RSCN Accept Payload 81
Table 45 DRLIR Request Payload 81
Table 46 DRLIR Accept Payload 82
Table 47 DSCN Request Payload 82
Table 48 DSCN Reason Codes 83
Table 49 DSCN Accept Payload 83
Table 50 Merge Request Payload 84
Table 51 Protocol Version Values 84
Table 52 Basic Zoning Payload 85

Table 53 Enhanced Zoning Payload 86
Table 54 Merge Request Accept Payload 87
Table 55 ACA Request Payload 88
Table 56 Acquire Change Authorization Accept Payload 89
Table 57 RCA Request Payload 89
Table 58 Release Change Authorization Accept Payload 90
Table 59 SFC Request Payload 91
Table 60 Operation Request Value 91
Table 61 Stage Fabric Configuration Update Accept Payload 92
Table 62 Payload for Operation Request Values 03 and 04 92
Table 63 Payload for Operation Request ‘Activate Zone Set Enhanced’ 93
Table 64 Payload for Operation Request ‘Deactivate Zone Set Enhanced’ 93
Table 65 Payload for Operation Request ‘Distribute Zone Set Database’ 94
Table 66 Payload for Operation Request ‘Activate Zone Set by Name’ 94
Table 67 Payload for Operation Request ‘Set Zoning Policies’ 95
Table 68 Update Fabric Configuration Request Payload 96
Table 69 Update Fabric Configuration Accept Payload 96
Table 70 ESC Request Payload 97
Table 71 Protocol Descriptor Format 97
Table 72 Protocol ID Values 98
Table 73 ESC Accept Payload 98
Table 74 ESS Request Payload 99
Table 75 Capability Object Format 100
Table 76 Name Server Capability Flags 101
Table 77 Fabric Controller Capability Flags 101
Table 78 Fabric Configuration Server Capability flags 102
Table 79 Enhanced Zone Server Capability flags 102
Table 80 Vendor Specific Capability Object 103
Table 81 ESS Accept Payload 104
Table 82 MRRA Request Payload 105
Table 83 Vendor Specific Field 105
Table 84 MRRA Response Payload 106
Table 85 MRRA Response Values 106
Table 86 Fabric Configuration Summary 107
Table 87 Responses to ELP Request for Originating Interconnect_Port 111
Table 88 Recommended BF and RCF Usage Summary 117
Table 89 B_Port - ILS Support 131
Table 90 Bridge Port Initialization Summary 132
Table 91 Path Selection (FSPF) Operation Summary 134
Table 92 Checksum Byte Order Calculation 140
Table 93 Neighbor Finite State Machine 147
Table 94 FC-CT Command Codes for dNS 160
Table 95 Name Server Entry Object 164
Table 96 FC-4 Descriptor Format for Name Server Object 165
Table 97 Entry Object Format Indicator 166
Table 98 Name Server Entry Object Description 166
Table 99 RA request payload 167
Table 100 RA Accept payload 167
Table 101 GE_ID request payload 167
Table 102 GE_ID Accept payload 168
Table 103 GE_PN request payload 168
Table 104 GE_PN Accept payload 168
Table 105 GE_NN request payload 169
Table 106 GE_NN Accept payload 169

Table 107 GE_IP request payload 169
Table 108 GE_IP Accept payload 170
Table 109 GE_FT request payload 170
Table 110 GE_FT Accept payload 170
Table 111 GE_PT request payload 171
Table 112 GE_PT Accept payload 171
Table 113 GE_ZM request payload 171
Table 114 GE_ZM Accept payload 172
Table 115 GE_ZN request payload 172
Table 116 GE_ZN Accept payload 172
Table 117 GE_IPP request payload 173
Table 118 GE_IPP Accept payload 173
Table 119 GE_FF request payload 173
Table 120 GE_FF Accept payload 174
Table 121 GE_FPN request payload 174
Table 122 GE_FPN Accept payload 174
Table 123 Fabric Configuration Service Command Codes for dMS 176
Table 124 FDMI Inter-Switch Message 180
Table 125 FDMI Header 180
Table 126 Vendor Specified 181
Table 127 FDMI Fabric Internal Command Codes 181
Table 128 Reason Code Explanation 182
Table 129 Registered HBA/Port List 183
Table 130 HBA Entry 184
Table 131 Port Entry 184
Table 132 Fabric Device Management Interface CT Commands for the dMS 185
Table 133 Fabric Internal Management Server Operations 185
Table 134 GCAP Request Payload 186
Table 135 GCAP CT_ACC Payload 186
Table 136 Capability Entry 186
Table 137 Fabric Configuration Server (CT_Subtype 01h) 187
Table 138 Unzoned Name Server (CT_Subtype 02h) 187
Table 139 Zoning Object List 193
Table 140 Zoning Object 193
Table 141 Zoning Object Types 194
Table 142 Protocol Format 194
Table 143 Zone Member Format 195
Table 144 Zone Member Type and Identifier Formats 195
Table 145 Zoning Object List 199
Table 146 Zoning Object Types 199
Table 147 Zone Set Object Format in the Zone Set Database 200
Table 148 Zone Set Object Format in the Active Zone Set 201
Table 149 Zone Reference Object Format 201
Table 150 Zone Object Format in the Zone Set Database 202
Table 151 Zone Object Format in the Active Zone Set 203
Table 152 Zone Member Format 204
Table 153 Zone Member Type and Identifier Formats 204
Table 154 Zone Member Identifier Format - Vendor Specified 205
Table 155 Zone Alias Object Format 205
Table 156 Zone Attribute Object Format 206
Table 157 Zone Attribute Block Format 206
Table 158 Zone Attribute Entry Format 207
Table 159 Zone Attribute Types 207
Table 160 Protocol Attribute Value 208

Table 161 Vendor Specified Attribute Value 210
Table 162 Basic Zoning Merge Rules 214
Table 163 Enhanced Zoning Merge Rules 215
Table 164 Timers and Constants for FC-SW-3 222
Table 165 SW_ILS Time-Out Values 223
Annex Table B.1 Responses to an ELP Request Initiator 231