

IEC 60086-3:2011-01(D)

Primary batteries - Part 3: Watch batteries

CONTENTS

| | |
|--|----|
| FOREWORD..... | 4 |
| INTRODUCTION..... | 6 |
| 1 Scope..... | 7 |
| 2 Normative references | 7 |
| 3 Terms and definitions | 7 |
| 4 Physical requirements | 8 |
| 4.1 Battery dimensions, symbols and size codes | 8 |
| 4.2 Terminals | 10 |
| 4.3 Projection of the negative terminal (h_5)..... | 10 |
| 4.4 Shape of negative terminal..... | 10 |
| 4.5 Mechanical resistance to pressure | 11 |
| 4.6 Deformation | 11 |
| 4.7 Leakage | 12 |
| 4.8 Marking | 12 |
| 4.8.1 General | 12 |
| 4.8.2 Disposal | 12 |
| 5 Electrical requirements | 12 |
| 5.1 Electrochemical system, nominal voltage, end-point voltage and open-circuit voltage | 12 |
| 5.2 Closed circuit voltage U_{cc} (CCV), internal resistance and impedance | 13 |
| 5.3 Capacity..... | 13 |
| 5.4 Capacity retention | 13 |
| 6 Sampling and quality assurance | 13 |
| 6.1 Sampling | 13 |
| 6.1.1 Testing by attributes | 13 |
| 6.1.2 Testing by variables | 14 |
| 6.2 Product quality indices | 14 |
| 7 Test methods | 14 |
| 7.1 Shape and dimensions | 14 |
| 7.1.1 Shape requirement | 14 |
| 7.2 Electrical characteristics..... | 14 |
| 7.2.1 Environmental conditions..... | 14 |
| 7.2.2 Equivalent circuit – effective internal resistance – DC method | 14 |
| 7.2.3 Equipment | 15 |
| 7.2.4 Measurement of open-circuit voltage U_{oc} (OCV) and closed circuit voltage U_{cc} (CCV) | 16 |
| 7.2.5 Calculation of the internal resistance R_i | 17 |
| 7.2.6 Measurement of the capacity..... | 17 |
| 7.2.7 Calculation of the internal resistance R_i during discharge in case of method A (optional) | 19 |
| 7.3 Test methods for determining the resistance to leakage | 20 |
| 7.3.1 Preconditioning and previous examination | 20 |
| 7.3.2 High temperature and humidity test | 21 |
| 7.3.3 Test by temperature cycles..... | 21 |
| 8 Visual examination and acceptance conditions | 22 |
| 8.1 Preconditioning | 22 |

| | | |
|---------------------|---|----|
| 8.2 | Magnification..... | 22 |
| 8.3 | Lighting | 22 |
| 8.4 | Leakage levels and classification | 22 |
| 8.5 | Acceptance conditions..... | 24 |
| Annex A (normative) | Designation..... | 25 |
| | Bibliography..... | 26 |
| | | |
| Figure 1 | – Dimensional drawing | 8 |
| Figure 2 | – Shape of negative terminal..... | 11 |
| Figure 3 | – Shape requirement..... | 14 |
| Figure 4 | – Schematic voltage transient | 15 |
| Figure 5 | – Curve: $U = f(t)$ | 16 |
| Figure 6 | – Circuitry principle | 16 |
| Figure 7 | – Circuitry principle for method A | 18 |
| Figure 8 | – Circuitry principle for method B | 19 |
| Figure 9 | – Test by temperature cycles | 21 |
| | | |
| Table 1 | – Dimensions and size codes | 9 |
| Table 2 | – Dimensions and size codes | 10 |
| Table 3 | – Minimum values of l_1 | 11 |
| Table 4 | – Applied force F by battery dimensions | 11 |
| Table 5 | – Standardised electrochemical systems | 13 |
| Table 6 | – Test method for U_{cc} (CCV) measurement..... | 17 |
| Table 7 | – Test method A for U_{cc} (CCV) measurement..... | 18 |
| Table 8 | – Discharge resistance (values) | 20 |
| Table 9 | – Storage conditions for the recommended test..... | 21 |
| Table 10 | – Storage conditions for optional test | 21 |
| Table 11 | – Leakage levels and classification | 23 |