ISO/IEC 29341-17-11:2011-08 (E)

Information technology - UPnP Device Architecture - Part 17-11: Quality of Service Device Control Protocol - Level 3 - Quality of Service Manager Service

Contents

Page

1 Overview and Scope....3
1.1 References & Terms....3
1.1.1 References....3
1.1.2 Terms and Abbreviations....5
2 Service Modeling Definitions....12
2.1 ServiceType....12
2.2 State Variables....12
2.2.1 XML Fragments as UPnP Arguments....12
2.2.2 A_ARG_TYPE_TrafficDescriptor....13
2.2.3 A_ARG_TYPE_TrafficHandle....33
2.2.4 A_ARG_TYPE_NumTrafficDescriptors....33
2.2.5 A_ARG_TYPE_NumPolicyHolders....33
2.2.6 A_ARG_TYPE_ ListOfTrafficDescriptors....33
2.2.7 A_ARG_TYPE_QmCapabilities....35
2.2.8 A_ARG_TYPE_ExtendedTrafficQosInfo....36
2.2.9 A_ARG_TYPE_ResultedQosType....38
2.2.10 Relationships Between State Variables....38
2.3 Eventing and Moderation....39
2.3.1 Event Model....39
2.4 Actions....39
2.4.1 RequestTrafficQos()....39
2.4.2 UpdateTrafficQos()....51
2.4.3 ReleaseTrafficQos()....59
2.4.4 BrowseAllTrafficDescriptors()....59
2.4.5 GetQmCapabilities()....60
2.4.6 RequestExtendedTrafficQos()....61
2.4.7 UpdateExtendedTrafficQos()....66
2.4.8 Common Error Codes....70
2.5 Theory of Operation (Informative)....72
2.5.1 Overview....72
2.5.2 Recovery from Failures....73
3 XML Service Description....75
4 Test....79
Annex A (normative) Traffic Descriptor Matrix....80
Annex B (informative) Methods for determining candidate streams for preemption based on UINs....83
Annex C (normative) The *res@tspec* property in the *ContentDirectory* Service....84
C.1 Definition of the XML Fragment....84

Figure 1 — An example traffic stream 22
Figure 2 — A traffic stream with a constant bit rate 24
Figure 3 — The non-constant bit-rate traffic (left) can be viewed as a constant bit-rate traffic of a higher constant bit-rate *D* (right) 24

Table 1-1 — Abbreviations 5
Table 2-1 — State Variables 13
Table 2-2 — Meaning of *PolicyHolderConsultedType* parameter 18
Table 2-3 — Traffic Specification Parameters 21
Table 2-4 — Meaning of *RequestedQosType* parameter 22
Table 2-5 — Meaning of *ResultedQosType* parameter 38
Table 2-6 — Event Moderation 39
Table 2-7 — Actions 39
Table 2-8 — Arguments for *RequestTrafficQos()* 40
Table 2-9 — Elements that MUST equal those of the original TrafficDescriptor 42
Table 2-10 — Default Priorities used by the *QoS Manager* based on 802.1D (Annex G) 44
Table 2-11 — Error Codes for *RequestTrafficQos()* 50
Table 2-12 — Elements that are allowed to be updated when calling UpdateTrafficQos() 52
Table 2-13 — Arguments for UpdateTrafficQos() 53
Table 2-14 — Error Codes for UpdateTrafficQos 58
Table 2-15 — Arguments for ReleaseTrafficQos 59
Table 2-16 — Error Codes for ReleaseTrafficQos 59
Table 2-17 — Arguments for BrowseAllTrafficDescriptors 60
Table 2-18 — Error Codes for BrowseAllTrafficDescriptors 60
Table 2-19 — Arguments for GetQmCapabilities 60
Table 2-20 — Error Codes for GetQmCapabilities 61
Table 2-21 — Arguments for RequestExtendedTrafficQos 61
Table 2-22 — Error Codes for RequestExtendedTrafficQos 65
Table 2-23 — Arguments for UpdateExtendedTrafficQos 66
Table 2-24 — Error Codes for UpdateExtendedTrafficQos 69
Table 2-25 — Common Error Codes 70