

# ISO/IEC 14776-261:2012-11 (E)

## Information technology - Small Computer System Interface (SCSI) - Part 261: SAS Protocol Layer (SPL)

---

| <b>Contents</b>  | <b>Page</b> |
|--|-------------|
| FOREWORD.....  | 18          |
| INTRODUCTION.....  | 20          |
| General .....  | 20          |
| SCSI standards family.....   | 21          |
| 1 Scope.....   | 23          |
| 2 Normative references.....  | 23          |
| 3 Terms, definitions, symbols, abbreviations, keywords, and conventions.....                   | 25          |
| 3.1 Terms and definitions.....   | 25          |
| 3.2 Symbols and abbreviations .....  | 46          |
| 3.3 Keywords .....   | 48          |
| 3.4 Editorial conventions .....  | 49          |
| 3.5 Class diagram and object diagram conventions.....  | 51          |
| 3.6 State machine conventions .....  | 55          |
| 3.6.1 State machine conventions overview.....  | 55          |
| 3.6.2 Transitions.....   | 56          |
| 3.6.3 Messages, requests, indications, confirmations, responses, and event notifications ..... | 57          |
| 3.6.4 State machine counters, timers, and variables .....                                      | 57          |
| 3.6.5 State machine arguments .....  | 57          |
| 3.7 Bit and byte ordering .....  | 58          |
| 3.8 Notation for procedures and functions .....  | 58          |
| 4 General .....  | 60          |
| 4.1 Architecture .....   | 60          |
| 4.1.1 Architecture overview.....   | 60          |
| 4.1.2 Physical links and phys.....   | 61          |
| 4.1.3 Logical links.....   | 66          |
| 4.1.4 Ports (narrow ports and wide ports).....   | 66          |
| 4.1.5 Application clients and device servers .....   | 69          |
| 4.1.6 SAS devices.....   | 70          |
| 4.1.7 Expander devices.....  | 71          |
| 4.1.8 Service delivery subsystem.....  | 72          |
| 4.1.9 Domains .....  | 73          |
| 4.1.10 Expander device topologies .....  | 75          |
| 4.1.11 Pathways.....   | 77          |
| 4.1.12 Connections .....   | 77          |
| 4.1.13 Broadcasts .....  | 79          |
| 4.2 Names and identifiers .....  | 81          |
| 4.2.1 Names and identifiers overview .....   | 81          |
| 4.2.2 NAA IEEE Registered format identifier .....  | 82          |
| 4.2.3 NAA Locally Assigned format identifier .....   | 83          |
| 4.2.4 SAS address .....  | 84          |
| 4.2.5 Hashed SAS addresses .....   | 84          |
| 4.2.6 Device names and expander device SAS addresses .....                                     | 84          |
| 4.2.7 Device name for SATA devices with world wide names .....                                 | 85          |
| 4.2.8 Port names.....  | 85          |
| 4.2.9 Port identifiers and SAS port SAS addresses.....   | 85          |
| 4.2.10 Phy identifiers.....  | 86          |

|  |     |
|--|-----|
| 4.3 State machines .....   | 87  |
| 4.3.1 State machine overview .....   | 87  |
| 4.3.2 Transmit data path .....   | 88  |
| 4.3.3 Receive data path .....  | 93  |
| 4.3.4 State machines and SAS Device, SAS Port, and SAS Phy classes .....         | 96  |
| 4.4 Resets .....   | 98  |
| 4.4.1 Reset overview .....   | 98  |
| 4.4.2 Hard reset .....   | 100 |
| 4.5 I_T nexus loss .....   | 100 |
| 4.6 Expander device model .....  | 101 |
| 4.6.1 Expander device model overview .....                                       | 101 |
| 4.6.2 Expander ports .....   | 102 |
| 4.6.3 Expander connection manager (ECM) .....                                    | 103 |
| 4.6.4 Expander connection router (ECR) .....                                     | 103 |
| 4.6.5 Broadcast propagation processor (BPP) .....                                | 104 |
| 4.6.6 Expander device interfaces .....   | 104 |
| 4.6.7 Expander device routing .....  | 111 |
| 4.6.8 Expander device reduced functionality .....                                | 115 |
| 4.6.9 Broadcast (Expander) handling .....  | 116 |
| 4.7 Discover process .....   | 116 |
| 4.7.1 Discover process overview .....  | 116 |
| 4.7.2 Starting the discover process (Broadcast (Change) handling) .....          | 116 |
| 4.7.3 Discover process traversal .....   | 116 |
| 4.7.4 Discover process in a self-configuring expander device .....               | 118 |
| 4.7.5 Enabling multiplexing .....  | 119 |
| 4.8 Configuration subprocess .....   | 120 |
| 4.8.1 Configuration subprocess overview .....                                    | 120 |
| 4.8.2 Allowed expander device topologies .....                                   | 120 |
| 4.8.3 Externally configurable expander device route table optimization .....     | 121 |
| 4.8.4 Externally configurable expander device expander route index order .....   | 122 |
| 4.9 Zoning .....   | 128 |
| 4.9.1 Zoning overview .....  | 128 |
| 4.9.2 Zoning expander device requirements .....                                  | 132 |
| 4.9.3 Zoning operation .....   | 134 |
| 4.9.4 Zone phy information and link reset sequences .....                        | 140 |
| 4.9.5 Broadcast processing in a zoning expander device with zoning enabled ..... | 142 |
| 4.9.6 Zone configuration .....   | 143 |
| 4.10 Phy power conditions .....  | 146 |
| 4.10.1 Low phy power conditions .....  | 146 |
| 4.10.2 SATA phy power conditions .....   | 148 |
| 4.11 SAS device and expander device power conditions .....                       | 148 |
| 4.12 Phy test functions .....  | 149 |
| 4.12.1 Phy test functions overview .....   | 149 |
| 4.12.2 Transmit pattern phy test function .....                                  | 149 |
| 4.13 Phy events .....  | 150 |
| 5 Phy layer .....  | 155 |
| 5.1 Phy layer overview .....   | 155 |
| 5.2 8b10b coding .....   | 155 |
| 5.2.1 8b10b coding overview .....  | 155 |
| 5.2.2 8b10b coding notation conventions .....                                    | 155 |
| 5.3 Character encoding and decoding .....  | 156 |
| 5.3.1 Introduction .....   | 156 |
| 5.3.2 Bit transmission order .....   | 156 |
| 5.3.3 Character transmission order .....   | 156 |
| 5.3.4 Frame transmission order .....   | 156 |
| 5.3.5 Running disparity (RD) .....   | 157 |
| 5.3.6 Data characters .....  | 157 |

|   |     |
|---|-----|
| 5.3.7 Control characters.....   | 163 |
| 5.3.8 Encoding characters in the transmitter.....   | 164 |
| 5.3.9 Decoding characters in the receiver.....  | 164 |
| 5.4 Dwords, primitives, data dwords, and invalid dwords.....                              | 164 |
| 5.5 Bit order.....  | 165 |
| 5.6 Out of band (OOB) signals.....  | 166 |
| 5.6.1 OOB signals overview.....   | 166 |
| 5.6.2 SP Transmission of OOB signals.....   | 166 |
| 5.6.3 Receiver detection of OOB signals.....  | 167 |
| 5.6.4 SATA port selection signal.....   | 169 |
| 5.6.5 Phy power conditions.....   | 170 |
| 5.7 Phy reset sequences.....  | 170 |
| 5.7.1 Phy reset sequences overview.....   | 170 |
| 5.7.2 SATA phy reset sequence.....  | 171 |
| 5.7.3 SAS to SATA phy reset sequence.....   | 172 |
| 5.7.4 SAS to SAS phy reset sequence.....  | 174 |
| 5.7.5 Phy reset sequence after devices are attached.....                                  | 196 |
| 5.8 Phy power condition sequences.....  | 197 |
| 5.8.1 Transitioning from the active phy power condition to a low phy power condition..... | 197 |
| 5.8.2 Transitioning from a low phy power condition to the active phy power condition..... | 197 |
| 5.8.3 Events during low phy power condition.....  | 198 |
| 5.9 SP (phy layer) state machine.....   | 200 |
| 5.9.1 SP state machine overview.....  | 200 |
| 5.9.2 SP transmitter and receiver.....  | 202 |
| 5.9.3 OOB sequence states.....  | 204 |
| 5.9.4 SAS speed negotiation states.....   | 209 |
| 5.9.5 SAS phy power conditions states.....  | 219 |
| 5.9.6 SATA host emulation states.....   | 222 |
| 5.9.7 SATA port selector state SP25:SATA_PortSel.....                                     | 227 |
| 5.9.8 SATA spinup hold state SP26:SATA_SpinupHold.....                                    | 228 |
| 5.10 SP_DWS (phy layer dword synchronization) state machine.....                          | 228 |
| 5.10.1 SP_DWS state machine overview.....   | 228 |
| 5.10.2 SP_DWS receiver.....   | 230 |
| 5.10.3 SP_DWS0:AcquireSync state.....   | 231 |
| 5.10.4 SP_DWS1:Valid1 state.....  | 231 |
| 5.10.5 SP_DWS2:Valid2 state.....  | 232 |
| 5.10.6 SP_DWS3:SyncAcquired state.....  | 232 |
| 5.10.7 SP_DWS4:Lost1 state.....   | 232 |
| 5.10.8 SP_DWS5:Lost1Recovered state.....  | 233 |
| 5.10.9 SP_DWS6:Lost2 state.....   | 233 |
| 5.10.10 SP_DWS7:Lost2Recovered state.....   | 234 |
| 5.10.11 SP_DWS8:Lost3 state.....  | 234 |
| 5.10.12 SP_DWS9:Lost3Recovered state.....   | 234 |
| 5.11 Multiplexing.....  | 235 |
| 5.12 Spinup.....  | 236 |
| 6 Link layer.....   | 237 |
| 6.1 Link layer overview.....  | 237 |
| 6.2 Primitives.....   | 237 |
| 6.2.1 Primitives overview.....  | 237 |
| 6.2.2 Primitive summary.....  | 238 |
| 6.2.3 Primitive encodings.....  | 243 |
| 6.2.4 Primitive sequences.....  | 248 |
| 6.2.5 Deletable primitives.....   | 252 |
| 6.2.6 Primitives not specific to type of connections.....                                 | 256 |

|   |     |
|---|-----|
| 6.2.7 Primitives used only inside SSP and SMP connections.....                    | 262 |
| 6.2.8 Primitives used only inside STP connections and on SATA physical links..... | 263 |
| 6.3 Physical link rate tolerance management .....                                 | 264 |
| 6.3.1 Physical link rate tolerance management overview .....                      | 264 |
| 6.3.2 Phys originating dwords.....  | 266 |
| 6.3.3 Expander phys forwarding dwords.....  | 266 |
| 6.4 Idle physical links .....   | 267 |
| 6.5 CRC .....   | 267 |
| 6.5.1 CRC overview .....  | 267 |
| 6.5.2 CRC generation .....  | 269 |
| 6.5.3 CRC checking.....   | 271 |
| 6.6 Scrambling .....  | 272 |
| 6.7 Bit order of CRC and scrambler .....  | 274 |
| 6.8 Address frames .....  | 277 |
| 6.8.1 Address frames overview.....  | 277 |
| 6.8.2 IDENTIFY address frame.....   | 279 |
| 6.8.3 OPEN address frame.....   | 282 |
| 6.9 Link reset sequence .....   | 285 |
| 6.9.1 Link reset sequence overview.....   | 285 |
| 6.9.2 Expander device handling of link reset sequences.....                       | 288 |
| 6.10 SL_IR (link layer identification and hard reset) state machines .....        | 288 |
| 6.10.1 SL_IR state machines overview.....   | 288 |
| 6.10.2 SL_IR transmitter and receiver .....                                       | 290 |
| 6.10.3 SL_IR_TIR (transmit IDENTIFY or HARD_RESET) state machine.....             | 290 |
| 6.10.4 SL_IR_RIF (receive IDENTIFY address frame) state machine.....              | 292 |
| 6.10.5 SL_IR_IRC (identification and hard reset control) state machine .....      | 293 |
| 6.11 Entering a low phy power condition .....                                     | 294 |
| 6.12 SAS domain changes (Broadcast (Change) usage) .....                          | 295 |
| 6.13 Connections .....  | 296 |
| 6.13.1 Connections overview .....   | 296 |
| 6.13.2 Opening a connection .....   | 296 |
| 6.13.3 Arbitration fairness .....   | 298 |
| 6.13.4 Arbitration inside an expander device .....                                | 300 |
| 6.13.5 BREAK handling .....   | 304 |
| 6.13.6 Aborting a connection request .....  | 305 |
| 6.13.7 Closing a connection.....  | 307 |
| 6.13.8 Breaking a connection.....   | 308 |
| 6.14 Rate matching .....  | 309 |
| 6.15 SL (link layer for SAS logical phys) state machines.....                     | 312 |
| 6.15.1 SL state machines overview .....   | 312 |
| 6.15.2 SL transmitter and receiver .....  | 315 |
| 6.15.3 SL_RA (receive OPEN address frame) state machine .....                     | 317 |
| 6.15.4 SL_CC (connection control) state machine.....                              | 317 |
| 6.16 XL (link layer for expander logical phys) state machine .....                | 330 |
| 6.16.1 XL state machine overview .....  | 330 |
| 6.16.2 XL transmitter and receiver .....  | 335 |
| 6.16.3 XL0:Idle state .....   | 336 |
| 6.16.4 XL1:Request_Path state .....   | 338 |
| 6.16.5 XL2:Request_Open state.....  | 340 |
| 6.16.6 XL3:Open_Confirm_Wait state .....  | 340 |
| 6.16.7 XL4:Open_Reject state .....  | 342 |
| 6.16.8 XL5:Forward_Open state .....   | 342 |
| 6.16.9 XL6:Open_Response_Wait state.....  | 343 |
| 6.16.10 XL7:Connected state.....  | 344 |

|  |     |
|--|-----|
| 6.16.11 XL8:Close_Wait state.....                            | 345 |
| 6.16.12 XL9:Break state.....                                 | 346 |
| 6.16.13 XL10:Break_Wait state .....                          | 347 |
| 6.16.14 XL11:PS_Request state.....                           | 347 |
| 6.16.15 XL12:PS_Quiet state.....                             | 348 |
| 6.17 SSP link layer.....                                     | 349 |
| 6.17.1 Opening an SSP connection.....                        | 349 |
| 6.17.2 Full duplex.....                                      | 349 |
| 6.17.3 SSP frame transmission and reception.....             | 350 |
| 6.17.4 SSP flow control.....                                 | 350 |
| 6.17.5 Interlocked frames.....                               | 351 |
| 6.17.6 Breaking an SSP connection .....                      | 353 |
| 6.17.7 Closing an SSP connection.....                        | 353 |
| 6.17.8 SSP (link layer for SSP phys) state machines .....    | 354 |
| 6.18 STP link layer.....                                     | 365 |
| 6.18.1 STP frame transmission and reception.....             | 365 |
| 6.18.2 STP flow control.....                                 | 366 |
| 6.18.3 Continued primitive sequence.....                     | 370 |
| 6.18.4 Affiliations.....                                     | 371 |
| 6.18.5 Opening an STP connection .....                       | 373 |
| 6.18.6 Closing an STP connection.....                        | 375 |
| 6.18.7 STP connection management examples .....              | 376 |
| 6.18.8 STP (link layer for STP phys) state machines.....     | 379 |
| 6.18.9 SMP target port support.....                          | 379 |
| 6.19 SMP link layer .....                                    | 379 |
| 6.19.1 SMP frame transmission and reception .....            | 379 |
| 6.19.2 SMP flow control .....                                | 379 |
| 6.19.3 Opening an SMP connection .....                       | 379 |
| 6.19.4 Closing an SMP connection.....                        | 380 |
| 6.19.5 SMP (link layer for SMP phys) state machines.....     | 380 |
| 7 Port layer.....  | 385 |
| 7.1 Port layer overview.....                                 | 385 |
| 7.2 PL (port layer) state machines .....                     | 385 |
| 7.2.1 PL state machines overview .....                       | 385 |
| 7.2.2 PL_OC (port layer overall control) state machine ..... | 387 |
| 7.2.3 PL_PM (port layer phy manager) state machine.....      | 398 |
| 8 Transport layer.....                                       | 409 |
| 8.1 Transport layer overview.....                            | 409 |
| 8.2 SSP transport layer .....                                | 410 |
| 8.2.1 SSP frame format.....                                  | 410 |
| 8.2.2 Information units.....                                 | 414 |
| 8.2.3 Sequences of SSP frames .....                          | 424 |
| 8.2.4 SSP transport layer handling of link layer errors..... | 427 |
| 8.2.5 SSP transport layer error handling summary .....       | 432 |
| 8.2.6 ST (transport layer for SSP ports) state machines..... | 434 |
| 8.3 STP transport layer .....                                | 470 |
| 8.3.1 Initial FIS.....                                       | 470 |
| 8.3.2 BIST Activate FIS.....                                 | 470 |
| 8.3.3 TT (transport layer for STP ports) state machines..... | 470 |
| 8.4 SMP transport layer .....                                | 471 |
| 8.4.1 SMP transport layer overview .....                     | 471 |
| 8.4.2 SMP_REQUEST frame.....                                 | 472 |
| 8.4.3 SMP_RESPONSE frame .....                               | 472 |
| 8.4.4 Sequence of SMP frames .....                           | 473 |

|  |     |
|--|-----|
| 8.4.5 MT (transport layer for SMP ports) state machines .....                  | 473 |
| 9 Application layer .....  | 478 |
| 9.1 Application layer overview .....   | 478 |
| 9.2 SCSI application layer .....   | 478 |
| 9.2.1 SCSI transport protocol services .....                                   | 478 |
| 9.2.2 Application client error handling .....                                  | 490 |
| 9.2.3 Device server error handling .....                                       | 491 |
| 9.2.4 Task router and task manager error handling .....                        | 492 |
| 9.2.5 SCSI transport protocol event notifications .....                        | 492 |
| 9.2.6 SCSI commands .....  | 492 |
| 9.2.7 SCSI mode parameters .....   | 493 |
| 9.2.8 SCSI log parameters .....  | 504 |
| 9.2.9 SCSI diagnostic parameters .....   | 507 |
| 9.2.10 SCSI power conditions .....   | 514 |
| 9.2.11 SCSI vital product data (VPD) .....                                     | 523 |
| 9.3 ATA application layer .....  | 526 |
| 9.4 Management application layer .....   | 526 |
| 9.4.1 READY LED signal behavior .....  | 526 |
| 9.4.2 Management protocol services .....                                       | 527 |
| 9.4.3 SMP functions .....  | 528 |
| Annex A (normative) Jitter tolerance patterns .....                            | 641 |
| Annex B (informative) SAS to SAS phy reset sequence examples .....             | 649 |
| Annex C (informative) CRC .....  | 654 |
| Annex D (informative) SAS address hashing .....                                | 658 |
| Annex E (informative) Scrambling .....   | 665 |
| Annex F (informative) ATA architectural notes .....                            | 669 |
| Annex G (informative) Minimum deletable primitive insertion rate summary ..... | 672 |
| Annex H (informative) Zone permission configuration descriptor examples .....  | 673 |
| Annex I (informative) SAS addressing .....                                     | 676 |
| Annex J (informative) Expander device handling of connections .....            | 677 |
| Annex K (informative) Primitive encoding .....                                 | 698 |
| Bibliography .....   | 701 |

|  |     |
|--|-----|
| Figure 1 — Organization of this standard .....   | 20  |
| Figure 2 — SCSI document relationships .....   | 21  |
| Figure 3 — ATA document relationships .....  | 21  |
| Figure 4 — Classes in class diagrams .....   | 51  |
| Figure 5 — Association relationships in class diagrams .....                                     | 52  |
| Figure 6 — Aggregation relationships in class diagrams .....                                     | 53  |
| Figure 7 — Generalization relationships in class diagrams .....                                  | 54  |
| Figure 8 — Dependency relationships in class diagrams .....                                      | 54  |
| Figure 9 — Objects in object diagrams .....  | 55  |
| Figure 10 — State machine conventions .....  | 56  |
| Figure 11 — SAS Domain class diagram .....   | 61  |
| Figure 12 — Phy class diagram .....  | 63  |
| Figure 13 — SAS phy object diagram .....   | 64  |
| Figure 14 — Expander phy object diagram .....  | 65  |
| Figure 15 — Ports (narrow ports and wide ports) .....  | 67  |
| Figure 16 — Port class diagram .....   | 68  |
| Figure 17 — Port object diagram .....  | 69  |
| Figure 18 — SAS devices .....  | 71  |
| Figure 19 — Expander device .....  | 72  |
| Figure 20 — Domains .....  | 73  |
| Figure 21 — SAS domain bridging to ATA domains .....   | 73  |
| Figure 22 — SAS domains bridging to ATA domains with SATA port selectors .....                   | 74  |
| Figure 23 — Devices spanning SAS domains .....   | 75  |
| Figure 24 — Single expander device topology example .....  | 75  |
| Figure 25 — Multiple expander device topologies .....  | 76  |
| Figure 26 — Potential pathways .....   | 77  |
| Figure 27 — Multiple connections on wide ports .....   | 79  |
| Figure 28 — State machines for SAS devices .....   | 87  |
| Figure 29 — State machines for expander devices .....  | 88  |
| Figure 30 — Transmit data path in a SAS phy .....  | 89  |
| Figure 31 — SSP link, port, SSP transport, and SCSI application layer state machines .....       | 90  |
| Figure 32 — SMP link, port, SMP transport, and management application layer state machines ..... | 91  |
| Figure 33 — STP link, port, STP transport, and ATA application layer state machines .....        | 92  |
| Figure 34 — Transmit data path and state machines in an expander phy .....                       | 93  |
| Figure 35 — Receive data path in a SAS phy .....   | 94  |
| Figure 36 — Receive data path in an expander phy .....   | 95  |
| Figure 37 — State machines and SAS Device classes .....  | 96  |
| Figure 38 — State machines and Expander Device classes .....                                     | 97  |
| Figure 39 — Reset terminology .....  | 99  |
| Figure 40 — Expander device model .....  | 102 |
| Figure 41 — Expander device interfaces .....   | 105 |
| Figure 42 — Expander device interface detail .....   | 106 |
| Figure 43 — Phy-based expander route table .....   | 114 |
| Figure 44 — Expander-based expander route table .....  | 115 |
| Figure 45 — Level-order traversal example .....  | 117 |
| Figure 46 — Examples of invalid topologies .....   | 121 |
| Figure 47 — Externally configurable expander device and table-to-table attachment .....          | 124 |
| Figure 48 — Expander route index levels example .....  | 125 |
| Figure 49 — Expander route index order example .....   | 127 |
| Figure 50 — Zoning example .....   | 129 |
| Figure 51 — One ZPSDS example .....  | 129 |
| Figure 52 — Zone manager location examples .....   | 130 |
| Figure 53 — Three ZPSDSes example .....  | 131 |
| Figure 54 — Extending a ZPSDS example .....  | 133 |
| Figure 55 — Overtaking a ZPSDS example .....   | 134 |
| Figure 56 — Zoning expander route table .....  | 139 |
| Figure 57 — SAS bit transmission logic .....   | 165 |
| Figure 58 — SAS bit reception logic .....  | 166 |

|   |     |
|---|-----|
| Figure 59 — OOB signal transmission .....   | 167 |
| Figure 60 — OOB signal detection .....  | 169 |
| Figure 61 — SATA OOB sequence .....   | 171 |
| Figure 62 — SATA speed negotiation sequence .....   | 172 |
| Figure 63 — SAS to SATA OOB sequence .....  | 173 |
| Figure 64 — SAS to SAS OOB sequence .....   | 175 |
| Figure 65 — SNW-1, SNW-2, and Final-SNW .....   | 178 |
| Figure 66 — SNW-3 .....   | 180 |
| Figure 67 — Train-SNW .....   | 185 |
| Figure 68 — SAS speed negotiation sequence SNW flowchart .....  | 187 |
| Figure 69 — SAS speed negotiation sequence (both phys SNW-1 through SNW-3) .....                      | 189 |
| Figure 70 — SAS speed negotiation sequence (phy A: SNW-1 through SNW-3, phy B: SNW-2 only) .....      | 190 |
| Figure 71 — SAS speed negotiation sequence (phy A: SNW-3 only, phy B: SNW-1 only) .....               | 191 |
| Figure 72 — SAS speed negotiation sequence - phy reset problem in Final-SNW .....                     | 192 |
| Figure 73 — SAS speed negotiation sequence - phy reset problem in SNW-3 .....                         | 193 |
| Figure 74 — SAS speed negotiation sequence - phy reset problem in Train-SNW .....                     | 194 |
| Figure 75 — SAS speed negotiation sequence - multiple Train-SNWs .....                                | 195 |
| Figure 76 — Hot-plug and the phy reset sequence .....   | 197 |
| Figure 77 — Transition to active phy power condition .....  | 198 |
| Figure 78 — Hot plug and low phy power condition .....  | 199 |
| Figure 79 — SP (phy layer) state machine - OOB sequence states .....                                  | 204 |
| Figure 80 — SP (phy layer) state machine - SAS speed negotiation states .....                         | 210 |
| Figure 81 — SP (phy layer) state machine - SAS speed negotiation states for SNW-3 and Train-SNW ..... | 211 |
| Figure 82 — SP (phy layer) state machine - SAS phy power condition states .....                       | 220 |
| Figure 83 — SP (phy layer) state machine - SATA host emulation states .....                           | 223 |
| Figure 84 — SP (phy layer) state machine – SATA port selector state .....                             | 227 |
| Figure 85 — SP (phy layer) state machine - SATA spinup hold state .....                               | 228 |
| Figure 86 — SP_DWS (phy layer dword synchronization) state machine .....                              | 230 |
| Figure 87 — Multiplexing disabled .....   | 235 |
| Figure 88 — Multiplexing enabled .....  | 235 |
| Figure 89 — Transmitting a repeated primitive sequence .....  | 249 |
| Figure 90 — Receiving a repeated primitive sequence .....   | 249 |
| Figure 91 — Extended primitive sequences .....  | 250 |
| Figure 92 — Triple primitive sequences .....  | 251 |
| Figure 93 — Redundant primitive sequences .....   | 252 |
| Figure 94 — Elasticity buffer .....   | 265 |
| Figure 95 — Address frame, SSP frame, and SMP frame CRC bit ordering .....                            | 270 |
| Figure 96 — STP frame CRC bit ordering .....  | 271 |
| Figure 97 — Transmit path bit ordering .....  | 274 |
| Figure 98 — Receive path bit ordering .....   | 275 |
| Figure 99 — STP transmit path bit ordering .....  | 276 |
| Figure 100 — STP receive path bit ordering .....  | 277 |
| Figure 101 — Address frame transmission .....   | 277 |
| Figure 102 — Identification sequence .....  | 286 |
| Figure 103 — Hard reset sequence .....  | 287 |
| Figure 104 — SL_IR (link layer identification and hard reset) state machines .....                    | 289 |
| Figure 105 — Transitioning from the active phy power condition to a low phy power condition .....     | 294 |
| Figure 106 — Example simultaneous connection recommendations for wide ports .....                     | 297 |
| Figure 107 — Aborting a connection request with a BREAK primitive sequence .....                      | 306 |
| Figure 108 — Connection request timeout example .....   | 307 |
| Figure 109 — Closing a connection example .....   | 308 |
| Figure 110 — Rate matching example .....  | 311 |
| Figure 111 — SL (link layer for SAS logical phys) state machines (part 1) .....                       | 313 |
| Figure 112 — SL (link layer for SAS logical phys) state machines (part 2) .....                       | 314 |
| Figure 113 — SL (link layer for SAS logical phys) state machines (part 3) .....                       | 315 |
| Figure 114 — XL (link layer for expander logical phys) state machine (part 1) .....                   | 332 |
| Figure 115 — XL (link layer for expander logical phys) state machine (part 2) .....                   | 333 |
| Figure 116 — XL (link layer for expander logical phys) state machine (part 3) .....                   | 334 |

|  |     |
|--|-----|
| Figure 117 — SSP frame transmission .....  | 350 |
| Figure 118 — Interlocked frames .....  | 352 |
| Figure 119 — Non-interlocked frames with the same initiator port transfer tags .....               | 352 |
| Figure 120 — Non-interlocked frames with different initiator port transfer tags .....              | 353 |
| Figure 121 — Closing an SSP connection example .....   | 354 |
| Figure 122 — SSP (link layer for SSP phys) state machines (part 1 - frame transmission) .....      | 356 |
| Figure 123 — SSP (link layer for SSP phys) state machines (part 2 - frame reception) .....         | 357 |
| Figure 124 — STP frame transmission .....  | 365 |
| Figure 125 — STP flow control .....  | 369 |
| Figure 126 — Transmitting a continued primitive sequence .....                                     | 371 |
| Figure 127 — Receiving a continued primitive sequence .....  | 371 |
| Figure 128 — Example simultaneous connection recommendations for an expander device .....          | 375 |
| Figure 129 — STP initiator port opening an STP connection .....                                    | 377 |
| Figure 130 — STP target port opening an STP connection .....                                       | 378 |
| Figure 131 — SMP frame transmission .....  | 379 |
| Figure 132 — SMP_IP (link layer for SMP initiator phys) state machine .....                        | 381 |
| Figure 133 — SMP_TP (link layer for SMP target phys) state machine .....                           | 383 |
| Figure 134 — Port layer examples .....   | 386 |
| Figure 135 — PL_OC (port layer overall control) state machine .....                                | 389 |
| Figure 136 — PL_PM (port layer phy manager) state machine (part 1) .....                           | 400 |
| Figure 137 — PL_PM (port layer phy manager) state machine (part 2) .....                           | 401 |
| Figure 138 — Task management function sequence of SSP frames .....                                 | 424 |
| Figure 139 — Non-data command sequence of SSP frames .....   | 425 |
| Figure 140 — Write command sequence of SSP frames .....  | 425 |
| Figure 141 — Read command sequence of SSP frames .....   | 426 |
| Figure 142 — Bidirectional command sequence of SSP frames .....                                    | 427 |
| Figure 143 — ST_I (transport layer for SSP initiator ports) state machines .....                   | 436 |
| Figure 144 — ST_T (transport layer for SSP target ports) state machines .....                      | 452 |
| Figure 145 — Sequence of SMP frames .....  | 473 |
| Figure 146 — MT_IP (transport layer for SMP initiator ports) state machine .....                   | 474 |
| Figure 147 — MT_TP (transport layer for SMP target ports) state machine .....                      | 476 |
| Figure 148 — SA_PC (SCSI application layer power condition) state machine for SAS .....            | 516 |
| Figure A.1 — CJTPAT pre-scrambling .....   | 642 |
| Figure B.1 — SAS speed negotiation sequence (phy A:SNW-1 only, phy B:SNW-1 only) .....             | 649 |
| Figure B.2 — SAS speed negotiation sequence (phy A:SNW-1, SNW-2, phy B:SNW-1, SNW-2) .....         | 650 |
| Figure B.3 — SAS speed negotiation sequence (phy A:SNW-1, SNW-2, SNW-3, phy B:SNW-1, SNW-2) .....  | 651 |
| Figure B.4 — SAS speed negotiation sequence (phy A:SNW-2, SNW-3, phy B:SNW-1, SNW-2) .....         | 652 |
| Figure B.5 — SAS speed negotiation sequence (phy A:SNW-1 only, phy B:SNW-2 only) .....             | 653 |
| Figure C.1 — CRC generator example .....   | 654 |
| Figure C.2 — CRC checker example .....   | 654 |
| Figure D.1 — BCH(69, 39, 9) code generator .....   | 659 |
| Figure E.1 — Scrambler .....   | 665 |
| Figure J.1 — Example topology .....  | 677 |
| Figure J.2 — Connection request - OPEN_ACCEPT .....  | 679 |
| Figure J.3 — Connection request - OPEN_REJECT by end device .....                                  | 680 |
| Figure J.4 — Connection request - OPEN_REJECT by expander device .....                             | 681 |
| Figure J.5 — Connection request - arbitration lost .....   | 682 |
| Figure J.6 — Connection request - backoff and retry .....  | 683 |
| Figure J.7 — Connection request - backoff and reverse path .....                                   | 684 |
| Figure J.8 — Connection close - single step .....  | 685 |
| Figure J.9 — Connection close - simultaneous .....   | 686 |
| Figure J.10 — BREAK handling during path arbitration when the BREAK_REPLY method is disabled ..... | 687 |
| Figure J.11 — BREAK handling during a connection when the BREAK_REPLY method is disabled .....     | 688 |
| Figure J.12 — BREAK handling during path arbitration when the BREAK_REPLY method is enabled .....  | 689 |
| Figure J.13 — BREAK handling during a connection when the BREAK_REPLY method is enabled .....      | 690 |
| Figure J.14 — STP connection - originated by STP initiator port .....                              | 691 |
| Figure J.15 — STP connection - originated by STP target port in an STP/SATA bridge .....           | 692 |
| Figure J.16 — STP connection close - originated by STP initiator port .....                        | 693 |
| Figure J.17 — STP connection close - originated by STP target port in an STP/SATA bridge .....     | 694 |
| Figure J.18 — XL1:Request_Path to XL5:Forward_Open transition .....                                | 695 |
| Figure J.19 — Partial pathway recovery .....   | 696 |