

# ISO/IEC 14776-261:2012-11 (E)

## Information technology - Small Computer System Interface (SCSI) - Part 261: SAS Protocol Layer (SPL)

---

<b>Contents</b>	<b>Page</b>
FOREWORD.....	18
INTRODUCTION.....	20
General .....	20
SCSI standards family.....	21
1 Scope.....	23
2 Normative references.....	23
3 Terms, definitions, symbols, abbreviations, keywords, and conventions.....	25
3.1 Terms and definitions.....	25
3.2 Symbols and abbreviations .....	46
3.3 Keywords .....	48
3.4 Editorial conventions .....	49
3.5 Class diagram and object diagram conventions.....	51
3.6 State machine conventions .....	55
3.6.1 State machine conventions overview.....	55
3.6.2 Transitions.....	56
3.6.3 Messages, requests, indications, confirmations, responses, and event notifications .....	57
3.6.4 State machine counters, timers, and variables .....	57
3.6.5 State machine arguments .....	57
3.7 Bit and byte ordering .....	58
3.8 Notation for procedures and functions .....	58
4 General .....	60
4.1 Architecture .....	60
4.1.1 Architecture overview.....	60
4.1.2 Physical links and phys.....	61
4.1.3 Logical links.....	66
4.1.4 Ports (narrow ports and wide ports).....	66
4.1.5 Application clients and device servers .....	69
4.1.6 SAS devices.....	70
4.1.7 Expander devices.....	71
4.1.8 Service delivery subsystem.....	72
4.1.9 Domains .....	73
4.1.10 Expander device topologies .....	75
4.1.11 Pathways.....	77
4.1.12 Connections .....	77
4.1.13 Broadcasts .....	79
4.2 Names and identifiers .....	81
4.2.1 Names and identifiers overview .....	81
4.2.2 NAA IEEE Registered format identifier .....	82
4.2.3 NAA Locally Assigned format identifier .....	83
4.2.4 SAS address .....	84
4.2.5 Hashed SAS addresses .....	84
4.2.6 Device names and expander device SAS addresses .....	84
4.2.7 Device name for SATA devices with world wide names .....	85
4.2.8 Port names.....	85
4.2.9 Port identifiers and SAS port SAS addresses.....	85
4.2.10 Phy identifiers.....	86

4.3 State machines .....	87
4.3.1 State machine overview .....	87
4.3.2 Transmit data path .....	88
4.3.3 Receive data path .....	93
4.3.4 State machines and SAS Device, SAS Port, and SAS Phy classes .....	96
4.4 Resets .....	98
4.4.1 Reset overview .....	98
4.4.2 Hard reset .....	100
4.5 I_T nexus loss .....	100
4.6 Expander device model .....	101
4.6.1 Expander device model overview .....	101
4.6.2 Expander ports .....	102
4.6.3 Expander connection manager (ECM) .....	103
4.6.4 Expander connection router (ECR) .....	103
4.6.5 Broadcast propagation processor (BPP) .....	104
4.6.6 Expander device interfaces .....	104
4.6.7 Expander device routing .....	111
4.6.8 Expander device reduced functionality .....	115
4.6.9 Broadcast (Expander) handling .....	116
4.7 Discover process .....	116
4.7.1 Discover process overview .....	116
4.7.2 Starting the discover process (Broadcast (Change) handling) .....	116
4.7.3 Discover process traversal .....	116
4.7.4 Discover process in a self-configuring expander device .....	118
4.7.5 Enabling multiplexing .....	119
4.8 Configuration subprocess .....	120
4.8.1 Configuration subprocess overview .....	120
4.8.2 Allowed expander device topologies .....	120
4.8.3 Externally configurable expander device route table optimization .....	121
4.8.4 Externally configurable expander device expander route index order .....	122
4.9 Zoning .....	128
4.9.1 Zoning overview .....	128
4.9.2 Zoning expander device requirements .....	132
4.9.3 Zoning operation .....	134
4.9.4 Zone phy information and link reset sequences .....	140
4.9.5 Broadcast processing in a zoning expander device with zoning enabled .....	142
4.9.6 Zone configuration .....	143
4.10 Phy power conditions .....	146
4.10.1 Low phy power conditions .....	146
4.10.2 SATA phy power conditions .....	148
4.11 SAS device and expander device power conditions .....	148
4.12 Phy test functions .....	149
4.12.1 Phy test functions overview .....	149
4.12.2 Transmit pattern phy test function .....	149
4.13 Phy events .....	150
5 Phy layer .....	155
5.1 Phy layer overview .....	155
5.2 8b10b coding .....	155
5.2.1 8b10b coding overview .....	155
5.2.2 8b10b coding notation conventions .....	155
5.3 Character encoding and decoding .....	156
5.3.1 Introduction .....	156
5.3.2 Bit transmission order .....	156
5.3.3 Character transmission order .....	156
5.3.4 Frame transmission order .....	156
5.3.5 Running disparity (RD) .....	157
5.3.6 Data characters .....	157

5.3.7 Control characters.....	163
5.3.8 Encoding characters in the transmitter.....	164
5.3.9 Decoding characters in the receiver.....	164
5.4 Dwords, primitives, data dwords, and invalid dwords.....	164
5.5 Bit order.....	165
5.6 Out of band (OOB) signals.....	166
5.6.1 OOB signals overview.....	166
5.6.2 SP Transmission of OOB signals.....	166
5.6.3 Receiver detection of OOB signals.....	167
5.6.4 SATA port selection signal.....	169
5.6.5 Phy power conditions.....	170
5.7 Phy reset sequences.....	170
5.7.1 Phy reset sequences overview.....	170
5.7.2 SATA phy reset sequence.....	171
5.7.3 SAS to SATA phy reset sequence.....	172
5.7.4 SAS to SAS phy reset sequence.....	174
5.7.5 Phy reset sequence after devices are attached.....	196
5.8 Phy power condition sequences.....	197
5.8.1 Transitioning from the active phy power condition to a low phy power condition.....	197
5.8.2 Transitioning from a low phy power condition to the active phy power condition.....	197
5.8.3 Events during low phy power condition.....	198
5.9 SP (phy layer) state machine.....	200
5.9.1 SP state machine overview.....	200
5.9.2 SP transmitter and receiver.....	202
5.9.3 OOB sequence states.....	204
5.9.4 SAS speed negotiation states.....	209
5.9.5 SAS phy power conditions states.....	219
5.9.6 SATA host emulation states.....	222
5.9.7 SATA port selector state SP25:SATA_PortSel.....	227
5.9.8 SATA spinup hold state SP26:SATA_SpinupHold.....	228
5.10 SP_DWS (phy layer dword synchronization) state machine.....	228
5.10.1 SP_DWS state machine overview.....	228
5.10.2 SP_DWS receiver.....	230
5.10.3 SP_DWS0:AcquireSync state.....	231
5.10.4 SP_DWS1:Valid1 state.....	231
5.10.5 SP_DWS2:Valid2 state.....	232
5.10.6 SP_DWS3:SyncAcquired state.....	232
5.10.7 SP_DWS4:Lost1 state.....	232
5.10.8 SP_DWS5:Lost1Recovered state.....	233
5.10.9 SP_DWS6:Lost2 state.....	233
5.10.10 SP_DWS7:Lost2Recovered state.....	234
5.10.11 SP_DWS8:Lost3 state.....	234
5.10.12 SP_DWS9:Lost3Recovered state.....	234
5.11 Multiplexing.....	235
5.12 Spinup.....	236
6 Link layer.....	237
6.1 Link layer overview.....	237
6.2 Primitives.....	237
6.2.1 Primitives overview.....	237
6.2.2 Primitive summary.....	238
6.2.3 Primitive encodings.....	243
6.2.4 Primitive sequences.....	248
6.2.5 Deletable primitives.....	252
6.2.6 Primitives not specific to type of connections.....	256

6.2.7 Primitives used only inside SSP and SMP connections.....	262
6.2.8 Primitives used only inside STP connections and on SATA physical links.....	263
6.3 Physical link rate tolerance management .....	264
6.3.1 Physical link rate tolerance management overview .....	264
6.3.2 Phys originating dwords.....	266
6.3.3 Expander phys forwarding dwords.....	266
6.4 Idle physical links .....	267
6.5 CRC .....	267
6.5.1 CRC overview .....	267
6.5.2 CRC generation .....	269
6.5.3 CRC checking.....	271
6.6 Scrambling .....	272
6.7 Bit order of CRC and scrambler .....	274
6.8 Address frames .....	277
6.8.1 Address frames overview.....	277
6.8.2 IDENTIFY address frame.....	279
6.8.3 OPEN address frame.....	282
6.9 Link reset sequence .....	285
6.9.1 Link reset sequence overview.....	285
6.9.2 Expander device handling of link reset sequences.....	288
6.10 SL_IR (link layer identification and hard reset) state machines .....	288
6.10.1 SL_IR state machines overview.....	288
6.10.2 SL_IR transmitter and receiver .....	290
6.10.3 SL_IR_TIR (transmit IDENTIFY or HARD_RESET) state machine.....	290
6.10.4 SL_IR_RIF (receive IDENTIFY address frame) state machine.....	292
6.10.5 SL_IR_IRC (identification and hard reset control) state machine .....	293
6.11 Entering a low phy power condition .....	294
6.12 SAS domain changes (Broadcast (Change) usage) .....	295
6.13 Connections .....	296
6.13.1 Connections overview .....	296
6.13.2 Opening a connection .....	296
6.13.3 Arbitration fairness .....	298
6.13.4 Arbitration inside an expander device .....	300
6.13.5 BREAK handling .....	304
6.13.6 Aborting a connection request .....	305
6.13.7 Closing a connection.....	307
6.13.8 Breaking a connection.....	308
6.14 Rate matching .....	309
6.15 SL (link layer for SAS logical phys) state machines.....	312
6.15.1 SL state machines overview .....	312
6.15.2 SL transmitter and receiver .....	315
6.15.3 SL_RA (receive OPEN address frame) state machine .....	317
6.15.4 SL_CC (connection control) state machine.....	317
6.16 XL (link layer for expander logical phys) state machine .....	330
6.16.1 XL state machine overview .....	330
6.16.2 XL transmitter and receiver .....	335
6.16.3 XL0:Idle state .....	336
6.16.4 XL1:Request_Path state .....	338
6.16.5 XL2:Request_Open state.....	340
6.16.6 XL3:Open_Confirm_Wait state .....	340
6.16.7 XL4:Open_Reject state .....	342
6.16.8 XL5:Forward_Open state .....	342
6.16.9 XL6:Open_Response_Wait state.....	343
6.16.10 XL7:Connected state.....	344

6.16.11 XL8:Close_Wait state.....	345
6.16.12 XL9:Break state.....	346
6.16.13 XL10:Break_Wait state .....	347
6.16.14 XL11:PS_Request state.....	347
6.16.15 XL12:PS_Quiet state.....	348
6.17 SSP link layer.....	349
6.17.1 Opening an SSP connection.....	349
6.17.2 Full duplex.....	349
6.17.3 SSP frame transmission and reception.....	350
6.17.4 SSP flow control.....	350
6.17.5 Interlocked frames.....	351
6.17.6 Breaking an SSP connection .....	353
6.17.7 Closing an SSP connection.....	353
6.17.8 SSP (link layer for SSP phys) state machines .....	354
6.18 STP link layer.....	365
6.18.1 STP frame transmission and reception.....	365
6.18.2 STP flow control.....	366
6.18.3 Continued primitive sequence.....	370
6.18.4 Affiliations.....	371
6.18.5 Opening an STP connection .....	373
6.18.6 Closing an STP connection.....	375
6.18.7 STP connection management examples .....	376
6.18.8 STP (link layer for STP phys) state machines.....	379
6.18.9 SMP target port support.....	379
6.19 SMP link layer .....	379
6.19.1 SMP frame transmission and reception .....	379
6.19.2 SMP flow control .....	379
6.19.3 Opening an SMP connection .....	379
6.19.4 Closing an SMP connection.....	380
6.19.5 SMP (link layer for SMP phys) state machines.....	380
7 Port layer.....	385
7.1 Port layer overview.....	385
7.2 PL (port layer) state machines .....	385
7.2.1 PL state machines overview .....	385
7.2.2 PL_OC (port layer overall control) state machine .....	387
7.2.3 PL_PM (port layer phy manager) state machine.....	398
8 Transport layer.....	409
8.1 Transport layer overview.....	409
8.2 SSP transport layer .....	410
8.2.1 SSP frame format.....	410
8.2.2 Information units.....	414
8.2.3 Sequences of SSP frames.....	424
8.2.4 SSP transport layer handling of link layer errors.....	427
8.2.5 SSP transport layer error handling summary .....	432
8.2.6 ST (transport layer for SSP ports) state machines.....	434
8.3 STP transport layer .....	470
8.3.1 Initial FIS.....	470
8.3.2 BIST Activate FIS.....	470
8.3.3 TT (transport layer for STP ports) state machines.....	470
8.4 SMP transport layer .....	471
8.4.1 SMP transport layer overview .....	471
8.4.2 SMP_REQUEST frame.....	472
8.4.3 SMP_RESPONSE frame .....	472
8.4.4 Sequence of SMP frames .....	473

8.4.5 MT (transport layer for SMP ports) state machines .....	473
9 Application layer .....	478
9.1 Application layer overview .....	478
9.2 SCSI application layer .....	478
9.2.1 SCSI transport protocol services .....	478
9.2.2 Application client error handling .....	490
9.2.3 Device server error handling .....	491
9.2.4 Task router and task manager error handling .....	492
9.2.5 SCSI transport protocol event notifications .....	492
9.2.6 SCSI commands .....	492
9.2.7 SCSI mode parameters .....	493
9.2.8 SCSI log parameters .....	504
9.2.9 SCSI diagnostic parameters .....	507
9.2.10 SCSI power conditions .....	514
9.2.11 SCSI vital product data (VPD) .....	523
9.3 ATA application layer .....	526
9.4 Management application layer .....	526
9.4.1 READY LED signal behavior .....	526
9.4.2 Management protocol services .....	527
9.4.3 SMP functions .....	528
Annex A (normative) Jitter tolerance patterns .....	641
Annex B (informative) SAS to SAS phy reset sequence examples .....	649
Annex C (informative) CRC .....	654
Annex D (informative) SAS address hashing .....	658
Annex E (informative) Scrambling .....	665
Annex F (informative) ATA architectural notes .....	669
Annex G (informative) Minimum deletable primitive insertion rate summary .....	672
Annex H (informative) Zone permission configuration descriptor examples .....	673
Annex I (informative) SAS addressing .....	676
Annex J (informative) Expander device handling of connections .....	677
Annex K (informative) Primitive encoding .....	698
Bibliography .....	701

Figure 1 — Organization of this standard .....	20
Figure 2 — SCSI document relationships .....	21
Figure 3 — ATA document relationships .....	21
Figure 4 — Classes in class diagrams .....	51
Figure 5 — Association relationships in class diagrams .....	52
Figure 6 — Aggregation relationships in class diagrams .....	53
Figure 7 — Generalization relationships in class diagrams .....	54
Figure 8 — Dependency relationships in class diagrams .....	54
Figure 9 — Objects in object diagrams .....	55
Figure 10 — State machine conventions .....	56
Figure 11 — SAS Domain class diagram .....	61
Figure 12 — Phy class diagram .....	63
Figure 13 — SAS phy object diagram .....	64
Figure 14 — Expander phy object diagram .....	65
Figure 15 — Ports (narrow ports and wide ports) .....	67
Figure 16 — Port class diagram .....	68
Figure 17 — Port object diagram .....	69
Figure 18 — SAS devices .....	71
Figure 19 — Expander device .....	72
Figure 20 — Domains .....	73
Figure 21 — SAS domain bridging to ATA domains .....	73
Figure 22 — SAS domains bridging to ATA domains with SATA port selectors .....	74
Figure 23 — Devices spanning SAS domains .....	75
Figure 24 — Single expander device topology example .....	75
Figure 25 — Multiple expander device topologies .....	76
Figure 26 — Potential pathways .....	77
Figure 27 — Multiple connections on wide ports .....	79
Figure 28 — State machines for SAS devices .....	87
Figure 29 — State machines for expander devices .....	88
Figure 30 — Transmit data path in a SAS phy .....	89
Figure 31 — SSP link, port, SSP transport, and SCSI application layer state machines .....	90
Figure 32 — SMP link, port, SMP transport, and management application layer state machines .....	91
Figure 33 — STP link, port, STP transport, and ATA application layer state machines .....	92
Figure 34 — Transmit data path and state machines in an expander phy .....	93
Figure 35 — Receive data path in a SAS phy .....	94
Figure 36 — Receive data path in an expander phy .....	95
Figure 37 — State machines and SAS Device classes .....	96
Figure 38 — State machines and Expander Device classes .....	97
Figure 39 — Reset terminology .....	99
Figure 40 — Expander device model .....	102
Figure 41 — Expander device interfaces .....	105
Figure 42 — Expander device interface detail .....	106
Figure 43 — Phy-based expander route table .....	114
Figure 44 — Expander-based expander route table .....	115
Figure 45 — Level-order traversal example .....	117
Figure 46 — Examples of invalid topologies .....	121
Figure 47 — Externally configurable expander device and table-to-table attachment .....	124
Figure 48 — Expander route index levels example .....	125
Figure 49 — Expander route index order example .....	127
Figure 50 — Zoning example .....	129
Figure 51 — One ZPSDS example .....	129
Figure 52 — Zone manager location examples .....	130
Figure 53 — Three ZPSDSes example .....	131
Figure 54 — Extending a ZPSDS example .....	133
Figure 55 — Overtaking a ZPSDS example .....	134
Figure 56 — Zoning expander route table .....	139
Figure 57 — SAS bit transmission logic .....	165
Figure 58 — SAS bit reception logic .....	166

Figure 59 — OOB signal transmission .....	167
Figure 60 — OOB signal detection .....	169
Figure 61 — SATA OOB sequence .....	171
Figure 62 — SATA speed negotiation sequence .....	172
Figure 63 — SAS to SATA OOB sequence .....	173
Figure 64 — SAS to SAS OOB sequence .....	175
Figure 65 — SNW-1, SNW-2, and Final-SNW .....	178
Figure 66 — SNW-3 .....	180
Figure 67 — Train-SNW .....	185
Figure 68 — SAS speed negotiation sequence SNW flowchart .....	187
Figure 69 — SAS speed negotiation sequence (both phys SNW-1 through SNW-3) .....	189
Figure 70 — SAS speed negotiation sequence (phy A: SNW-1 through SNW-3, phy B: SNW-2 only) .....	190
Figure 71 — SAS speed negotiation sequence (phy A: SNW-3 only, phy B: SNW-1 only) .....	191
Figure 72 — SAS speed negotiation sequence - phy reset problem in Final-SNW .....	192
Figure 73 — SAS speed negotiation sequence - phy reset problem in SNW-3 .....	193
Figure 74 — SAS speed negotiation sequence - phy reset problem in Train-SNW .....	194
Figure 75 — SAS speed negotiation sequence - multiple Train-SNWs .....	195
Figure 76 — Hot-plug and the phy reset sequence .....	197
Figure 77 — Transition to active phy power condition .....	198
Figure 78 — Hot plug and low phy power condition .....	199
Figure 79 — SP (phy layer) state machine - OOB sequence states .....	204
Figure 80 — SP (phy layer) state machine - SAS speed negotiation states .....	210
Figure 81 — SP (phy layer) state machine - SAS speed negotiation states for SNW-3 and Train-SNW .....	211
Figure 82 — SP (phy layer) state machine - SAS phy power condition states .....	220
Figure 83 — SP (phy layer) state machine - SATA host emulation states .....	223
Figure 84 — SP (phy layer) state machine – SATA port selector state .....	227
Figure 85 — SP (phy layer) state machine - SATA spinup hold state .....	228
Figure 86 — SP_DWS (phy layer dword synchronization) state machine .....	230
Figure 87 — Multiplexing disabled .....	235
Figure 88 — Multiplexing enabled .....	235
Figure 89 — Transmitting a repeated primitive sequence .....	249
Figure 90 — Receiving a repeated primitive sequence .....	249
Figure 91 — Extended primitive sequences .....	250
Figure 92 — Triple primitive sequences .....	251
Figure 93 — Redundant primitive sequences .....	252
Figure 94 — Elasticity buffer .....	265
Figure 95 — Address frame, SSP frame, and SMP frame CRC bit ordering .....	270
Figure 96 — STP frame CRC bit ordering .....	271
Figure 97 — Transmit path bit ordering .....	274
Figure 98 — Receive path bit ordering .....	275
Figure 99 — STP transmit path bit ordering .....	276
Figure 100 — STP receive path bit ordering .....	277
Figure 101 — Address frame transmission .....	277
Figure 102 — Identification sequence .....	286
Figure 103 — Hard reset sequence .....	287
Figure 104 — SL_IR (link layer identification and hard reset) state machines .....	289
Figure 105 — Transitioning from the active phy power condition to a low phy power condition .....	294
Figure 106 — Example simultaneous connection recommendations for wide ports .....	297
Figure 107 — Aborting a connection request with a BREAK primitive sequence .....	306
Figure 108 — Connection request timeout example .....	307
Figure 109 — Closing a connection example .....	308
Figure 110 — Rate matching example .....	311
Figure 111 — SL (link layer for SAS logical phys) state machines (part 1) .....	313
Figure 112 — SL (link layer for SAS logical phys) state machines (part 2) .....	314
Figure 113 — SL (link layer for SAS logical phys) state machines (part 3) .....	315
Figure 114 — XL (link layer for expander logical phys) state machine (part 1) .....	332
Figure 115 — XL (link layer for expander logical phys) state machine (part 2) .....	333
Figure 116 — XL (link layer for expander logical phys) state machine (part 3) .....	334

Figure 117 — SSP frame transmission .....	350
Figure 118 — Interlocked frames .....	352
Figure 119 — Non-interlocked frames with the same initiator port transfer tags .....	352
Figure 120 — Non-interlocked frames with different initiator port transfer tags .....	353
Figure 121 — Closing an SSP connection example .....	354
Figure 122 — SSP (link layer for SSP phys) state machines (part 1 - frame transmission) .....	356
Figure 123 — SSP (link layer for SSP phys) state machines (part 2 - frame reception) .....	357
Figure 124 — STP frame transmission .....	365
Figure 125 — STP flow control .....	369
Figure 126 — Transmitting a continued primitive sequence .....	371
Figure 127 — Receiving a continued primitive sequence .....	371
Figure 128 — Example simultaneous connection recommendations for an expander device .....	375
Figure 129 — STP initiator port opening an STP connection .....	377
Figure 130 — STP target port opening an STP connection .....	378
Figure 131 — SMP frame transmission .....	379
Figure 132 — SMP_IP (link layer for SMP initiator phys) state machine .....	381
Figure 133 — SMP_TP (link layer for SMP target phys) state machine .....	383
Figure 134 — Port layer examples .....	386
Figure 135 — PL_OC (port layer overall control) state machine .....	389
Figure 136 — PL_PM (port layer phy manager) state machine (part 1) .....	400
Figure 137 — PL_PM (port layer phy manager) state machine (part 2) .....	401
Figure 138 — Task management function sequence of SSP frames .....	424
Figure 139 — Non-data command sequence of SSP frames .....	425
Figure 140 — Write command sequence of SSP frames .....	425
Figure 141 — Read command sequence of SSP frames .....	426
Figure 142 — Bidirectional command sequence of SSP frames .....	427
Figure 143 — ST_I (transport layer for SSP initiator ports) state machines .....	436
Figure 144 — ST_T (transport layer for SSP target ports) state machines .....	452
Figure 145 — Sequence of SMP frames .....	473
Figure 146 — MT_IP (transport layer for SMP initiator ports) state machine .....	474
Figure 147 — MT_TP (transport layer for SMP target ports) state machine .....	476
Figure 148 — SA_PC (SCSI application layer power condition) state machine for SAS .....	516
Figure A.1 — CJTPAT pre-scrambling .....	642
Figure B.1 — SAS speed negotiation sequence (phy A:SNW-1 only, phy B:SNW-1 only) .....	649
Figure B.2 — SAS speed negotiation sequence (phy A:SNW-1, SNW-2, phy B:SNW-1, SNW-2) .....	650
Figure B.3 — SAS speed negotiation sequence (phy A:SNW-1, SNW-2, SNW-3, phy B:SNW-1, SNW-2) .....	651
Figure B.4 — SAS speed negotiation sequence (phy A:SNW-2, SNW-3, phy B:SNW-1, SNW-2) .....	652
Figure B.5 — SAS speed negotiation sequence (phy A:SNW-1 only, phy B:SNW-2 only) .....	653
Figure C.1 — CRC generator example .....	654
Figure C.2 — CRC checker example .....	654
Figure D.1 — BCH(69, 39, 9) code generator .....	659
Figure E.1 — Scrambler .....	665
Figure J.1 — Example topology .....	677
Figure J.2 — Connection request - OPEN_ACCEPT .....	679
Figure J.3 — Connection request - OPEN_REJECT by end device .....	680
Figure J.4 — Connection request - OPEN_REJECT by expander device .....	681
Figure J.5 — Connection request - arbitration lost .....	682
Figure J.6 — Connection request - backoff and retry .....	683
Figure J.7 — Connection request - backoff and reverse path .....	684
Figure J.8 — Connection close - single step .....	685
Figure J.9 — Connection close - simultaneous .....	686
Figure J.10 — BREAK handling during path arbitration when the BREAK_REPLY method is disabled .....	687
Figure J.11 — BREAK handling during a connection when the BREAK_REPLY method is disabled .....	688
Figure J.12 — BREAK handling during path arbitration when the BREAK_REPLY method is enabled .....	689
Figure J.13 — BREAK handling during a connection when the BREAK_REPLY method is enabled .....	690
Figure J.14 — STP connection - originated by STP initiator port .....	691
Figure J.15 — STP connection - originated by STP target port in an STP/SATA bridge .....	692
Figure J.16 — STP connection close - originated by STP initiator port .....	693
Figure J.17 — STP connection close - originated by STP target port in an STP/SATA bridge .....	694
Figure J.18 — XL1:Request_Path to XL5:Forward_Open transition .....	695
Figure J.19 — Partial pathway recovery .....	696