

ISO/IEC 14776-261:2012-11 (E)

Information technology - Small Computer System Interface (SCSI) - Part 261: SAS Protocol Layer (SPL)

Contents	Page
FOREWORD.....	18
INTRODUCTION.....	20
General	20
SCSI standards family.....	21
1 Scope.....	23
2 Normative references.....	23
3 Terms, definitions, symbols, abbreviations, keywords, and conventions.....	25
3.1 Terms and definitions.....	25
3.2 Symbols and abbreviations	46
3.3 Keywords	48
3.4 Editorial conventions	49
3.5 Class diagram and object diagram conventions.....	51
3.6 State machine conventions	55
3.6.1 State machine conventions overview.....	55
3.6.2 Transitions.....	56
3.6.3 Messages, requests, indications, confirmations, responses, and event notifications	57
3.6.4 State machine counters, timers, and variables	57
3.6.5 State machine arguments	57
3.7 Bit and byte ordering	58
3.8 Notation for procedures and functions	58
4 General	60
4.1 Architecture	60
4.1.1 Architecture overview.....	60
4.1.2 Physical links and phys	61
4.1.3 Logical links.....	66
4.1.4 Ports (narrow ports and wide ports).....	66
4.1.5 Application clients and device servers	69
4.1.6 SAS devices.....	70
4.1.7 Expander devices.....	71
4.1.8 Service delivery subsystem.....	72
4.1.9 Domains	73
4.1.10 Expander device topologies	75
4.1.11 Pathways.....	77
4.1.12 Connections	77
4.1.13 Broadcasts	79
4.2 Names and identifiers	81
4.2.1 Names and identifiers overview	81
4.2.2 NAA IEEE Registered format identifier	82
4.2.3 NAA Locally Assigned format identifier	83
4.2.4 SAS address	84
4.2.5 Hashed SAS addresses	84
4.2.6 Device names and expander device SAS addresses	84
4.2.7 Device name for SATA devices with world wide names	85
4.2.8 Port names.....	85
4.2.9 Port identifiers and SAS port SAS addresses.....	85
4.2.10 Phy identifiers.....	86

4.3 State machines	87
4.3.1 State machine overview	87
4.3.2 Transmit data path	88
4.3.3 Receive data path	93
4.3.4 State machines and SAS Device, SAS Port, and SAS Phy classes	96
4.4 Resets	98
4.4.1 Reset overview	98
4.4.2 Hard reset	100
4.5 I_T nexus loss	100
4.6 Expander device model	101
4.6.1 Expander device model overview	101
4.6.2 Expander ports	102
4.6.3 Expander connection manager (ECM)	103
4.6.4 Expander connection router (ECR)	103
4.6.5 Broadcast propagation processor (BPP)	104
4.6.6 Expander device interfaces	104
4.6.7 Expander device routing	111
4.6.8 Expander device reduced functionality	115
4.6.9 Broadcast (Expander) handling	116
4.7 Discover process	116
4.7.1 Discover process overview	116
4.7.2 Starting the discover process (Broadcast (Change) handling)	116
4.7.3 Discover process traversal	116
4.7.4 Discover process in a self-configuring expander device	118
4.7.5 Enabling multiplexing	119
4.8 Configuration subprocess	120
4.8.1 Configuration subprocess overview	120
4.8.2 Allowed expander device topologies	120
4.8.3 Externally configurable expander device route table optimization	121
4.8.4 Externally configurable expander device expander route index order	122
4.9 Zoning	128
4.9.1 Zoning overview	128
4.9.2 Zoning expander device requirements	132
4.9.3 Zoning operation	134
4.9.4 Zone phy information and link reset sequences	140
4.9.5 Broadcast processing in a zoning expander device with zoning enabled	142
4.9.6 Zone configuration	143
4.10 Phy power conditions	146
4.10.1 Low phy power conditions	146
4.10.2 SATA phy power conditions	148
4.11 SAS device and expander device power conditions	148
4.12 Phy test functions	149
4.12.1 Phy test functions overview	149
4.12.2 Transmit pattern phy test function	149
4.13 Phy events	150
5 Phy layer	155
5.1 Phy layer overview	155
5.2 8b10b coding	155
5.2.1 8b10b coding overview	155
5.2.2 8b10b coding notation conventions	155
5.3 Character encoding and decoding	156
5.3.1 Introduction	156
5.3.2 Bit transmission order	156
5.3.3 Character transmission order	156
5.3.4 Frame transmission order	156
5.3.5 Running disparity (RD)	157
5.3.6 Data characters	157

5.3.7 Control characters.....	163
5.3.8 Encoding characters in the transmitter.....	164
5.3.9 Decoding characters in the receiver.....	164
5.4 Dwords, primitives, data dwords, and invalid dwords.....	164
5.5 Bit order.....	165
5.6 Out of band (OOB) signals.....	166
5.6.1 OOB signals overview.....	166
5.6.2 SP Transmission of OOB signals.....	166
5.6.3 Receiver detection of OOB signals.....	167
5.6.4 SATA port selection signal.....	169
5.6.5 Phy power conditions.....	170
5.7 Phy reset sequences.....	170
5.7.1 Phy reset sequences overview.....	170
5.7.2 SATA phy reset sequence.....	171
5.7.3 SAS to SATA phy reset sequence.....	172
5.7.4 SAS to SAS phy reset sequence.....	174
5.7.5 Phy reset sequence after devices are attached.....	196
5.8 Phy power condition sequences.....	197
5.8.1 Transitioning from the active phy power condition to a low phy power condition.....	197
5.8.2 Transitioning from a low phy power condition to the active phy power condition.....	197
5.8.3 Events during low phy power condition.....	198
5.9 SP (phy layer) state machine.....	200
5.9.1 SP state machine overview.....	200
5.9.2 SP transmitter and receiver.....	202
5.9.3 OOB sequence states.....	204
5.9.4 SAS speed negotiation states.....	209
5.9.5 SAS phy power conditions states.....	219
5.9.6 SATA host emulation states.....	222
5.9.7 SATA port selector state SP25:SATA_PortSel.....	227
5.9.8 SATA spinup hold state SP26:SATA_SpinupHold.....	228
5.10 SP_DWS (phy layer dword synchronization) state machine.....	228
5.10.1 SP_DWS state machine overview.....	228
5.10.2 SP_DWS receiver.....	230
5.10.3 SP_DWS0:AcquireSync state.....	231
5.10.4 SP_DWS1:Valid1 state.....	231
5.10.5 SP_DWS2:Valid2 state.....	232
5.10.6 SP_DWS3:SyncAcquired state.....	232
5.10.7 SP_DWS4:Lost1 state.....	232
5.10.8 SP_DWS5:Lost1Recovered state.....	233
5.10.9 SP_DWS6:Lost2 state.....	233
5.10.10 SP_DWS7:Lost2Recovered state.....	234
5.10.11 SP_DWS8:Lost3 state.....	234
5.10.12 SP_DWS9:Lost3Recovered state.....	234
5.11 Multiplexing.....	235
5.12 Spinup.....	236
6 Link layer.....	237
6.1 Link layer overview.....	237
6.2 Primitives.....	237
6.2.1 Primitives overview.....	237
6.2.2 Primitive summary.....	238
6.2.3 Primitive encodings.....	243
6.2.4 Primitive sequences.....	248
6.2.5 Deletable primitives.....	252
6.2.6 Primitives not specific to type of connections.....	256

6.2.7 Primitives used only inside SSP and SMP connections.....	262
6.2.8 Primitives used only inside STP connections and on SATA physical links.....	263
6.3 Physical link rate tolerance management	264
6.3.1 Physical link rate tolerance management overview	264
6.3.2 Phys originating dwords.....	266
6.3.3 Expander phys forwarding dwords.....	266
6.4 Idle physical links	267
6.5 CRC	267
6.5.1 CRC overview	267
6.5.2 CRC generation	269
6.5.3 CRC checking.....	271
6.6 Scrambling	272
6.7 Bit order of CRC and scrambler	274
6.8 Address frames	277
6.8.1 Address frames overview.....	277
6.8.2 IDENTIFY address frame.....	279
6.8.3 OPEN address frame.....	282
6.9 Link reset sequence	285
6.9.1 Link reset sequence overview.....	285
6.9.2 Expander device handling of link reset sequences.....	288
6.10 SL_IR (link layer identification and hard reset) state machines	288
6.10.1 SL_IR state machines overview.....	288
6.10.2 SL_IR transmitter and receiver	290
6.10.3 SL_IR_TIR (transmit IDENTIFY or HARD_RESET) state machine.....	290
6.10.4 SL_IR_RIF (receive IDENTIFY address frame) state machine.....	292
6.10.5 SL_IR_IRC (identification and hard reset control) state machine	293
6.11 Entering a low phy power condition	294
6.12 SAS domain changes (Broadcast (Change) usage)	295
6.13 Connections	296
6.13.1 Connections overview	296
6.13.2 Opening a connection	296
6.13.3 Arbitration fairness	298
6.13.4 Arbitration inside an expander device	300
6.13.5 BREAK handling	304
6.13.6 Aborting a connection request	305
6.13.7 Closing a connection.....	307
6.13.8 Breaking a connection.....	308
6.14 Rate matching	309
6.15 SL (link layer for SAS logical phys) state machines.....	312
6.15.1 SL state machines overview	312
6.15.2 SL transmitter and receiver	315
6.15.3 SL_RA (receive OPEN address frame) state machine	317
6.15.4 SL_CC (connection control) state machine.....	317
6.16 XL (link layer for expander logical phys) state machine	330
6.16.1 XL state machine overview	330
6.16.2 XL transmitter and receiver	335
6.16.3 XL0:Idle state	336
6.16.4 XL1:Request_Path state	338
6.16.5 XL2:Request_Open state.....	340
6.16.6 XL3:Open_Confirm_Wait state	340
6.16.7 XL4:Open_Reject state	342
6.16.8 XL5:Forward_Open state	342
6.16.9 XL6:Open_Response_Wait state.....	343
6.16.10 XL7:Connected state.....	344

6.16.11 XL8:Close_Wait state.....	345
6.16.12 XL9:Break state.....	346
6.16.13 XL10:Break_Wait state	347
6.16.14 XL11:PS_Request state.....	347
6.16.15 XL12:PS_Quiet state.....	348
6.17 SSP link layer.....	349
6.17.1 Opening an SSP connection	349
6.17.2 Full duplex.....	349
6.17.3 SSP frame transmission and reception.....	350
6.17.4 SSP flow control.....	350
6.17.5 Interlocked frames.....	351
6.17.6 Breaking an SSP connection	353
6.17.7 Closing an SSP connection.....	353
6.17.8 SSP (link layer for SSP phys) state machines	354
6.18 STP link layer.....	365
6.18.1 STP frame transmission and reception	365
6.18.2 STP flow control.....	366
6.18.3 Continued primitive sequence.....	370
6.18.4 Affiliations.....	371
6.18.5 Opening an STP connection	373
6.18.6 Closing an STP connection.....	375
6.18.7 STP connection management examples	376
6.18.8 STP (link layer for STP phys) state machines.....	379
6.18.9 SMP target port support.....	379
6.19 SMP link layer	379
6.19.1 SMP frame transmission and reception	379
6.19.2 SMP flow control	379
6.19.3 Opening an SMP connection	379
6.19.4 Closing an SMP connection.....	380
6.19.5 SMP (link layer for SMP phys) state machines.....	380
7 Port layer.....	385
7.1 Port layer overview.....	385
7.2 PL (port layer) state machines	385
7.2.1 PL state machines overview	385
7.2.2 PL_OC (port layer overall control) state machine	387
7.2.3 PL_PM (port layer phy manager) state machine.....	398
8 Transport layer.....	409
8.1 Transport layer overview.....	409
8.2 SSP transport layer	410
8.2.1 SSP frame format.....	410
8.2.2 Information units.....	414
8.2.3 Sequences of SSP frames	424
8.2.4 SSP transport layer handling of link layer errors.....	427
8.2.5 SSP transport layer error handling summary	432
8.2.6 ST (transport layer for SSP ports) state machines.....	434
8.3 STP transport layer	470
8.3.1 Initial FIS.....	470
8.3.2 BIST Activate FIS.....	470
8.3.3 TT (transport layer for STP ports) state machines	470
8.4 SMP transport layer	471
8.4.1 SMP transport layer overview	471
8.4.2 SMP_REQUEST frame.....	472
8.4.3 SMP_RESPONSE frame	472
8.4.4 Sequence of SMP frames	473

8.4.5 MT (transport layer for SMP ports) state machines	473
9 Application layer	478
9.1 Application layer overview	478
9.2 SCSI application layer	478
9.2.1 SCSI transport protocol services	478
9.2.2 Application client error handling	490
9.2.3 Device server error handling	491
9.2.4 Task router and task manager error handling	492
9.2.5 SCSI transport protocol event notifications	492
9.2.6 SCSI commands	492
9.2.7 SCSI mode parameters	493
9.2.8 SCSI log parameters	504
9.2.9 SCSI diagnostic parameters	507
9.2.10 SCSI power conditions	514
9.2.11 SCSI vital product data (VPD)	523
9.3 ATA application layer	526
9.4 Management application layer	526
9.4.1 READY LED signal behavior	526
9.4.2 Management protocol services	527
9.4.3 SMP functions	528
Annex A (normative) Jitter tolerance patterns	641
Annex B (informative) SAS to SAS phy reset sequence examples	649
Annex C (informative) CRC	654
Annex D (informative) SAS address hashing	658
Annex E (informative) Scrambling	665
Annex F (informative) ATA architectural notes	669
Annex G (informative) Minimum deletable primitive insertion rate summary	672
Annex H (informative) Zone permission configuration descriptor examples	673
Annex I (informative) SAS addressing	676
Annex J (informative) Expander device handling of connections	677
Annex K (informative) Primitive encoding	698
Bibliography	701

Figure 1 — Organization of this standard	20
Figure 2 — SCSI document relationships	21
Figure 3 — ATA document relationships	21
Figure 4 — Classes in class diagrams	51
Figure 5 — Association relationships in class diagrams	52
Figure 6 — Aggregation relationships in class diagrams	53
Figure 7 — Generalization relationships in class diagrams	54
Figure 8 — Dependency relationships in class diagrams	54
Figure 9 — Objects in object diagrams	55
Figure 10 — State machine conventions	56
Figure 11 — SAS Domain class diagram	61
Figure 12 — Phy class diagram	63
Figure 13 — SAS phy object diagram	64
Figure 14 — Expander phy object diagram	65
Figure 15 — Ports (narrow ports and wide ports)	67
Figure 16 — Port class diagram	68
Figure 17 — Port object diagram	69
Figure 18 — SAS devices	71
Figure 19 — Expander device	72
Figure 20 — Domains	73
Figure 21 — SAS domain bridging to ATA domains	73
Figure 22 — SAS domains bridging to ATA domains with SATA port selectors	74
Figure 23 — Devices spanning SAS domains	75
Figure 24 — Single expander device topology example	75
Figure 25 — Multiple expander device topologies	76
Figure 26 — Potential pathways	77
Figure 27 — Multiple connections on wide ports	79
Figure 28 — State machines for SAS devices	87
Figure 29 — State machines for expander devices	88
Figure 30 — Transmit data path in a SAS phy	89
Figure 31 — SSP link, port, SSP transport, and SCSI application layer state machines	90
Figure 32 — SMP link, port, SMP transport, and management application layer state machines	91
Figure 33 — STP link, port, STP transport, and ATA application layer state machines	92
Figure 34 — Transmit data path and state machines in an expander phy	93
Figure 35 — Receive data path in a SAS phy	94
Figure 36 — Receive data path in an expander phy	95
Figure 37 — State machines and SAS Device classes	96
Figure 38 — State machines and Expander Device classes	97
Figure 39 — Reset terminology	99
Figure 40 — Expander device model	102
Figure 41 — Expander device interfaces	105
Figure 42 — Expander device interface detail	106
Figure 43 — Phy-based expander route table	114
Figure 44 — Expander-based expander route table	115
Figure 45 — Level-order traversal example	117
Figure 46 — Examples of invalid topologies	121
Figure 47 — Externally configurable expander device and table-to-table attachment	124
Figure 48 — Expander route index levels example	125
Figure 49 — Expander route index order example	127
Figure 50 — Zoning example	129
Figure 51 — One ZPSDS example	129
Figure 52 — Zone manager location examples	130
Figure 53 — Three ZPSDSes example	131
Figure 54 — Extending a ZPSDS example	133
Figure 55 — Overtaking a ZPSDS example	134
Figure 56 — Zoning expander route table	139
Figure 57 — SAS bit transmission logic	165
Figure 58 — SAS bit reception logic	166

Figure 59 — OOB signal transmission	167
Figure 60 — OOB signal detection	169
Figure 61 — SATA OOB sequence	171
Figure 62 — SATA speed negotiation sequence	172
Figure 63 — SAS to SATA OOB sequence	173
Figure 64 — SAS to SAS OOB sequence	175
Figure 65 — SNW-1, SNW-2, and Final-SNW	178
Figure 66 — SNW-3	180
Figure 67 — Train-SNW	185
Figure 68 — SAS speed negotiation sequence SNW flowchart	187
Figure 69 — SAS speed negotiation sequence (both phys SNW-1 through SNW-3)	189
Figure 70 — SAS speed negotiation sequence (phy A: SNW-1 through SNW-3, phy B: SNW-2 only)	190
Figure 71 — SAS speed negotiation sequence (phy A: SNW-3 only, phy B: SNW-1 only)	191
Figure 72 — SAS speed negotiation sequence - phy reset problem in Final-SNW	192
Figure 73 — SAS speed negotiation sequence - phy reset problem in SNW-3	193
Figure 74 — SAS speed negotiation sequence - phy reset problem in Train-SNW	194
Figure 75 — SAS speed negotiation sequence - multiple Train-SNWs	195
Figure 76 — Hot-plug and the phy reset sequence	197
Figure 77 — Transition to active phy power condition	198
Figure 78 — Hot plug and low phy power condition	199
Figure 79 — SP (phy layer) state machine - OOB sequence states	204
Figure 80 — SP (phy layer) state machine - SAS speed negotiation states	210
Figure 81 — SP (phy layer) state machine - SAS speed negotiation states for SNW-3 and Train-SNW	211
Figure 82 — SP (phy layer) state machine - SAS phy power condition states	220
Figure 83 — SP (phy layer) state machine - SATA host emulation states	223
Figure 84 — SP (phy layer) state machine – SATA port selector state	227
Figure 85 — SP (phy layer) state machine - SATA spinup hold state	228
Figure 86 — SP_DWS (phy layer dword synchronization) state machine	230
Figure 87 — Multiplexing disabled	235
Figure 88 — Multiplexing enabled	235
Figure 89 — Transmitting a repeated primitive sequence	249
Figure 90 — Receiving a repeated primitive sequence	249
Figure 91 — Extended primitive sequences	250
Figure 92 — Triple primitive sequences	251
Figure 93 — Redundant primitive sequences	252
Figure 94 — Elasticity buffer	265
Figure 95 — Address frame, SSP frame, and SMP frame CRC bit ordering	270
Figure 96 — STP frame CRC bit ordering	271
Figure 97 — Transmit path bit ordering	274
Figure 98 — Receive path bit ordering	275
Figure 99 — STP transmit path bit ordering	276
Figure 100 — STP receive path bit ordering	277
Figure 101 — Address frame transmission	277
Figure 102 — Identification sequence	286
Figure 103 — Hard reset sequence	287
Figure 104 — SL_IR (link layer identification and hard reset) state machines	289
Figure 105 — Transitioning from the active phy power condition to a low phy power condition	294
Figure 106 — Example simultaneous connection recommendations for wide ports	297
Figure 107 — Aborting a connection request with a BREAK primitive sequence	306
Figure 108 — Connection request timeout example	307
Figure 109 — Closing a connection example	308
Figure 110 — Rate matching example	311
Figure 111 — SL (link layer for SAS logical phys) state machines (part 1)	313
Figure 112 — SL (link layer for SAS logical phys) state machines (part 2)	314
Figure 113 — SL (link layer for SAS logical phys) state machines (part 3)	315
Figure 114 — XL (link layer for expander logical phys) state machine (part 1)	332
Figure 115 — XL (link layer for expander logical phys) state machine (part 2)	333
Figure 116 — XL (link layer for expander logical phys) state machine (part 3)	334

Figure 117 — SSP frame transmission	350
Figure 118 — Interlocked frames	352
Figure 119 — Non-interlocked frames with the same initiator port transfer tags	352
Figure 120 — Non-interlocked frames with different initiator port transfer tags	353
Figure 121 — Closing an SSP connection example	354
Figure 122 — SSP (link layer for SSP phys) state machines (part 1 - frame transmission)	356
Figure 123 — SSP (link layer for SSP phys) state machines (part 2 - frame reception)	357
Figure 124 — STP frame transmission	365
Figure 125 — STP flow control	369
Figure 126 — Transmitting a continued primitive sequence	371
Figure 127 — Receiving a continued primitive sequence	371
Figure 128 — Example simultaneous connection recommendations for an expander device	375
Figure 129 — STP initiator port opening an STP connection	377
Figure 130 — STP target port opening an STP connection	378
Figure 131 — SMP frame transmission	379
Figure 132 — SMP_IP (link layer for SMP initiator phys) state machine	381
Figure 133 — SMP_TP (link layer for SMP target phys) state machine	383
Figure 134 — Port layer examples	386
Figure 135 — PL_OC (port layer overall control) state machine	389
Figure 136 — PL_PM (port layer phy manager) state machine (part 1)	400
Figure 137 — PL_PM (port layer phy manager) state machine (part 2)	401
Figure 138 — Task management function sequence of SSP frames	424
Figure 139 — Non-data command sequence of SSP frames	425
Figure 140 — Write command sequence of SSP frames	425
Figure 141 — Read command sequence of SSP frames	426
Figure 142 — Bidirectional command sequence of SSP frames	427
Figure 143 — ST_I (transport layer for SSP initiator ports) state machines	436
Figure 144 — ST_T (transport layer for SSP target ports) state machines	452
Figure 145 — Sequence of SMP frames	473
Figure 146 — MT_IP (transport layer for SMP initiator ports) state machine	474
Figure 147 — MT_TP (transport layer for SMP target ports) state machine	476
Figure 148 — SA_PC (SCSI application layer power condition) state machine for SAS	516
Figure A.1 — CJTPAT pre-scrambling	642
Figure B.1 — SAS speed negotiation sequence (phy A:SNW-1 only, phy B:SNW-1 only)	649
Figure B.2 — SAS speed negotiation sequence (phy A:SNW-1, SNW-2, phy B:SNW-1, SNW-2)	650
Figure B.3 — SAS speed negotiation sequence (phy A:SNW-1, SNW-2, SNW-3, phy B:SNW-1, SNW-2)	651
Figure B.4 — SAS speed negotiation sequence (phy A:SNW-2, SNW-3, phy B:SNW-1, SNW-2)	652
Figure B.5 — SAS speed negotiation sequence (phy A:SNW-1 only, phy B:SNW-2 only)	653
Figure C.1 — CRC generator example	654
Figure C.2 — CRC checker example	654
Figure D.1 — BCH(69, 39, 9) code generator	659
Figure E.1 — Scrambler	665
Figure J.1 — Example topology	677
Figure J.2 — Connection request - OPEN_ACCEPT	679
Figure J.3 — Connection request - OPEN_REJECT by end device	680
Figure J.4 — Connection request - OPEN_REJECT by expander device	681
Figure J.5 — Connection request - arbitration lost	682
Figure J.6 — Connection request - backoff and retry	683
Figure J.7 — Connection request - backoff and reverse path	684
Figure J.8 — Connection close - single step	685
Figure J.9 — Connection close - simultaneous	686
Figure J.10 — BREAK handling during path arbitration when the BREAK_REPLY method is disabled	687
Figure J.11 — BREAK handling during a connection when the BREAK_REPLY method is disabled	688
Figure J.12 — BREAK handling during path arbitration when the BREAK_REPLY method is enabled	689
Figure J.13 — BREAK handling during a connection when the BREAK_REPLY method is enabled	690
Figure J.14 — STP connection - originated by STP initiator port	691
Figure J.15 — STP connection - originated by STP target port in an STP/SATA bridge	692
Figure J.16 — STP connection close - originated by STP initiator port	693
Figure J.17 — STP connection close - originated by STP target port in an STP/SATA bridge	694
Figure J.18 — XL1:Request_Path to XL5:Forward_Open transition	695
Figure J.19 — Partial pathway recovery	696