ISO/IEC 14776-333:2013-10 (E)

Information technology - Small Computer System Interface (SCSI) - Part 333: SCSI Stream Commands - 3 (SSC-3)

Contents

Page

FOREWORD 9
INTRODUCTION 11
1 Scope 12
2 Normative references 13
3 Terms, definitions, acronyms, keywords and conventions 14
3.1 Terms and definitions 14
3.2 Acronyms 22
3.3 Keywords 22
3.4 Editorial conventions 23
3.5 Notation conventions – State diagrams 24
4 General concepts 26
4.1 Overview 26
4.2 Sequential-access device model 26
4.2.1 Sequential-access device model overview 26
4.2.2 Physical elements 26
4.2.3 Removable volumes 29
4.2.4 Device entity 29
4.2.5 Early-warning 32
4.2.6 Programmable early warning 32
4.2.7 Partitions within a volume 33
4.2.8 Logical objects 34
4.2.9 Logical files 35
4.2.10 Object buffering 35
4.2.11 Synchronize operation behavior 36
4.2.12 Direction and position definitions 36
4.2.13 Error reporting 37
4.2.14 Write protection 39
4.2.15 Progress indication 41
4.2.16 Tagged command queuing 42
4.2.17 Block address mode 43
4.2.18 TapeAlert application client interface 52
4.2.19 READ ATTRIBUTE and WRITE ATTRIBUTE command support 58
4.2.20 Reservations 59
4.2.21 WORM volume and WORM mode 61
4.2.22 Logical block encryption 61
4.2.23 External data encryption control 72
4.2.24 Logical block encryption key protection 78
4.2.25 Appending data to a volume containing encrypted logical blocks 78
4.2.26 Self-test operations 79
4.2.27 Capability-based command (CbCS) security 79
5 Explicit address command descriptions for sequential-access devices 81
5.1 Summary of commands for explicit address mode 81
5.2 ERASE(16) command 84
5.3 READ(16) command 85
5.4 READ REVERSE(16) command 89
5.5 VERIFY(16) command 90
5.6 WRITE(16) command 92
5.7 WRITE FILEMARKS(16) command 94

6 Implicit address command descriptions for sequential-access devices 96
6.1 Summary of commands for implicit address mode 96
6.2 ERASE(6) command 99
6.3 LOCATE(10) command 100
6.4 READ(6) command 101
6.5 READ REVERSE(6) command 103
6.6 SPACE(6) command 103
6.7 VERIFY(6) command 106
6.8 WRITE(6) command 107
6.9 WRITE FILEMARKS(6) command 108
7 Common command descriptions for sequential-access devices 110
7.1 FORMAT MEDIUM command 110
7.2 LOAD UNLOAD command 111
7.3 LOCATE(16) command 113
7.4 PREVENT ALLOW MEDIUM REMOVAL command 114
7.5 READ BLOCK LIMITS command 115
7.6 READ POSITION command 117
7.6.1 READ POSITION command description 117
7.6.2 READ POSITION DATA format, short form 118
7.6.3 READ POSITION data format, long form 120
7.6.4 READ POSITION data format, extended form 122
7.7 RECOVER BUFFERED DATA command 123
7.8 REPORT DENSITY SUPPORT command 124
7.8.1 REPORT DENSITY SUPPORT command description 124
7.8.2 REPORT DENSITY SUPPORT header 124
7.8.3 Density support report 125
7.8.4 Medium type support report 127
7.9 REWIND command 129
7.10 SET CAPACITY command 130
7.11 SPACE(16) command 130
8 Parameters for sequential-access devices 134
8.1 Diagnostic parameters 134
8.2 Log parameters 134
8.2.1 Log parameters overview 134
8.2.2 Sequential-Access Device log page 135
8.2.3 TapeAlert log page 137
8.2.4 Device Statistics log page 138
8.2.5 Tape Diagnostic Data log page 140
8.2.6 Current Service Information log page 144
8.2.7 Requested Recovery log page 149
8.3 Mode parameters 152
8.3.1 Mode parameters overview 152
8.3.2 Data Compression mode page 155
8.3.3 Device Configuration mode page 159
8.3.4 Medium Partition mode page 163
8.3.5 Read-Write Error Recovery mode page 166
8.3.6 Informational Exceptions Control mode page 168
8.3.7 Medium Configuration mode page 169
8.3.8 Device Configuration Extension mode page 170

8.4 Vital product data (VPD) parameters 172
8.4.1 VPD parameters overview and page codes 172
8.4.2 Sequential-access Device Capabilities VPD page 173
8.4.3 Manufacturer-assigned Serial Number VPD page 173
8.4.4 TapeAlert Supported Flags VPD page 174
8.4.5 Automation Device Serial Number VPD page 174
8.5 Security protocol parameters 175
8.5.1 Security protocol overview 175
8.5.2 SECURITY PROTOCOL IN command specifying Tape Data Encryption security protocol 175
8.5.3 SECURITY PROTOCOL OUT command specifying Tape Data Encryption security protocol 190
8.5.4 SECURITY PROTOCOL IN and SECURITY PROTOCOL OUT descriptors 201
Annex A (informative) Application client recommendations for using TapeAlert 205
Annex B (informative) Security environment 211
Annex C (informative) Example keyless copy operation flowchart 213
Annex D (informative) Sense logical block information for error conditions 215
BIBLIOGRAPHY 220

Figure 1 — SCSI document relationships 12
Figure 2 — Example state diagram 25
Figure 3 — Typical volume layout 27
Figure 4 — Typical medium track layout 27
Figure 5 — Serpentine recording example 28
Figure 6 — Parallel recording example 28
Figure 7 — Helical scan recording example 28
Figure 8 — UML example of SCSI target device and device entity 30
Figure 9 — Early-warning example 32
Figure 10 — Programmable early warning example 32
Figure 11 — Partitioning example - one partition per track group 33
Figure 12 — Partitioning example - one partition per two track groups 34
Figure 13 — Partitioning example - two partitions per track group 34
Figure 14 — Block address mode state diagram, overview 45
Figure 15 — Block address mode state diagram, Idle state 46
Figure 16 — Block address mode state diagram, Explicit Address Mode - Neutral 48
Figure 17 — Block address mode state diagram, Explicit Address Mode - Write Capable 50
Figure 18 — Block address mode state diagram, Implicit Address Mode 51
Figure B.1 — Simple security deployment environment 211
Figure C.1 — Example keyless copy operation flowchart 214

Table 1 — Numbering conventions examples 24
Table 2 — Device entity attributes 30
Table 3 — Stream commands sense data descriptor 37
Table 4 — Information sense data descriptor 38
Table 5 — Error conditions and sense keys 38
Table 6 — Write protect additional sense code combinations 40
Table 7 — Commands providing progress indication without changing ready state 41
Table 8 — Commands changing ready state and providing progress indication 42
Table 9 — TapeAlert flags severity 52
Table 10 — TapeAlert flags 53
Table 11 — TapeAlert flag activation conditions 57
Table 12 — Device common attributes 58
Table 13 — Medium common attributes 59
Table 14 — SSC-3 commands that are allowed in the presence of various reservations 60
Table 15 — Default I_T_L nexus logical block encryption information 69
Table 16 — Logical block encryption parameters for encryption request policies 74
Table 17 — Logical block encryption parameters for decryption request policies 75
Table 18 — Logical block encryption parameters for encryption request indicator settings 76
Table 19 — Logical block encryption parameters for decryption request indicator settings 76
Table 20 — Logical block encryption period timer expired indicator 77
Table 21 — Association between commands and CbCS permissions 79
Table 22 — Explicit address command set for sequential-access devices 81
Table 23 — ERASE(16) command 84
Table 24 — METHOD field 85
Table 25 — READ(16) command 86
Table 26 — READ REVERSE(16) command 89
Table 27 — VERIFY(16) command 90
Table 28 — WRITE(16) command 92
Table 29 — WRITE FILEMARKS(16) command 94
Table 30 — Implicit address command set for sequential-access devices 96
Table 31 — ERASE(6) command 99
Table 32 — LOCATE(10) command 100
Table 33 — READ(6) command 101
Table 34 — READ REVERSE(6) command 103
Table 35 — SPACE(6) command 104
Table 36 — CODE field 104
Table 37 — VERIFY(6) command 106
Table 38 — WRITE(6) command 107
Table 39 — WRITE FILEMARKS(6) command 108
Table 40 — FORMAT MEDIUM command 110
Table 41 — FORMAT field 111
Table 42 — LOAD UNLOAD command 112
Table 43 — LOCATE(16) command 113
Table 44 — DEST_TYPE field 114
Table 45 — PREVENT ALLOW MEDIUM REMOVAL command 114
Table 46 — PREVENT field 115
Table 47 — READ BLOCK LIMITS command 115
Table 48 — READ BLOCK LIMITS data 116
Table 49 — READ POSITION command 117
Table 50 — READ POSITION service action codes 117
Table 51 — READ POSITION data format, short form 118
Table 52 — READ POSITION data format, long form 120
Table 53 — READ POSITION data format, extended form 122
Table 54 — RECOVER BUFFERED data command 123
Table 55 — REPORT DENSITY SUPPORT command 124
Table 56 — REPORT DENSITY SUPPORT header 124
Table 57 — Density support data block descriptor 125
Table 58 — Medium type descriptor 128
Table 59 — REWIND command 129
Table 60 — SET CAPACITY command 130

Table 61 — SPACE(16) command 131
Table 62 — Space positioning information 132
Table 63 — Diagnostic page codes 134
Table 64 — Log page codes 134
Table 65 — Parameter codes for Sequential-Access Device log page 135
Table 66 — TapeAlert log page 137
Table 67 — TapeAlert parameter format 137
Table 68 — Device Statistics log page 138
Table 69 — Device Statistics log parameter codes 138
Table 70 — Device statistics data counter log parameter format 139
Table 71 — Medium type log parameter format 140
Table 72 — Medium type parameter format 140
Table 73 — Tape Diagnostic Data log page 141
Table 74 — Tape diagnostic data log parameter format 142
Table 75 — Current Service Information log page 144
Table 76 — Service information log parameter format 144
Table 77 — Service information descriptor 145
Table 78 — SERVICE INFORMATION DESCRIPTOR TYPE field 145
Table 79 — Vendor-specific service information descriptor 145
Table 80 — Device information descriptor 146
Table 81 — DEC field 146
Table 82 — DEVICE REQUESTED RECOVERY field 147
Table 83 — Volume information descriptor 147
Table 84 — VIC field 147
Table 85 — VICQ field 148
Table 86 — TapeAlert flag specific information descriptor 149
Table 87 — Requested Recovery log page 150
Table 88 — REQUESTED RECOVERY LOG PARAMETER CODES 150
Table 89 — Requested recovery log parameter format 150
Table 90 — RECOVERY PROCEDURES 151
Table 91 — Device-specific parameter 152
Table 92 — Buffered modes 152
Table 93 — SPEED field 153
Table 94 — Sequential-access density codes 153
Table 95 — Mode page codes and subpage codes 154
Table 96 — Data Compression mode page 155
Table 97 — Possible boundaries and resulting sense keys due to data compression 156
Table 98 — Compression algorithm identifiers 158
Table 99 — Device Configuration mode page 159
Table 100 — EOD DEFINED field 160
Table 101 — WTRE field 161
Table 102 — REWIND ON RESET field 162
Table 103 — Medium Partition mode page 163
Table 104 — PSUM field 164
Table 105 — MEDIUM FORMAT RECOGNITION field 165
Table 106 — Read-Write Error Recovery mode page 166
Table 107 — Informational Exceptions Control mode page 168
Table 108 — TEST bit and TEST FLAG NUMBER field 168
Table 109 — Medium Configuration mode page 169
Table 110 — WORM MODE LABEL RESTRICTIONS field 170
Table 111 — WORM MODE FILEMARKS RESTRICTIONS field 170
Table 112 — Device Configuration Extension mode page 170
Table 113 — SHORT ERASE MODE field 172
Table 114 — Sequential-access device VPD page codes 172
Table 115 — Sequential-access Device Capabilities VPD page 173
Table 116 — Manufacturer-assigned Serial Number VPD page 173
Table 117 — TapeAlert Supported Flags VPD page 174
Table 118 — Automation Device Serial Number VPD page 174
Table 119 — SECURITY PROTOCOL SPECIFIC field 175
Table 120 — Tape Data Encryption In Support page 176

Table 121 — Tape Data Encryption Out Support page 176
Table 122 — Data Encryption Capabilities page 177
Table 123 — EXTDECC field 177
Table 124 — CFG_P field 178
Table 125 — Logical block encryption algorithm descriptor 178
Table 126 — DECRYPT_C field 179
Table 127 — ENCRYPT_C field 179
Table 128 — AVFCLP field 180
Table 129 — NONCE_C field 180
Table 130 — DKAD_C field 181
Table 131 — EEMC_C field 181
Table 132 — RDMC_C field 182
Table 133 — Supported Key Formats page 182
Table 134 — Data Encryption Management Capabilities page 183
Table 135 — Data Encryption Status page 184
Table 136 — PARAMETERS CONTROL field 185
Table 137 — Next Block Encryption Status page 186
Table 138 — COMPRESSION STATUS field 187
Table 139 — ENCRYPTION STATUS field 187
Table 140 — Random Number page 189
Table 141 — Device Service Key Wrapping Public Key page 189
Table 142 — PUBLIC KEY TYPE field 190
Table 143 — SECURITY PROTOCOL SPECIFIC field 190
Table 144 — Set Data Encryption page 191
Table 145 — SCOPE field 192
Table 146 — CEEM field 192
Table 147 — RDMC field 193
Table 148 — ENCRYPTION MODE field 194
Table 149 — DECRYPTION MODE field 195
Table 150 — LOGICAL BLOCK ENCRYPTION KEY FORMAT field 196
Table 151 — KEY field format with KEY FORMAT field set to 00h 197
Table 152 — KEY field format with KEY FORMAT field set to 01h 198
Table 153 — KEY field format with KEY FORMAT field set to 02h 198
Table 154 — PARAMETER SET field 198
Table 155 — ECIES-HC REQUIREMENTS AND PARAMETERS FOR ECIES-KEM 200
Table 156 — ECIES-HC REQUIREMENTS AND PARAMETERS FOR ECIES-DEM 200
Table 157 — SA Encapsulation page 201
Table 158 — Tape Data Encryption descriptor format 201
Table 159 — KEY DESCRIPTOR TYPE field 202
Table 160 — AUTHENTICATED field 202
Table 161 — Wrapped Key descriptor format 203
Table 162 — WRAPPED KEY DESCRIPTOR TYPE field 203
Table A.1 — TapeAlert log page parameter codes 205
Table B.1 — Security environment threats 212
Table D.1 — Sense logical block error indications for read and write operations 215
Table D.2 — INFORMATION field and position for read and write operations 217
Table D.3 — Summary of length error conditions on read type commands 219