

ISO/IEC 29145-1:2014-03 (E)

Information technology - Wireless Beacon-enabled Energy Efficient Mesh network (WiBEEM) for wireless home network services - Part 1: PHY Layer

| Contents | Page |
|---|------|
| FOREWORD..... | 5 |
| INTRODUCTION..... | 7 |
| 1 Scope..... | 8 |
| 2 Normative reference..... | 8 |
| 3 Terms, definitions and abbreviations..... | 8 |
| 3.1 Terms and definitions..... | 8 |
| 3.2 Abbreviations..... | 10 |
| 3.3 Conventions..... | 11 |
| 4 Conformance..... | 11 |
| 5 Overview of the WiBEEM technology..... | 12 |
| 5.1 General description..... | 12 |
| 5.2 Functions and descriptions of device types..... | 13 |
| 5.3 Functional overview of WiBEEM..... | 13 |
| 5.3.1 General..... | 13 |
| 5.3.2 Superframe structure of WiBEEM..... | 13 |
| 5.3.3 Data transfer model..... | 14 |
| 6 PHY layer specifications..... | 15 |
| 6.1 General..... | 15 |
| 6.2 General requirements and definitions..... | 16 |
| 6.2.1 General..... | 16 |
| 6.2.2 Operating frequency range..... | 16 |
| 6.2.3 Channel assignments and numbering..... | 16 |
| 6.2.4 RF power measurement..... | 16 |
| 6.2.5 Transmit power..... | 17 |
| 6.2.6 Out-of-band spurious emission..... | 17 |
| 6.2.7 Receiver sensitivity definitions..... | 17 |
| 6.3 PHY service specifications..... | 17 |
| 6.3.1 General..... | 17 |
| 6.3.2 PHY data service..... | 18 |
| 6.3.3 PHY management service..... | 20 |
| 6.3.4 PHY enumerations description..... | 27 |
| 6.4 PPDU format..... | 28 |
| 6.4.1 Function..... | 28 |
| 6.4.2 General packet format..... | 28 |
| 6.5 PHY constants and PIB attributes..... | 29 |
| 6.5.1 Function..... | 29 |
| 6.5.2 PHY constants..... | 30 |
| 6.5.3 PHY PIB attributes..... | 30 |

| | | |
|--------|---|----|
| 6.6 | 2 450 MHz PHY specifications | 30 |
| 6.6.1 | Requirements | 30 |
| 6.6.2 | Data rate | 30 |
| 6.6.3 | Modulation and spreading..... | 31 |
| 6.7 | General radio specifications | 34 |
| 6.7.1 | Application of specifications..... | 34 |
| 6.7.2 | TX-to-RX turnaround time | 34 |
| 6.7.3 | RX-to-TX turnaround time | 34 |
| 6.7.4 | Error-vector magnitude (EVM) definition | 34 |
| 6.7.5 | Transmit centre frequency tolerance | 35 |
| 6.7.6 | Transmit power | 35 |
| 6.7.7 | Receiver maximum input level of desired signal..... | 35 |
| 6.7.8 | Receiver ED | 35 |
| 6.7.9 | LQI | 35 |
| 6.7.10 | CCA..... | 36 |
| | Bibliography..... | 37 |
| | | |
| | Figure 1 – Superframe structure of WiBEEM | 13 |
| | Figure 2 – Communication from an end device to a co-ordinator in a beacon and non-beacon mode | 14 |
| | Figure 3 – Communication from a co-ordinator to an end device in a beacon and non-beacon mode | 14 |
| | Figure 4 – Communications between co-ordinators in a beacon and non-beacon mode | 15 |
| | Figure 5 – Communications between end devices | 15 |
| | Figure 6 – PHY reference model | 17 |
| | Figure 7 – Modulation and spreading functions | 31 |
| | Figure 8 – Symbol-to-chip mapping..... | 32 |
| | Figure 9 – O-QPSK chip offset..... | 32 |
| | Figure 10 – Sample baseband chip sequences with pulse shaping..... | 33 |
| | Figure 11 – Error vector calculation | 34 |
| | | |
| | Table 1 – Frequency bands and data rate | 16 |
| | Table 2 – Receiver sensitivity definitions | 17 |
| | Table 3 – PD-SAP primitives..... | 18 |
| | Table 4 – PD_Data.request parameters | 18 |
| | Table 5 – PD_DATA.confirm parameters..... | 19 |
| | Table 6 – PD_DATA.indication parameters | 20 |
| | Table 7 – PLME-SAP primitives | 20 |
| | Table 8 – PLME-CCA confirm primitive | 21 |
| | Table 9 – PLME_ED.confirm parameters | 22 |
| | Table 10 – PLME_GET.request parameters | 23 |
| | Table 11 – PLME_GET.confirm parameters | 24 |
| | Table 12 – PLME-SET-TRX-STATE.request parameters | 24 |
| | Table 13 – PLME-SET-TRX-STATE.confirm parameters | 25 |

| | |
|---|----|
| Table 14 – PLME_SET.request parameters | 26 |
| Table 15 – PLME_SET.confirm parameters..... | 27 |
| Table 16 – PHY enumerations description | 28 |
| Table 17 – Format of the PDU | 28 |
| Table 18 – Format of the SFD field | 29 |
| Table 19 – Frame length values | 29 |
| Table 20 – PHY constants..... | 30 |
| Table 21 – PHY PIB attributes | 30 |
| Table 22 – Minimum receiver jamming resistance requirements for 2 450 MHz PHY | 33 |