

# ISO/IEC 29145-2:2014-03 (E)

## Information Technology - Wireless Beacon-enabled Energy Efficient Mesh network (WiBEEM) for wireless home network services - Part 2: MAC Layer

---

Contents	Page
FOREWORD .....	5
INTRODUCTION .....	6
1 Scope .....	7
2 Normative reference .....	7
3 Terms, definitions and abbreviations .....	7
3.1 Terms and definitions .....	7
3.2 Abbreviations .....	8
3.3 Conventions .....	9
4 Conformance .....	10
5 Overview of the WiBEEM technology .....	10
6 MAC layer specifications .....	10
6.1 General .....	10
6.2 MAC layer service specifications .....	10
6.2.1 Service overview .....	10
6.2.2 MAC data service .....	11
6.2.3 MAC management service .....	17
6.2.4 Association primitives .....	17
6.2.5 Disassociation primitives .....	22
6.2.6 Beacon notification primitive .....	24
6.2.7 Primitives for reading PIB attributes .....	27
6.2.8 RAP management primitives .....	28
6.2.9 Primitives for orphan notification .....	31
6.2.10 Primitives for resetting the MAC layer .....	34
6.2.11 Primitives for specifying the receiver enable time .....	35
6.2.12 Primitives for channel scanning .....	37
6.2.13 Communication status primitive .....	39
6.2.14 Primitives for writing MAC PIB attributes .....	41
6.2.15 Primitives for updating the superframe configuration .....	42
6.2.16 Primitives for synchronising with a WRC .....	45
6.2.17 Primitives for requesting data from a WRC .....	47
6.3 MAC frame formats .....	49
6.3.1 General .....	49
6.3.2 General MAC frame format .....	50
6.3.3 Beacon frame format .....	52
6.3.4 MAC command frame format .....	52
Bibliography .....	62
Figure 1 – MAC layer structure .....	11
Figure 2 – Message sequence chart describing the MAC data service .....	16
Figure 3 – Message sequence chart for association .....	22
Figure 4 – Message sequence chart for disassociation .....	24
Figure 5 – Message sequence chart for RAP allocation initiated by a device .....	31
Figure 6 – Message sequence chart for RAP deallocation initiated by a device and the WMC .....	31

Figure 7 – Beacon lost (orphan notification) message sequence chart .....	33
Figure 8 – Message sequence chart for updating the superframe configuration.....	45
Figure 9 – Message sequence chart for synchronising to a WRC in a beacon-enabled WPAN.....	47
Figure 10 – Message sequence chart for requesting data from the WRC.....	49
Figure 11 – General MAC frame format.....	50
Figure 12 – Beacon frame format.....	52
Table 1 – MLDE-DATA.request parameters.....	12
Table 2 – MLDE-DATA.confirm parameters.....	13
Table 3 – MLDE-DATA.indication parameters .....	14
Table 4 – MLDE-ERASE.request parameters .....	15
Table 5 – MLDE-ERASE.confirm parameters .....	16
Table 6 – Summary of the primitives accessed through the MLME-SAP .....	17
Table 7 – MLME-ASSOCIATE.request parameters.....	18
Table 8 – MLME-ASSOCIATE.indication parameters .....	19
Table 9 – MLME-ASSOCIATE.response parameters .....	20
Table 10 – MLME-ASSOCIATE.confirm parameters .....	21
Table 11 – MLME-DISASSOCIATE.request parameters .....	22
Table 12 – MLME-DISASSOCIATE.indication parameters .....	23
Table 13 – MLME-DISASSOCIATE.confirm parameters .....	24
Table 14 – MLME-BEACON-NOTIFY.indication parameters .....	25
Table 15 – Elements of mesh descriptor .....	26
Table 16 – MLME-READ-MIB.request parameters.....	27
Table 17 – MLME-READ-MIB.confirm parameters.....	28
Table 18 – MLME- RAP-MANAGEMENT.request parameters.....	29
Table 19 – MLME-RAP-MANAGEMENT.confirm parameters .....	29
Table 20 – MLME-RAP-MANAGEMENT.indication parameters.....	30
Table 21 – MLME-BEACON-LOST.indication parameters.....	32
Table 22 – MLME-BEACON-LOST.indication parameters.....	33
Table 23 – MLME-RESET.request parameters .....	34
Table 24 – MLME-RESET.confirm parameters .....	35
Table 25 – MLME-RX-ON.request parameters .....	35
Table 26 – MLME-RX-ON.confirm parameters .....	36
Table 27 – MLME-SCAN.request parameters .....	37
Table 28 – MLME-SCAN.confirm parameters .....	39
Table 29 – MLME-COMM-RESULT.indication parameters.....	40
Table 30 – MLME-WRITE-MIB.request parameters .....	41
Table 31 – MLME-WRITE-MIB.confirm parameters .....	42
Table 32 – MLME-START.request parameters .....	43
Table 33 – MLME-START.confirm parameters .....	44
Table 34 – MLME-SYNC.request parameters .....	45
Table 35 – MLME-SYNC-LOSS.indication parameters .....	46

Table 36 – MLME-INDIRECT-COMM.request parameters .....	48
Table 37 – MLME-INDIRECT-COMM.confirm parameters .....	48
Table 38 – MAC command frame .....	53
Table 39 – Association request command .....	53
Table 41 – Association response command .....	54
Table 42 – Association status field.....	55
Table 43 – Disassociation notification command format .....	55
Table 44 – Disassociation reason code .....	56
Table 45 – Data request command format.....	57
Table 46 – Mesh ID conflict notification command format.....	57
Table 47 – Orphan notification command format .....	58
Table 48 – Beacon request command format .....	58
Table 49 – Co-ordinator realignment command format .....	59
Table 50 – CFP request command format .....	60
Table 51 – CFP characteristics field format.....	60
Table 52 – Rate reconfiguration request format .....	60
Table 53 – Data rate .....	61
Table 54 – Rate reconfiguration request command format .....	61