

ISO/IEC 29145-2:2014-03 (E)

Information Technology - Wireless Beacon-enabled Energy Efficient Mesh network (WiBEEM) for wireless home network services - Part 2: MAC Layer

Contents	Page
FOREWORD	5
INTRODUCTION	6
1 Scope	7
2 Normative reference	7
3 Terms, definitions and abbreviations	7
3.1 Terms and definitions	7
3.2 Abbreviations	8
3.3 Conventions	9
4 Conformance	10
5 Overview of the WiBEEM technology	10
6 MAC layer specifications	10
6.1 General	10
6.2 MAC layer service specifications	10
6.2.1 Service overview	10
6.2.2 MAC data service	11
6.2.3 MAC management service	17
6.2.4 Association primitives	17
6.2.5 Disassociation primitives	22
6.2.6 Beacon notification primitive	24
6.2.7 Primitives for reading PIB attributes	27
6.2.8 RAP management primitives	28
6.2.9 Primitives for orphan notification	31
6.2.10 Primitives for resetting the MAC layer	34
6.2.11 Primitives for specifying the receiver enable time	35
6.2.12 Primitives for channel scanning	37
6.2.13 Communication status primitive	39
6.2.14 Primitives for writing MAC PIB attributes	41
6.2.15 Primitives for updating the superframe configuration	42
6.2.16 Primitives for synchronising with a WRC	45
6.2.17 Primitives for requesting data from a WRC	47
6.3 MAC frame formats	49
6.3.1 General	49
6.3.2 General MAC frame format	50
6.3.3 Beacon frame format	52
6.3.4 MAC command frame format	52
Bibliography	62
Figure 1 – MAC layer structure	11
Figure 2 – Message sequence chart describing the MAC data service	16
Figure 3 – Message sequence chart for association	22
Figure 4 – Message sequence chart for disassociation	24
Figure 5 – Message sequence chart for RAP allocation initiated by a device	31
Figure 6 – Message sequence chart for RAP deallocation initiated by a device and the WMC	31

Figure 7 – Beacon lost (orphan notification) message sequence chart	33
Figure 8 – Message sequence chart for updating the superframe configuration.....	45
Figure 9 – Message sequence chart for synchronising to a WRC in a beacon-enabled WPAN.....	47
Figure 10 – Message sequence chart for requesting data from the WRC.....	49
Figure 11 – General MAC frame format.....	50
Figure 12 – Beacon frame format.....	52
Table 1 – MLDE-DATA.request parameters.....	12
Table 2 – MLDE-DATA.confirm parameters.....	13
Table 3 – MLDE-DATA.indication parameters	14
Table 4 – MLDE-ERASE.request parameters	15
Table 5 – MLDE-ERASE.confirm parameters	16
Table 6 – Summary of the primitives accessed through the MLME-SAP	17
Table 7 – MLME-ASSOCIATE.request parameters.....	18
Table 8 – MLME-ASSOCIATE.indication parameters	19
Table 9 – MLME-ASSOCIATE.response parameters	20
Table 10 – MLME-ASSOCIATE.confirm parameters	21
Table 11 – MLME-DISASSOCIATE.request parameters	22
Table 12 – MLME-DISASSOCIATE.indication parameters	23
Table 13 – MLME-DISASSOCIATE.confirm parameters	24
Table 14 – MLME-BEACON-NOTIFY.indication parameters	25
Table 15 – Elements of mesh descriptor	26
Table 16 – MLME-READ-MIB.request parameters.....	27
Table 17 – MLME-READ-MIB.confirm parameters.....	28
Table 18 – MLME- RAP-MANAGEMENT.request parameters.....	29
Table 19 – MLME-RAP-MANAGEMENT.confirm parameters	29
Table 20 – MLME-RAP-MANAGEMENT.indication parameters.....	30
Table 21 – MLME-BEACON-LOST.indication parameters.....	32
Table 22 – MLME-BEACON-LOST.indication parameters.....	33
Table 23 – MLME-RESET.request parameters	34
Table 24 – MLME-RESET.confirm parameters	35
Table 25 – MLME-RX-ON.request parameters	35
Table 26 – MLME-RX-ON.confirm parameters	36
Table 27 – MLME-SCAN.request parameters	37
Table 28 – MLME-SCAN.confirm parameters	39
Table 29 – MLME-COMM-RESULT.indication parameters.....	40
Table 30 – MLME-WRITE-MIB.request parameters	41
Table 31 – MLME-WRITE-MIB.confirm parameters	42
Table 32 – MLME-START.request parameters	43
Table 33 – MLME-START.confirm parameters	44
Table 34 – MLME-SYNC.request parameters	45
Table 35 – MLME-SYNC-LOSS.indication parameters	46

Table 36 – MLME-INDIRECT-COMM.request parameters	48
Table 37 – MLME-INDIRECT-COMM.confirm parameters	48
Table 38 – MAC command frame	53
Table 39 – Association request command	53
Table 41 – Association response command	54
Table 42 – Association status field.....	55
Table 43 – Disassociation notification command format	55
Table 44 – Disassociation reason code	56
Table 45 – Data request command format.....	57
Table 46 – Mesh ID conflict notification command format.....	57
Table 47 – Orphan notification command format	58
Table 48 – Beacon request command format	58
Table 49 – Co-ordinator realignment command format	59
Table 50 – CFP request command format	60
Table 51 – CFP characteristics field format.....	60
Table 52 – Rate reconfiguration request format	60
Table 53 – Data rate	61
Table 54 – Rate reconfiguration request command format	61