ISO/IEC 17760-101:2015-06 (E)

Information technology - AT Attachment 8 - Part 101: ATA/ATAPI Command Set (ATA8-ACS)

CONTENTS

FOREWORD 14

INTRODUCTION 16

1 Scope 17

2 Normative references 17

3 Terms, definitions and conventions 18

3.1 Terms and definitions 18

3.2 Conventions 25

3.2.1 Overview 25

3.2.2 Precedence 25

3.2.3 Lists 26

3.2.4 Keywords 26

3.2.5 Numbering 27

3.2.6 Bit conventions 28

3.2.7 State diagram conventions 28

3.2.8 Byte, word, DWord, and QWord Relationships 29

3.2.9 ATA string convention 31

4 Feature set definitions 32

4.1 Overview 32

4.2 General feature set 32

4.3 The PACKET feature set 33

4.3.1 Overview 33

4.3.2 Identification of PACKET feature set devices 34

4.3.3 Signature for ATAPI devices 34

4.3.4 The PACKET command 34

4.4 48-bit Address feature set 34

4.5 Advanced Power Management (APM) feature set 35

4.6 Automatic Acoustic Management (AAM) feature set 35

4.7 CompactFlash Association (CFA) feature set 35

4.8 Device Configuration Overlay (DCO) feature set 36

4.9 Free-fall Control feature set 38

4.10 General Purpose Logging (GPL) feature set 38

4.11 Host Protected Area (HPA) feature set 39

4.11.1 HPA overview 39

4.11.2 HPA security extensions 39

4.11.3 28-bit and 48-bit HPA commands interactions 39

4.11.4 IDENTIFY DEVICE data 41

4.11.5 Determination of SET MAX security extension status 41

4.11.6 HPA State Transition Diagrams 41

4.12 Long Logical Sector (LLS) feature set 56
4.13 Long Physical Sector (LPS) feature set 58
4.14 Media Card Pass Through Command feature set 60
4.15 Native Command Queuing (NCQ) feature set 60
4.15.1 Overview 60
4.15.2 Command Phases 61
4.16 NV Cache feature set 61
4.16.1 Overview 61
4.16.2 Pinning 61
4.16.3 NV Cache Management 62
4.16.4 Rotating media state after power-on event 62
4.17 NV Cache Power Management feature set 62
4.18 Power Management feature set 63
4.18.1 Overview 63
4.18.2 Power management commands 63
4.18.3 Standby timer 64
4.18.4 Power modes 64
4.19 Power-Up In Standby (PUIS) feature set 66
4.20 Security feature set 66
4.20.1 Overview 66
4.20.2 Passwords 67
4.20.3 Master Password Capability 67
4.20.4 Frozen Mode 67
4.20.5 Commands 67
4.20.6 IDENTIFY DEVICE data 67
4.20.7 Security initial setting 68
4.20.8 Password rules 68
4.20.9 Password attempt counter 68
4.20.10 Security states 69
4.20.11 Master Password Identifier feature 78
4.21 Self-Monitoring, Analysis, and Reporting Technology (SMART) feature set 79
4.21.1 Overview 79
4.21.2 Device SMART data structure 79
4.21.3 Background data collection 79
4.21.4 Off-line/Captive mode data collection 79
4.21.5 Threshold exceeded condition 79
4.21.6 SMART feature set commands 79
4.21.7 SMART operation with power management modes 79
4.21.8 SMART device error log reporting 80
4.22 Software Settings Preservation (SSP) feature set 80
4.23 Streaming feature set 81
4.23.1 Streaming feature set overview 81
4.23.2 Streaming commands 81
4.24 Tagged Command Queuing (TCQ) feature set 82
4.24.1 Overview 82
4.24.2 Queueing 83
4.25 Trusted Computing feature set 83
4.26 Write-Read-Verify feature set 84

5 ATA protocols 86
6 Normal and Error Output field descriptions 87
6.1 Overview 87
6.2 Status field 87
6.2.1 Overview 87
6.2.2 Busy bit 87
6.2.3 Check Condition bit 87
6.2.4 Data Request bit 87
6.2.5 Deferred Write Error bit 87
6.2.6 Device Fault bit 88
6.2.7 Device Ready bit 88
6.2.8 Error bit 88
6.2.9 Service bit 88
6.2.10 Stream Error bit 88
6.2.11 Transport Dependent (TD) 88
6.3 Error field 89
6.3.1 Overview 89
6.3.2 Abort bit 89
6.3.3 Attempted Partial Range Removal bit 89
6.3.4 Command Completion Time Out bit 89
6.3.5 End of Media bit 89
6.3.6 ID Not Found bit 89
6.3.7 Illegal Length Indicator bit 90
6.3.8 Insufficient LBA Range Entries Remaining bit 90
6.3.9 Insufficient NV Cache Space bit 90
6.3.10 Interface CRC bit 90
6.3.11 Media Error bit 90
6.3.12 Sense Key field 90
6.3.13 Uncorrectable Error bit 90
6.4 Interrupt Reason field 90
6.4.1 Overview 90
6.4.2 Command/Data bit 90
6.4.3 Input/Output (I/O) bit 90
6.4.4 Release bit 91
6.4.5 Tag field 91
6.5 Count field 91
6.5.1 Overview 91
6.5.2 NCQ Tag field 91
6.6 SActive field 91
6.7 SATA Status 91
7 Command descriptions 92
7.1 Command description introduction 92
7.1.1 Overview 92
7.1.2 Command Name - Command Code [/Subcommand Code], Command Protocol 92
7.1.3 Feature Set 92
7.1.4 Inputs 93
7.1.5 Normal Outputs 93
7.1.6 Error Outputs 94
7.1.7 Input From the Device to the Host Data Structure 94
7.1.8 Output From the Host to the Device Data Structure 95
7.1.9 Unsupported commands 95

7.2 CFA ERASE SECTORS - C0h, Non-Data 95
7.3 CFA REQUEST EXTENDED ERROR CODE - 03h, Non-Data 96
7.4 CFA TRANSLATE SECTOR - 87h, PIO Data-In 98
7.5 CFA WRITE MULTIPLE WITHOUT ERASE - CDh, PIO Data-Out 99
7.6 CFA WRITE SECTORS WITHOUT ERASE - 38h, PIO Data-Out 100
7.7 CHECK MEDIA CARD TYPE - D1h, Non-Data 101
7.8 CHECK POWER MODE - E5h, Non-Data 102
7.9 CONFIGURE STREAM - 51h, Non-Data 103
7.10 Device Configuration Overlay (DCO) 104
7.10.1 DCO Overview 104
7.10.2 DEVICE CONFIGURATION FREEZE LOCK - B1h/C1h, Non-Data 105
7.10.3 DEVICE CONFIGURATION IDENTIFY - B1h/C2h, PIO Data-In 106
7.10.4 DEVICE CONFIGURATION RESTORE - B1h/C0h, Non-Data 110
7.10.5 DEVICE CONFIGURATION SET - B1h/C3h, PIO Data-Out 111
7.11 DEVICE RESET - 08h, Device Reset 118
7.12 DOWNLOAD MICROCODE - 92h, PIO Data-Out/Non-Data 119
7.13 EXECUTE DEVICE DIAGNOSTIC - 90h, Execute Device Diagnostic 121
7.14 FLUSH CACHE - E7h, Non-Data 122
7.15 FLUSH CACHE EXT - EAh, Non-Data 124
7.16 IDENTIFY DEVICE - ECh, PIO Data-In 125
7.17 IDENTIFY PACKET DEVICE - A1h, PIO Data-In 163
7.18 IDLE - E3h, Non-Data 181
7.19 IDLE IMMEDIATE - E1h, Non-Data 182
7.20 Non-Volatile Cache 183
7.20.1 NV Cache Overview 183
7.20.2 NV Cache Power Management Overview 184
7.20.3 ADD LBA(S) TO NV CACHE PINNED SET - B6h/10h, DMA 184
7.20.4 FLUSH NV CACHE - B6h/14h, Non-Data 186
7.20.5 NV CACHE DISABLE- B6h/16h, Non-Data 187
7.20.6 NV CACHE ENABLE - B6h/15h, Non-Data 188
7.20.7 QUERY NV CACHE MISSES - B6h/13h, DMA 189
7.20.8 QUERY NV CACHE PINNED SET - B6h/12h, DMA 191
7.20.9 REMOVE LBA(S) FROM NV CACHE PINNED SET - B6h/11h, DMA/Non-Data 192
7.20.10 RETURN FROM NV CACHE POWER MODE - B6h/01h, Non-Data 194
7.20.11 SET NV CACHE POWER MODE - B6h/00h, Non-Data 195
7.21 NOP - 00h, Non-Data 196
7.22 PACKET - A0h, Packet 197
7.23 READ BUFFER - E4h, PIO Data-In 199
7.24 READ DMA - C8h, DMA 200
7.25 READ DMA EXT - 25h, DMA 201
7.26 READ DMA QUEUED - C7h, DMA Queued 202
7.27 READ DMA QUEUED EXT- 26h, DMA Queued 203
7.28 READ FPDMA QUEUED - 60h, DMA Queued 205

7.29 READ LOG EXT - 2Fh, PIO Data-In 206
7.30 READ LOG DMA EXT - 47h, DMA 207
7.31 READ MULTIPLE - C4h, PIO Data-In 208
7.32 READ MULTIPLE EXT - 29h, PIO Data-In 209
7.33 READ NATIVE MAX ADDRESS - F8h, Non-Data 210
7.34 READ NATIVE MAX ADDRESS EXT - 27h, Non-Data 211
7.35 READ SECTOR(S) - 20h, PIO Data-In 212
7.36 READ SECTOR(S) EXT - 24h, PIO Data-In 213
7.37 READ STREAM DMA EXT - 2Ah, DMA 214
7.38 READ STREAM EXT - 2Bh, PIO Data-In 216
7.39 READ VERIFY SECTOR(S) - 40h, Non-Data 217
7.40 READ VERIFY SECTOR(S) EXT - 42h, Non-Data 218
7.41 SECURITY DISABLE PASSWORD - F6h, PIO Data-Out 219
7.42 SECURITY ERASE PREPARE - F3h, Non-Data 220
7.43 SECURITY ERASE UNIT - F4h, PIO Data-Out 221
7.44 SECURITY FREEZE LOCK - F5h, Non-Data 223
7.45 SECURITY SET PASSWORD - F1h, PIO Data-Out 224
7.46 SECURITY UNLOCK - F2h, PIO Data-Out 225
7.47 SERVICE - A2h, DMA Queued 227
7.48 SET FEATURES - EFh, Non-Data 228
7.48.3 Enable/disable 8-bit PIO data transfer 230
7.48.4 Enable/disable volatile write cache 230
7.48.5 Set transfer mode 230
7.48.6 Enable/disable the APM feature set 231
7.48.7 Enable/disable the PUIS feature set 232
7.48.8 PUIS feature set device spin-up 232
7.48.9 Enable/disable CFA power mode 1 232
7.48.10 Enable/Disable Write-Read-Verify feature set 233
7.48.11 Enable/disable the AAM feature set 233
7.48.12 Set Maximum Host Interface Sector Times 234
7.48.13 Enable/disable read look-ahead 234
7.48.14 Enable/disable release interrupt 235
7.48.15 Enable/disable SERVICE interrupt 235
7.48.16 Enable/disable reverting to defaults 235
7.48.17 Enable/Disable the Free-fall Control feature set 235
7.48.18 Enable/Disable SATA feature 235
7.49 SET MAX 237
7.49.2 SET MAX ADDRESS - F9h, Non-Data 238
7.49.3 SET MAX FREEZE LOCK – F9h/04h, Non-Data 240
7.49.4 SET MAX LOCK - F9h/02h, Non-Data 241
7.49.5 SET MAX SET PASSWORD - F9h/01h, PIO Data-Out 242
7.49.6 SET MAX UNLOCK - F9h/03h, PIO Data-Out 243
7.50 SET MAX ADDRESS EXT - 37h, Non-Data 245
7.51 SET MULTIPLE MODE - C6h, Non-Data 246
7.52 SLEEP - E6h, Non-Data 247
7.53 SMART 248

7.53.2 SMART DISABLE OPERATIONS - B0h/D9h, Non-Data 249
7.53.3 SMART ENABLE/DISABLE ATTRIBUTE AUTOSAVE - B0h/D2h, Non-Data 250
7.53.4 SMART ENABLE OPERATIONS - B0h/D8h, Non-Data 251
7.53.5 SMART EXECUTE OFF-LINE IMMEDIATE - B0h/D4h, Non-Data 253
7.53.6 SMART READ DATA - B0h/D0h, PIO Data-In 257
7.53.7 SMART READ LOG - B0h/D5h, PIO Data-In 262
7.53.8 SMART RETURN STATUS - B0h/DAh, Non-Data 263
7.53.9 SMART WRITE LOG - B0h/D6h, PIO Data-Out 264
7.54 STANDBY - E2h, Non-Data 265
7.55 STANDBY IMMEDIATE - E0h, Non-Data 266
7.56 TRUSTED NON-DATA - 5Bh, Non-Data 267
7.57 TRUSTED RECEIVE - 5Ch, PIO Data-In 268
7.58 TRUSTED RECEIVE DMA - 5Dh, DMA 271
7.59 TRUSTED SEND - 5Eh, PIO Data-Out 273
7.60 TRUSTED SEND DMA - 5Fh, DMA 275
7.61 WRITE BUFFER - E8h, PIO Data-Out 276
7.62 WRITE DMA - CAh, DMA 277
7.63 WRITE DMA EXT - 35h, DMA 278
7.64 WRITE DMA FUA EXT - 3Dh, DMA 279
7.65 WRITE DMA QUEUED - CCh, DMA Queued 279
7.66 WRITE DMA QUEUED EXT - 36h, DMA Queued 282
7.67 WRITE DMA QUEUED FUA EXT - 3Eh, DMA Queued 284
7.68 WRITE FPDMA QUEUED - 61h, DMA Queued 285
7.69 WRITE LOG EXT - 3Fh, PIO Data-Out 286
7.70 WRITE LOG DMA EXT - 57h, DMA 287
7.71 WRITE MULTIPLE - C5h, PIO Data-Out 288
7.72 WRITE MULTIPLE EXT - 39h, PIO Data-Out 289
7.73 WRITE MULTIPLE FUA EXT - CEh, PIO Data-Out 290
7.74 WRITE SECTOR(S) - 30h, PIO Data-Out 291
7.75 WRITE SECTOR(S) EXT - 34h, PIO Data-Out 292
7.76 WRITE STREAM DMA EXT - 3Ah, DMA 293
7.77 WRITE STREAM EXT - 3Bh, PIO Data-Out 295
7.78 WRITE UNCORRECTABLE EXT - 45h, Non-Data 296
8 SCT Command Transport 298
8.1 Overview 298
8.1.1 General 298
8.1.2 SCT command nesting and interspersing with standard commands 298
8.1.3 Resets 298
8.2 Processing SCT commands 299
8.2.1 Processing SCT commands overview 299
8.2.2 SCT capability identification 299
8.2.3 SCT command transfer 299
8.2.4 SCT data transfer 303
8.2.5 SCT status 305

8.3 SCT Command Set 309
8.3.1 Overview 309
8.3.2 SCT Read/Write Long command 310
8.3.3 SCT Write Same command 312
8.3.4 SCT Error Recovery Control command 315
8.3.5 SCT Feature Control command 317
8.3.6 SCT Data Table command 320
9 Normal and Error Outputs 324
9.1 Overview 324
9.2 Normal Outputs 324
9.3 Error Outputs 344
Annex A (normative) – Log definitions 386
Annex B (informative) – Command Set summary 407
Annex C (informative) – Design and programming considerations for large physical sector devices 432
Annex D (informative) – How to use SCT commands 434
Annex E (informative) – Implementation Guidelines For 1 024/4 096 Byte Sector Sizes 442
Bibliography 448