

# ISO/IEC 17760-101:2015-06 (E)

## Information technology - AT Attachment 8 - Part 101: ATA/ATAPI Command Set (ATA8-ACS)

---

### CONTENTS

- FOREWORD..... 14
- INTRODUCTION ..... 16
- 1 Scope ..... 17
- 2 Normative references ..... 17
- 3 Terms, definitions and conventions ..... 18
  - 3.1 Terms and definitions ..... 18
  - 3.2 Conventions ..... 25
    - 3.2.1 Overview ..... 25
    - 3.2.2 Precedence ..... 25
    - 3.2.3 Lists ..... 26
    - 3.2.4 Keywords ..... 26
    - 3.2.5 Numbering ..... 27
    - 3.2.6 Bit conventions ..... 28
    - 3.2.7 State diagram conventions ..... 28
    - 3.2.8 Byte, word, DWord, and QWord Relationships ..... 29
    - 3.2.9 ATA string convention ..... 31
- 4 Feature set definitions ..... 32
  - 4.1 Overview ..... 32
  - 4.2 General feature set ..... 32
  - 4.3 The PACKET feature set ..... 33
    - 4.3.1 Overview ..... 33
    - 4.3.2 Identification of PACKET feature set devices ..... 34
    - 4.3.3 Signature for ATAPI devices ..... 34
    - 4.3.4 The PACKET command ..... 34
  - 4.4 48-bit Address feature set ..... 34
  - 4.5 Advanced Power Management (APM) feature set ..... 35
  - 4.6 Automatic Acoustic Management (AAM) feature set ..... 35
  - 4.7 CompactFlash Association (CFA) feature set ..... 35
  - 4.8 Device Configuration Overlay (DCO) feature set ..... 36
  - 4.9 Free-fall Control feature set ..... 38
  - 4.10 General Purpose Logging (GPL) feature set ..... 38
  - 4.11 Host Protected Area (HPA) feature set ..... 39
    - 4.11.1 HPA overview ..... 39
    - 4.11.2 HPA security extensions ..... 39
    - 4.11.3 28-bit and 48-bit HPA commands interactions ..... 39
    - 4.11.4 IDENTIFY DEVICE data ..... 41
    - 4.11.5 Determination of SET MAX security extension status ..... 41
    - 4.11.6 HPA State Transition Diagrams ..... 41

4.12 Long Logical Sector (LLS) feature set .....	56
4.13 Long Physical Sector (LPS) feature set .....	58
4.14 Media Card Pass Through Command feature set .....	60
4.15 Native Command Queuing (NCQ) feature set .....	60
4.15.1 Overview .....	60
4.15.2 Command Phases .....	61
4.16 NV Cache feature set .....	61
4.16.1 Overview .....	61
4.16.2 Pinning .....	61
4.16.3 NV Cache Management .....	62
4.16.4 Rotating media state after power-on event .....	62
4.17 NV Cache Power Management feature set .....	62
4.18 Power Management feature set .....	63
4.18.1 Overview .....	63
4.18.2 Power management commands .....	63
4.18.3 Standby timer .....	64
4.18.4 Power modes .....	64
4.19 Power-Up In Standby (PUIS) feature set .....	66
4.20 Security feature set .....	66
4.20.1 Overview .....	66
4.20.2 Passwords .....	67
4.20.3 Master Password Capability .....	67
4.20.4 Frozen Mode .....	67
4.20.5 Commands .....	67
4.20.6 IDENTIFY DEVICE data .....	67
4.20.7 Security initial setting .....	68
4.20.8 Password rules .....	68
4.20.9 Password attempt counter .....	68
4.20.10 Security states .....	69
4.20.11 Master Password Identifier feature .....	78
4.21 Self-Monitoring, Analysis, and Reporting Technology (SMART) feature set .....	79
4.21.1 Overview .....	79
4.21.2 Device SMART data structure .....	79
4.21.3 Background data collection .....	79
4.21.4 Off-line/Captive mode data collection .....	79
4.21.5 Threshold exceeded condition .....	79
4.21.6 SMART feature set commands .....	79
4.21.7 SMART operation with power management modes .....	79
4.21.8 SMART device error log reporting .....	80
4.22 Software Settings Preservation (SSP) feature set .....	80
4.23 Streaming feature set .....	81
4.23.1 Streaming feature set overview .....	81
4.23.2 Streaming commands .....	81
4.24 Tagged Command Queuing (TCQ) feature set .....	82
4.24.1 Overview .....	82
4.24.2 Queueing .....	83
4.25 Trusted Computing feature set .....	83
4.26 Write-Read-Verify feature set .....	84

5 ATA protocols .....	86
6 Normal and Error Output field descriptions .....	87
6.1 Overview .....	87
6.2 Status field .....	87
6.2.1 Overview .....	87
6.2.2 Busy bit .....	87
6.2.3 Check Condition bit .....	87
6.2.4 Data Request bit .....	87
6.2.5 Deferred Write Error bit .....	87
6.2.6 Device Fault bit .....	88
6.2.7 Device Ready bit .....	88
6.2.8 Error bit .....	88
6.2.9 Service bit .....	88
6.2.10 Stream Error bit .....	88
6.2.11 Transport Dependent (TD) .....	88
6.3 Error field .....	89
6.3.1 Overview .....	89
6.3.2 Abort bit .....	89
6.3.3 Attempted Partial Range Removal bit .....	89
6.3.4 Command Completion Time Out bit .....	89
6.3.5 End of Media bit .....	89
6.3.6 ID Not Found bit .....	89
6.3.7 Illegal Length Indicator bit .....	90
6.3.8 Insufficient LBA Range Entries Remaining bit .....	90
6.3.9 Insufficient NV Cache Space bit .....	90
6.3.10 Interface CRC bit .....	90
6.3.11 Media Error bit .....	90
6.3.12 Sense Key field .....	90
6.3.13 Uncorrectable Error bit .....	90
6.4 Interrupt Reason field .....	90
6.4.1 Overview .....	90
6.4.2 Command/Data bit .....	90
6.4.3 Input/Output (I/O) bit .....	90
6.4.4 Release bit .....	91
6.4.5 Tag field .....	91
6.5 Count field .....	91
6.5.1 Overview .....	91
6.5.2 NCQ Tag field .....	91
6.6 SActive field .....	91
6.7 SATA Status .....	91
7 Command descriptions .....	92
7.1 Command description introduction .....	92
7.1.1 Overview .....	92
7.1.2 Command Name - Command Code [/Subcommand Code], Command Protocol .....	92
7.1.3 Feature Set .....	92
7.1.4 Inputs .....	93
7.1.5 Normal Outputs .....	93
7.1.6 Error Outputs .....	94
7.1.7 Input From the Device to the Host Data Structure .....	94
7.1.8 Output From the Host to the Device Data Structure .....	95
7.1.9 Unsupported commands .....	95

7.2 CFA ERASE SECTORS - C0h, Non-Data .....	95
7.3 CFA REQUEST EXTENDED ERROR CODE - 03h, Non-Data .....	96
7.4 CFA TRANSLATE SECTOR - 87h, PIO Data-In .....	98
7.5 CFA WRITE MULTIPLE WITHOUT ERASE - CDh, PIO Data-Out .....	99
7.6 CFA WRITE SECTORS WITHOUT ERASE - 38h, PIO Data-Out .....	100
7.7 CHECK MEDIA CARD TYPE - D1h, Non-Data .....	101
7.8 CHECK POWER MODE - E5h, Non-Data .....	102
7.9 CONFIGURE STREAM - 51h, Non-Data .....	103
7.10 Device Configuration Overlay (DCO) .....	104
7.10.1 DCO Overview .....	104
7.10.2 DEVICE CONFIGURATION FREEZE LOCK - B1h/C1h, Non-Data .....	105
7.10.3 DEVICE CONFIGURATION IDENTIFY - B1h/C2h, PIO Data-In .....	106
7.10.4 DEVICE CONFIGURATION RESTORE - B1h/C0h, Non-Data .....	110
7.10.5 DEVICE CONFIGURATION SET - B1h/C3h, PIO Data-Out.....	111
7.11 DEVICE RESET - 08h, Device Reset .....	118
7.12 DOWNLOAD MICROCODE - 92h, PIO Data-Out/Non-Data .....	119
7.13 EXECUTE DEVICE DIAGNOSTIC - 90h, Execute Device Diagnostic .....	121
7.14 FLUSH CACHE - E7h, Non-Data .....	122
7.15 FLUSH CACHE EXT - EAh, Non-Data .....	124
7.16 IDENTIFY DEVICE - ECh, PIO Data-In .....	125
7.17 IDENTIFY PACKET DEVICE - A1h, PIO Data-In .....	163
7.18 IDLE - E3h, Non-Data .....	181
7.19 IDLE IMMEDIATE - E1h, Non-Data .....	182
7.20 Non-Volatile Cache .....	183
7.20.1 NV Cache Overview .....	183
7.20.2 NV Cache Power Management Overview .....	184
7.20.3 ADD LBA(S) TO NV CACHE PINNED SET - B6h/10h, DMA.....	184
7.20.4 FLUSH NV CACHE - B6h/14h, Non-Data .....	186
7.20.5 NV CACHE DISABLE- B6h/16h, Non-Data.....	187
7.20.6 NV CACHE ENABLE - B6h/15h, Non-Data.....	188
7.20.7 QUERY NV CACHE MISSES - B6h/13h, DMA.....	189
7.20.8 QUERY NV CACHE PINNED SET - B6h/12h, DMA.....	191
7.20.9 REMOVE LBA(S) FROM NV CACHE PINNED SET - B6h/11h, DMA/Non-Data.....	192
7.20.10 RETURN FROM NV CACHE POWER MODE - B6h/01h, Non-Data.....	194
7.20.11 SET NV CACHE POWER MODE - B6h/00h, Non-Data.....	195
7.21 NOP - 00h, Non-Data .....	196
7.22 PACKET - A0h, Packet .....	197
7.23 READ BUFFER - E4h, PIO Data-In .....	199
7.24 READ DMA - C8h, DMA .....	200
7.25 READ DMA EXT - 25h, DMA .....	201
7.26 READ DMA QUEUED - C7h, DMA Queued .....	202
7.27 READ DMA QUEUED EXT- 26h, DMA Queued .....	203
7.28 READ FPDMA QUEUED - 60h, DMA Queued .....	205

7.29 READ LOG EXT - 2Fh, PIO Data-In .....	206
7.30 READ LOG DMA EXT - 47h, DMA .....	207
7.31 READ MULTIPLE - C4h, PIO Data-In .....	208
7.32 READ MULTIPLE EXT - 29h, PIO Data-In .....	209
7.33 READ NATIVE MAX ADDRESS - F8h, Non-Data .....	210
7.34 READ NATIVE MAX ADDRESS EXT - 27h, Non-Data .....	211
7.35 READ SECTOR(S) - 20h, PIO Data-In .....	212
7.36 READ SECTOR(S) EXT - 24h, PIO Data-In .....	213
7.37 READ STREAM DMA EXT - 2Ah, DMA .....	214
7.38 READ STREAM EXT - 2Bh, PIO Data-In .....	216
7.39 READ VERIFY SECTOR(S) - 40h, Non-Data .....	217
7.40 READ VERIFY SECTOR(S) EXT - 42h, Non-Data .....	218
7.41 SECURITY DISABLE PASSWORD - F6h, PIO Data-Out .....	219
7.42 SECURITY ERASE PREPARE - F3h, Non-Data .....	220
7.43 SECURITY ERASE UNIT - F4h, PIO Data-Out .....	221
7.44 SECURITY FREEZE LOCK - F5h, Non-Data .....	223
7.45 SECURITY SET PASSWORD - F1h, PIO Data-Out .....	224
7.46 SECURITY UNLOCK - F2h, PIO Data-Out .....	225
7.47 SERVICE - A2h, DMA Queued .....	227
7.48 SET FEATURES - EFh, Non-Data .....	228
7.48.3 Enable/disable 8-bit PIO data transfer .....	230
7.48.4 Enable/disable volatile write cache .....	230
7.48.5 Set transfer mode .....	230
7.48.6 Enable/disable the APM feature set .....	231
7.48.7 Enable/disable the PUIS feature set .....	232
7.48.8 PUIS feature set device spin-up .....	232
7.48.9 Enable/disable CFA power mode 1 .....	232
7.48.10 Enable/Disable Write-Read-Verify feature set .....	233
7.48.11 Enable/disable the AAM feature set .....	233
7.48.12 Set Maximum Host Interface Sector Times .....	234
7.48.13 Enable/disable read look-ahead .....	234
7.48.14 Enable/disable release interrupt .....	235
7.48.15 Enable/disable SERVICE interrupt .....	235
7.48.16 Enable/disable reverting to defaults .....	235
7.48.17 Enable/Disable the Free-fall Control feature set .....	235
7.48.18 Enable/Disable SATA feature .....	235
7.49 SET MAX .....	237
7.49.2 SET MAX ADDRESS - F9h, Non-Data.....	238
7.49.3 SET MAX FREEZE LOCK – F9h/04h, Non-Data .....	240
7.49.4 SET MAX LOCK - F9h/02h, Non-Data .....	241
7.49.5 SET MAX SET PASSWORD - F9h/01h, PIO Data-Out.....	242
7.49.6 SET MAX UNLOCK - F9h/03h, PIO Data-Out.....	243
7.50 SET MAX ADDRESS EXT - 37h, Non-Data .....	245
7.51 SET MULTIPLE MODE - C6h, Non-Data .....	246
7.52 SLEEP - E6h, Non-Data .....	247
7.53 SMART .....	248

7.53.2 SMART DISABLE OPERATIONS - B0h/D9h, Non-Data.....	249
7.53.3 SMART ENABLE/DISABLE ATTRIBUTE AUTOSAVE - B0h/D2h, Non-Data .....	250
7.53.4 SMART ENABLE OPERATIONS - B0h/D8h, Non-Data.....	251
7.53.5 SMART EXECUTE OFF-LINE IMMEDIATE - B0h/D4h, Non-Data .....	253
7.53.6 SMART READ DATA - B0h/D0h, PIO Data-In .....	257
7.53.7 SMART READ LOG - B0h/D5h, PIO Data-In .....	262
7.53.8 SMART RETURN STATUS - B0h/DAh, Non-Data.....	263
7.53.9 SMART WRITE LOG - B0h/D6h, PIO Data-Out.....	264
7.54 STANDBY - E2h, Non-Data .....	265
7.55 STANDBY IMMEDIATE - E0h, Non-Data .....	266
7.56 TRUSTED NON-DATA - 5Bh, Non-Data .....	267
7.57 TRUSTED RECEIVE - 5Ch, PIO Data-In .....	268
7.58 TRUSTED RECEIVE DMA - 5Dh, DMA .....	271
7.59 TRUSTED SEND - 5Eh, PIO Data-Out .....	273
7.60 TRUSTED SEND DMA - 5Fh, DMA .....	275
7.61 WRITE BUFFER - E8h, PIO Data-Out .....	276
7.62 WRITE DMA - CAh, DMA .....	277
7.63 WRITE DMA EXT - 35h, DMA .....	278
7.64 WRITE DMA FUA EXT - 3Dh, DMA .....	279
7.65 WRITE DMA QUEUED - CCh, DMA Queued .....	279
7.66 WRITE DMA QUEUED EXT - 36h, DMA Queued .....	282
7.67 WRITE DMA QUEUED FUA EXT - 3Eh, DMA Queued .....	284
7.68 WRITE FPDMA QUEUED - 61h, DMA Queued .....	285
7.69 WRITE LOG EXT - 3Fh, PIO Data-Out .....	286
7.70 WRITE LOG DMA EXT - 57h, DMA .....	287
7.71 WRITE MULTIPLE - C5h, PIO Data-Out .....	288
7.72 WRITE MULTIPLE EXT - 39h, PIO Data-Out .....	289
7.73 WRITE MULTIPLE FUA EXT - CEh, PIO Data-Out .....	290
7.74 WRITE SECTOR(S) - 30h, PIO Data-Out .....	291
7.75 WRITE SECTOR(S) EXT - 34h, PIO Data-Out .....	292
7.76 WRITE STREAM DMA EXT - 3Ah, DMA .....	293
7.77 WRITE STREAM EXT - 3Bh, PIO Data-Out .....	295
7.78 WRITE UNCORRECTABLE EXT - 45h, Non-Data .....	296
8 SCT Command Transport .....	298
8.1 Overview .....	298
8.1.1 General .....	298
8.1.2 SCT command nesting and interspersing with standard commands .....	298
8.1.3 Resets .....	298
8.2 Processing SCT commands .....	299
8.2.1 Processing SCT commands overview .....	299
8.2.2 SCT capability identification .....	299
8.2.3 SCT command transfer .....	299
8.2.4 SCT data transfer .....	303
8.2.5 SCT status .....	305

8.3 SCT Command Set .....	309
8.3.1 Overview .....	309
8.3.2 SCT Read/Write Long command.....	310
8.3.3 SCT Write Same command.....	312
8.3.4 SCT Error Recovery Control command.....	315
8.3.5 SCT Feature Control command.....	317
8.3.6 SCT Data Table command .....	320
9 Normal and Error Outputs .....	324
9.1 Overview .....	324
9.2 Normal Outputs .....	324
9.3 Error Outputs .....	344
Annex A (normative) – Log definitions .....	386
Annex B (informative) – Command Set summary.....	407
Annex C (informative) – Design and programming considerations for large physical sector devices.....	432
Annex D (informative) – How to use SCT commands .....	434
Annex E (informative) – Implementation Guidelines For 1 024/4 096 Byte Sector Sizes .....	442
Bibliography .....	448