ISO/IEC 14776-153:2015-02 (E)

Information technology - Small Computer System Interface (SCSI) - Part 153: Serial Attached SCSI - 2.1 (SAS-2.1)

Contents

Page

FOREWORD 10
INTRODUCTION 12
General 12
SCSI standards family 12
1 Scope 14
2 Normative references 14
3 Terms, definitions, symbols, abbreviations, keywords, and conventions 16
3.1 Terms and definitions 16
3.2 Symbols and abbreviations 28
3.2.1 Abbreviations 28
3.2.2 Units 30
3.2.3 Symbols 30
3.2.4 Mathematical operators 31
3.3 Keywords 32
3.4 Editorial conventions 33
4 General 34
4.1 Physical links and phys 34
4.2 Phy test functions 34
5 Physical layer 35
5.1 Physical layer overview 35
5.2 Conventions for defining maximum limits for S-parameters 35
5.3 Compliance points 36
5.4 Interconnects 45
5.4.1 SATA connectors and cable assemblies 45
5.4.2 SAS connectors and cables 46
5.4.3 Connectors 49
5.4.4 Cable assemblies 94
5.4.5 Backplanes 118
5.5 TxRx connection characteristics 119
5.5.1 TxRx connection characteristics overview 119
5.5.2 TxRx connection general characteristics 120
5.5.3 Passive TxRx connection S-parameter limits 120
5.5.4 Passive TxRx connection characteristics for untrained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s 122
5.5.5 Passive TxRx connection characteristics for trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s 123
5.5.6 TxRx connection characteristics for active cable assemblies 124

5.6 Test loads 126
5.6.1 Test loads overview 126
5.6.2 Zero-length test load 127
5.6.3 TCTF test load 129
5.6.4 Low-loss TCTF test load 133
5.6.5 Reference transmitter test load 134
5.7 Transmitter device and receiver device electrical characteristics 139
5.7.1 General electrical characteristics 139
5.7.2 Transmitter device and receiver device transients 139
5.7.3 Eye masks and the jitter transfer function (JTF) 140
5.7.4 Transmitter device characteristics 144
5.7.5 Receiver device characteristics 155
5.7.6 Spread spectrum clocking (SSC) 170
5.7.7 Non-tracking clock architecture 173
5.8 READY LED signal electrical characteristics 173
5.9 Out of band (OOB) signals 175
5.9.1 OOB signals overview 175
5.9.2 Transmitting OOB signals 176
5.9.3 Receiving OOB signals 178
5.9.4 Transmitting the SATA port selection signal 179

Annex A (normative) – Jitter tolerance pattern (JTPAT) 180

Annex B (normative) – SASWDP 182

Annex C (informative) – StatEye 190

Annex D (informative) – Signal performance measurements 232

Annex E (informative) – Description of the included Touchstone models 253

Annex F (informative) – Mini SAS 4x active cable assembly power supply and voltage detection circuitry 259

Annex G (informative) – SAS icons 260

Bibliography 262