

ISO 16639:2017-01 (E)

Surveillance of the activity concentrations of airborne radioactive substances in the workplace of nuclear facilities

| Contents | | Page |
|--------------------|---|-------------|
| Foreword | | v |
| Introduction | | vi |
| 1 | Scope | 1 |
| 2 | Normative references | 2 |
| 3 | Terms and definitions | 2 |
| 4 | Symbols | 5 |
| 5 | Developing the surveillance program | 5 |
| 5.1 | Reasons for conducting a surveillance programme | 5 |
| 5.1.1 | General | 5 |
| 5.1.2 | Sampling when respiratory protective equipment is used | 6 |
| 5.1.3 | Sampling to establish air contamination areas | 6 |
| 5.1.4 | Air sampling as a basis for determining worker intakes | 6 |
| 5.1.5 | Air monitoring for early warning of elevated air concentrations | 6 |
| 5.2 | Graded approach to sampling | 7 |
| 5.3 | Frequency of sampling | 8 |
| 5.3.1 | General | 8 |
| 5.3.2 | Grab vs. continuous sampling | 8 |
| 5.3.3 | Continuous monitoring of activity concentrations | 8 |
| 5.3.4 | Prompt analysis of certain samples | 9 |
| 5.4 | Substitutes for air sampling | 9 |
| 6 | Location of samplers and monitors | 9 |
| 6.1 | General | 9 |
| 6.2 | Types of air flow studies | 9 |
| 6.2.1 | General | 9 |
| 6.2.2 | Qualitative airflow studies | 9 |
| 6.2.3 | Quantitative airflow studies | 10 |
| 6.3 | Location of samplers for estimating committed effective dose | 10 |
| 6.4 | Location of samplers for evaluating effectiveness of containment | 11 |
| 6.5 | Location of samplers for posting of air contamination areas | 11 |
| 6.6 | Location of portable samplers | 12 |
| 6.7 | Location of CAM for continuous monitoring of the activity concentration | 12 |
| 7 | Collection of samples | 12 |
| 7.1 | General | 12 |
| 7.2 | Sampling of aerosol particles | 12 |
| 7.3 | Gas Sampling | 13 |
| 8 | Evaluation of sampling results | 14 |
| 8.1 | Determining the average activity concentration | 14 |
| 8.2 | Uncertainty | 14 |
| 8.3 | Techniques for correcting for radon progeny interference | 15 |
| 8.4 | Evaluating changes in activity concentration over time | 15 |
| 8.5 | Review of sampling results | 15 |

| | | |
|------------------------------|--|-----------|
| 9 | Evaluating the effectiveness of the sampling program | 16 |
| 9.1 | General | 16 |
| 9.2 | Dose-based assessment of the adequacy of the sampling program | 16 |
| 10 | Quality assurance and quality control | 17 |
| 10.1 | General | 17 |
| 10.2 | Sample identification, handling, and storage | 17 |
| 10.3 | Sampling and monitoring equipment | 17 |
| 10.3.1 | General | 17 |
| 10.3.2 | Performance of measuring instruments | 18 |
| 10.3.3 | Air in-leakage testing | 18 |
| 10.4 | Documentation and record keeping | 18 |
| Annex A (informative) | Examples for the determination of uncertainty, decision threshold and detection limit according to ISO 11929 | 20 |
| Annex B (informative) | Correcting for the interference of radon progeny | 27 |
| Annex C (informative) | Normalized concentration and exposure | 29 |
| Annex D (informative) | Example applications of evaluating sampling program sensitivity from the viewpoint of potential missed exposure | 30 |
| Bibliography | | 32 |