

ISO/IEC TR 11801-9902:2017-06 (E)

Information technology - Generic cabling for customer premises - Part 9902: Specifications for End-to-end link configurations

Contents	Page
FOREWORD.....	5
INTRODUCTION.....	6
1 Scope.....	7
2 Normative references.....	7
3 Terms, definitions, abbreviated terms and symbols.....	7
3.1 Terms and definitions.....	7
3.2 Abbreviated terms.....	8
3.3 Symbols.....	8
4 Specifications.....	9
5 Examples of end-to-end link configurations.....	10
6 Performance specifications when using end-to-end link limits.....	11
6.1 General.....	11
6.2 Worst case limits.....	12
6.3 Insertion loss limits.....	13
6.4 Return loss.....	14
6.5 NEXT limits.....	16
6.6 PSNEXT limits.....	17
6.7 ACR-F Limits.....	18
6.8 PSACR-F.....	19
6.9 TCL specifications.....	19
6.10 ELTCTL specifications.....	20
6.11 Coupling attenuation specifications.....	20
6.12 DC loop resistance.....	20
6.13 Propagation delay.....	21
6.14 Delay skew.....	21
6.15 DC resistance unbalance within a pair.....	21
7 E2E link performance.....	21
7.1 General.....	21
7.2 Reference performance testing.....	22
7.3 Installation performance testing.....	22
7.4 Installation performance testing of E2E links.....	22
8 Testing of end-to-end links.....	23
Annex A (informative) CP cords.....	24
A.1 Specifications for Class D and Class E CP cords.....	24
A.2 Specifications for Class E _A CP cords.....	24
A.2.1 General.....	24
A.2.2 Insertion loss.....	24
A.2.3 Return loss.....	24
A.2.4 NEXT.....	25
A.2.5 PSNEXT.....	25
A.2.6 ACR-F.....	25
A.2.7 PSACR-F.....	25
A.2.8 TCL.....	26
A.2.9 ELTCTL.....	26

A.2.10	Propagation delay.....	26
A.2.11	Delay skew	26
A.2.12	DC resistance unbalance within a pair	26
	Bibliography.....	27
Figure 1	– Symbols for bulkhead connections	9
Figure 2	– One-segment, two-connections, E2E link	10
Figure 3	– Two-segments, three-connections, E2E link	10
Figure 4	– Three-segments, one-connection bulkheads, four-connections, E2E link	10
Figure 5	– Three-segments, six-connections, E2E link	10
Figure 6	– Three-segments, four-connections, E2E link	11
Figure 7	– Three-segments, four-connections, E2E link	11
Figure 8	– Four-segments, five-connections, E2E link	11
Figure 9	– Five-segments, six-connections, E2E link.....	11
Figure A.1	– One-segment, two-connection, CP cord	24
Table 1	– Worst case Class D E2E link performance at key frequencies	12
Table 2	– Worst case Class E E2E link performance at key frequencies	13
Table 3	– Class D E2E link insertion loss limits	13
Table 4	– Class E E2E link insertion loss limits	14
Table 5	– Class D E2E link return loss limits	14
Table 6	– Class E E2E link return loss limits	15
Table 7	– Class D E2E link NEXT limits	16
Table 8	– Class E E2E link NEXT limits	16
Table 9	– Class D E2E link PSNEXT limits.....	17
Table 10	– Class E E2E link PSNEXT limits	17
Table 11	– Class D E2E Link ACR-F limits	18
Table 12	–Class E E2E Link ACR-F limits	18
Table 13	– Class D E2E link PSACR-F limits	19
Table 14	– Class E E2E link PSACR-F limits.....	19
Table 15	– E2E link TCL	19
Table 16	– E2E link segment ELTCTL.....	20
Table 17	– Minimum E2E link coupling attenuation	20
Table 18	– E2E link segment DC loop resistance	20
Table 19	– E2E link delay	21
Table 20	– E2E link delay skew	21
Table 21	– E2E link DC resistance unbalance	21
Table 22	– Test regime for reference performance and installation performance – Balanced cabling of Classes D to E	23
Table A.1	– Class E _A insertion loss specifications	24
Table A.2	– Class E _A return loss specifications	25

Table A.3 – Class E_A NEXT specifications.....	25
Table A.4 – Class E_A PSNEXT specifications	25
Table A.5 – Class E_A ACR-F specifications	25
Table A.6 – Class E_A PSACR-F specifications	26
Table A.7 – Class E_A propagation delay specifications	26
Table A.8 – Class E_A delay skew specifications.....	26
Table A.9 – E2E link DC resistance unbalance	26