

ISO/IEC 29341-26-1:2017-09 (E)

Information technology - UPnP Device Architecture - Part 26-1: Telephony device control protocol - Level 2 - Telephony architecture

| Contents | | Page |
|--|--|-------------|
| 1 | Scope | v |
| 2 | Normative references | 1 |
| 3 | Terms, definitions and abbreviated terms | 1 |
| 3.1 | Provisioning terms | 1 |
| 3.2 | Symbols | 1 |
| 3.3 | General telephony terms | 2 |
| 4 | Text conventions | 2 |
| 5 | Introduction | 2 |
| 6 | Telephony Reference Architecture | 3 |
| 6.1 | Telephony Basic Architecture Paradigm | 3 |
| 6.2 | Telephony Components Overview | 5 |
| 6.2.1 | Call Management Service | 6 |
| 6.2.2 | Media Management Service | 7 |
| 6.2.3 | Interaction of Media and Call Management Service | 7 |
| 6.2.4 | Messaging Service | 8 |
| 6.2.5 | Presence Service | 9 |
| 6.2.6 | Calendar Service | 9 |
| 6.2.7 | Address Book Service | 10 |
| 6.2.8 | Phone Management via Data Model | 10 |
| 6.2.9 | InputConfig Service | 11 |
| 6.2.10 | Security | 12 |
| Annex A (informative) Deployment Scenarios | | 13 |
| Annex B (informative) Bibliography | | 20 |
| Figure 1 -- UPnP Telephony Basic Architecture | | 3 |
| Figure 2 -- Architecture with a Telephony Control Point (TelCP) on an independent Device (3-Box Model) | | 4 |
| Figure 3 -- Service Level Architectural View | | 4 |
| Figure 4 -- UPnP Devices and Services for Telephony Architecture | | 5 |
| Figure 5 -- A Deployment Scenario with Two Telephony Server Devices in a Single Physical Box | | 6 |
| Figure 6 -- Call Management Service | | 7 |
| Figure 7 -- Media Management Service | | 7 |
| Figure 8 -- Architecture for Media Management Service | | 8 |
| Figure 9 -- Messaging Service Interaction Diagram | | 8 |
| Figure 10 -- Architecture for Presence Service | | 9 |

| | |
|---|----|
| Figure 11 -- Architecture for Calendar Service | 10 |
| Figure 12 -- Architecture for Address Book Service | 10 |
| Figure 13 -- Phone Management via Data Model Interaction Diagram | 11 |
| Figure 14 -- Architecture for InputConfig Service (IS) | 11 |
| Figure 15 -- Architecture for Security Service | 12 |
| Figure A.1 -- Architecture with Telephony Control Point on a TV | 13 |
| Figure A.2 -- Deployment with a TelCP on a TC - Multiple TV Model | 13 |
| Figure A.3 -- Deployment with a TelCP on a TV - Multiple Phone Model | 14 |
| Figure A.4 -- An Architecture with a Telephony Control Point (TelCP) and a Telephony Client (TC) on a TV (2-Box Model) | 14 |
| Figure A.5 -- Deployment model with a Telephony Control Point (TelCP) and a Telephony Client (TC) on a TV (2-Box Model) - Multiple TV Model | 15 |
| Figure A.6 -- Deployment model with a Telephony Control Point (TelCP) and a Telephony Server (TS) on a Phone (2-Box Physical Model) | 15 |
| Figure A.7 -- Deployment with a phone having a Telephony Server (TS) and a Telephony Control Point (TelCP) - Multiple TV Model | 16 |
| Figure A.8 -- Deployment with a Telephony Control Point (TelCP) on a Phone | 16 |
| Figure A.9 -- Deployment with a Telephony Control Point (TelCP) on a Phone - Multiple TV Model ... | 17 |
| Figure A.10 -- Deployment with an independent Telephony Control point (TelCP) -3 Box Scenario .. | 17 |
| Figure A.11 -- Deployment with an independent Telephony Control Point (TelCP) - 3- Box with Multiple TV Model | 18 |
| Figure A.12 -- Messaging Service Deployment with Phone as the Messaging Aggregator | 18 |
| Figure A.13 -- Multiple Telephony Servers in a telephone | 19 |