

# ISO/IEC 11801-4:2017-11 (E)

## Information technology - Generic cabling for customer premises - Part 4: Single-tenant homes

---

### CONTENTS

- FOREWORD.....5
- INTRODUCTION.....7
- 1 Scope.....9
- 2 Normative references .....9
- 3 Terms, definitions and abbreviated terms .....9
  - 3.1 Terms and definitions.....9
  - 3.2 Abbreviated terms.....10
- 4 Conformance.....11
- 5 Structure of the generic cabling system .....11
  - 5.1 General.....11
  - 5.2 Functional elements.....12
  - 5.3 Cabling subsystems for ICT and BCT.....12
    - 5.3.1 General .....12
    - 5.3.2 Primary home cabling subsystem.....14
    - 5.3.3 Secondary home cabling subsystem .....14
  - 5.4 Cabling structure .....14
  - 5.5 Interfaces.....15
    - 5.5.1 Equipment interfaces and test interfaces .....15
    - 5.5.2 Channel and permanent link .....16
    - 5.5.3 Network access cabling .....17
    - 5.5.4 External network interface .....18
  - 5.6 Accommodation of functional elements .....18
    - 5.6.1 General .....18
    - 5.6.2 Coverage areas .....19
    - 5.6.3 Dimensioning and configuring.....20
    - 5.6.4 Connecting hardware.....21
    - 5.6.5 Application outlets .....21
    - 5.6.6 Equipment cords.....21
- 6 Channel performance requirements .....22
  - 6.1 General.....22
  - 6.2 Environmental performance .....22
  - 6.3 Transmission performance .....22
    - 6.3.1 Channel construction.....22
    - 6.3.2 Balanced cabling .....22
    - 6.3.3 Coaxial cabling .....23
    - 6.3.4 Optical fibre cabling.....23
- 7 Link performance requirements .....23
  - 7.1 General.....23
  - 7.2 Balanced cabling .....23
  - 7.3 Coaxial cabling .....23
  - 7.4 Optical fibre cabling .....23

8	Reference implementations .....	23
8.1	General.....	23
8.2	Channel construction .....	24
8.3	Balanced cabling .....	24
8.3.1	General .....	24
8.3.2	ICT channels .....	25
8.3.3	BCT channels .....	25
8.4	Coaxial cabling .....	26
8.5	Optical fibre cabling .....	26
8.5.1	General .....	26
8.5.2	Component selection .....	26
8.5.3	Dimensions.....	26
9	Cable requirements .....	26
9.1	General.....	26
9.2	Balanced cables .....	27
9.2.1	ICT cabling .....	27
9.2.2	BCT cabling.....	27
9.3	Coaxial cables .....	27
9.4	Optical fibre cables .....	27
10	Connecting hardware requirements .....	27
10.1	General requirements .....	27
10.2	Connecting hardware for balanced cabling.....	27
10.2.1	General requirements .....	27
10.2.2	Electrical, mechanical and environmental performance .....	27
10.3	Connecting hardware for coaxial cabling.....	28
10.3.1	General requirements .....	28
10.3.2	Electrical, mechanical and environmental performance .....	28
10.4	Connecting hardware for optical fibre cabling.....	28
10.4.1	General requirements .....	28
10.4.2	Optical, mechanical and environmental performance .....	28
11	Cords .....	28
11.1	Jumpers.....	28
11.2	Balanced cords .....	28
11.3	Coaxial cords.....	28
11.4	Optical fibre cords.....	28
Annex A	(informative) Reference implementation of TV and radio applications – use of baluns .....	29
A.1	Types and locations of baluns.....	29
A.1.1	General .....	29
A.1.2	Baluns at the ENI and baluns at the equipment interface toward the PHD .....	29
A.1.3	Baluns near or in the BO .....	30
A.1.4	Baluns in the cord between BO and the terminal equipment .....	31
A.2	Home network interface .....	31
	Bibliography.....	33

Figure 1 – Relationships between the generic cabling documents produced by ISO/IEC JTC 1/SC 25 .....	7
Figure 2 – Structure of the generic cabling system.....	12
Figure 3 – Interconnect and cross-connect models .....	13
Figure 4 – Interconnect and cross-connects at the PHD.....	13
Figure 5 – Hierarchical structure of a generic cabling system in support of ICT and BCT applications.....	14
Figure 6 – Equipment and test interfaces in support of ICT and BCT applications .....	16
Figure 7 – Channels and permanent links within the home.....	17
Figure 8 – Examples of interconnection of home and network access cabling .....	18
Figure 9 – Overview of a generic cabling for home.....	19
Figure 10 – Interconnection of home cabling subsystems.....	20
Figure 11 – Reference implementations for ICT and BCT channels (PHD/SHD to TO/BO).....	24
Figure A.1 – Balun at the ENI .....	29
Figure A.2 – Baluns in the PHD .....	30
Figure A.3 – Balun built into the system outlet .....	30
Figure A.4 – Balun in the cord between BO and the TE.....	31
Figure A.5 – Types of HNI.....	32
Table 1 – Maximum channel lengths for reference implementations of ICT/BCT channels .....	21
Table 2 – Link length equations .....	25
Table A.1 – Insertion loss and total sectional slope.....	32