

# ISO/IEC 11801-5:2017-11 (E)

## Information technology - Generic cabling for customer premises - Part 5: Data centres

---

### CONTENTS

- FOREWORD..... 6
- INTRODUCTION..... 8
- 1 Scope..... 10
- 2 Normative references ..... 10
- 3 Terms, definitions and abbreviated terms ..... 11
  - 3.1 Terms and definitions..... 11
  - 3.2 Abbreviated terms..... 13
- 4 Conformance..... 13
- 5 Structure of the generic cabling system ..... 14
  - 5.1 General..... 14
  - 5.2 Functional elements..... 14
  - 5.3 General structure and hierarchy..... 14
  - 5.4 Cabling subsystems ..... 16
    - 5.4.1 General ..... 16
    - 5.4.2 Network access cabling subsystem..... 16
    - 5.4.3 Main distribution cabling subsystem..... 16
    - 5.4.4 Intermediate distribution cabling subsystem..... 16
    - 5.4.5 Zone distribution cabling subsystem ..... 16
    - 5.4.6 Design objectives ..... 17
  - 5.5 Accommodation of functional elements ..... 17
  - 5.6 Interfaces..... 17
    - 5.6.1 Equipment interfaces and test interfaces ..... 17
    - 5.6.2 Channels and links ..... 18
  - 5.7 Dimensioning and configuring ..... 19
    - 5.7.1 Distributors ..... 19
    - 5.7.2 Redundancy ..... 20
    - 5.7.3 External network interface ..... 21
    - 5.7.4 Cables ..... 22
    - 5.7.5 Equipment cords..... 22
    - 5.7.6 Patch cords and jumpers ..... 22
    - 5.7.7 Equipment outlets..... 22
    - 5.7.8 LDP ..... 23
    - 5.7.9 Building entrance facilities ..... 23
  - 5.8 Earthing and equipotential bonding ..... 23
- 6 Channel performance requirements ..... 23
  - 6.1 General..... 23
  - 6.2 Environmental performance ..... 25
  - 6.3 Transmission performance ..... 25
    - 6.3.1 General ..... 25
    - 6.3.2 Balanced cabling ..... 25
    - 6.3.3 Optical fibre cabling ..... 25

7	Link performance requirements .....	26
7.1	General.....	26
7.2	Balanced cabling .....	26
7.3	Optical fibre cabling .....	26
8	Reference implementations .....	26
8.1	General.....	26
8.2	Balanced cabling .....	26
8.2.1	Assumptions.....	26
8.2.2	Zone distribution cabling.....	27
8.2.3	Cabling between distributors.....	30
8.2.4	Network access cabling .....	33
8.3	Optical fibre cabling .....	35
8.3.1	General .....	35
8.3.2	Component choice.....	35
8.3.3	Dimensions.....	36
9	Cable requirements .....	36
9.1	General.....	36
9.2	Balanced cables .....	36
9.3	Optical fibre cables .....	36
10	Connecting hardware requirements .....	36
10.1	General requirements .....	36
10.1.1	Overview .....	36
10.1.2	Location .....	36
10.1.3	Design.....	37
10.1.4	Operating environment .....	37
10.1.5	Mounting .....	37
10.1.6	Installation practices.....	37
10.1.7	Marking and colour coding.....	37
10.2	Connecting hardware for balanced cabling.....	37
10.2.1	General requirements .....	37
10.2.2	Performance marking.....	37
10.2.3	Mechanical characteristics.....	37
10.3	Connecting hardware for optical fibre cabling.....	38
10.3.1	General requirements .....	38
10.3.2	ENI requirements.....	38
10.3.3	EO requirements .....	38
10.3.4	Optical fibre assignments at the EO.....	39
10.3.5	Other connecting hardware.....	39
11	Requirements for cords and jumpers .....	39
11.1	Jumpers.....	39
11.2	Balanced cords .....	39
11.3	Optical fibre cords.....	39

Annex A (normative) Combination of balanced cabling links.....	40
A.1 General.....	40
A.2 Requirements .....	40
Annex B (informative) Usage of high density connecting hardware within optical fibre cabling.....	41
B.1 General.....	41
B.2 Use cases for high density connecting hardware .....	41
Annex C (informative) Examples of structures in accordance with ISO/IEC 11801-5 .....	45
C.1 General.....	45
C.2 Data centre minimum configuration .....	46
C.3 End of Row concept .....	47
C.4 Middle of Row concept.....	48
C.5 Top of Rack concept .....	49
C.6 End of Row and Middle of Row concept with redundancy.....	50
C.7 Top of Rack concept with redundancy .....	51
C.8 End of Row concept with full redundancy .....	52
C.9 Top of Rack concept with redundancy .....	53
Annex D (informative) Examples of networking architectures .....	54
D.1 General.....	54
D.2 Data centre fabric fat-tree .....	54
D.3 Data centre fabric full-mesh .....	55
D.4 Data centre fabric interconnected meshes .....	55
D.5 Data centre fabric centralized switch.....	56
D.6 Data centre fabric virtual switch .....	57
Bibliography.....	58
Figure 1 – Relationships between the generic cabling documents produced by ISO/IEC JTC 1/SC 25 .....	8
Figure 2 – Structure of generic cabling within a data centre .....	15
Figure 3 – Hierarchical structure of generic cabling within a data centre .....	15
Figure 4 – Example of accommodation of functional elements .....	17
Figure 5 – Test and equipment interfaces .....	19
Figure 6 – Connection of functional elements providing redundancy .....	21
Figure 7 – Examples of external service cabling connections to the ENI .....	22
Figure 8 – Example of a channel with four connections .....	24
Figure 9 – Example of a system showing the location of cabling interfaces .....	25
Figure 10 – Zone distribution cabling models .....	28
Figure 11 – Cabling model between distributors using Class E <sub>A</sub> to F <sub>A</sub> .....	31
Figure 12 – Cabling model between distributors using Class I and II .....	31
Figure 13 – Network access cabling models.....	34
Figure A.1 – Examples of combination of different links .....	40
Figure B.1 – Examples of high density connecting hardware within main distribution cabling and intermediate distribution cabling.....	42
Figure B.2 – Examples of high density connecting hardware at the LDP and EO within zone distribution cabling .....	44

Figure C.1 – Key for Figures C.2 through C.9 .....	45
Figure C.2 – Example of a minimum configuration .....	46
Figure C.3 – Example of End of Row configuration .....	47
Figure C.4 – Example of Middle of Row configuration .....	48
Figure C.5 – Example of Top of Rack configuration.....	49
Figure C.6 – Example of End of Row configuration with redundancy .....	50
Figure C.7 – Example of Top of Rack configuration with redundancy .....	51
Figure C.8 – Example of End of Row configuration with full redundancy .....	52
Figure C.9 – Example of Top of Rack configuration with full redundancy.....	53
Figure D.1 – Fat-tree example .....	54
Figure D.2 – Full-mesh example .....	55
Figure D.3 – Interconnected mesh example .....	56
Figure D.4 – Centralized switch example .....	56
Figure D.5 – Virtual switch example .....	57
Table 1 – Zone distribution cabling – length assumptions for balanced cabling using Classes E <sub>A</sub> to F <sub>A</sub> .....	29
Table 2 – Zone distribution cabling – length assumptions for balanced cabling using Classes I and II.....	30
Table 3 – Zone distribution channel length equations for Classes .....	30
Table 4 – Cabling between distributors – length assumptions for balanced cabling using Classes E <sub>A</sub> to F <sub>A</sub> .....	31
Table 5 – Cabling between distributors – length assumptions for balanced cabling using Classes I and II .....	32
Table 6 – Length equations for cabling between distributors .....	32
Table 7 – Network access cabling channel equations.....	35
Table 8 – Connecting hardware of the type used at the EO.....	37