ISO/IEC 11801-5:2017-11 (E)

Information technology - Generic cabling for customer premises - Part 5: Data centres

CONTENTS

FOREWORD 6
INTRODUCTION 8
1 Scope 10
2 Normative references 10
3 Terms, definitions and abbreviated terms 11
3.1 Terms and definitions 11
3.2 Abbreviated terms 13
4 Conformance 13
5 Structure of the generic cabling system 14
5.1 General 14
5.2 Functional elements 14
5.3 General structure and hierarchy 14
5.4 Cabling subsystems 16
5.4.1 General 16
5.4.2 Network access cabling subsystem 16
5.4.3 Main distribution cabling subsystem 16
5.4.4 Intermediate distribution cabling subsystem 16
5.4.5 Zone distribution cabling subsystem 16
5.4.6 Design objectives 17
5.5 Accommodation of functional elements 17
5.6 Interfaces 17
5.6.1 Equipment interfaces and test interfaces 17
5.6.2 Channels and links 18
5.7 Dimensioning and configuring 19
5.7.1 Distributors 19
5.7.2 Redundancy 20
5.7.3 External network interface 21
5.7.4 Cables 22
5.7.5 Equipment cords 22
5.7.6 Patch cords and jumpers 22
5.7.7 Equipment outlets 22
5.7.8 LDP 23
5.7.9 Building entrance facilities 23
5.8 Earthing and equipotential bonding 23
6 Channel performance requirements 23
6.1 General 23
6.2 Environmental performance 25
6.3 Transmission performance 25
6.3.1 General 25
6.3.2 Balanced cabling 25
6.3.3 Optical fibre cabling 25

7 Link performance requirements 26
7.1 General 26
7.2 Balanced cabling 26
7.3 Optical fibre cabling 26
8 Reference implementations 26
8.1 General 26
8.2 Balanced cabling 26
8.2.1 Assumptions 26
8.2.2 Zone distribution cabling 27
8.2.3 Cabling between distributors 30
8.2.4 Network access cabling 33
8.3 Optical fibre cabling 35
8.3.1 General 35
8.3.2 Component choice 35
8.3.3 Dimensions 36
9 Cable requirements 36
9.1 General 36
9.2 Balanced cables 36
9.3 Optical fibre cables 36
10 Connecting hardware requirements 36
10.1 General requirements 36
10.1.1 Overview 36
10.1.2 Location 36
10.1.3 Design 37
10.1.4 Operating environment 37
10.1.5 Mounting 37
10.1.6 Installation practices 37
10.1.7 Marking and colour coding 37
10.2 Connecting hardware for balanced cabling 37
10.2.1 General requirements 37
10.2.2 Performance marking 37
10.2.3 Mechanical characteristics 37
10.3 Connecting hardware for optical fibre cabling 38
10.3.1 General requirements 38
10.3.2 ENI requirements 38
10.3.3 EO requirements 38
10.3.4 Optical fibre assignments at the EO 39
10.3.5 Other connecting hardware 39
11 Requirements for cords and jumpers 39
11.1 Jumpers 39
11.2 Balanced cords 39
11.3 Optical fibre cords 39

Annex A (normative) Combination of balanced cabling links 40
A.1 General 40
A.2 Requirements 40
Annex B (informative) Usage of high density connecting hardware within optical fibre cabling 41
B.1 General 41
B.2 Use cases for high density connecting hardware 41
Annex C (informative) Examples of structures in accordance with ISO/IEC 11801-5 45
C.1 General 45
C.2 Data centre minimum configuration 46
C.3 End of Row concept 47
C.4 Middle of Row concept 48
C.5 Top of Rack concept 49
C.6 End of Row and Middle of Row concept with redundancy 50
C.7 Top of Rack concept with redundancy 51
C.8 End of Row concept with full redundancy 52
C.9 Top of Rack concept with redundancy 53
Annex D (informative) Examples of networking architectures 54
D.1 General 54
D.2 Data centre fabric fat-tree 54
D.3 Data centre fabric full-mesh 55
D.4 Data centre fabric interconnected meshes 55
D.5 Data centre fabric centralized switch 56
D.6 Data centre fabric virtual switch 57
Bibliography 58

Figure 1 – Relationships between the generic cabling documents produced by ISO/IEC JTC 1/SC 25 8
Figure 2 – Structure of generic cabling within a data centre 15
Figure 3 – Hierarchical structure of generic cabling within a data centre 15
Figure 4 – Example of accommodation of functional elements 17
Figure 5 – Test and equipment interfaces 19
Figure 6 – Connection of functional elements providing redundancy 21
Figure 7 – Examples of external service cabling connections to the ENI 22
Figure 8 – Example of a channel with four connections 24
Figure 9 – Example of a system showing the location of cabling interfaces 25
Figure 10 – Zone distribution cabling models 28
Figure 11 – Cabling model between distributors using Class E_A to F_A 31
Figure 12 – Cabling model between distributors using Class I and II 31
Figure 13 – Network access cabling models 34
Figure A.1 – Examples of combination of different links 40
Figure B.1 – Examples of high density connecting hardware within main distribution cabling and intermediate distribution cabling 42
Figure B.2 – Examples of high density connecting hardware at the LDP and EO within zone distribution cabling 44

Figure C.1 – Key for Figures C.2 through C.9 45
Figure C.2 – Example of a minimum configuration 46
Figure C.3 – Example of End of Row configuration 47
Figure C.4 – Example of Middle of Row configuration 48
Figure C.5 – Example of Top of Rack configuration 49
Figure C.6 – Example of End of Row configuration with redundancy 50
Figure C.7 – Example of Top of Rack configuration with redundancy 51
Figure C.8 – Example of End of Row configuration with full redundancy 52
Figure C.9 – Example of Top of Rack configuration with full redundancy 53
Figure D.1 – Fat-tree example 54
Figure D.2 – Full-mesh example 55
Figure D.3 – Interconnected mesh example 56
Figure D.4 – Centralized switch example 56
Figure D.5 – Virtual switch example 57

Table 1 – Zone distribution cabling – length assumptions for balanced cabling using Classes E_A to F_A 29
Table 2 – Zone distribution cabling – length assumptions for balanced cabling using Classes I and II 30
Table 3 – Zone distribution channel length equations for Classes 30
Table 4 – Cabling between distributors – length assumptions for balanced cabling using Classes E_A to F_A 31
Table 5 – Cabling between distributors – length assumptions for balanced cabling using Classes I and II 32
Table 6 – Length equations for cabling between distributors 32
Table 7 – Network access cabling channel equations 35
Table 8 – Connecting hardware of the type used at the EO 37