

ISO/IEC 14776-154:2017-12 (E)

Information technology - Small Computer System Interface (SCSI) - Part 154: Serial Attached SCSI - 3 (SAS-3)

CONTENTS

| | |
|----------------------------------------------------------------------------------------------------------------|----|
| FOREWORD..... | 14 |
| INTRODUCTION..... | 16 |
| 1 Scope..... | 18 |
| 2 Normative references..... | 18 |
| 3 Terms, definitions, symbols, abbreviations, keywords, and conventions..... | 20 |
| 3.1 Terms and definitions..... | 20 |
| 3.2 Symbols and abbreviations..... | 33 |
| 3.2.1 Abbreviations..... | 33 |
| 3.2.2 Symbols..... | 36 |
| 3.2.2.1 Units..... | 36 |
| 3.2.2.2 Mathematical operators..... | 36 |
| 3.2.2.3 Other symbols..... | 37 |
| 3.3 Keywords..... | 38 |
| 3.4 Editorial conventions..... | 39 |
| 3.5 Numeric and character conventions..... | 40 |
| 3.5.1 Numeric conventions..... | 40 |
| 3.5.2 Units of measure..... | 40 |
| 3.5.3 Byte encoded character strings conventions..... | 41 |
| 4 General..... | 42 |
| 4.1 Physical links and phys..... | 42 |
| 4.2 Phy test functions..... | 42 |
| 5 Physical layer..... | 43 |
| 5.1 Physical layer overview..... | 43 |
| 5.2 Conventions for defining maximum limits for S-parameters..... | 43 |
| 5.3 Compliance points..... | 44 |
| 5.3.1 Compliance points overview..... | 44 |
| 5.3.2 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s compliance points..... | 45 |
| 5.3.3 12 Gbit/s compliance points..... | 53 |
| 5.4 Interconnects..... | 55 |
| 5.4.1 SATA connectors and cable assemblies..... | 55 |
| 5.4.2 SAS connectors and cables..... | 56 |
| 5.4.3 Connectors..... | 60 |
| 5.4.3.1 Connectors overview..... | 60 |
| 5.4.3.2 Connector categories..... | 62 |
| 5.4.3.3 Recommended electrical performance limits for mated connector pairs supporting rates of 12 Gbit/s..... | 63 |
| 5.4.3.4 SAS internal connectors..... | 64 |
| 5.4.3.4.1 SAS Drive connectors..... | 64 |
| 5.4.3.4.1.1 SAS Drive plug connector..... | 64 |
| 5.4.3.4.1.2 SAS Drive cable receptacle connector..... | 65 |
| 5.4.3.4.1.3 SAS Drive backplane receptacle connector..... | 66 |
| 5.4.3.4.1.4 SAS Drive connector pin assignments..... | 67 |
| 5.4.3.4.1.5 SAS MultiLink Drive plug connector..... | 69 |
| 5.4.3.4.1.6 SAS MultiLink Drive cable receptacle connector..... | 69 |
| 5.4.3.4.1.7 SAS MultiLink Drive backplane receptacle connector..... | 70 |
| 5.4.3.4.1.8 SAS MultiLink Drive connector pin assignments..... | 70 |
| 5.4.3.4.1.9 Micro SAS plug connector..... | 74 |
| 5.4.3.4.1.10 Micro SAS receptacle connector..... | 74 |
| 5.4.3.4.1.11 Micro SAS connector pin assignments..... | 75 |
| 5.4.3.4.2 SAS 4i connectors..... | 76 |
| 5.4.3.4.2.1 SAS 4i cable receptacle connector..... | 76 |

| | |
|----------------------------------------------------------------------------------------------------------------|-----|
| 5.4.3.4.2.2 SAS 4i plug connector..... | 76 |
| 5.4.3.4.2.3 SAS 4i connector pin assignments | 77 |
| 5.4.3.4.3 Mini SAS 4i connectors..... | 79 |
| 5.4.3.4.3.1 Mini SAS 4i cable plug connector | 79 |
| 5.4.3.4.3.2 Mini SAS 4i receptacle connector | 79 |
| 5.4.3.4.3.3 Mini SAS 4i connector pin assignments..... | 80 |
| 5.4.3.4.4 Mini SAS HD internal connectors | 82 |
| 5.4.3.4.4.1 Mini SAS HD 4i cable plug connector | 82 |
| 5.4.3.4.4.2 Mini SAS HD 8i cable plug connector | 83 |
| 5.4.3.4.4.3 Mini SAS HD 4i receptacle connector | 84 |
| 5.4.3.4.4.4 Mini SAS HD 8i receptacle connector | 85 |
| 5.4.3.4.4.5 Mini SAS HD 16i receptacle connector..... | 86 |
| 5.4.3.4.4.6 Mini SAS HD 4i connector pin assignments..... | 87 |
| 5.4.3.5 SAS external connectors..... | 90 |
| 5.4.3.5.1 Mini SAS 4x connectors..... | 90 |
| 5.4.3.5.1.1 Mini SAS 4x cable plug connector | 90 |
| 5.4.3.5.1.2 Mini SAS 4x receptacle connector | 97 |
| 5.4.3.5.1.3 Mini SAS 4x connector pin assignments..... | 103 |
| 5.4.3.5.1.4 Mini SAS 4x active connector pin assignments | 104 |
| 5.4.3.5.1.5 Mini SAS 4x active cable power requirements..... | 105 |
| 5.4.3.5.2 Mini SAS HD external connectors | 106 |
| 5.4.3.5.2.1 Mini SAS HD 4x cable plug connector | 106 |
| 5.4.3.5.2.2 Mini SAS HD 8x cable plug connector | 107 |
| 5.4.3.5.2.3 Mini SAS HD 4x receptacle connector | 108 |
| 5.4.3.5.2.4 Mini SAS HD 8x receptacle connector | 109 |
| 5.4.3.5.2.5 Mini SAS HD 16x receptacle connector..... | 110 |
| 5.4.3.5.2.6 Mini SAS HD 4x connector pin assignments..... | 111 |
| 5.4.3.5.2.7 Mini SAS HD external connector management interface..... | 112 |
| 5.4.3.5.2.8 Mini SAS HD external connector memory map..... | 113 |
| 5.4.3.5.3 QSFP+ connectors | 113 |
| 5.4.3.5.3.1 QSFP+ cable plug..... | 113 |
| 5.4.3.5.3.2 QSFP+ receptacle..... | 114 |
| 5.4.3.5.3.3 QSFP+ connector pin assignments | 115 |
| 5.4.3.5.3.4 QSFP+ memory map | 116 |
| 5.4.4 Cable assemblies..... | 117 |
| 5.4.4.1 SAS internal cable assemblies..... | 117 |
| 5.4.4.1.1 SAS Drive cable assemblies..... | 117 |
| 5.4.4.1.2 SAS internal symmetric cable assemblies..... | 119 |
| 5.4.4.1.2.1 SAS internal symmetric cable assemblies overview | 119 |
| 5.4.4.1.2.2 SAS internal symmetric cable assembly - SAS 4i..... | 120 |
| 5.4.4.1.2.3 SAS internal symmetric cable assembly - Mini SAS 4i | 121 |
| 5.4.4.1.2.4 SAS internal symmetric cable assembly - Mini SAS HD 4i..... | 122 |
| 5.4.4.1.2.5 SAS internal symmetric cable assembly - Mini SAS HD 8i..... | 123 |
| 5.4.4.1.2.6 SAS internal symmetric cable assembly - SAS 4i to Mini SAS 4i with vendor-specific sidebands..... | 124 |
| 5.4.4.1.2.7 SAS internal symmetric cable assembly - SAS 4i controller to Mini SAS 4i backplane with SGPIO..... | 125 |
| 5.4.4.1.2.8 SAS internal symmetric cable assembly - Mini SAS 4i controller to SAS 4i backplane with SGPIO..... | 126 |
| 5.4.4.1.2.9 SAS internal symmetric cable assembly - Mini SAS 4i to Mini SAS HD 4i | 127 |
| 5.4.4.1.3 SAS internal fanout cable assemblies | 128 |
| 5.4.4.1.3.1 SAS internal fanout cable assemblies overview | 128 |
| 5.4.4.1.3.2 SAS internal controller-based fanout cable assemblies..... | 129 |
| 5.4.4.1.3.3 SAS internal backplane-based fanout cable assemblies | 132 |
| 5.4.4.2 SAS external cable assemblies..... | 135 |
| 5.4.4.2.1 SAS external cable assemblies overview | 135 |
| 5.4.4.2.2 SAS external cable assembly - Mini SAS 4x..... | 136 |
| 5.4.4.2.3 SAS external cable assembly - Mini SAS HD 4x..... | 139 |

| | |
|-------------------------------------------------------------------------------------------------------------------------------------------------|-----|
| 5.4.4.2.4 SAS external cable assembly - Mini SAS HD 8x | 141 |
| 5.4.4.2.5 SAS external cable assembly - Mini SAS HD 8x to Mini SAS HD 4x | 143 |
| 5.4.4.2.6 SAS external cable assembly - Mini SAS HD 4x to Mini SAS 4x | 145 |
| 5.4.4.2.7 SAS external cable assembly - QSFP+ | 146 |
| 5.4.5 Backplanes | 146 |
| 5.5 TxRx connection characteristics | 147 |
| 5.5.1 TxRx connection characteristics overview | 147 |
| 5.5.2 TxRx connection general characteristics | 148 |
| 5.5.3 Passive TxRx connection S-parameter limits | 149 |
| 5.5.4 Passive TxRx connection characteristics for untrained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s | 151 |
| 5.5.5 Passive TxRx connection characteristics for trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s | 152 |
| 5.5.6 Passive TxRx connection characteristics for trained 12 Gbit/s | 153 |
| 5.5.7 TxRx connection characteristics for active cable assemblies | 157 |
| 5.5.7.1 Active cable assembly electrical characteristics for trained 6 Gbit/s overview | 157 |
| 5.5.7.2 Active cable assembly output electrical characteristics for trained 6 Gbit/s | 157 |
| 5.5.7.3 Active cable assembly S-parameter limits for trained 6 Gbit/s and trained 12 Gbit/s | 158 |
| 5.5.7.4 Active cable assembly electrical characteristics overview for 12 Gbit/s | 159 |
| 5.5.7.5 Active cable assembly electrical characteristics for 12 Gbit/s | 160 |
| 5.6 Test loads | 161 |
| 5.6.1 Test loads overview | 161 |
| 5.6.2 Zero-length test load | 162 |
| 5.6.3 TCTF test load | 163 |
| 5.6.4 Low-loss TCTF test load | 168 |
| 5.6.5 Trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s reference transmitter test load | 169 |
| 5.7 End to end simulation for trained 12 Gbit/s | 173 |
| 5.7.1 End to end simulation for trained 12 Gbit/s overview | 173 |
| 5.7.2 Usage models for end to end simulation for trained 12 Gbit/s | 174 |
| 5.7.3 Reference transmitter equalization for trained 12 Gbit/s | 175 |
| 5.7.4 Crosstalk measurement for end to end simulations and 12 Gbit/s jitter tolerance | 177 |
| 5.8 Transmitter device and receiver device electrical characteristics | 178 |
| 5.8.1 General electrical characteristics | 178 |
| 5.8.2 Transmitter device and receiver device transients | 179 |
| 5.8.3 Eye masks and the JTF | 180 |
| 5.8.3.1 Eye masks overview | 180 |
| 5.8.3.2 JTF | 180 |
| 5.8.3.3 Transmitter device eye mask for untrained 1.5 Gbit/s and 3 Gbit/s | 181 |
| 5.8.3.4 Receiver device eye mask for untrained 1.5 Gbit/s and 3 Gbit/s | 182 |
| 5.8.3.5 Receiver device jitter tolerance eye mask for untrained 1.5 Gbit/s and 3 Gbit/s | 182 |
| 5.8.4 Transmitter device characteristics | 184 |
| 5.8.4.1 Transmitter device characteristics overview | 184 |
| 5.8.4.2 Transmitter device coupling requirements | 184 |
| 5.8.4.3 Transmitter device general electrical characteristics | 184 |
| 5.8.4.4 Transmitter device signal output characteristics for untrained 1.5 Gbit/s and 3 Gbit/s as measured with the zero-length test load | 186 |
| 5.8.4.5 Transmitter device signal output characteristics for untrained 1.5 Gbit/s and 3 Gbit/s as measured with each test load | 187 |
| 5.8.4.6 Transmitter device signal output characteristics for trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s .. | 189 |
| 5.8.4.6.1 Transmitter device signal output characteristics for trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s overview | 189 |
| 5.8.4.6.2 Trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s transmitter device test procedure | 190 |
| 5.8.4.6.3 Trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s Transmitter device S-parameter limits | 191 |
| 5.8.4.6.4 Recommended trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s transmitter device settings for interoperability | 192 |
| 5.8.4.6.5 Trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s reference transmitter device characteristics | 193 |
| 5.8.4.6.6 Trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s Transmitter equalization, VMA, and $V_{P,P}$ measurement | 194 |
| 5.8.4.7 Transmitter device signal output characteristics for trained 12 Gbit/s | 196 |
| 5.8.4.7.1 Transmitter device signal output characteristics for trained 12 Gbit/s overview | 196 |

| | |
|---------------------------------------------------------------------------------------------------------------------------------|-----|
| 5.8.4.7.2 12 Gbit/s Transmitter device S-parameter limits..... | 203 |
| 5.8.4.7.3 12 Gbit/s reference transmitter device..... | 205 |
| 5.8.4.7.4 Transmitter device end to end simulation characteristics for trained 12 Gbit/s | 207 |
| 5.8.4.7.5 Transmitter device signal output characteristics at CTS for 12 Gbit/s when an active cable is connected..... | 208 |
| 5.8.4.8 Transmitter device signal output characteristics for OOB signals | 208 |
| 5.8.5 Receiver device characteristics | 210 |
| 5.8.5.1 Receiver device characteristics overview..... | 210 |
| 5.8.5.2 Receiver device coupling requirements | 210 |
| 5.8.5.3 Receiver device general electrical characteristics..... | 211 |
| 5.8.5.4 Delivered signal characteristics for untrained 1.5 Gbit/s and 3 Gbit/s..... | 213 |
| 5.8.5.5 Maximum delivered jitter for untrained 1.5 Gbit/s and 3 Gbit/s | 214 |
| 5.8.5.6 Receiver device jitter tolerance for untrained 1.5 Gbit/s and 3 Gbit/s | 215 |
| 5.8.5.7 Receiver device and delivered signal characteristics for trained 1.5 Gbit/s, 3 Gbit/s, 6 Gbit/s, and 12 Gbit/s | 216 |
| 5.8.5.7.1 Delivered signal characteristics for trained 1.5 Gbit/s, 3 Gbit/s, 6 Gbit/s, and 12 Gbit/s | 216 |
| 5.8.5.7.2 Receiver device S-parameter limits | 216 |
| 5.8.5.7.3 Reference receiver device characteristics | 218 |
| 5.8.5.7.3.1 Reference receiver device overview | 218 |
| 5.8.5.7.3.2 Reference receiver device DFE | 219 |
| 5.8.5.7.3.3 Reference receiver device equalization for trained 12 Gbit/s..... | 219 |
| 5.8.5.7.4 Reference receiver device termination characteristics for trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s | 220 |
| 5.8.5.7.5 Reference receiver device termination characteristics for trained 12 Gbit/s..... | 220 |
| 5.8.5.7.6 Stressed receiver device jitter tolerance test | 221 |
| 5.8.5.7.6.1 Stressed receiver device jitter tolerance test overview for trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s | 221 |
| 5.8.5.7.6.2 Stressed receiver device jitter tolerance test procedure for trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s | 223 |
| 5.8.5.7.6.3 Test equipment calibration and ISI generator calibration for trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s | 224 |
| 5.8.5.7.6.4 Crosstalk source calibration for trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s..... | 224 |
| 5.8.5.7.6.5 Stressed receiver device jitter tolerance test procedure for trained 12 Gbit/s..... | 225 |
| 5.8.5.7.6.6 ISI generator calibration for trained 12 Gbit/s | 225 |
| 5.8.5.7.6.7 Crosstalk calibration for the trained 12 Gbit/s stressed receiver device jitter tolerance test | 228 |
| 5.8.5.7.6.8 Applied RJ for trained 12 Gbit/s stressed receiver device jitter tolerance test | 228 |
| 5.8.5.7.6.9 Applied SJ..... | 228 |
| 5.8.5.8 Delivered signal characteristics for OOB signals | 230 |
| 5.8.6 Spread spectrum clocking (SSC)..... | 230 |
| 5.8.6.1 SSC overview..... | 230 |
| 5.8.6.2 Transmitter SSC modulation | 231 |
| 5.8.6.3 Receiver SSC modulation tolerance | 232 |
| 5.8.6.4 Expander device center-spreading tolerance buffer..... | 233 |
| 5.8.7 Non-tracking clock architecture..... | 234 |
| 5.9 READY LED signal electrical characteristics..... | 234 |
| 5.10 POWER DISABLE signal electrical characteristics | 235 |
| 5.11 Out of band (OOB) signals | 237 |
| 5.11.1 OOB signals overview..... | 237 |
| 5.11.2 Transmitting OOB signals..... | 238 |
| 5.11.3 Receiving OOB signals..... | 240 |
| 5.11.4 Transmitting the SATA port selection signal..... | 241 |
| Annex A (normative) Jitter tolerance pattern (JTPAT) | 242 |
| Annex B (normative) SASWDP | 244 |
| B.1 SASWDP introduction | 244 |
| B.2 SASWDP.m..... | 244 |

| | |
|---------------------------------------------------------------------------------------------------------------------|-----|
| B.3 SASWDP_testcase.m | 251 |
| Annex C (informative) StatEye | 253 |
| C.1 StatEye introduction | 253 |
| C.2 analysis.py | 253 |
| C.3 cdr.py | 254 |
| C.4 extractJitter.py | 255 |
| C.5 penrose.py | 257 |
| C.6 portalocker.py | 259 |
| C.7 stateye.py | 262 |
| C.8 touchstone.py | 277 |
| C.9 testcase.py | 285 |
| C.10 testall.py | 290 |
| C.11 File StatEye_readme.pdf | 293 |
| C.11.1 How to install and run the SAS-2.1 StatEye | 293 |
| Annex D (normative) End to end simulation for trained 12 Gbit/s | 294 |
| D.1 Detailed end to end simulation procedure description for trained 12 Gbit/s | 294 |
| D.2 Trained 12 Gbit/s usage models, S-parameter files, and crosstalk amplitude | 296 |
| D.2.1 Transmitter device connected to a separable passive TxRx connection segment | 296 |
| D.2.2 Transmitter device connected to a non-separable passive TxRx connection segment | 298 |
| D.2.3 TxRx connection segment | 301 |
| D.2.4 Stressed Receiver device delivered signal calibration end to end simulation diagram | 302 |
| Annex E (informative) 12 Gbit/s S-parameters and end to end simulation | 304 |
| E.1 S-parameters for 12 Gbit/s simulation | 304 |
| E.1.1 Measurement procedure | 304 |
| E.1.2 Multiple channel segments | 305 |
| E.2 End to end simulation using SAS3_EYEOPENING | 306 |
| Annex F (informative) Signal performance measurements | 307 |
| F.1 Signal performance measurements overview | 307 |
| F.2 Glossary | 307 |
| F.3 Simple physical link | 307 |
| F.3.1 Simple physical link overview | 307 |
| F.3.2 Assumptions for the structure of the transmitter device and the receiver device | 308 |
| F.3.3 Definition of receiver sensitivity and receiver device sensitivity | 309 |
| F.4 Signal measurement architecture | 310 |
| F.4.1 General | 310 |
| F.4.2 Relationship between signal compliance measurements at interoperability points and operation in systems | 310 |
| F.5 De-embedding connectors in test fixtures | 311 |
| F.6 De-embedding test fixture for 12 Gbit/s transmitter compliance | 311 |
| F.7 Measurement conditions for signal output at the transmitter device | 312 |
| F.8 Measurement conditions for signal tolerance at the transmitter device | 313 |
| F.9 Measurement conditions for signal output at the receiver device | 315 |
| F.10 Measurement conditions for signal tolerance at the receiver device | 315 |
| F.11 S-parameter measurements | 316 |
| F.11.1 S-parameter overview | 316 |
| F.11.2 S-parameter naming conventions | 316 |
| F.11.3 Use of single ended instrumentation in differential applications | 317 |
| F.11.4 Measurement configurations for physical link elements | 319 |
| F.11.4.1 Measurement configuration overview | 319 |
| F.11.4.2 Transmitter device S_{22} measurements | 319 |
| F.11.4.3 Receiver device S_{11} measurements | 320 |
| F.11.4.4 TxRx connection S_{11} measurements at IT or CT | 320 |
| F.11.4.5 TxRx connection S_{22} measurements at IR or CR | 321 |
| F.12 Calibration of JMDs | 322 |

| | |
|---------------------------------------------------------------------------------------------------------------------------------|---------|
| F.12.1 Calibration of JMDs overview | 322 |
| F.12.1.1 Purpose of JMD calibration | 322 |
| F.12.1.2 Overview of low frequency calibration for SSC configurations | 322 |
| F.12.1.3 Overview of low frequency calibration for non-SSC configurations | 324 |
| F.12.1.4 High frequency calibration | 324 |
| F.12.2 JMD calibration procedure | 325 |
| F.12.2.1 General characteristics and equipment | 325 |
| F.12.2.2 Calibration of the JMD for testing SSC configurations | 326 |
| F.12.2.3 Calibration of the JMD for testing non-SSC configurations | 327 |
| Annex G (informative) Description of the included Touchstone models for trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s | 329 |
| G.1 Description of included Touchstone models for trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s overview ... | 329 |
| G.2 Reference transmitter device termination model for trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s | 329 |
| G.3 Reference receiver device termination model for trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s | 330 |
| G.4 Generic return loss circuit model for trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s | 331 |
| G.5 Reference transmitter test load for trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s | 332 |
| Annex H (informative) Mini SAS 4x active cable assembly power supply and voltage detection circuitry | 335 |
| Annex I (informative) SAS icons | 336 |
| Annex J (informative) Standards bodies contact information | 338 |
| Bibliography | 339 |

| | |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----|
| Figure 1 – SCSI document relationships | 16 |
| Figure 2 – ATA document relationships | 17 |
| Figure 3 – Physical links and phys | 42 |
| Figure 4 – Maximum limits for S-parameters definitions | 44 |
| Figure 5 – 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s External cable assembly CT compliance points and CR compliance points | 46 |
| Figure 6 – Backplane with SAS Drive connector 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s IT compliance points and IR compliance points | 47 |
| Figure 7 – Backplane with SAS Drive connector 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s compliance points with SATA phy attached | 48 |
| Figure 8 – SAS multilane internal cable assembly 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s IT compliance points and IR compliance points | 49 |
| Figure 9 – SAS multilane internal cable assembly and backplane 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s IT compliance points and IR compliance points | 50 |
| Figure 10 – SAS multilane internal cable assembly and backplane 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s IT compliance points and IR compliance points with SATA device attached | 51 |
| Figure 11 – SAS Drive cable assembly 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s IT compliance points and IR compliance points | 52 |
| Figure 12 – 12 Gbit/s TxRx connection and compliance points | 53 |
| Figure 13 – Simulated 12 Gbit/s TxRx connection and compliance points | 53 |
| Figure 14 – 12 Gbit/s CTS and CR compliance points | 54 |
| Figure 15 – SATA connectors and cables | 55 |
| Figure 16 – SAS Drive cable environments | 56 |
| Figure 17 – SAS Drive backplane environment | 57 |
| Figure 18 – SAS external cable environment | 57 |
| Figure 19 – SAS internal symmetric cable environment - controller to backplane | 58 |
| Figure 20 – SAS internal symmetric cable environment - controller to controller | 58 |
| Figure 21 – SAS internal controller-based fanout cable environment | 59 |
| Figure 22 – SAS internal backplane-based fanout cable environment | 59 |
| Figure 23 – Recommended $ S_{DD21} $, $ S_{CC22} $, $ S_{DD22} $, NEXT, and FEXT limits for connector mated pairs supporting rates of 12 Gbit/s | 64 |
| Figure 24 – SAS Drive plug connector | 65 |
| Figure 25 – Single-port SAS Drive cable receptacle connector | 65 |
| Figure 26 – Dual-port SAS Drive cable receptacle connector | 66 |
| Figure 27 – SAS Drive backplane receptacle connector | 66 |
| Figure 28 – SAS MultiLink Drive plug connector | 69 |
| Figure 29 – SAS MultiLink Drive cable receptacle connector | 69 |
| Figure 30 – SAS MultiLink Drive backplane receptacle connector | 70 |
| Figure 31 – Micro SAS plug connector | 74 |
| Figure 32 – Micro SAS receptacle connector | 74 |
| Figure 33 – SAS 4i cable receptacle connector | 76 |
| Figure 34 – SAS 4i plug connector | 76 |
| Figure 35 – Mini SAS 4i cable plug connector | 79 |
| Figure 36 – Mini SAS 4i receptacle connector | 79 |
| Figure 37 – Mini SAS HD 4i cable plug connector | 82 |
| Figure 38 – Mini SAS HD 8i cable plug connector | 83 |
| Figure 39 – Mini SAS HD 4i receptacle connector | 84 |
| Figure 40 – Mini SAS HD 8i receptacle connector | 85 |
| Figure 41 – Mini SAS HD 16i receptacle connector | 86 |
| Figure 42 – Mini SAS 4x cable plug connector | 90 |
| Figure 43 – Mini SAS 4x cable plug connector for untrained 1.5 Gbit/s and 3 Gbit/s that attaches to an enclosure out port or an enclosure in port | 92 |
| Figure 44 – Mini SAS 4x cable plug connector for untrained 1.5 Gbit/s and 3 Gbit/s that attaches to an enclosure out port | 92 |
| Figure 45 – Mini SAS 4x cable plug connector for untrained 1.5 Gbit/s and 3 Gbit/s that attaches to an enclosure in port | 93 |
| Figure 46 – Mini SAS 4x cable plug connector for trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s that attaches to an enclosure out port or an enclosure in port | 93 |

| | |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|
| Figure 47 – Mini SAS 4x cable plug connector for trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s that attaches to an enclosure out port | 94 |
| Figure 48 – Mini SAS 4x cable plug connector for trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s that attaches to an enclosure in port | 94 |
| Figure 49 – Mini SAS 4x active cable plug connector for trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s that attaches to an enclosure out port or an enclosure in port | 95 |
| Figure 50 – Mini SAS 4x active cable plug connector for trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s that attaches to an enclosure out port | 95 |
| Figure 51 – Mini SAS 4x active cable plug connector for trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s that attaches to an enclosure in port | 96 |
| Figure 52 – Mini SAS 4x receptacle connector | 97 |
| Figure 53 – Mini SAS 4x receptacle connector - end device or enclosure universal port for untrained 1.5 Gbit/s and 3 Gbit/s | 98 |
| Figure 54 – Mini SAS 4x receptacle connector - enclosure out port for untrained 1.5 Gbit/s and 3 Gbit/s | 99 |
| Figure 55 – Mini SAS 4x receptacle connector - enclosure in port for untrained 1.5 Gbit/s and 3 Gbit/s | 99 |
| Figure 56 – Mini SAS 4x receptacle connector - end device or enclosure universal port for trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s and for untrained 1.5 Gbit/s and 3 Gbit/s | 100 |
| Figure 57 – Mini SAS 4x receptacle connector - enclosure out port for trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s and for untrained 1.5 Gbit/s and 3 Gbit/s | 100 |
| Figure 58 – Mini SAS 4x receptacle connector - enclosure in port for trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s and for untrained 1.5 Gbit/s and 3 Gbit/s | 101 |
| Figure 59 – Mini SAS 4x active receptacle connector - end device or enclosure universal port | 101 |
| Figure 60 – Mini SAS 4x active receptacle connector - enclosure out port | 102 |
| Figure 61 – Mini SAS 4x active receptacle connector - enclosure in port | 102 |
| Figure 62 – Mini SAS HD 4x cable plug connector | 106 |
| Figure 63 – Mini SAS HD 8x cable plug connector | 107 |
| Figure 64 – Mini SAS HD 4x receptacle connector | 108 |
| Figure 65 – Mini SAS HD 8x receptacle connector | 109 |
| Figure 66 – Mini SAS HD 16x receptacle connector | 110 |
| Figure 67 – QSFP+ cable plug connector | 113 |
| Figure 68 – QSFP+ receptacle connector | 114 |
| Figure 69 – Single-port SAS Drive cable assembly | 117 |
| Figure 70 – Dual-port SAS Drive cable assembly | 118 |
| Figure 71 – MultiLink SAS Drive cable assembly | 119 |
| Figure 72 – SAS internal symmetric cable assembly - SAS 4i | 120 |
| Figure 73 – SAS internal symmetric cable assembly - Mini SAS 4i | 121 |
| Figure 74 – SAS internal symmetric cable assembly - Mini SAS HD 4i | 122 |
| Figure 75 – SAS internal symmetric cable assembly - Mini SAS HD 8i | 123 |
| Figure 76 – SAS internal symmetric cable assembly - SAS 4i to Mini SAS 4i with vendor-specific sideband signals | 124 |
| Figure 77 – SAS internal symmetric cable assembly - SAS 4i controller to Mini SAS 4i backplane with SGPIO connections | 125 |
| Figure 78 – SAS internal symmetric cable assembly - Mini SAS 4i controller to SAS 4i backplane with SGPIO connections | 126 |
| Figure 79 – SAS internal symmetric cable assembly - Mini SAS 4i to Mini SAS HD 4i | 127 |
| Figure 80 – SAS internal controller-based fanout cable assembly - SAS 4i | 129 |
| Figure 81 – SAS internal controller-based fanout cable assembly - Mini SAS 4i | 130 |
| Figure 82 – SAS internal controller-based fanout cable assembly - Mini SAS HD 4i | 131 |
| Figure 83 – SAS internal backplane-based fanout cable assembly - SAS 4i | 132 |
| Figure 84 – SAS internal backplane-based fanout cable assembly - Mini SAS 4i | 133 |
| Figure 85 – SAS internal backplane-based fanout cable assembly - Mini SAS HD 4i | 134 |
| Figure 86 – Mini SAS 4x external cable assembly | 136 |
| Figure 87 – Mini SAS 4x active external cable assembly | 137 |
| Figure 88 – SAS external cable assembly with Mini SAS 4x cable plug connectors | 138 |
| Figure 89 – SAS external cable assembly - Mini SAS HD 4x | 139 |
| Figure 90 – SAS external cable assembly with Mini SAS HD 4x cable plug connectors | 140 |
| Figure 91 – SAS external cable assembly - Mini SAS HD 8x | 141 |
| Figure 92 – SAS external cable assembly with Mini SAS HD 8x cable plug connectors | 142 |

| | |
|-----------------------------------------------------------------------------------------------------------------------------------------|-----|
| Figure 93 – SAS external cable assembly - Mini SAS HD 8x to Mini SAS HD 4x | 143 |
| Figure 94 – SAS external cable assembly with a Mini SAS HD 8x cable plug connector and two Mini SAS HD 4x cable plug connectors | 144 |
| Figure 95 – SAS external cable assembly - Mini SAS HD 4x to Mini SAS 4x | 145 |
| Figure 96 – SAS external cable assembly with a Mini SAS HD 4x cable plug connector and a Mini SAS 4x cable plug connector | 146 |
| Figure 97 – Passive TxRx connection $ S_{DD22} $, $ S_{CD22} $, $ S_{CD21} $, and NEXT limits | 151 |
| Figure 98 – Example of a passive TxRx connection compliance testing for trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s | 152 |
| Figure 99 – Example passive TxRx connection compliance testing for trained 12 Gbit/s | 154 |
| Figure 100 – Passive TxRx connection segment between CTS and CR or ITS and IR end to end simulation diagram for trained 12 Gbit/s | 155 |
| Figure 101 – Active cable S-parameter limits | 159 |
| Figure 102 – Active cable eye mask for 12 Gbit/s | 160 |
| Figure 103 – Zero-length test load for transmitter device compliance point | 162 |
| Figure 104 – Zero-length test load for receiver device compliance point | 162 |
| Figure 105 – Zero-length test load $ S_{DD21}(f) $ requirements | 163 |
| Figure 106 – TCTF test load | 163 |
| Figure 107 – TCTF test load $ S_{DD21}(f) $ and ISI loss requirements at IT for untrained 3 Gbit/s | 164 |
| Figure 108 – TCTF test load $ S_{DD21}(f) $ and ISI loss requirements at CT for untrained 3 Gbit/s | 165 |
| Figure 109 – TCTF test load $ S_{DD21}(f) $ and ISI loss requirements at IT for untrained 1.5 Gbit/s | 166 |
| Figure 110 – TCTF test load $ S_{DD21}(f) $ and ISI loss requirements at CT for untrained 1.5 Gbit/s | 167 |
| Figure 111 – Low-loss TCTF test load | 168 |
| Figure 112 – Low-loss TCTF test load $ S_{DD21}(f) $ and ISI loss requirements | 169 |
| Figure 113 – Trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s reference transmitter with a test load $ S_{DD21}(f) $ up to 6 GHz | 170 |
| Figure 114 – Trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s reference transmitter test load pulse response | 171 |
| Figure 115 – Trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s reference transmitter test load impulse response for 6 Gbit/s | 172 |
| Figure 116 – Trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s reference transmitter test load D24.3 response | 173 |
| Figure 117 – NEXT and FEXT measurement definition | 174 |
| Figure 118 – Reference sampling point and reference pulse response cursor | 175 |
| Figure 119 – Reference transmitter coefficient error computation | 176 |
| Figure 120 – Convergence of reference transmitter equalization | 177 |
| Figure 121 – Transmitter device transient test circuit | 179 |
| Figure 122 – Receiver device transient test circuit | 179 |
| Figure 123 – Transmitter device eye mask | 181 |
| Figure 124 – Receiver device eye mask | 182 |
| Figure 125 – Deriving a receiver device jitter tolerance eye mask for untrained 1.5 Gbit/s and 3 Gbit/s | 183 |
| Figure 126 – Transmitter device common mode voltage limit | 190 |
| Figure 127 – Transmitter device $ S_{CC22} $, $ S_{DD22} $, and $ S_{CD22} $ limits | 192 |
| Figure 128 – Trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s reference transmitter device | 193 |
| Figure 129 – Trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s reference transmitter device termination S-parameters model | 194 |
| Figure 130 – Transmitter equalization measurement | 195 |
| Figure 131 – Minimum and maximum coefficient ranges at maximum peak to peak voltage | 198 |
| Figure 132 – 12 Gbit/s transmitter device common mode voltage limit | 199 |
| Figure 133 – Transmitter circuit compliance test configuration | 201 |
| Figure 134 – 12 Gbit/s transmitter circuit output waveform | 202 |
| Figure 135 – 12 Gbit/s transmitter device $ S_{CC22} $, $ S_{DD22} $, and $ S_{CD22} $ limits | 204 |
| Figure 136 – 12 Gbit/s reference transmitter device | 205 |
| Figure 137 – 12 Gbit/s reference transmitter | 205 |
| Figure 138 – Simulation of the reference transmitter from a captured signal | 208 |
| Figure 139 – Applied SJ for untrained 1.5 Gbit/s and 3 Gbit/s | 215 |
| Figure 140 – Receiver device $ S_{CC11} $, $ S_{DD11} $, and $ S_{CD11} $ limits | 217 |
| Figure 141 – Reference receiver device for trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s | 218 |
| Figure 142 – Reference receiver device for trained 12 Gbit/s | 218 |

| | |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|
| Figure 143 – Reference receiver device termination S-parameters for trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s | 220 |
| Figure 144 – Stressed receiver device jitter tolerance test block diagram for trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s | 221 |
| Figure 145 – Stressed receiver device jitter tolerance test D24.3 eye opening for trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s | 223 |
| Figure 146 – Stressed receiver transmitter equalization adjustment for 12 Gbit/s | 225 |
| Figure 147 – Simulation of the reference transmitter from a captured signal | 226 |
| Figure 148 – Applied SJ for trained 1.5 Gbit/s, 3 Gbit/s, 6 Gbit/s, and 12 Gbit/s without SSC support | 228 |
| Figure 149 – Applied SJ for trained 1.5 Gbit/s, 3 Gbit/s, 6 Gbit/s and 12 Gbit/s with SSC support | 229 |
| Figure 150 – Center-spreading tolerance buffer | 234 |
| Figure 151 – OOB signal transmission | 239 |
| Figure 152 – SATA port selection signal | 241 |
| Figure C.1 – Reference channel eye opening | 293 |
| Figure D.1 – Trained 12 Gbit/s die to die insertion loss model | 294 |
| Figure D.2 – Transmitter device end to end simulation diagram that includes a separable TxRx connection segment | 297 |
| Figure D.3 – End to end simulation diagram from target device usage model for a transmitter device connected to a non-separable TxRx connection segment | 299 |
| Figure D.4 – End to end simulation diagram of the target device usage model for a transmitter device connected to a non-separable TxRx connection segment | 300 |
| Figure D.5 – Stressed receiver device delivered signal calibration end to end simulation diagram | 302 |
| Figure E.1 – S-parameter measurement connections for a four port VNA | 304 |
| Figure E.2 – Example of a SAS three TxRx connection segment | 305 |
| Figure F.1 – A simple physical link | 307 |
| Figure F.2 – Transmitter device details | 308 |
| Figure F.3 – Receiver device details | 309 |
| Figure F.4 – De-embedding of connectors in test fixtures | 311 |
| Figure F.5 – De-embedding to ET for 12 Gbit/s transmitter compliance | 312 |
| Figure F.6 – De-embedding calibration test structure | 312 |
| Figure F.7 – Measurement conditions for signal output at the transmitter device | 313 |
| Figure F.8 – Transmitter device signal output measurement test fixture details | 313 |
| Figure F.9 – Measurement conditions for signal tolerance at the transmitter device | 314 |
| Figure F.10 – Calibration of test fixture for signal tolerance at the transmitter device | 314 |
| Figure F.11 – Measurement conditions for signal output at the receiver device | 315 |
| Figure F.12 – Measurement conditions for signal tolerance at the receiver device | 315 |
| Figure F.13 – Calibration of test fixture for signal tolerance at the receiver device | 316 |
| Figure F.14 – S-parameter port naming conventions | 317 |
| Figure F.15 – Four single ended port or two differential port element | 318 |
| Figure F.16 – S-parameters for single ended and differential systems | 318 |
| Figure F.17 – Measurement conditions for S_{22} at the transmitter device connector | 319 |
| Figure F.18 – Measurement conditions for S_{11} at the receiver device connector | 320 |
| Figure F.19 – Measurement conditions for S_{11} at IT or CT | 321 |
| Figure F.20 – Measurement conditions for S_{22} at IR or CR | 322 |
| Figure G.1 – Reference transmitter device and reference receiver device termination circuit model | 329 |
| Figure G.2 – Generic return loss circuit model | 331 |
| Figure G.3 – Generic return loss model $ S_{11} $ | 332 |
| Figure G.4 – Reference transmitter test load measurement setup | 333 |
| Figure G.5 – Reference transmitter test load $ S_{DD21}(f) $ up to 20 GHz | 334 |
| Figure H.1 – Dual comparator design for active cable assembly detection | 335 |
| Figure I.1 – SAS primary icon | 336 |
| Figure I.2 – SAS alternate icon | 336 |
| Figure I.3 – MultiLink SAS icon | 337 |

| | |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|
| Table 1 – Numbering conventions | 40 |
| Table 2 – Comparison of decimal prefixes and binary prefixes | 41 |
| Table 3 – Compliance points..... | 45 |
| Table 4 – Connectors..... | 60 |
| Table 5 – Connector categories..... | 62 |
| Table 6 – Recommended electrical performance limits for the mated connector pairs that support rates of 12 Gbit/s..... | 63 |
| Table 7 – SAS Drive connector pin assignments..... | 67 |
| Table 8 – SAS MultiLink connector pin assignments..... | 71 |
| Table 9 – Micro SAS connector pin assignments | 75 |
| Table 10 – Controller SAS 4i connector pin assignments and physical link usage..... | 77 |
| Table 11 – Backplane SAS 4i connector pin assignments and physical link usage | 78 |
| Table 12 – Controller Mini SAS 4i connector pin assignments and physical link usage | 80 |
| Table 13 – Backplane Mini SAS 4i connector pin assignments and physical link usage..... | 81 |
| Table 14 – Controller Mini SAS HD 4i connector pin assignments and physical link usage..... | 87 |
| Table 15 – Backplane Mini SAS HD 4i connector pin assignments and physical link usage..... | 88 |
| Table 16 – Mini SAS 4x cable plug connector and Mini SAS 4x active cable plug connector icons, key slot positions, and key positions | 91 |
| Table 17 – Mini SAS 4x receptacle connector icons, key positions, and key slot positions..... | 98 |
| Table 18 – Mini SAS 4x connector pin assignments and physical link usage..... | 103 |
| Table 19 – Mini SAS 4x active connector pin assignments and physical link usage | 104 |
| Table 20 – Mini SAS 4x active cable supplied power requirements | 105 |
| Table 21 – Mini SAS HD 4x connector pin assignments and physical link usage | 111 |
| Table 22 – Management interface connection requirements | 112 |
| Table 23 – QSFP+ connector pin assignments | 115 |
| Table 24 – TxRx connection general characteristics | 148 |
| Table 25 – Maximum limits for S-parameters of the passive TxRx connection between ITS and IR or CTS and CR..... | 150 |
| Table 26 – Passive TxRx connection characteristics for trained 6 Gbit/s | 152 |
| Table 27 – Passive TxRx connection characteristics for trained 12 Gbit/s at ET and ER..... | 156 |
| Table 28 – Active cable assembly output electrical characteristics for trained 6 Gbit/s..... | 157 |
| Table 29 – Maximum limits for S-parameters for active cable assemblies | 158 |
| Table 30 – Active cable assembly electrical characteristics for 12 Gbit/s..... | 160 |
| Table 31 – General electrical characteristics | 178 |
| Table 32 – JTF parameters..... | 181 |
| Table 33 – Transmitter device general electrical characteristics | 184 |
| Table 34 – Transmitter device termination characteristics..... | 185 |
| Table 35 – Transmitter device signal output characteristics for untrained 1.5 Gbit/s and 3 Gbit/s as measured with the zero-length test load at IT and CT | 186 |
| Table 36 – Transmitter device signal output characteristics for untrained 1.5 Gbit/s and 3 Gbit/s as measured with each test load at IT and CT | 188 |
| Table 37 – Transmitter device signal output characteristics for trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s at IT and CT..... | 189 |
| Table 38 – Transmitter device common mode voltage limit characteristics..... | 190 |
| Table 39 – Maximum limits for S-parameters at IT _S or CT _S | 191 |
| Table 40 – Recommended trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s transmitter device settings at IT and CT compliance point | 192 |
| Table 41 – Trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s reference transmitter device characteristics at IT and CT compliance point | 193 |
| Table 42 – Transmitter device signal output characteristics for trained 12 Gbit/s at ET, IT, and CT | 196 |
| Table 43 – 12 Gbit/s transmitter device common mode voltage limit characteristics..... | 199 |
| Table 44 – Transmitter coefficient requests and corresponding transmitter circuit response | 200 |
| Table 45 – Transmitter circuit coefficient presets at ET..... | 203 |
| Table 46 – 12 Gbit/s maximum limits for S-parameters at IT _S or CT _S | 204 |
| Table 47 – 12 Gbit/s reference transmitter device characteristics at ET..... | 206 |
| Table 48 – Transmitter device characteristics for trained 12 Gbit/s at ET and ER | 207 |
| Table 49 – Transmitter device signal output characteristics for 12 Gbit/s at CTS when an active cable is connected..... | 208 |

| | |
|------------------------------------------------------------------------------------------------------------------------------------------------|-----|
| Table 50 – Transmitter device signal output characteristics for OOB signals | 209 |
| Table 51 – Receiver device general electrical characteristics | 211 |
| Table 52 – Recommended receiver device common mode tolerance for 6 Gbit/s, and 12 Gbit/s | 211 |
| Table 53 – Receiver device termination characteristics | 212 |
| Table 54 – Delivered signal characteristics for untrained 1.5 Gbit/s and 3 Gbit/s as measured with the zero-length test load at IR and CR..... | 213 |
| Table 55 – Maximum delivered jitter for untrained 1.5 Gbit/s and 3 Gbit/s at IR and CR | 214 |
| Table 56 – Receiver device jitter tolerance for untrained 1.5 Gbit/s and 3 Gbit/s at IR and CR | 215 |
| Table 57 – f_{\min} , f_c , and f_{\max} for untrained 1.5 Gbit/s and 3 Gbit/s..... | 216 |
| Table 58 – Delivered signal characteristics for trained 1.5 Gbit/s, 3 Gbit/s, 6 Gbit/s, and 12 Gbit/s at IR and CR compliance point..... | 216 |
| Table 59 – Maximum limits for S-parameters at IR or CR | 217 |
| Table 60 – Reference receiver equalization stage characteristics for trained 12 Gbit/s | 219 |
| Table 61 – Stressed receiver device jitter tolerance test characteristics for trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s..... | 222 |
| Table 62 – Number of bits received per number of errors for desired BER..... | 224 |
| Table 63 – ISI generator characteristics for trained 12 Gbit/s at ET and ER | 227 |
| Table 64 – RJ characteristics for trained 12 Gbit/s stressed receiver device tolerance test..... | 228 |
| Table 65 – f_{\min} , f_c , and f_{\max} for trained 1.5 Gbit/s, 3 Gbit/s, 6 Gbit/s, and 12 Gbit/s without SSC support ... | 229 |
| Table 66 – f_{\min} , f_c , f_{\max} , and SJ_{lf} for trained 1.5 Gbit/s, 3 Gbit/s, 6 Gbit/s, and 12 Gbit/s with SSC support..... | 229 |
| Table 67 – Delivered signal characteristics for OOB signals | 230 |
| Table 68 – SSC modulation types..... | 230 |
| Table 69 – SAS phy transmitter SSC modulation types..... | 231 |
| Table 70 – Expander phy transmitter SSC modulation types | 232 |
| Table 71 – Receiver SSC modulation types tolerance..... | 232 |
| Table 72 – Expander device center-spreading tolerance buffer | 233 |
| Table 73 – Output characteristics of the READY LED signal..... | 235 |
| Table 74 – Characteristics of the POWER DISABLE signal applied to the SAS target device..... | 236 |
| Table 75 – OOB signal timing specifications..... | 237 |
| Table 76 – OOB signal transmitter device requirements | 238 |
| Table 77 – OOB signal receiver device burst time detection requirements | 240 |
| Table 78 – OOB signal receiver device idle time detection requirements..... | 240 |
| Table 79 – OOB signal receiver device negation time detection requirements | 240 |
| Table 80 – SATA port selection signal transmitter device requirements..... | 241 |
| Table A.1 – JTPAT for RD+ | 242 |
| Table A.2 – JTPAT for RD- | 243 |
| Table D.1 – Crosstalk transmitter characteristics..... | 295 |
| Table D.2 – S-parameter files for transmitter devices connected to separable TxRx connection segment.. | 296 |
| Table D.3 – The S-parameter files for a transmitter device connected to a non-separable TxRx connection segment..... | 298 |
| Table D.4 – S-parameter files for a TxRx connection segment | 301 |
| Table D.5 – S-parameter files for stressed receiver device delivered signal calibration..... | 303 |
| Table F.1 – High frequency jitter source amplitudes..... | 325 |
| Table F.2 – Low frequency jitter source calibration amplitudes | 327 |
| Table F.3 – Low frequency jitter attenuation targets | 328 |
| Table J.1 – Standards bodies | 338 |