

# ISO/IEC 14763-4:2018-02 (E)

## Information technology - Implementation and operation of customer premises cabling - Part 4: Measurement of end-to-end (E2E)-Links

---

### CONTENTS

- FOREWORD..... 3
- INTRODUCTION..... 4
- 1 Scope..... 5
- 2 Normative references ..... 5
- 3 Terms, definitions and abbreviated terms ..... 6
  - 3.1 Terms and definitions..... 6
  - 3.2 Abbreviated terms..... 6
- 4 Conformance..... 6
- 5 Configuration and limits of performance of E2E link..... 6
- 6 Test configuration of E2E link ..... 7
- 7 E2E link testing ..... 7
- 8 Laboratory testing of E2E link..... 7
- 9 Field testing of E2E link..... 8
  - 9.1 Visual inspection..... 8
  - 9.2 Requirements of field test equipment ..... 8
  - 9.3 Field test measurement parameters ..... 8
- 10 Test head requirements ..... 8
  - 10.1 General..... 8
  - 10.2 Test head requirements according to the IEC 60603-7 series..... 8
  - 10.3 Test head requirements of IEC 61076-2-101 ..... 9
  - 10.4 Test head requirements of IEC 61076-2-109 ..... 9
- Annex A (normative) Additional requirements for test head designs ..... 10
  - A.1 General..... 10
  - A.2 Outline of additional NEXT requirements..... 10
  - A.3 Additional test head requirements ..... 10
    - A.3.1 Category 5 test head requirements ..... 10
    - A.3.2 Category 6 test head requirements ..... 11
- Bibliography..... 12
  
- Figure 1 – Reference planes and configuration of E2E link ..... 7
  
- Table A.1 – Category 5 E2E link test head de-embedded NEXT performance in the range of frequency of  $50 \text{ MHz} \leq f < 100 \text{ MHz}$  ..... 11
- Table A.2 – Category 6 E2E link test head de-embedded NEXT performance in the range of frequency of  $50 \text{ MHz} \leq f < 250 \text{ MHz}$  ..... 11