ISO 4037-3:2019 (E)

Radiological protection — X and gamma reference radiation for calibrating dosemeters and doserate meters and for determining their response as a function of photon energy — Part 3: Calibration of area and personal dosemeters and the measurement of their response as a function of energy and angle of incidence

Contents

Foreword

Introduction

1 Scope

2 Normative references

3 Terms and definitions

4 Procedures applicable to all area and personal dosemeters

4.1 General principles
4.1.1 Radiation qualities
4.1.2 Recommended conversion coefficients
4.1.3 Point of test and reference point
4.1.4 Axes of rotation
4.1.5 Condition of the dosemeter to be calibrated
4.1.6 Effects associated with electron ranges
4.2 Methods for the determination of the calibration factor and of the response
4.2.1 Operation of the standard instrument
4.2.2 Measurements without a monitor for the source output

5 Particular procedures for area dosemeters

5.1 General principles
5.2 Quantities to be measured

6 Conversion coefficients for area dosimetry

6.1 Conversion coefficients from air kerma, Ka, to H'(0,07)
6.1.1 Mono-energetic radiation
6.1.2 Low air kerma rate series
6.1.3 Narrow series
6.1.4 Wide series
6.1.5 High air kerma rate series
6.1.6 Radionuclides
6.2 Conversion coefficients from air kerma, Ka, to H'(3)
6.2.1 Mono-energetic radiation
6.2.2 Low air kerma rate series
6.2.3 Narrow series
6.2.4 Wide series
6.2.5 High air kerma rate series
6.2.6 Radionuclides
6.2.7 High energy photon radiations
6.3 Conversion coefficient from air kerma, Ka, to H*(10)
6.3.1 Mono-energetic radiation
6.3.2 Low air kerma rate series
6.3.3 Narrow series
6.3.4 Wide series
6.3.5 High air kerma rate series
6.3.6 Radionuclides

6.3.7 High energy photon radiations

7 Particular procedures for personal dosemeters

7.1 General principles
7.2 Quantities to be measured
7.3 Experimental conditions
7.3.1 Use of phantoms
7.3.2 Geometrical considerations in divergent beams
7.3.3 Simultaneous irradiation of several dosemeters
7.3.4 Influence of the orientation on the values of Hp(0,07)
7.3.5 Length of the rod phantom

8 Conversion coefficients for personal dosimetry

8.1 General
8.2 Conversion coefficients from air kerma, Ka, to Hp(0,07) in the rod phantom
8.2.1 Mono-energetic radiations
8.2.2 Low air kerma rate series
8.2.3 Narrow series
8.2.4 Wide series
8.2.5 High air kerma rate series
8.2.6 Radionuclides
8.3 Conversion coefficients from air kerma, Ka, to Hp(0,07) in the pillar phantom
8.3.1 Mono-energetic radiations
8.3.2 Low air kerma rate series
8.3.3 Narrow series
8.3.4 Wide series
8.3.5 High air kerma rate series
8.3.6 Radionuclides
8.4 Conversion coefficients from air kerma, Ka, to Hp(0,07) in the ICRU slab phantom
8.4.1 Mono-energetic radiations
8.4.2 Low air kerma rate series
8.4.3 Narrow series
8.4.4 Wide series
8.4.5 High air kerma rate series
8.4.6 Radionuclides
8.5 Conversion coefficients from air kerma, Ka, to Hp(3) in the cylinder phantom
8.5.1 Mono-energetic radiations
8.5.2 Low air kerma rate series
8.5.3 Narrow series
8.5.4 Wide series
8.5.5 High air kerma rate series
8.5.6 Radionuclides
8.5.7 High energy photon radiations
8.6 Conversion coefficients from air kerma, Ka, to Hp(10) in the ICRU slab phantom
8.6.1 Mono-energetic radiations
8.6.2 Low air kerma rate series
8.6.3 Narrow series
8.6.4 Wide series
8.6.5 High air kerma rate series
8.6.6 Radionuclides
8.6.7 High energy photon radiations

9 Uncertainties

9.1 Statement of uncertainties

Annex A (informative) Estimated conversion coefficients for fluorescence X radiation

A.1 Principle
A.2 General
A.3 Estimated conversion coefficients for area dosimetry
A.3.1 Estimated conversion coefficients from air kerma, Ka, to H'(0,07)
A.3.2 Estimated conversion coefficient from air kerma, Ka, to H*(10)
A.4 Estimated conversion coefficients for personal dosimetry
A.4.1 Estimated conversion coefficients from air kerma, Ka, to Hp(0,07) in the rod phantom
A.4.2 Estimated conversion coefficients from air kerma, Ka, to Hp(0,07) in the pillar phantom

A.4.3 Estimated conversion coefficients from air kerma, Ka, to Hp(0,07) in the ICRU slab phantom
A.4.4 Estimated conversion coefficients from air kerma, Ka, to Hp(10) in the ICRU slab phantom

Annex B (informative) Estimated conversion coefficients for gamma radiation emitted by 241Am radionuclide

B.1 General
B.2 Estimated conversion coefficients for area dosimetry
B.2.1 Estimated conversion coefficients from air kerma, Ka, to H'(0,07)
B.2.2 Estimated conversion coefficients from air kerma, Ka, to H*(10)
B.3 Estimated conversion coefficients for personal dosimetry
B.3.1 Estimated conversion coefficients from air kerma, Ka, to Hp(0,07) in the rod phantom
B.3.2 Estimated conversion coefficients from air kerma, Ka, to Hp(0,07) in the pillar phantom
B.3.3 Estimated conversion coefficients from air kerma, Ka, to Hp(0,07) in the ICRU slab phantom
B.3.4 Estimated conversion coefficients from air kerma, Ka, to Hp(10) in the ICRU slab phantom

Annex C (informative) Estimated conversion coefficients for continuous filtered X radiation based on the quality index

Annex D (informative) Additional information

D.1 Statement of reference conditions and required standard test conditions
D.1.1 Radiological parameters
D.1.2 Other parameters
D.2 Effects associated with electron ranges

Page count: 68