

# ISO/IEC TR 11801-9906:2020-02 (E)

## Information technology - Generic cabling for customer premises - Part 9906: Balanced 1-pair cabling channels up to 600 MHz for single pair Ethernet (SPE)

---

### Contents

Page

- FOREWORD ..... 6
- INTRODUCTION ..... 8
- 1 Scope ..... 9
- 2 Normative references ..... 9
- 3 Terms, definitions and symbols ..... 9
  - 3.1 Terms and definitions ..... 9
  - 3.2 Symbols ..... 10
- 4 Balanced 1-pair cabling channels ..... 10
  - 4.1 General ..... 10
  - 4.2 Component specifications ..... 11
  - 4.3 Environmental classifications ..... 11
  - 4.4 Channel reference implementations ..... 12
  - 4.5 Balanced 1-pair cabling channel signal transmission specifications ..... 12
    - 4.5.1 Return loss (RL) ..... 12
    - 4.5.2 Insertion loss (IL) ..... 12
    - 4.5.3 Unbalance attenuation and coupling attenuation ..... 13
    - 4.5.4 Alien (exogenous) crosstalk ..... 15
    - 4.5.5 DC loop resistance ..... 16
    - 4.5.6 Propagation delay ..... 16
- Annex A (informative) Balanced 1-pair cable specifications ..... 17
  - A.1 General ..... 17
  - A.2 Cables using alternative conductor sizes ..... 17
  - A.3 Balanced 1-pair cable specifications ..... 17
    - A.3.1 Return loss (RL) ..... 17
    - A.3.2 Insertion loss (IL) ..... 18
    - A.3.3 Unbalance attenuation and coupling attenuation ..... 18
    - A.3.4 Alien (exogenous) crosstalk ..... 20
    - A.3.5 DC resistance ..... 21
    - A.3.6 Propagation delay ..... 21
- Annex B (informative) Balanced 1-pair connector specifications ..... 22
  - B.1 General ..... 22
  - B.2 Balanced 1-pair connector specifications ..... 22
    - B.2.1 Return loss (RL) ..... 22
    - B.2.2 Insertion loss (IL) ..... 22
    - B.2.3 Unbalance attenuation and coupling attenuation ..... 23
    - B.2.4 Alien (exogenous) crosstalk ..... 24
    - B.2.5 DC resistance (DCR) ..... 25
    - B.2.6 Propagation delay (delay) ..... 25

Annex C (informative) Link segment specifications .....	26
C.1 General.....	26
C.2 Return loss (RL).....	26
C.2.1 1000BASE-T1, ISO/IEC/IEEE 8802-3:2017/AMD4 .....	26
C.2.2 100BASE-T1, ISO/IEC/IEEE 8802-3:2017/AMD1 .....	26
C.2.3 10BASE-T1S, IEEE 802.3cg .....	26
C.2.4 10BASE-T1L, IEEE 802.3cg .....	27
C.3 Insertion loss (IL).....	27
C.3.1 1000BASE-T1, ISO/IEC/IEEE 8802-3:2017/AMD4 .....	27
C.3.2 100BASE-T1, ISO/IEC/IEEE 8802-3:2017/AMD1 .....	27
C.4 TCL - 10BASE-T1L, IEEE 802.3cg .....	28
C.5 ELTCTL - 10BASE-T1L, IEEE 802.3cg.....	29
C.6 PS ANEXT .....	29
C.6.1 1000BASE-T1, Type A, ISO/IEC/IEEE 8802-3:2017/AMD4 .....	29
C.6.2 1000BASE-T1, Type B, ISO/IEC/IEEE 8802-3:2017/AMD4 .....	29
C.6.3 100BASE-T1, ISO/IEC/IEEE 8802-3:2017/AMD1 .....	29
C.6.4 10BASE-T1S, IEEE 802.3cg .....	30
C.6.5 10BASE-T1L, IEEE 802.3cg .....	30
C.7 PS AACR-F.....	30
C.7.1 1000BASE-T1, Type A, ISO/IEC/IEEE 8802-3:2017/AMD4 .....	30
C.7.2 1000BASE-T1, Type B, ISO/IEC/IEEE 8802-3:2017/AMD4 .....	30
C.7.3 100BASE-T1, ISO/IEC/IEEE 8802-3:2017/AMD1 .....	31
C.7.4 10BASE-T1S, IEEE 802.3cg .....	31
C.7.5 10BASE-T1L, IEEE 802.3cg .....	31
C.8 Coupling attenuation .....	31
C.8.1 1000BASE-T1, Type A, ISO/IEC/IEEE 8802-3:2017/AMD4 .....	31
C.8.2 1000BASE-T1, Type B, ISO/IEC/IEEE 8802-3:2017/AMD4 .....	32
C.8.3 100BASE-T1, ISO/IEC/IEEE 8802-3:2017/AMD1 .....	32
C.8.4 10BASE-T1S, IEEE 802.3cg .....	32
C.8.5 10BASE-T1L, IEEE 802.3cg .....	32
C.9 Delay .....	33
C.9.1 1000BASE-T1, Type A, ISO/IEC/IEEE 8802-3:2017/AMD4 .....	33
C.9.2 1000BASE-T1, Type B, ISO/IEC/IEEE 8802-3:2017/AMD4 .....	33
C.9.3 10BASE-T1L, IEEE 802.3cg .....	33
Annex D (informative) Considerations for balanced 1-pair channels bundled in a 4-pair cabling channel.....	34
Annex E (informative) Conductor size effects for reduced insertion loss.....	35
E.1 Channel parameters affected by conductor size and AWG .....	35
E.2 IL parameter variation due to conductor size variation .....	36
E.3 AWG .....	36
Bibliography .....	37
Table 1 – SPE signal transmission functional space.....	11
Table 2 – Balanced 1-pair cabling channel return loss (RL).....	12
Table 3 – Balanced 1-pair cabling channel IL.....	13
Table 4 – Balanced 1-pair cabling channel TCL .....	14
Table 5 – Balanced 1-pair cabling channel ELTCTL .....	14
Table 6 – Balanced 1-pair cabling channel coupling attenuation .....	15
Table 7 – Balanced 1-pair cabling channel PS ANEXT .....	15
Table 8 – Balanced 1-pair cabling channel PS AACR-F .....	16
Table 9 – Balanced 1 pair cabling channel DC loop resistance .....	16

Table 10 – Balanced 1-pair cabling channel propagation delay .....	16
Table A.1 – Balanced 1-pair cable standards .....	17
Table A.2 – Balanced 1-pair cable RL .....	18
Table A.3 – Balanced 1-pair cable IL .....	18
Table A.4 – Balanced 1-pair cable TCL .....	19
Table A.5 – Balanced 1-pair cable ELTCTL .....	19
Table A.6 – Balanced 1-pair cable coupling attenuation .....	20
Table A.7 – Balanced 1-pair cable PS ANEXT .....	20
Table A.8 – Balanced 1-pair cable PS AACR-F .....	21
Table A.9 – Balanced 1-pair cable DC resistance.....	21
Table A.10 – Balanced 1-pair cable propagation delay.....	21
Table B.1 – Balanced 1-pair connector standards .....	22
Table B.2 – Balanced 1-pair connector RL .....	22
Table B.3 – Balanced 1-pair connector IL .....	23
Table B.4 – Balanced 1-pair connector TCL .....	23
Table B.5 – Balanced 1-pair connector TCTL .....	23
Table B.6 – Balanced 1-pair connector coupling attenuation .....	24
Table B.7 – Balanced 1-pair connector PS ANEXT.....	24
Table B.8 – Balanced 1-pair connector PS AACR-F .....	24
Table B.9 – Balanced 1-pair connector DCR .....	25
Table B.10 – Balanced 1-pair connector delay .....	25
Table C.1 – Return loss limits for 15 m and 40 m link segment .....	26
Table C.2 – Return loss limits for 15 m link segment.....	26
Table C.3 – Return loss limits for 15 m link segment.....	26
Table C.4 – Return loss limits for 1 000 m link segment.....	27
Table C.5 – Insertion loss limits of a 15 m and 40 m link segment.....	27
Table C.6 – Insertion loss limits for a 15 m link segment.....	27
Table C.7 – Insertion loss limits for a 15 m link segment.....	28
Table C.8 – Insertion loss limits for a 1 000 m link segment.....	28
Table C.9 – TCL for a 1 000 m link segment .....	28
Table C.10 – ELTCTL for a 1 000 m link segment .....	29
Table C.11 – PS ANEXT for a 15 m link segment.....	29
Table C.12 – PS ANEXT for a 40 m link segment.....	29
Table C.13 – PS ANEXT for a 15 m link segment.....	29
Table C.14 – PS ANEXT for a 15 m link segment.....	30
Table C.15 – PS ANEXT for a 1 000 m link segment.....	30
Table C.16 – PS AACR-F for a 15 m link segment .....	30
Table C.17 – PS AACR-F for a 40 m link segment .....	30
Table C.18 – PS AACR-F for a 15 m link segment .....	31
Table C.19 – PS AACR-F for a 15 m link segment .....	31
Table C.20 – PS AACR-F for a 1 000 m link segment.....	31
Table C.21 – Coupling attenuation for a 15 m link segment.....	31
Table C.22 – Coupling attenuation for a 40 m link segment.....	32
Table C.23 – Coupling attenuation for a 15 m link segment.....	32
Table C.24 – Coupling attenuation for a 15 m link segment.....	32
Table C.25 – Coupling attenuation for a 1 000 m link segment.....	32

Table C.26 – Delay for a 15 m link segment.....	33
Table C.27 – Delay for a 40 m link segment.....	33
Table C.28 – Delay for a 1 000 m link segment.....	33
Table E.1 – Conductor diameter IL factors to be used with example 24 AWG cable with 1,8 conductor IL coefficient.....	35