

# ISO/IEC 14543-3-10:2020-03 (E)

## Information technology - Home electronic systems (HES) architecture - Part 3-10: Wireless short-packet (WSP) protocol optimized for energy harvesting - Architecture and lower layer protocols

---

Contents	Page
FOREWORD.....	4
INTRODUCTION.....	6
1 Scope.....	8
2 Normative references .....	8
3 Terms, definitions and abbreviated terms .....	8
3.1 Terms and definitions.....	8
3.2 Abbreviated terms.....	13
4 Conformance.....	13
5 Architecture.....	13
5.1 Generic protocol description .....	13
5.1.1 Overview .....	13
5.1.2 Physical layer .....	14
5.1.3 Data link layer .....	14
5.1.4 Network layer .....	14
5.1.5 Transport layer .....	15
5.1.6 Session layer.....	15
5.1.7 Presentation layer .....	15
5.1.8 Application layer.....	15
5.2 Data unit description .....	15
6 Layer 1 – Physical layer .....	16
6.1 Overview.....	16
6.2 General description.....	16
6.3 Requirements for the 315 MHz AMWSP protocol .....	18
6.4 Requirements for the 868,3 MHz AMWSP protocol.....	21
6.5 Frame structure .....	23
7 Layer 2 – Data link layer.....	25
7.1 Overview.....	25
7.2 Subtelegram timing.....	25
7.3 Data integrity .....	26
7.3.1 General .....	26
7.3.2 4 bit summation hash function algorithm .....	27
7.3.3 8 bit summation hash function algorithm .....	27
7.3.4 8 bit cyclic redundancy check (CRC) hash function algorithm .....	27
7.4 Listen before talk .....	28
8 Layer 3 – Network layer.....	28
8.1 Overview.....	28
8.2 Switch telegram .....	28
8.3 Repeater.....	29
8.3.1 General .....	29
8.3.2 Time response for collision avoidance .....	29
8.3.3 Bits of a repeater level in the STATUS byte .....	30

8.4	Addressing.....	30
8.4.1	General .....	30
8.4.2	Encapsulation.....	31
Annex A (informative)	Examples of how to evaluate the hash values .....	32
Bibliography.....		34
Figure 1	– Structure of a subtelegram .....	15
Figure 2	– Illustration of an ASK envelope and various physical parameters .....	17
Figure 3	– Complete frame structure for the 868,3 MHz AMWSP protocol .....	23
Figure 4	– Encoded subframe .....	24
Figure 5	– TX maturity time divided into four 10 ms time ranges .....	25
Figure 6	– Conversion of a switch telegram to a normal telegram.....	29
Figure 7	– Example of an encapsulation .....	31
Figure A.1	– Example of a C code program of the 4 bit long summation hash value .....	32
Figure A.2	– Example of a C code program of the 8 bit long summation hash value .....	32
Figure A.3	– Efficient C code program for the evaluation of an 8 bit long CRC type hash value .....	33
Table 1	– AMWSP protocol stack structure (OSI).....	14
Table 2	– Transmitter requirements for the 315 MHz AMWSP protocol .....	19
Table 3	– Receiver requirements for the 315 MHz AMWSP protocol .....	20
Table 4	– Minimum required link budget for the 315 MHz AMWSP protocol.....	20
Table 5	– Maximum RX power for the 315 MHz AMWSP protocol .....	21
Table 6	– Transmitter requirements for the 868,3 MHz AMWSP protocol.....	21
Table 7	– Receiver requirements for the 868,3 MHz AMWSP protocol .....	22
Table 8	– Minimum required link budget for the 868,3 MHz AMWSP protocol.....	22
Table 9	– Maximum RX power for the 868,3 MHz AMWSP protocol .....	23
Table 10	– Frame definition for the 315 MHz AMWSP protocol .....	24
Table 11	– Frame definition for the 868,3 MHz AMWSP protocol .....	24
Table 12	– Maturity time parameters .....	25
Table 13	– Allocation of time slots to the different subtelegrams .....	26
Table 14	– Identification of the hash function used in the telegram .....	27
Table 15	– Conversion of the telegram type and STATUS fields from a switch telegram to a telegram .....	29
Table 16	– STATUS byte with repeater level bits .....	30
Table 17	– Repeating bits in STATUS byte .....	30