

ISO/IEC TR 11801-9909:2020-06 (E)

Information technology - Generic cabling systems for customer premises - Part 9909: Evaluation of balanced cabling in support of 25 Gbit/s for reach greater than 30 metres

Contents	Page
FOREWORD.....	4
INTRODUCTION.....	6
1 Scope.....	7
2 Normative references	7
3 Terms and definitions	7
3.1 Terms and definitions.....	7
3.2 Abbreviated terms.....	7
4 Extended reach channel specifications	8
4.1 General.....	8
4.2 Channel performance enhancement methods for increased SNR	8
4.2.1 General	8
4.2.2 Reduced delay and delay skew.....	9
4.2.3 Enhanced cable.....	9
4.2.4 Enhanced connector	9
4.3 Example channel specifications with length scaling.....	9
4.3.1 General	9
4.3.2 Return loss (RL)	10
4.3.3 Insertion loss (IL).....	10
4.3.4 Near-end crosstalk loss (NEXT).....	11
4.3.5 Attenuation to crosstalk loss ratio near-end (ACR-N).....	11
4.3.6 Attenuation to crosstalk ratio far-end (ACR-F)	12
4.3.7 Alien (exogenous) crosstalk.....	12
4.3.8 DC loop resistance	13
4.3.9 Propagation delay.....	13
4.3.10 Delay skew.....	13
4.3.11 Unbalance attenuation near end (TCL) and far end (ELTCTL), and coupling attenuation	14
Annex A (informative) Reduced delay and delay skew	15
A.1 Reduced delay relation to extended reach	15
A.1.1 General	15
A.1.2 Example reduced delay evaluation.....	15
A.2 Delay relation to insertion loss (IL).....	15
A.2.1 General	15
A.2.2 Relation of variable relative permittivity to attenuation	16
A.2.3 Relation of dissipation factor to attenuation:	16
Annex B (informative) Enhanced capacity	18
B.1 Enhanced cabling components.....	18
B.1.1 General	18
B.1.2 Enhanced cable.....	18
B.1.3 Enhanced connector	18

B.2	Channel SNR margin-to-capacity	18
B.2.1	General	18
B.2.2	Margin-to-capacity calculation and comparison.....	18
B.2.3	Margin-to-capacity versus frequency.....	19
B.2.4	Margin-to-capacity versus reach	20
Bibliography.....		21
Figure B.1 – Margin-to-capacity versus frequency for 25 Gbit/s rate for 50 m reach		19
Figure B.2 – Margin-to-capacity versus reach for 25 Gbit/s at 1 000 MHz frequency		20
Table 1 – Enhancement methods for 25 Gbit/s extended reach.....		9
Table 2 – Formulae for return loss specifications for example 50 m channel		10
Table 3 – Formulae for insertion loss specifications for example 50 m channel		10
Table 4 – Formulae for pair-to-pair NEXT specifications for example 50 m channel		11
Table 5 – Formula for PS NEXT specifications for example 50 m channel.....		11
Table 6 – Formulae for ACR-F specifications for example 50 m channel		12
Table 7 – Formulae for PS ACR-F specifications for example 50 m channel.....		12
Table 8 – Formulae for PS ANEXT specifications for example 50 m channel.....		13
Table 9 – Formulae for PS AACR-F specifications for example 50 m channel		13
Table 10 – Formulae for propagation delay specifications for a 50 m channel		13
Table 11 – Delay skew specifications for a 50 m channel.....		13
Table 12 – TCL for example 50 m channel		14
Table 13 – ELTCTL for example 50 m channel.....		14
Table 14 – Coupling attenuation for example 50 m channel for E_1 and E_2		14