ISO/IEC TR 11801-9909:2020-06 (E)

Information technology - Generic cabling systems for customer premises - Part 9909: Evaluation of balanced cabling in support of 25 Gbit/s for reach greater than 30 metres

Contents

Page

FOREWORD 4
INTRODUCTION 6
1 Scope 7
2 Normative references 7
3 Terms and definitions 7
3.1 Terms and definitions 7
3.2 Abbreviated terms 7
4 Extended reach channel specifications 8
4.1 General 8
4.2 Channel performance enhancement methods for increased SNR 8
4.2.1 General 8
4.2.2 Reduced delay and delay skew 9
4.2.3 Enhanced cable 9
4.2.4 Enhanced connector 9
4.3 Example channel specifications with length scaling 9
4.3.1 General 9
4.3.2 Return loss (RL) 10
4.3.3 Insertion loss (IL) 10
4.3.4 Near-end crosstalk loss (NEXT) 11
4.3.5 Attenuation to crosstalk loss ratio near-end (ACR-N) 11
4.3.6 Attenuation to crosstalk ratio far-end (ACR-F) 12
4.3.7 Alien (exogenous) crosstalk 12
4.3.8 DC loop resistance 13
4.3.9 Propagation delay 13
4.3.10 Delay skew 13
4.3.11 Unbalance attenuation near end (TCL) and far end (ELTCTL), and coupling attenuation 14
Annex A (informative) Reduced delay and delay skew 15
A.1 Reduced delay relation to extended reach 15
A.1.1 General 15
A.1.2 Example reduced delay evaluation 15
A.2 Delay relation to insertion loss (IL) 15
A.2.1 General 15
A.2.2 Relation of variable relative permittivity to attenuation 16
A.2.3 Relation of dissipation factor to attenuation: 16
Annex B (informative) Enhanced capacity 18
B.1 Enhanced cabling components 18
B.1.1 General 18
B.1.2 Enhanced cable 18
B.1.3 Enhanced connector 18

B.2 Channel SNR margin-to-capacity 18
B.2.1 General 18
B.2.2 Margin-to-capacity calculation and comparison 18
B.2.3 Margin-to-capacity versus frequency 19
B.2.4 Margin-to-capacity versus reach 20

Bibliography 21
Figure B.1 – Margin-to-capacity versus frequency for 25 Gbit/s rate for 50 m reach 19
Figure B.2 – Margin-to-capacity versus reach for 25 Gbit/s at 1 000 MHz frequency 20

Table 1 – Enhancement methods for 25 Gbit/s extended reach 9
Table 2 – Formulae for return loss specifications for example 50 m channel 10
Table 3 – Formulae for insertion loss specifications for example 50 m channel 10
Table 4 – Formulae for pair-to-pair NEXT specifications for example 50 m channel 11
Table 5 – Formula for PS NEXT specifications for example 50 m channel 11
Table 6 – Formulae for ACR-F specifications for example 50 m channel 12
Table 7 – Formulae for PS ACR-F specifications for example 50 m channel 12
Table 8 – Formulae for PS ANEXT specifications for example 50 m channel 13
Table 9 – Formulae for PS AACR-F specifications for example 50 m channel 13
Table 10 – Formulae for propagation delay specifications for a 50 m channel 13
Table 11 – Delay skew specifications for a 50 m channel 13
Table 12 – TCL for example 50 m channel 14
Table 13 – ELTCTL for example 50 m channel 14
Table 14 – Coupling attenuation for example 50 m channel for E_1 and E_2 14