

# ISO/IEC 17760-103:2021-06 (E)

## Information technology - AT Attachment - Part 103: ATA/ATAPI Command Set - 3 (ACS-3)

---

### Contents

Page

FOREWORD.....	16
INTRODUCTION .....	18
1 Scope .....	20
2 Normative references .....	20
3 Terms, definitions, abbreviations, and conventions .....	21
3.1 Terms and definitions .....	21
3.2 Symbols and abbreviations.....	30
3.2.1 Abbreviations .....	30
3.2.2 Units: .....	31
3.2.3 Mathematical operators: .....	31
3.2.4 Other Symbols .....	31
3.3 Conventions.....	31
3.3.1 Overview .....	31
3.3.2 Precedence .....	32
3.3.3 Lists .....	32
3.3.4 Keywords .....	33
3.3.5 Numbering .....	34
3.3.6 Bit conventions .....	35
3.3.7 Number range convention .....	35
3.3.8 State diagram conventions .....	35
3.3.9 Byte, word, DWord, QWord, and DQWord Relationships .....	37
3.3.10 ATA string convention .....	38
3.3.11 Offset Convention .....	39
4 Feature set definitions .....	40
4.1 Overview.....	40
4.1.1 Feature set summary .....	40
4.1.2 Capacity reporting .....	41
4.2 General feature set .....	42
4.3 The PACKET feature set .....	42
4.3.1 Overview .....	42
4.3.2 Identification of PACKET feature set devices .....	43
4.3.3 Signature for ATAPI devices .....	43
4.3.4 The PACKET command .....	43
4.4 48-bit Address feature set.....	43
4.5 Accessible Max Address Configuration feature set .....	44
4.5.1 Overview .....	44
4.5.2 SET ACCESSIBLE MAX ADDRESS EXT description .....	44
4.5.3 Device Statistics data .....	44
4.6 Advanced Power Management (APM) feature set .....	44
4.7 CompactFlash Association (CFA) feature set.....	45
4.8 Device Statistics Notification (DSN) feature set.....	45
4.8.1 Overview .....	45
4.8.2 DSN notifications .....	46
4.8.3 DSN notifications setup .....	46
4.9 Extended Power Conditions (EPC) feature set.....	47
4.9.1 Overview .....	47
4.9.2 Power conditions .....	47
4.9.3 Power condition timers .....	47
4.9.4 Interaction with resets, commands, and other features if the EPC feature set is enabled .....	48

4.10	Free-fall Control feature set .....	49
4.11	General Purpose Logging (GPL) feature set .....	49
4.12	Long Logical Sector (LLS) feature set .....	50
4.13	Long Physical Sector (LPS) feature set .....	51
4.14	Native Command Queuing (NCQ) feature set .....	53
4.14.1	Overview .....	53
4.14.2	Priority .....	54
4.14.3	Unload with NCQ commands outstanding .....	54
4.14.4	Command Phases .....	54
4.15	Power Management feature set.....	55
4.15.1	Overview .....	55
4.15.2	Power management commands .....	55
4.15.3	Standby timer .....	56
4.15.4	Power Management states and transitions .....	57
4.16	Power-Up In Standby (PUIS) feature set.....	60
4.16.1	Overview .....	60
4.16.2	Interactions with IDENTIFY DEVICE and IDENTIFY PACKET DEVICE commands .....	60
4.16.3	PUIS feature set device spin-up subcommand .....	60
4.17	Sanitize Device feature set .....	61
4.17.1	Overview .....	61
4.17.2	Sanitize operation scope .....	61
4.17.3	Sanitize commands .....	61
4.17.4	Sanitize operations .....	61
4.17.5	Command processing during sanitize operations .....	62
4.17.6	Sanitize Operation Completed Without Error value .....	62
4.17.7	Failure Mode Policy value .....	62
4.17.8	Sanitize Antifreeze value .....	63
4.17.9	Sanitize Device state machine .....	63
4.18	Security feature set.....	66
4.18.1	Overview .....	66
4.18.2	Disabling and enabling the Security feature set .....	66
4.18.3	Passwords .....	66
4.18.4	Master password capability .....	67
4.18.5	Frozen mode .....	67
4.18.6	Commands .....	67
4.18.7	Security initial setting .....	67
4.18.8	Password Rules .....	67
4.18.9	Password attempt counter and SECURITY COUNT EXPIRED bit .....	68
4.18.10	Master Password Identifier feature .....	68
4.18.11	Security states .....	69
4.19	Self-Monitoring, Analysis, and Reporting Technology (SMART) feature set .....	78
4.19.1	Overview .....	78
4.19.2	Device SMART data structure .....	78
4.19.3	Background data collection .....	78
4.19.4	Off-line/Captive mode data collection .....	78
4.19.5	Threshold exceeded condition .....	79
4.19.6	SMART feature set commands .....	79
4.19.7	SMART operation with power management modes .....	79
4.19.8	SMART device error log reporting .....	79
4.20	Sense Data Reporting feature set .....	79
4.21	Software Settings Preservation (SSP) feature set.....	80
4.22	SATA Hardware Feature Control.....	81
4.23	Streaming feature set .....	82
4.23.1	Streaming feature set overview .....	82
4.23.2	Streaming commands .....	82
4.24	Trusted Computing feature set .....	83
4.25	Write-Read-Verify feature set .....	84

5 ATA protocols .....	85
6 Normal and Error Output field descriptions .....	86
6.1 Overview .....	86
6.2 STATUS field .....	86
6.2.1 Overview .....	86
6.2.2 ALIGNMENT ERROR bit .....	86
6.2.3 BUSY bit .....	87
6.2.4 CHECK CONDITION bit .....	87
6.2.5 DATA REQUEST bit .....	87
6.2.6 DEFERRED WRITE ERROR bit .....	87
6.2.7 DEVICE FAULT bit .....	87
6.2.8 DEVICE READY bit .....	87
6.2.9 ERROR bit .....	87
6.2.10 SENSE DATA AVAILABLE bit .....	88
6.2.11 STREAM ERROR bit .....	88
6.2.12 Transport Dependent bits and fields .....	88
6.3 ERROR field .....	89
6.3.1 Overview .....	89
6.3.2 ABORT bit .....	89
6.3.3 COMMAND COMPLETION TIME OUT bit .....	89
6.3.4 END OF MEDIA bit .....	89
6.3.5 ID NOT FOUND bit .....	89
6.3.6 ILLEGAL LENGTH INDICATOR bit .....	90
6.3.7 INTERFACE CRC bit .....	90
6.3.8 SENSE KEY field .....	90
6.3.9 UNCORRECTABLE ERROR bit .....	90
6.4 INTERRUPT REASON field .....	90
6.4.1 Overview .....	90
6.4.2 COMMAND/DATA bit .....	90
6.4.3 INPUT/OUTPUT bit .....	90
6.5 COUNT field .....	90
6.5.1 Overview .....	90
6.5.2 Contiguous stream logical sectors that contain potentially bad data .....	90
6.5.3 NCQ Tag .....	91
6.6 SACTIVE field .....	91
6.7 SATA STATUS field .....	91
6.8 LBA field .....	91
6.8.1 Overview .....	91
6.8.2 LBA of First Unrecoverable Error .....	91
7 Command descriptions .....	92
7.1 Command description introduction .....	92
7.1.1 Overview .....	92
7.1.10 Command Code Usage .....	96
7.2 Accessible Max Address Configuration .....	97
7.2.1 Accessible Max Address Configuration overview .....	97
7.2.2 GET NATIVE MAX ADDRESS EXT – 78h/0000h, Non-Data .....	97
7.2.3 SET ACCESSIBLE MAX ADDRESS EXT – 78h/0001h, Non-Data .....	98
7.2.4 FREEZE ACCESSIBLE MAX ADDRESS EXT – 78h/0002h, Non-Data .....	99
7.3 CHECK POWER MODE – E5h, Non-Data .....	100
7.4 CONFIGURE STREAM – 51h, Non-Data .....	101
7.5 DATA SET MANAGEMENT – 06h, DMA .....	103
7.6 DEVICE RESET – 08h, Device Reset .....	106
7.7 DOWNLOAD MICROCODE – 92h, PIO Data-Out/Non-Data .....	107
7.8 DOWNLOAD MICROCODE DMA – 93h, DMA .....	120
7.9 EXECUTE DEVICE DIAGNOSTIC – 90h, Execute Device Diagnostic .....	121

7.10	FLUSH CACHE – E7h, Non-Data .....	123
7.11	FLUSH CACHE EXT – EAh, Non-Data .....	124
7.12	IDENTIFY DEVICE – ECh, PIO Data-In .....	125
7.13	IDENTIFY PACKET DEVICE – A1h, PIO Data-In .....	162
7.14	IDLE – E3h, Non-Data .....	182
7.15	IDLE IMMEDIATE – E1h, Non-Data .....	184
7.16	NCQ QUEUE MANAGEMENT – 63h, Non-Data .....	186
7.16.8	ABORT NCQ QUEUE – 63h/0h, Non-Data .....	188
7.16.9	DEADLINE HANDLING – 63h/1h, Non-Data .....	191
7.17	NOP – 00h, Non-Data .....	194
7.18	PACKET – A0h, Packet .....	195
7.19	READ BUFFER – E4h, PIO Data-In .....	198
7.20	READ BUFFER DMA – E9h, DMA .....	199
7.21	READ DMA – C8h, DMA .....	200
7.22	READ DMA EXT – 25h, DMA .....	201
7.23	READ FPDMA QUEUED – 60h, DMA Queued .....	202
7.24	READ LOG EXT – 2Fh, PIO Data-In .....	204
7.25	READ LOG DMA EXT – 47h, DMA .....	206
7.26	READ MULTIPLE – C4h, PIO Data-In .....	207
7.27	READ MULTIPLE EXT – 29h, PIO Data-In .....	208
7.28	READ SECTOR(S) – 20h, PIO Data-In .....	209
7.29	READ SECTOR(S) EXT – 24h, PIO Data-In .....	210
7.30	READ STREAM DMA EXT – 2Ah, DMA .....	211
7.31	READ STREAM EXT – 2Bh, PIO Data-In .....	214
7.32	READ VERIFY SECTOR(S) – 40h, Non-Data .....	215
7.33	READ VERIFY SECTOR(S) EXT – 42h, Non-Data .....	216
7.34	RECEIVE FPDMA QUEUED – 65h, DMA Queued .....	217
7.35	REQUEST SENSE DATA EXT – 0Bh, Non-Data .....	219
7.36	Sanitize Device .....	220
7.36.2	BLOCK ERASE EXT – B4h/0012h, Non-Data .....	221
7.36.3	CRYPTO SCRAMBLE EXT – B4h/0011h, Non-Data .....	224
7.36.4	OVERWRITE EXT – B4h/0014h, Non-Data .....	226
7.36.5	SANITIZE ANTIFREEZE LOCK EXT – B4h/0040h, Non-Data .....	229
7.36.6	SANITIZE FREEZE LOCK EXT – B4h/0020h, Non-Data .....	231
7.36.7	SANITIZE STATUS EXT – B4h/0000h, Non-Data .....	232
7.37	SECURITY DISABLE PASSWORD – F6h, PIO Data-Out .....	234
7.38	SECURITY ERASE PREPARE – F3h, Non-Data .....	236
7.39	SECURITY ERASE UNIT – F4h, PIO Data-Out .....	237
7.40	SECURITY FREEZE LOCK – F5h, Non-Data .....	239
7.41	SECURITY SET PASSWORD – F1h, PIO Data-Out .....	240
7.42	SECURITY UNLOCK – F2h, PIO Data-Out .....	242
7.43	SEND FPDMA QUEUED – 64h, DMA Queued .....	244
7.43.4	SFQ DATA SET MANAGEMENT – 64h/00h, DMA Queued .....	246
7.44	SET DATE & TIME EXT – 77h, Non-Data .....	248
7.45	SET FEATURES – EFh, Non-Data .....	249
7.45.6	SET FEATURES subcommands .....	250
7.45.7	Enable/disable volatile write cache .....	252
7.45.8	Set transfer mode .....	253
7.45.9	Enable/disable the APM feature set .....	254
7.45.10	Enable/disable the PUIS feature set .....	254
7.45.11	PUIS feature set device spin-up .....	254
7.45.12	Enable/Disable Write-Read-Verify feature set .....	255
7.45.13	Set Maximum Host Interface Sector Times .....	256
7.45.14	Enable/disable read look-ahead .....	256
7.45.15	Enable/disable reverting to defaults .....	256
7.45.16	Enable/Disable the Free-fall Control feature set .....	257
7.45.17	Enable/Disable SATA feature .....	257

7.45.18	Enable/Disable the Sense Data Reporting feature set .....	259
7.45.19	Long Physical Sector Alignment Error Reporting Control .....	259
7.45.20	Extended Power Conditions subcommand .....	260
7.45.21	Enable/Disable the DSN feature set .....	270
7.46	SET MULTIPLE MODE – C6h, Non-Data .....	271
7.47	SLEEP – E6h, Non-Data .....	273
7.48	SMART .....	274
7.48.2	SMART DISABLE OPERATIONS – B0h/D9h, Non-Data .....	275
7.48.3	SMART ENABLE/DISABLE ATTRIBUTE AUTOSAVE – B0h/D2h, Non-Data .....	276
7.48.4	SMART ENABLE OPERATIONS – B0h/D8h, Non-Data .....	278
7.48.5	SMART EXECUTE OFF-LINE IMMEDIATE – B0h/D4h, Non-Data .....	279
7.48.6	SMART READ DATA – B0h/D0h, PIO Data-In .....	283
7.48.7	SMART READ LOG – B0h/D5h, PIO Data-In .....	288
7.48.8	SMART RETURN STATUS – B0h/DAh, Non-Data .....	289
7.48.9	SMART WRITE LOG – B0h/D6h, PIO Data-Out .....	290
7.49	STANDBY – E2h, Non-Data .....	291
7.50	STANDBY IMMEDIATE – E0h, Non-Data .....	292
7.51	TRUSTED NON-DATA – 5Bh, Non-Data .....	293
7.52	TRUSTED RECEIVE – 5Ch, PIO Data-In .....	295
7.53	TRUSTED RECEIVE DMA – 5Dh, DMA .....	302
7.54	TRUSTED SEND – 5Eh, PIO Data-Out .....	303
7.55	TRUSTED SEND DMA – 5Fh, DMA .....	305
7.56	WRITE BUFFER – E8h, PIO Data-Out .....	306
7.57	WRITE BUFFER DMA – EBh, DMA .....	307
7.58	WRITE DMA – CAh, DMA .....	308
7.59	WRITE DMA EXT – 35h, DMA .....	309
7.60	WRITE DMA FUA EXT – 3Dh, DMA .....	310
7.61	WRITE FPDMA QUEUED – 61h, DMA Queued .....	311
7.62	WRITE LOG EXT – 3Fh, PIO Data-Out .....	313
7.63	WRITE LOG DMA EXT – 57h, DMA .....	315
7.64	WRITE MULTIPLE – C5h, PIO Data-Out .....	316
7.65	WRITE MULTIPLE EXT – 39h, PIO Data-Out .....	317
7.66	WRITE MULTIPLE FUA EXT – CEh, PIO Data-Out .....	319
7.67	WRITE SECTOR(S) – 30h, PIO Data-Out .....	321
7.68	WRITE SECTOR(S) EXT – 34h, PIO Data-Out .....	322
7.69	WRITE STREAM DMA EXT – 3Ah, DMA .....	323
7.70	WRITE STREAM EXT – 3Bh, PIO Data-Out .....	326
7.71	WRITE UNCORRECTABLE EXT – 45h, Non-Data .....	327
8	SCT Command Transport .....	329
8.1	Introduction .....	329
8.1.1	Overview .....	329
8.1.2	SCT command interactions with ATA commands .....	330
8.1.3	Resets .....	330
8.2	Processing SCT commands .....	331
8.2.1	Processing SCT commands overview .....	331
8.2.2	SCT capability identification .....	331
8.2.3	SCT Command transfer .....	331
8.2.4	SCT data transfer .....	336
8.2.5	SCT status .....	342
8.3	SCT Command Set .....	348
8.3.1	Overview .....	348
8.3.2	SCT Write Same command .....	349
8.3.3	SCT Error Recovery Control command .....	354
8.3.4	SCT Feature Control command .....	356
8.3.5	SCT Data Table command .....	360

9 Normal and Error Outputs .....	364
9.1 Overview .....	364
9.2 Normal Outputs.....	364
9.3 Error Outputs .....	380
Annex A (normative) Log Definitions .....	409
A.1 Overview .....	409
A.2 General Purpose Log Directory (GPL Log Address 00h) .....	412
A.3 SMART Log Directory (SMART Logging Log Address 00h) .....	412
A.4 Comprehensive SMART Error log (Log Address 02h) .....	413
A.5 Device Statistics log (Log Address 04h) .....	414
A.5.1 Overview .....	414
A.5.2 List of Supported Device Statistics log pages (log page 00h) .....	416
A.5.3 Free Fall Statistics (log page 02h) .....	417
A.5.4 General Statistics (log page 01h) .....	419
A.5.5 General Errors Statistics (log page 04h) .....	423
A.5.6 Rotating Media Statistics (log page 03h) .....	425
A.5.7 Solid State Device Statistics (log page 07h) .....	430
A.5.8 Temperature Statistics (log page 05h) .....	431
A.5.9 Transport Statistics (log page 06h) .....	439
A.5.10 Reserved (log page 08h..FFh) .....	441
A.6 Device Vendor Specific logs (Log Addresses A0h-DFh) .....	441
A.7 Extended Comprehensive SMART Error log (Log Address 03h) .....	441
A.8 Power Conditions log (Log Address 08h) .....	445
A.8.2 Idle power conditions (log page 00h) .....	445
A.8.3 Standby power conditions (log page 01h) .....	446
A.8.4 Power Conditions log descriptor .....	446
A.9 Extended SMART Self-Test log (Log Address 07h) .....	449
A.10 Host Specific logs (Log Addresses 80h-9Fh) .....	451
A.11 IDENTIFY DEVICE data log (Log Address 30h) .....	452
A.11.1 Overview .....	452
A.11.2 List of Supported IDENTIFY DEVICE data log pages (Page 00h) .....	452
A.11.3 Copy of IDENTIFY DEVICE data (page 01h) .....	453
A.11.4 Capacity (page 02) .....	453
A.11.5 Supported Capabilities (page 03h) .....	456
A.11.6 Current Settings (page 04h) .....	469
A.11.7 Strings (page 05h) .....	477
A.11.8 Security (page 06h) .....	478
A.11.9 Parallel ATA (page 07h) .....	484
A.11.10 Serial ATA (page 08h) .....	496
A.12 LBA Status log (Log Address 19h) .....	502
A.12.1 Overview .....	502
A.12.2 Number of LBA Valid Ranges log page (Page 0000h) .....	503
A.12.3 LBA Status log pages .....	503
A.12.4 LBA Status Descriptor .....	504
A.13 LPS Mis-alignment log (Log Address 0Dh) .....	505
A.14 NCQ Command Error log (Log Address 10h) .....	507
A.14.1 Overview .....	507
A.14.2 NCQ TAG field .....	507
A.14.3 NQ bit .....	507
A.14.4 UNL bit .....	508
A.14.5 Return Fields .....	508
A.14.6 NCQ Autosense .....	508
A.14.7 Checksum .....	508
A.15 Read Stream Error log (Log Address 22h) .....	509
A.16 SATA Phy Event Counters log (Log Address 11h) .....	510
A.17 SATA NCQ Queue Management log (Log Address 12h) .....	512

A.17.1	Overview .....	512
A.17.2	SUPPORTS ABORT NCQ QUEUE bit .....	512
A.17.3	SUPPORTS ABORT ALL AT bit .....	512
A.17.4	SUPPORTS ABORT STREAMING AT bit .....	512
A.17.5	SUPPORTS ABORT NON-STREAMING AT bit .....	513
A.17.6	SUPPORTS ABORT SELECTED TTAG AT bit .....	513
A.17.7	SUPPORTS DEADLINE HANDLING bit .....	513
A.17.8	SUPPORTS WDNC bit .....	513
A.17.9	SUPPORTS RDNC bit .....	513
A.18	SATA NCQ Send and Receive log (Log Address 13h) .....	514
A.18.1	Overview .....	514
A.18.2	SFQ DATA SET MANAGEMENT SUPPORTED bit .....	514
A.18.3	SFQ DATA SET MANAGEMENT SUPPORTS TRIM bit .....	514
A.19	Selective Self-Test log (Log Address 09h) .....	515
A.20	SMART Self-Test log (Log Address 06h) .....	517
A.21	Summary SMART Error log (Log Address 01h) .....	518
A.22	Write Stream Error log (Log Address 21h) .....	521
A.23	Current Device Internal Status Data log (Log Address 24h) .....	522
A.23.1	Overview .....	522
A.23.2	Current Device Internal Status Data header page .....	523
A.23.3	Current Device Internal Status data pages .....	525
A.23.4	Examples of data area usage .....	525
A.24	Saved Device Internal Status Data log (Log Address 25h) .....	527
A.24.1	Overview .....	527
A.24.2	Saved Device Internal Status Data header page .....	527
A.24.3	Current Device Internal Status data pages .....	528
A.25	Device Statistics Notifications log (Log Address 0Ah) .....	528
Annex B (informative)	Command Set Summary .....	532
Annex C (informative)	How to Use SCT Commands .....	559
C.1	How to Use SCT Commands Overview .....	559
C.2	Examples of Log Page Command Sequences .....	561
C.3	Issuing an SCT Command to a Device .....	566
C.3.1	Step 1 – Build a Key Page .....	566
C.3.2	Step 2 – Issue the SCT command .....	567
C.3.3	Step 3 – Transfer Data if Required .....	568
C.3.4	Step 4 – Final Status/SCT Command Completion .....	569
Annex D (informative)	Implementation Guidelines for 1 024- and 4 096-Byte Sector Sizes .....	570
D.1	General .....	570
D.2	Overview .....	570
D.3	Implementation .....	572
D.3.1	4 096-Byte Physical Sector Size Implementation .....	572
D.3.2	Reporting Alignment (512-Byte LBA Only) .....	572
D.3.3	RMW operations (512-Byte LBA Only) .....	573
D.4	Implementation Issues (512-Byte LBA Only) .....	573
D.4.1	Overview .....	573
D.4.2	Drive Partitioning .....	574
D.4.3	File System Formatting .....	575
D.4.4	Virtual Memory accessing .....	575
D.4.5	Bootting .....	575
Bibliography	.....	576