

ISO/IEC 17760-103:2021-06 (E)

Information technology - AT Attachment - Part 103: ATA/ATAPI Command Set - 3 (ACS-3)

Contents

Page

| | |
|---|----|
| FOREWORD..... | 16 |
| INTRODUCTION | 18 |
| 1 Scope | 20 |
| 2 Normative references | 20 |
| 3 Terms, definitions, abbreviations, and conventions | 21 |
| 3.1 Terms and definitions | 21 |
| 3.2 Symbols and abbreviations..... | 30 |
| 3.2.1 Abbreviations | 30 |
| 3.2.2 Units: | 31 |
| 3.2.3 Mathematical operators: | 31 |
| 3.2.4 Other Symbols | 31 |
| 3.3 Conventions..... | 31 |
| 3.3.1 Overview | 31 |
| 3.3.2 Precedence | 32 |
| 3.3.3 Lists | 32 |
| 3.3.4 Keywords | 33 |
| 3.3.5 Numbering | 34 |
| 3.3.6 Bit conventions | 35 |
| 3.3.7 Number range convention | 35 |
| 3.3.8 State diagram conventions | 35 |
| 3.3.9 Byte, word, DWord, QWord, and DQWord Relationships | 37 |
| 3.3.10 ATA string convention | 38 |
| 3.3.11 Offset Convention | 39 |
| 4 Feature set definitions | 40 |
| 4.1 Overview..... | 40 |
| 4.1.1 Feature set summary | 40 |
| 4.1.2 Capacity reporting | 41 |
| 4.2 General feature set | 42 |
| 4.3 The PACKET feature set | 42 |
| 4.3.1 Overview | 42 |
| 4.3.2 Identification of PACKET feature set devices | 43 |
| 4.3.3 Signature for ATAPI devices | 43 |
| 4.3.4 The PACKET command | 43 |
| 4.4 48-bit Address feature set..... | 43 |
| 4.5 Accessible Max Address Configuration feature set | 44 |
| 4.5.1 Overview | 44 |
| 4.5.2 SET ACCESSIBLE MAX ADDRESS EXT description | 44 |
| 4.5.3 Device Statistics data | 44 |
| 4.6 Advanced Power Management (APM) feature set | 44 |
| 4.7 CompactFlash Association (CFA) feature set..... | 45 |
| 4.8 Device Statistics Notification (DSN) feature set..... | 45 |
| 4.8.1 Overview | 45 |
| 4.8.2 DSN notifications | 46 |
| 4.8.3 DSN notifications setup | 46 |
| 4.9 Extended Power Conditions (EPC) feature set..... | 47 |
| 4.9.1 Overview | 47 |
| 4.9.2 Power conditions | 47 |
| 4.9.3 Power condition timers | 47 |
| 4.9.4 Interaction with resets, commands, and other features if the EPC feature set is enabled | 48 |

| | | |
|---------|---|----|
| 4.10 | Free-fall Control feature set | 49 |
| 4.11 | General Purpose Logging (GPL) feature set | 49 |
| 4.12 | Long Logical Sector (LLS) feature set | 50 |
| 4.13 | Long Physical Sector (LPS) feature set | 51 |
| 4.14 | Native Command Queuing (NCQ) feature set | 53 |
| 4.14.1 | Overview | 53 |
| 4.14.2 | Priority | 54 |
| 4.14.3 | Unload with NCQ commands outstanding | 54 |
| 4.14.4 | Command Phases | 54 |
| 4.15 | Power Management feature set..... | 55 |
| 4.15.1 | Overview | 55 |
| 4.15.2 | Power management commands | 55 |
| 4.15.3 | Standby timer | 56 |
| 4.15.4 | Power Management states and transitions | 57 |
| 4.16 | Power-Up In Standby (PUIS) feature set..... | 60 |
| 4.16.1 | Overview | 60 |
| 4.16.2 | Interactions with IDENTIFY DEVICE and IDENTIFY PACKET DEVICE commands | 60 |
| 4.16.3 | PUIS feature set device spin-up subcommand | 60 |
| 4.17 | Sanitize Device feature set | 61 |
| 4.17.1 | Overview | 61 |
| 4.17.2 | Sanitize operation scope | 61 |
| 4.17.3 | Sanitize commands | 61 |
| 4.17.4 | Sanitize operations | 61 |
| 4.17.5 | Command processing during sanitize operations | 62 |
| 4.17.6 | Sanitize Operation Completed Without Error value | 62 |
| 4.17.7 | Failure Mode Policy value | 62 |
| 4.17.8 | Sanitize Antifreeze value | 63 |
| 4.17.9 | Sanitize Device state machine | 63 |
| 4.18 | Security feature set..... | 66 |
| 4.18.1 | Overview | 66 |
| 4.18.2 | Disabling and enabling the Security feature set | 66 |
| 4.18.3 | Passwords | 66 |
| 4.18.4 | Master password capability | 67 |
| 4.18.5 | Frozen mode | 67 |
| 4.18.6 | Commands | 67 |
| 4.18.7 | Security initial setting | 67 |
| 4.18.8 | Password Rules | 67 |
| 4.18.9 | Password attempt counter and SECURITY COUNT EXPIRED bit | 68 |
| 4.18.10 | Master Password Identifier feature | 68 |
| 4.18.11 | Security states | 69 |
| 4.19 | Self-Monitoring, Analysis, and Reporting Technology (SMART) feature set | 78 |
| 4.19.1 | Overview | 78 |
| 4.19.2 | Device SMART data structure | 78 |
| 4.19.3 | Background data collection | 78 |
| 4.19.4 | Off-line/Captive mode data collection | 78 |
| 4.19.5 | Threshold exceeded condition | 79 |
| 4.19.6 | SMART feature set commands | 79 |
| 4.19.7 | SMART operation with power management modes | 79 |
| 4.19.8 | SMART device error log reporting | 79 |
| 4.20 | Sense Data Reporting feature set | 79 |
| 4.21 | Software Settings Preservation (SSP) feature set..... | 80 |
| 4.22 | SATA Hardware Feature Control..... | 81 |
| 4.23 | Streaming feature set | 82 |
| 4.23.1 | Streaming feature set overview | 82 |
| 4.23.2 | Streaming commands | 82 |
| 4.24 | Trusted Computing feature set | 83 |
| 4.25 | Write-Read-Verify feature set | 84 |

| | |
|---|-----|
| 5 ATA protocols | 85 |
| 6 Normal and Error Output field descriptions | 86 |
| 6.1 Overview | 86 |
| 6.2 STATUS field | 86 |
| 6.2.1 Overview | 86 |
| 6.2.2 ALIGNMENT ERROR bit | 86 |
| 6.2.3 BUSY bit | 87 |
| 6.2.4 CHECK CONDITION bit | 87 |
| 6.2.5 DATA REQUEST bit | 87 |
| 6.2.6 DEFERRED WRITE ERROR bit | 87 |
| 6.2.7 DEVICE FAULT bit | 87 |
| 6.2.8 DEVICE READY bit | 87 |
| 6.2.9 ERROR bit | 87 |
| 6.2.10 SENSE DATA AVAILABLE bit | 88 |
| 6.2.11 STREAM ERROR bit | 88 |
| 6.2.12 Transport Dependent bits and fields | 88 |
| 6.3 ERROR field | 89 |
| 6.3.1 Overview | 89 |
| 6.3.2 ABORT bit | 89 |
| 6.3.3 COMMAND COMPLETION TIME OUT bit | 89 |
| 6.3.4 END OF MEDIA bit | 89 |
| 6.3.5 ID NOT FOUND bit | 89 |
| 6.3.6 ILLEGAL LENGTH INDICATOR bit | 90 |
| 6.3.7 INTERFACE CRC bit | 90 |
| 6.3.8 SENSE KEY field | 90 |
| 6.3.9 UNCORRECTABLE ERROR bit | 90 |
| 6.4 INTERRUPT REASON field | 90 |
| 6.4.1 Overview | 90 |
| 6.4.2 COMMAND/DATA bit | 90 |
| 6.4.3 INPUT/OUTPUT bit | 90 |
| 6.5 COUNT field | 90 |
| 6.5.1 Overview | 90 |
| 6.5.2 Contiguous stream logical sectors that contain potentially bad data | 90 |
| 6.5.3 NCQ Tag | 91 |
| 6.6 SACTIVE field | 91 |
| 6.7 SATA STATUS field | 91 |
| 6.8 LBA field | 91 |
| 6.8.1 Overview | 91 |
| 6.8.2 LBA of First Unrecoverable Error | 91 |
| 7 Command descriptions | 92 |
| 7.1 Command description introduction | 92 |
| 7.1.1 Overview | 92 |
| 7.1.10 Command Code Usage | 96 |
| 7.2 Accessible Max Address Configuration | 97 |
| 7.2.1 Accessible Max Address Configuration overview | 97 |
| 7.2.2 GET NATIVE MAX ADDRESS EXT – 78h/0000h, Non-Data | 97 |
| 7.2.3 SET ACCESSIBLE MAX ADDRESS EXT – 78h/0001h, Non-Data | 98 |
| 7.2.4 FREEZE ACCESSIBLE MAX ADDRESS EXT – 78h/0002h, Non-Data | 99 |
| 7.3 CHECK POWER MODE – E5h, Non-Data | 100 |
| 7.4 CONFIGURE STREAM – 51h, Non-Data | 101 |
| 7.5 DATA SET MANAGEMENT – 06h, DMA | 103 |
| 7.6 DEVICE RESET – 08h, Device Reset | 106 |
| 7.7 DOWNLOAD MICROCODE – 92h, PIO Data-Out/Non-Data | 107 |
| 7.8 DOWNLOAD MICROCODE DMA – 93h, DMA | 120 |
| 7.9 EXECUTE DEVICE DIAGNOSTIC – 90h, Execute Device Diagnostic | 121 |

| | | |
|---------|--|-----|
| 7.10 | FLUSH CACHE – E7h, Non-Data | 123 |
| 7.11 | FLUSH CACHE EXT – EAh, Non-Data | 124 |
| 7.12 | IDENTIFY DEVICE – ECh, PIO Data-In | 125 |
| 7.13 | IDENTIFY PACKET DEVICE – A1h, PIO Data-In | 162 |
| 7.14 | IDLE – E3h, Non-Data | 182 |
| 7.15 | IDLE IMMEDIATE – E1h, Non-Data | 184 |
| 7.16 | NCQ QUEUE MANAGEMENT – 63h, Non-Data | 186 |
| 7.16.8 | ABORT NCQ QUEUE – 63h/0h, Non-Data | 188 |
| 7.16.9 | DEADLINE HANDLING – 63h/1h, Non-Data | 191 |
| 7.17 | NOP – 00h, Non-Data | 194 |
| 7.18 | PACKET – A0h, Packet | 195 |
| 7.19 | READ BUFFER – E4h, PIO Data-In | 198 |
| 7.20 | READ BUFFER DMA – E9h, DMA | 199 |
| 7.21 | READ DMA – C8h, DMA | 200 |
| 7.22 | READ DMA EXT – 25h, DMA | 201 |
| 7.23 | READ FPDMA QUEUED – 60h, DMA Queued | 202 |
| 7.24 | READ LOG EXT – 2Fh, PIO Data-In | 204 |
| 7.25 | READ LOG DMA EXT – 47h, DMA | 206 |
| 7.26 | READ MULTIPLE – C4h, PIO Data-In | 207 |
| 7.27 | READ MULTIPLE EXT – 29h, PIO Data-In | 208 |
| 7.28 | READ SECTOR(S) – 20h, PIO Data-In | 209 |
| 7.29 | READ SECTOR(S) EXT – 24h, PIO Data-In | 210 |
| 7.30 | READ STREAM DMA EXT – 2Ah, DMA | 211 |
| 7.31 | READ STREAM EXT – 2Bh, PIO Data-In | 214 |
| 7.32 | READ VERIFY SECTOR(S) – 40h, Non-Data | 215 |
| 7.33 | READ VERIFY SECTOR(S) EXT – 42h, Non-Data | 216 |
| 7.34 | RECEIVE FPDMA QUEUED – 65h, DMA Queued | 217 |
| 7.35 | REQUEST SENSE DATA EXT – 0Bh, Non-Data | 219 |
| 7.36 | Sanitize Device | 220 |
| 7.36.2 | BLOCK ERASE EXT – B4h/0012h, Non-Data | 221 |
| 7.36.3 | CRYPTO SCRAMBLE EXT – B4h/0011h, Non-Data | 224 |
| 7.36.4 | OVERWRITE EXT – B4h/0014h, Non-Data | 226 |
| 7.36.5 | SANITIZE ANTIFREEZE LOCK EXT – B4h/0040h, Non-Data | 229 |
| 7.36.6 | SANITIZE FREEZE LOCK EXT – B4h/0020h, Non-Data | 231 |
| 7.36.7 | SANITIZE STATUS EXT – B4h/0000h, Non-Data | 232 |
| 7.37 | SECURITY DISABLE PASSWORD – F6h, PIO Data-Out | 234 |
| 7.38 | SECURITY ERASE PREPARE – F3h, Non-Data | 236 |
| 7.39 | SECURITY ERASE UNIT – F4h, PIO Data-Out | 237 |
| 7.40 | SECURITY FREEZE LOCK – F5h, Non-Data | 239 |
| 7.41 | SECURITY SET PASSWORD – F1h, PIO Data-Out | 240 |
| 7.42 | SECURITY UNLOCK – F2h, PIO Data-Out | 242 |
| 7.43 | SEND FPDMA QUEUED – 64h, DMA Queued | 244 |
| 7.43.4 | SFQ DATA SET MANAGEMENT – 64h/00h, DMA Queued | 246 |
| 7.44 | SET DATE & TIME EXT – 77h, Non-Data | 248 |
| 7.45 | SET FEATURES – EFh, Non-Data | 249 |
| 7.45.6 | SET FEATURES subcommands | 250 |
| 7.45.7 | Enable/disable volatile write cache | 252 |
| 7.45.8 | Set transfer mode | 253 |
| 7.45.9 | Enable/disable the APM feature set | 254 |
| 7.45.10 | Enable/disable the PUIS feature set | 254 |
| 7.45.11 | PUIS feature set device spin-up | 254 |
| 7.45.12 | Enable/Disable Write-Read-Verify feature set | 255 |
| 7.45.13 | Set Maximum Host Interface Sector Times | 256 |
| 7.45.14 | Enable/disable read look-ahead | 256 |
| 7.45.15 | Enable/disable reverting to defaults | 256 |
| 7.45.16 | Enable/Disable the Free-fall Control feature set | 257 |
| 7.45.17 | Enable/Disable SATA feature | 257 |

| | | |
|---------|---|-----|
| 7.45.18 | Enable/Disable the Sense Data Reporting feature set | 259 |
| 7.45.19 | Long Physical Sector Alignment Error Reporting Control | 259 |
| 7.45.20 | Extended Power Conditions subcommand | 260 |
| 7.45.21 | Enable/Disable the DSN feature set | 270 |
| 7.46 | SET MULTIPLE MODE – C6h, Non-Data | 271 |
| 7.47 | SLEEP – E6h, Non-Data | 273 |
| 7.48 | SMART | 274 |
| 7.48.2 | SMART DISABLE OPERATIONS – B0h/D9h, Non-Data | 275 |
| 7.48.3 | SMART ENABLE/DISABLE ATTRIBUTE AUTOSAVE – B0h/D2h, Non-Data | 276 |
| 7.48.4 | SMART ENABLE OPERATIONS – B0h/D8h, Non-Data | 278 |
| 7.48.5 | SMART EXECUTE OFF-LINE IMMEDIATE – B0h/D4h, Non-Data | 279 |
| 7.48.6 | SMART READ DATA – B0h/D0h, PIO Data-In | 283 |
| 7.48.7 | SMART READ LOG – B0h/D5h, PIO Data-In | 288 |
| 7.48.8 | SMART RETURN STATUS – B0h/DAh, Non-Data | 289 |
| 7.48.9 | SMART WRITE LOG – B0h/D6h, PIO Data-Out | 290 |
| 7.49 | STANDBY – E2h, Non-Data | 291 |
| 7.50 | STANDBY IMMEDIATE – E0h, Non-Data | 292 |
| 7.51 | TRUSTED NON-DATA – 5Bh, Non-Data | 293 |
| 7.52 | TRUSTED RECEIVE – 5Ch, PIO Data-In | 295 |
| 7.53 | TRUSTED RECEIVE DMA – 5Dh, DMA | 302 |
| 7.54 | TRUSTED SEND – 5Eh, PIO Data-Out | 303 |
| 7.55 | TRUSTED SEND DMA – 5Fh, DMA | 305 |
| 7.56 | WRITE BUFFER – E8h, PIO Data-Out | 306 |
| 7.57 | WRITE BUFFER DMA – EBh, DMA | 307 |
| 7.58 | WRITE DMA – CAh, DMA | 308 |
| 7.59 | WRITE DMA EXT – 35h, DMA | 309 |
| 7.60 | WRITE DMA FUA EXT – 3Dh, DMA | 310 |
| 7.61 | WRITE FPDMA QUEUED – 61h, DMA Queued | 311 |
| 7.62 | WRITE LOG EXT – 3Fh, PIO Data-Out | 313 |
| 7.63 | WRITE LOG DMA EXT – 57h, DMA | 315 |
| 7.64 | WRITE MULTIPLE – C5h, PIO Data-Out | 316 |
| 7.65 | WRITE MULTIPLE EXT – 39h, PIO Data-Out | 317 |
| 7.66 | WRITE MULTIPLE FUA EXT – CEh, PIO Data-Out | 319 |
| 7.67 | WRITE SECTOR(S) – 30h, PIO Data-Out | 321 |
| 7.68 | WRITE SECTOR(S) EXT – 34h, PIO Data-Out | 322 |
| 7.69 | WRITE STREAM DMA EXT – 3Ah, DMA | 323 |
| 7.70 | WRITE STREAM EXT – 3Bh, PIO Data-Out | 326 |
| 7.71 | WRITE UNCORRECTABLE EXT – 45h, Non-Data | 327 |
| 8 | SCT Command Transport | 329 |
| 8.1 | Introduction | 329 |
| 8.1.1 | Overview | 329 |
| 8.1.2 | SCT command interactions with ATA commands | 330 |
| 8.1.3 | Resets | 330 |
| 8.2 | Processing SCT commands | 331 |
| 8.2.1 | Processing SCT commands overview | 331 |
| 8.2.2 | SCT capability identification | 331 |
| 8.2.3 | SCT Command transfer | 331 |
| 8.2.4 | SCT data transfer | 336 |
| 8.2.5 | SCT status | 342 |
| 8.3 | SCT Command Set | 348 |
| 8.3.1 | Overview | 348 |
| 8.3.2 | SCT Write Same command | 349 |
| 8.3.3 | SCT Error Recovery Control command | 354 |
| 8.3.4 | SCT Feature Control command | 356 |
| 8.3.5 | SCT Data Table command | 360 |

| | |
|--|-----|
| 9 Normal and Error Outputs | 364 |
| 9.1 Overview | 364 |
| 9.2 Normal Outputs..... | 364 |
| 9.3 Error Outputs | 380 |
| Annex A (normative) Log Definitions | 409 |
| A.1 Overview | 409 |
| A.2 General Purpose Log Directory (GPL Log Address 00h) | 412 |
| A.3 SMART Log Directory (SMART Logging Log Address 00h) | 412 |
| A.4 Comprehensive SMART Error log (Log Address 02h) | 413 |
| A.5 Device Statistics log (Log Address 04h) | 414 |
| A.5.1 Overview | 414 |
| A.5.2 List of Supported Device Statistics log pages (log page 00h) | 416 |
| A.5.3 Free Fall Statistics (log page 02h) | 417 |
| A.5.4 General Statistics (log page 01h) | 419 |
| A.5.5 General Errors Statistics (log page 04h) | 423 |
| A.5.6 Rotating Media Statistics (log page 03h) | 425 |
| A.5.7 Solid State Device Statistics (log page 07h) | 430 |
| A.5.8 Temperature Statistics (log page 05h) | 431 |
| A.5.9 Transport Statistics (log page 06h) | 439 |
| A.5.10 Reserved (log page 08h..FFh) | 441 |
| A.6 Device Vendor Specific logs (Log Addresses A0h-DFh) | 441 |
| A.7 Extended Comprehensive SMART Error log (Log Address 03h) | 441 |
| A.8 Power Conditions log (Log Address 08h) | 445 |
| A.8.2 Idle power conditions (log page 00h) | 445 |
| A.8.3 Standby power conditions (log page 01h) | 446 |
| A.8.4 Power Conditions log descriptor | 446 |
| A.9 Extended SMART Self-Test log (Log Address 07h) | 449 |
| A.10 Host Specific logs (Log Addresses 80h-9Fh) | 451 |
| A.11 IDENTIFY DEVICE data log (Log Address 30h) | 452 |
| A.11.1 Overview | 452 |
| A.11.2 List of Supported IDENTIFY DEVICE data log pages (Page 00h) | 452 |
| A.11.3 Copy of IDENTIFY DEVICE data (page 01h) | 453 |
| A.11.4 Capacity (page 02) | 453 |
| A.11.5 Supported Capabilities (page 03h) | 456 |
| A.11.6 Current Settings (page 04h) | 469 |
| A.11.7 Strings (page 05h) | 477 |
| A.11.8 Security (page 06h) | 478 |
| A.11.9 Parallel ATA (page 07h) | 484 |
| A.11.10 Serial ATA (page 08h) | 496 |
| A.12 LBA Status log (Log Address 19h) | 502 |
| A.12.1 Overview | 502 |
| A.12.2 Number of LBA Valid Ranges log page (Page 0000h) | 503 |
| A.12.3 LBA Status log pages | 503 |
| A.12.4 LBA Status Descriptor | 504 |
| A.13 LPS Mis-alignment log (Log Address 0Dh) | 505 |
| A.14 NCQ Command Error log (Log Address 10h) | 507 |
| A.14.1 Overview | 507 |
| A.14.2 NCQ TAG field | 507 |
| A.14.3 NQ bit | 507 |
| A.14.4 UNL bit | 508 |
| A.14.5 Return Fields | 508 |
| A.14.6 NCQ Autosense | 508 |
| A.14.7 Checksum | 508 |
| A.15 Read Stream Error log (Log Address 22h) | 509 |
| A.16 SATA Phy Event Counters log (Log Address 11h) | 510 |
| A.17 SATA NCQ Queue Management log (Log Address 12h) | 512 |

| | | |
|-----------------------|--|-----|
| A.17.1 | Overview | 512 |
| A.17.2 | SUPPORTS ABORT NCQ QUEUE bit | 512 |
| A.17.3 | SUPPORTS ABORT ALL AT bit | 512 |
| A.17.4 | SUPPORTS ABORT STREAMING AT bit | 512 |
| A.17.5 | SUPPORTS ABORT NON-STREAMING AT bit | 513 |
| A.17.6 | SUPPORTS ABORT SELECTED TTAG AT bit | 513 |
| A.17.7 | SUPPORTS DEADLINE HANDLING bit | 513 |
| A.17.8 | SUPPORTS WDNC bit | 513 |
| A.17.9 | SUPPORTS RDNC bit | 513 |
| A.18 | SATA NCQ Send and Receive log (Log Address 13h) | 514 |
| A.18.1 | Overview | 514 |
| A.18.2 | SFQ DATA SET MANAGEMENT SUPPORTED bit | 514 |
| A.18.3 | SFQ DATA SET MANAGEMENT SUPPORTS TRIM bit | 514 |
| A.19 | Selective Self-Test log (Log Address 09h) | 515 |
| A.20 | SMART Self-Test log (Log Address 06h) | 517 |
| A.21 | Summary SMART Error log (Log Address 01h) | 518 |
| A.22 | Write Stream Error log (Log Address 21h) | 521 |
| A.23 | Current Device Internal Status Data log (Log Address 24h) | 522 |
| A.23.1 | Overview | 522 |
| A.23.2 | Current Device Internal Status Data header page | 523 |
| A.23.3 | Current Device Internal Status data pages | 525 |
| A.23.4 | Examples of data area usage | 525 |
| A.24 | Saved Device Internal Status Data log (Log Address 25h) | 527 |
| A.24.1 | Overview | 527 |
| A.24.2 | Saved Device Internal Status Data header page | 527 |
| A.24.3 | Current Device Internal Status data pages | 528 |
| A.25 | Device Statistics Notifications log (Log Address 0Ah) | 528 |
| Annex B (informative) | Command Set Summary | 532 |
| Annex C (informative) | How to Use SCT Commands | 559 |
| C.1 | How to Use SCT Commands Overview | 559 |
| C.2 | Examples of Log Page Command Sequences | 561 |
| C.3 | Issuing an SCT Command to a Device | 566 |
| C.3.1 | Step 1 – Build a Key Page | 566 |
| C.3.2 | Step 2 – Issue the SCT command | 567 |
| C.3.3 | Step 3 – Transfer Data if Required | 568 |
| C.3.4 | Step 4 – Final Status/SCT Command Completion | 569 |
| Annex D (informative) | Implementation Guidelines for 1 024- and 4 096-Byte Sector Sizes | 570 |
| D.1 | General | 570 |
| D.2 | Overview | 570 |
| D.3 | Implementation | 572 |
| D.3.1 | 4 096-Byte Physical Sector Size Implementation | 572 |
| D.3.2 | Reporting Alignment (512-Byte LBA Only) | 572 |
| D.3.3 | RMW operations (512-Byte LBA Only) | 573 |
| D.4 | Implementation Issues (512-Byte LBA Only) | 573 |
| D.4.1 | Overview | 573 |
| D.4.2 | Drive Partitioning | 574 |
| D.4.3 | File System Formatting | 575 |
| D.4.4 | Virtual Memory accessing | 575 |
| D.4.5 | Bootting | 575 |
| Bibliography | | 576 |