ISO/IEC 10192-4-2:2024-09 (E)

Information technology - Home electronic system (HES) interfaces - Part 4-2: Common user interface and cluster-to-cluster interface to support interworking among home cluster systems - Interfaces, services and objects

Contents

Page

FOREWORD 4
INTRODUCTION 6
1 Scope 8
2 Normative references 8
3 Terms, definitions, and abbreviated terms 9
3.1 Terms and definitions 9
3.2 Abbreviated terms 10
4 Conformance 11
5 HES components for common user interface 11
6 Common user interface 13
7 CUI operational information 13
7.1 Usage 13
7.2 CUI operational information composition 15
7.3 Delivery of CUI operational information 15
7.4 Interoperability of heterogeneous CUI operational information 16
7.5 CUI selection and resultant actions for handling devices 16
7.5.1 General 16
7.5.2 Acquisition of user's set of devices 17
7.5.3 Synchronization of user devices 17
7.5.4 Handling of request and response for user devices 17
8 Secure C2C connection 17
9 C2C authorization 18
9.1 General 18
9.2 User identity federation 18
9.3 C2C authorization procedure 21
10 C2C interface 22
11 CUI service 22
12 C2C interworking application ISEE group 22
12.1 General 22
12.2 C2C authorization controller service 23
12.3 C2C authorization processor service 23
12.4 C2C controller service 23
12.5 C2C processor service 24
12.6 Other services 24
12.7 HAN interface module 25
13 Privacy, security, and safety considerations 25
Bibliography 26

Figure 1 – Core interoperability and HES standards 7

Figure 2 – HES gateway applications standards 7
Figure 3 – CUI components of alternative #1: common user interface in a cluster 12
Figure 4 – CUI components of alternative #2: common user interface as a separate device 12
Figure 5 – CUI components of alternative #3: common user interface in a service module 12
Figure 6 – Translation between CUI operational information and interactive media 13
Figure 7 – Interactive visual and touch media 14
Figure 8 – Interactive speaker and voice media 14
Figure 9 – Interoperability of heterogenous CUI systems 16
Figure 10 – TLS based C2C secure connection 18
Figure 11 – Configuration of user identities and devices 19
Figure 12 – Configuration of user identity federation table 21
Figure 13 – C2C authorization procedure 22
Figure 14 – Structure of C2C interworking application ISEE group 23
Figure 15 – Address referencing of binding map service to a device in a cluster 24

Table 1 – Correlation between roles in OAuth 2.0 and CUI components 21