

ISO/IEC TR 11801-9906:2025-01 (E)

Information technology - Generic cabling for customer premises - Part 9906: Balanced 1-pair cabling channels up to 600 MHz for single pair Ethernet (SPE)

Contents	Page
FOREWORD.....	4
INTRODUCTION.....	6
1 Scope.....	7
2 Normative references	7
3 Terms, definitions and symbols.....	8
3.1 Terms and definitions.....	8
3.2 Symbols.....	8
4 Single-pair Ethernet (SPE) link segment specifications	8
4.1 General.....	8
4.2 Link segment specifications	8
4.3 Environmental classifications	9
4.4 SPE link segment signal transmission specifications.....	9
4.4.1 SPE link segment return loss (RL)	9
4.4.2 SPE link segment insertion loss (IL)	10
4.4.3 SPE link segment unbalance attenuation and coupling attenuation	11
4.4.4 SPE link segment alien (exogenous) crosstalk	14
4.4.5 SPE link segment DC loop resistance	16
4.4.6 SPE link segment propagation delay.....	16
5 Balanced single-pair cabling channels	16
5.1 General.....	16
5.2 Component specifications	17
5.3 Environmental classifications	17
5.4 Channel reference implementations	17
Annex A (informative) Balanced single-pair cable specifications	18
A.1 General.....	18
A.2 Cables using alternative conductor sizes	18
A.3 Balanced single-pair cable specifications	19
A.3.1 Return loss (RL)	19
A.3.2 Insertion loss (IL).....	19
A.3.3 Unbalance attenuation and coupling attenuation	20
A.3.4 Alien (exogenous) crosstalk	22
A.3.5 DC resistance	24
A.3.6 Propagation delay.....	24
Annex B (informative) Balanced single-pair connector specifications	25
Annex C (informative) Conductor size effects for reduced insertion loss	26
C.1 Channel parameters affected by conductor size and AWG	26
C.2 IL parameter variation due to conductor size variation	27
C.3 AWG	27
Bibliography.....	28

Table 1 – SPE link segment characteristics.....	9
Table 2 – SPE link segment return loss (RL).....	10
Table 3 – SPE link segment IL	11
Table 4 – SPE link segment TCL	12
Table 5 – SPE link segment ELTCTL	13
Table 6 – SPE link segment coupling attenuation.....	14
Table 7 – SPE link segment PS ANEXT	15
Table 8 – SPE link segment PS AACR-F.....	15
Table 9 – SPE link segment DC loop resistance.....	16
Table 10 – SPE link segment propagation delay	16
Table 11 – Balanced single-pair cabling channels.....	17
Table A.1 – Balanced single-pair cable standards.....	18
Table A.2 – Balanced single-pair cable RL.....	19
Table A.3 – Balanced single-pair cable IL	19
Table A.4 – Balanced single-pair cable TCL.....	20
Table A.5 – Balanced single-pair cable ELTCTL	21
Table A.6 – Balanced single-pair cable coupling attenuation and low-frequency coupling attenuation.....	22
Table A.7 – Balanced single-pair cable PS ANEXT	23
Table A.8 – Balanced single-pair cable PS AACR-F.....	23
Table A.9 – Balanced single-pair cable DC resistance	24
Table A.10 – Balanced single-pair cable propagation delay	24
Table B.1 – Balanced single-pair connector standards.....	25
Table C.1 – Conductor diameter IL factors to be used with example 24 AWG cable with 1,8 conductor IL coefficient.....	26

