ISO/IEC 10192-4-3:2025-07 (E)

Information technology - Home electronic system (HES) interfaces - Part 4-3: Common user interface and cluster-to-cluster interface to support interworking among home cluster systems - Messaging

Contents

Page

FOREWORD 3
INTRODUCTION 5
1 Scope 7
2 Normative references 7
3 Terms, definitions, and abbreviated terms 8
3.1 Terms and definitions 8
3.2 Abbreviated terms 9
4 Conformance 9
5 Messaging architecture for CUI 9
6 Messaging for handling devices 11
6.1 Operations 11
6.1.1 CUI messaging over the C2C interface 11
6.1.2 CUI messaging within the HES gateway 11
6.1.3 CUI messaging within a cluster or the separate device 12
6.2 HES-CLIP messaging flows 12
6.2.1 Overview 12
6.2.2 Retrieval of all devices of a user 13
6.2.3 Retrieval of a device property 14
6.2.4 Update of a device property 15
6.2.5 Subscription to an event of a device 17
6.2.6 Notification of an event of a device 19
6.3 HES-CLDPE messaging flows 19
7 Messaging for user object relationship 20
8 Messaging for C2C authorization 21
9 Messaging for C2C interface 23
10 Privacy, security, and safety considerations 23
Bibliography 24

Figure 1 – Core interoperability and HES standards 6
Figure 2 – HES gateway applications standards 6
Figure 3 – Messaging architecture of alternative #1: common user interface in a cluster 10
Figure 4 – Messaging architecture of alternative #2: common user interface in a separate device 10
Figure 5 – Messaging architecture of alternative #3: common user interface in a service module 11
Figure 6 – CUI messaging within a cluster or a separate device 12
Figure 7 – Messaging flow for retrieval of all devices of a user 13
Figure 8 – Messaging flow for retrieval of a device property 14
Figure 9 – Messaging flow for update of a device property 16
Figure 10 – Messaging flow for subscription to an event of a device 17

Figure 11 – Messaging flow for notification of an event of a device 19
Figure 12 – User object relationships 21
Figure 13 – Messaging for setup of user object relationship 21
Figure 14 – Messaging flow for creating a user identity federation 22
Figure 15 – Messaging flow for adding a user identity into existing federation 22
Figure 16 – Messaging flow for issuing, using and verifying an access token 23

Table 1 – Description of messages for retrieval of all devices of a user 13
Table 2 – Description of parameters in HES-CLIP messages for retrieval of all devices of a user 14
Table 3 – Description of messages for retrieval of a device property 15
Table 4 – Description of parameters in HES-CLIP messages for retrieval of a device property 15
Table 5 – Description of messages for update of a device property 16
Table 6 – Description of parameters in HES-CLIP messages for update of a device property 17
Table 7 – Description of messages for subscription to an event of a device 18
Table 8 – Description of parameters in HES-CLIP messages for subscription to an event of a device 18
Table 9 – Description of messages for notification of an event of a device 19
Table 10 – Description of parameters in HES-CLIP messages for notification of an event of a device 19