

ISO/IEC 14543-4-303:2026-06 (E)

Information technology - Home electronic system (HES) architecture - Part 4-303: Application protocol for electric vehicle supply equipment (EVSE) chargers and controllers

Contents	Page
INTRODUCTION	5
1 Scope	6
2 Normative references	6
3 Terms, definitions, and abbreviated terms	6
3.1 Terms and definitions	6
3.2 Abbreviated terms	8
4 Conformance	8
5 Configuration	8
6 Application layer	10
6.1 General	10
6.2 NECD objects	10
6.3 NECD services	11
6.4 Object-specific NECD properties	11
6.5 Application operation	13
6.5.1 General	13
6.5.2 Continuous requests	13
6.5.3 Response wait time value for controllers	13
6.5.4 Resending a frame	13
6.5.5 Processing object property counter	13
6.5.6 Property values of write requests	13
6.5.7 Property values of read requests	14
7 Normal operation	14
7.1 General	14
7.2 Start-up operation	15
7.2.1 General	15
7.2.2 Start-up processing of NECD nodes	15
7.2.3 Search processing	16
7.2.4 Obtaining NECD attribute information	16
7.2.5 Obtaining EVSE charger attribute information	17
7.3 Occasional operation	18
7.3.1 General	18
7.3.2 Obtaining vehicle connection and chargeable status	18
7.3.3 Controlling EVSE charger	20
7.4 Fault status notification	22
8 Remote control	22
9 Considerations on controllers	23
Annex A (informative) Terms and NECD protocol frame format on ISO/IEC 14543-4-3 and IEC 62394	24

A.1	Terms correspondence between ISO/IEC 14543-4-3 and IEC 62394	24
A.2	NECD protocol frame format	24
Annex B (informative)	Communication link between EVSE charger and CEM in IEC 63380-1	26
Annex C (informative)	Relationship between ISO/IEC 14543-4 series and the HES gateway, based on ISO/IEC 15045 series and ISO/IEC 18012 series	27
	Bibliography	34
Figure 1 – Relationship between IEC 62394, ISO/IEC 14543-4-3, and ISO/IEC 14543-4-303		5
Figure 2 – Physical configuration, and the path and direction of electricity and communication		9
Figure 3 – NECD configurations		9
Figure 4 – Assumed network stack		10
Figure 5 – Summary of normal operation sequences		15
Figure 6 – Sequence for obtaining NECD attribute information		17
Figure 7 – Sequence of obtaining EVSE charger attribute information		18
Figure 8 – Sequence to obtain vehicle connection and chargeable status of EVSE charger		19
Figure 9 – Sequence to control EVSE charger		21
Figure 10 – Remote control		22
Figure A.1 – NECD protocol frame format		25
Figure B.1 – Communication link between EVSE charger and CEM in IEC 63380-1		26
Figure C.1 – Measurement points for AC EVSEs translated into ISO/IEC 18012-3		32
Figure C.2 – Measurement points for DC EVSEs translated into ISO/IEC 18012-3		33
Table 1 – NECD objects for EVSE chargers		10
Table 2 – NECD objects for controllers		11
Table 3 – NECD services		11
Table 4 – NECD properties of device object (super class)		11
Table 5 – NECD properties of device object		12
Table 6 – Response wait time values for controllers		13
Table A.1 – Terms correspondence table between ISO/IEC 14543-4-3 and IEC 62394		24
Table C.1 – List of the translation between ISO/IEC 14543-4-303, IEC 62394, and HES gateway lexicon (ISO/IEC 18012-3) supported		27
Table C.2 – List of the translation between ISO/IEC 14543-4-303, IEC 62394, and HES gateway lexicon (ISO/IEC 18012-3) not supported at this time		31