ISO/IEC 14543-4-304:2026-06 (E)

Information technology - Home electronic system (HES) architecture - Part 4-304: Application protocol for electric vehicle supply equipment (EVSE) charger and dischargers and controllers

Contents

Page

FOREWORD 3
INTRODUCTION 5
1 Scope 6
2 Normative references 6
3 Terms, definitions, and abbreviated terms 6
3.1 Terms and definitions 6
3.2 Abbreviated terms 8
4 Conformance 8
5 Configuration 8
6 Application layer 10
6.1 General 10
6.2 NECD objects 10
6.3 NECD services 11
6.4 Object-specific NECD properties 11
6.5 Application operation 13
6.5.1 General 13
6.5.2 Continuous requests 13
6.5.3 Response wait time value for controllers 13
6.5.4 Resending a frame 14
6.5.5 Processing object property counter 14
6.5.6 Property values of write requests 14
6.5.7 Property values of read requests 14
7 Normal operation 15
7.1 General 15
7.2 Start-up operation 15
7.2.1 General 15
7.2.2 Start-up processing of NECD nodes 15
7.2.3 Search processing 16
7.2.4 Obtaining NECD attribute information 16
7.2.5 Obtaining EVSE charger and discharger attribute information 17
7.3 Occasional operation 18
7.3.1 General 18
7.3.2 Obtaining vehicle connection and chargeable or dischargeable status 18
7.3.3 Controlling EVSE charger and discharger when chargeable and not dischargeable 20
7.3.4 Controlling EVSE charger and discharger when dischargeable and not chargeable 23
7.3.5 Controlling EVSE charger and discharger when chargeable and dischargeable 25
7.4 Fault status notification 28
8 Remote control 28

9 Considerations on controllers 29
Annex A (informative) Terms and NECD protocol frame format on ISO/IEC 14543-4-3 and IEC 62394 30
A.1 Terms correspondence between ISO/IEC 14543-4-3 and IEC 62394 30
A.2 NECD protocol frame format 30
Annex B (informative) Communication link between EVSE charger and discharger and CEM in IEC 63380-1 32
Annex C (informative) Relationship between ISO/IEC 14543-4 series and the HES gateway, based on ISO/IEC 15045 series and ISO/IEC 18012 series 33
Bibliography 45

Figure 1 – Relationship between IEC 62394, ISO/IEC 14543-4-3, and ISO/IEC 14543-4-304 5
Figure 2 – Physical configuration, and the path and direction of electricity and communication 9
Figure 3 – Connection configurations 9
Figure 4 – Assumed network stack 10
Figure 5 – Summary of normal operation sequences 15
Figure 6 – Sequence for obtaining NECD attribute information 17
Figure 7 – Sequence of obtaining EVSE charger and discharger attribute information 18
Figure 8 – Sequence to obtain vehicle connection and chargeable status of EVSE charger and discharger 20
Figure 9 – Sequence to control EVSE charger and discharger when chargeable and not dischargeable 22
Figure 10 – Sequence to control EVSE charger and discharger when dischargeable and not chargeable 24
Figure 11 – Sequence to control EVSE charger and discharger when chargeable and dischargeable 27
Figure 12 – Remote control 28
Figure A.1 – NECD protocol frame format 31
Figure B.1 – Communication link between EVSE charger and discharger and CEM in IEC 63380-1 32
Figure C.1 – Measurement points for AC EVSEs translated into ISO/IEC 18012-3 44
Figure C.2 – Measurement points for DC EVSEs translated into ISO/IEC 18012-3 44

Table 1 – NECD objects for EVSE charger and dischargers 10
Table 2 – NECD objects for controllers 10
Table 3 – NECD services 11
Table 4 – NECD properties of device object (super class) 11
Table 5 – NECD properties of device object 12
Table 6 – Response wait time values for controllers 13
Table A.1 – Terms correspondence table between ISO/IEC 14543-4-3 and IEC 62394 30
Table C.1 – List of the translation between ISO/IEC 14543-4-304, IEC 62394, and HES gateway lexicon (ISO/IEC 18012-3) supported 33
Table C.2 – List of the translation between ISO/IEC 14543-4-304, IEC 62394, and HES gateway lexicon (ISO/IEC 18012-3) not supported at this time 42