

ISO/IEC 14543-4-304:2026-06 (E)

Information technology - Home electronic system (HES) architecture - Part 4-304: Application protocol for electric vehicle supply equipment (EVSE) charger and dischargers and controllers

Contents	Page
FOREWORD	3
INTRODUCTION	5
1 Scope	6
2 Normative references	6
3 Terms, definitions, and abbreviated terms	6
3.1 Terms and definitions	6
3.2 Abbreviated terms	8
4 Conformance	8
5 Configuration	8
6 Application layer	10
6.1 General	10
6.2 NECD objects	10
6.3 NECD services	11
6.4 Object-specific NECD properties	11
6.5 Application operation	13
6.5.1 General	13
6.5.2 Continuous requests	13
6.5.3 Response wait time value for controllers	13
6.5.4 Resending a frame	14
6.5.5 Processing object property counter	14
6.5.6 Property values of write requests	14
6.5.7 Property values of read requests	14
7 Normal operation	15
7.1 General	15
7.2 Start-up operation	15
7.2.1 General	15
7.2.2 Start-up processing of NECD nodes	15
7.2.3 Search processing	16
7.2.4 Obtaining NECD attribute information	16
7.2.5 Obtaining EVSE charger and discharger attribute information	17
7.3 Occasional operation	18
7.3.1 General	18
7.3.2 Obtaining vehicle connection and chargeable or dischargeable status	18
7.3.3 Controlling EVSE charger and discharger when chargeable and not dischargeable	20
7.3.4 Controlling EVSE charger and discharger when dischargeable and not chargeable	23
7.3.5 Controlling EVSE charger and discharger when chargeable and dischargeable	25
7.4 Fault status notification	28
8 Remote control	28

9	Considerations on controllers	29
	Annex A (informative) Terms and NECD protocol frame format on ISO/IEC 14543-4-3 and IEC 62394	30
	A.1 Terms correspondence between ISO/IEC 14543-4-3 and IEC 62394	30
	A.2 NECD protocol frame format	30
	Annex B (informative) Communication link between EVSE charger and discharger and CEM in IEC 63380-1	32
	Annex C (informative) Relationship between ISO/IEC 14543-4 series and the HES gateway, based on ISO/IEC 15045 series and ISO/IEC 18012 series	33
	Bibliography	45
	 Figure 1 – Relationship between IEC 62394, ISO/IEC 14543-4-3, and ISO/IEC 14543-4-304	5
	Figure 2 – Physical configuration, and the path and direction of electricity and communication	9
	Figure 3 – Connection configurations	9
	Figure 4 – Assumed network stack	10
	Figure 5 – Summary of normal operation sequences	15
	Figure 6 – Sequence for obtaining NECD attribute information	17
	Figure 7 – Sequence of obtaining EVSE charger and discharger attribute information	18
	Figure 8 – Sequence to obtain vehicle connection and chargeable status of EVSE charger and discharger	20
	Figure 9 – Sequence to control EVSE charger and discharger when chargeable and not dischargeable	22
	Figure 10 – Sequence to control EVSE charger and discharger when dischargeable and not chargeable	24
	Figure 11 – Sequence to control EVSE charger and discharger when chargeable and dischargeable	27
	Figure 12 – Remote control	28
	Figure A.1 – NECD protocol frame format	31
	Figure B.1 – Communication link between EVSE charger and discharger and CEM in IEC 63380-1	32
	Figure C.1 – Measurement points for AC EVSEs translated into ISO/IEC 18012-3	44
	Figure C.2 – Measurement points for DC EVSEs translated into ISO/IEC 18012-3	44
	 Table 1 – NECD objects for EVSE charger and dischargers	10
	Table 2 – NECD objects for controllers	10
	Table 3 – NECD services	11
	Table 4 – NECD properties of device object (super class)	11
	Table 5 – NECD properties of device object	12
	Table 6 – Response wait time values for controllers	13
	Table A.1 – Terms correspondence table between ISO/IEC 14543-4-3 and IEC 62394	30
	Table C.1 – List of the translation between ISO/IEC 14543-4-304, IEC 62394, and HES gateway lexicon (ISO/IEC 18012-3) supported	33
	Table C.2 – List of the translation between ISO/IEC 14543-4-304, IEC 62394, and HES gateway lexicon (ISO/IEC 18012-3) not supported at this time	42