

ISO/IEC 14165-114 :2005-04 (E)

Information technology_ - Fibre Channel_ - Part_114: 100 MB/s Balanced copper physical interface (FC-100-DF-EL-S)

CONTENTS

- FOREWORD.....5
- INTRODUCTION.....6
- 1 Scope7
- 2 Normative references7
- 3 Definitions, symbols and abbreviations.....8
 - 3.1 Definitions8
 - 3.2 Symbols9
 - 3.3 Abbreviations9
- 4 MAC interface9
 - 4.1 General9
 - 4.2 Overview9
 - 4.3 Detailed specification.....10
 - 4.3.1 RD<7:0> received data10
 - 4.3.2 RV receive valid.....10
 - 4.3.3 RE receive error.....10
 - 4.3.4 RCLK receive clock.....10
 - 4.3.5 TD<7:0> transmit data.....10
 - 4.3.6 TV transmit valid.....11
 - 4.3.7 TE transmit error.....11
 - 4.3.8 TCLK transmit clock11
 - 4.3.9 DC characteristics.....11
 - 4.3.10 MAC characteristics11
 - 4.3.11 MAC, GMII and MII interfaces.....11
 - 4.4 Testing.....12
 - 4.5 Data stream.....12
 - 4.6 Service control functions.....12
 - 4.7 Timers.....13
 - 4.8 Delay requirements.....13
 - 4.9 Reset13
- 5 Operation13
 - 5.1 Detail of the physical interfaces13
 - 5.2 Signalling14
 - 5.3 Frame format.....14
 - 5.4 Functions at the MAC interface15
- 6 Coding15
 - 6.1 Timers.....15
 - 6.2 Receive status OK.....15
 - 6.3 Errors.....15
 - 6.4 PHY control15
 - 6.5 Bit error rate.....15
- 7 Test15

7	Test	15
7.1	General	15
7.2	Tests	16
7.3	Fixtures	16
7.4	Interoperability compliance points	16
8	Transmitter signal	16
8.1	General	16
8.2	Differential output voltage and accuracy	16
8.3	Scrambling	16
8.4	Transmit eye diagram	17
8.5	Jitter	17
9	Receiver signal	18
9.1	General	18
9.2	Differential input voltage and accuracy	18
9.3	Descrambling	18
9.4	Receive eye diagram	18
10	Electrical and mechanical requirements	19
10.1	Isolation	19
10.2	Clock frequency	19
10.3	Receiver common mode rejection	19
10.4	Transmitter common mode output voltage	19
10.5	Input tolerance	19
10.6	Return loss	20
10.7	Connector	20
10.8	Connector configuration	20
11	Cabling channel	20
11.1	General conditions	20
11.2	External noise	20
12	Environmental	20
12.1	Safety	20
12.2	Grounding	20
12.3	Telephone voltages	21
12.4	Susceptibility	21
12.5	Temperature and humidity	21
12.6	Labelling	21
	BIBLIOGRAPHY	22

Figure 1 – Model.....	6
Figure 2 – MAC interface	9
Figure 3 – Interface overview via 100 Ω Class F cabling	10
Figure 4 – MAC interface data stream	12
Figure 5 - State diagram of MLT-3.....	13
Figure 6 – Coding scheme of MLT-3.....	13
Figure 7 – Transmission with MLT-3.....	14
Figure 8 – Frame format	14
Figure 9 – Scrambler polynomial and correspondent circuit diagram	16
Figure 10 – Transmission eye diagram	17
Figure 11 – Transmission eye diagram detail.....	17
Figure 12 – Receiver eye diagram.....	18
Figure 13 – Receiver common mode rejection test.....	19
Figure 14 – Common mode voltage test	19
Table 1 – DC characteristics	11
Table 2 – AC characteristics	11
Table 3 – Signal mapping.....	12
Table 4 – Delay requirements	13
Table 5 – Control functions	15
Table 6 – Eye diagram mask at points R1 and R2.....	18
Table 7 – Return loss.....	20
Table 8 – Connector configuration.....	20