ISO/IEC 14165-241 :2005-06 (E)

Information technology_- Fibre Channel_- Part_241: Backbone 2 (FC-BB-2)

Contents

FOREWORD 10

INTRODUCTION 11

1 Scope 13

2 Normative references 13
2.1 Approved references 13
2.2 Other references 13

3 Definitions and Conventions 14
3.1 Common Defintions 14
3.2 FC-BB-2_ATM Definitions 15
3.3 FC-BB-2_SONET Definitions 17
3.4 FCIP and TCP/IP Definitions 18
3.5 Symbols and abbreviations 20
3.5.1 General 20
3.5.2 FC-BB-2_ATM 20
3.5.3 FC-BB-2_SONET 21
3.5.4 FC-BB-2_IP 21
3.6 Keywords 21
3.6.1 expected 21
3.6.2 invalid 21
3.6.3 mandatory 22
3.6.4 may 22
3.6.5 may not 22
3.6.6 obsolete 22
3.6.7 optional 22
3.6.8 reserved 22
3.6.9 shall 22
3.6.10 should 22
3.7 Conventions 22
3.8 Notations for Procedure and Functions 23

4 FC-BB-2 Structure and Concepts 24
4.1 FC-BB-2 Backbone Mappings 24
4.2 FC-BB-2 Reference Models 24
4.3 FC-BB-2 Specifications Overview 25
4.3.1 FC-BB-2_ATM 25
4.3.2 FC-BB-2_SONET 26
4.3.3 FC-BB-2_IP 26
4.4 FC-BB-2 Requirements 26
4.4.1 Fibre Channel Class support 26
4.4.2 Payload transparency 27
4.4.3 Latency delay and timeout value 27
4.4.4 QoS and bandwidth 27
4.4.5 In-order delivery 27
4.4.6 Flow control 27
4.5 FC-BB-2 Link Service Codes 28

5 FC-BB-2_ATM and FC-BB-2_SONET messages and formats 29
5.1 Applicability 29

5.2 Message Formats 29
5.2.1 LLC/SNAP Header format 29
5.2.2 BBW_Header format 30
5.2.3 BBW message payload format for SFC 31
5.2.4 BBW message payload format for SR 31
5.2.4.1 SR_Header Formats 31
5.2.4.2 SR_BBW messages 33
5.2.4.3 Format Field Parameters 34
5.2.4.4 SR Commands and Responses 34
5.2.4.5 Exception condition reporting and recovery 37

6 The SR and SFC Protocol Procedures 41
6.1 Applicability 41
6.2 SR Protocol Overview 41
6.3 Description of the SR procedure 42
6.3.1 SR mode of operation 42
6.3.2 SR procedure for addressing 42
6.3.3 SR procedure for the use of the P/F bit 42
6.3.4 SR procedure for data link set-up and disconnection 42
6.3.4.1 Data link set-up 42
6.3.4.2 Information transfer phase 43
6.3.4.3 Data link disconnection 43
6.3.4.4 Disconnected Phase 44
6.3.4.5 Collision of unnumbered commands 44
6.3.4.6 Collision of SR_DM response with SR_SM or SR_DISC command . 45
6.3.4.7 Collision of SR_DM responses 45
6.3.5 Procedures for information transfer using multi-selective reject 45
6.3.5.1 Procedures for SR_I messages 45
6.3.5.2 Sending new SR_I messages 45
6.3.5.3 Receiving an in-sequence SR_I message 45
6.3.5.4 Reception of invalid messages 46
6.3.5.5 Reception of out-of-sequence SR_I messages 46
6.3.5.6 Receiving acknowledgement 47
6.3.5.7 Receiving a SR_SREJ response message 47
6.3.5.8 Receiving a SR_RNR message 48
6.3.5.9 BBW busy condition 48
6.3.5.10 Awaiting acknowledgement 49
6.3.5.11 Receiving a SR_RR response messages with the F bit set to 1 49
6.3.5.12 Responding to command messages with the P bit set to 1 50
6.3.6 SR conditions for data link resetting or data link re-initialization (data link set-up) 50
6.3.6.1 Condition 1 50
6.3.6.2 Condition 2 50
6.3.6.3 Condition 3 50
6.3.6.4 Condition 4 50
6.3.7 SR procedure for data link resetting 50
6.3.7.1 Procedure 1 50
6.3.7.2 Procedure 2 51
6.3.7.3 Procedure 3 51
6.3.8 List of SR system parameters 52
6.3.8.1 Timer T1 52
6.3.8.2 Parameter T2 52
6.3.8.3 Maximum number of attempts to complete a transmission N2 52
6.3.8.4 Maximum number of outstanding SR_I messages k 52

6.4 Simple Flow Control (SFC) 53

7 FC-BB-2_ATM Structure and Concepts 54
7.1 Applicability 54
7.2 FC-BB-2_ATM Overview 54
7.3 FC-BB-2_ATM Functional Model 55
7.3.1 B_Port Network Interface 55
7.3.2 ATM Network Interface 55
7.3.3 Mapping and Encapsulation. 55
7.3.4 FC-BB-2_ATM Forwarding 56
7.3.5 Call Handling and ATM Service 56
7.3.6 Frame Handling 57

8 Mapping and Message Encapsulation using AAL5 58
8.1 Applicability 58
8.2 Overview. 58
8.3 Mapping BBW messages to AAL5. 58

9 FC-BB-2_ATM Service Considerations. 61
9.1 Applicability 61
9.2 ATM Service Type 61
9.3 Latency Delay and Timeout Value 61
9.4 Bandwidth Sharing and Allocation. 61
9.5 Quality of Service (QoS) 62
9.6 Delivery Order 62
9.7 Loss and Flow Control 63

10 FC-BB-2_SONET Structure and Concepts 64
10.1 Applicability and Related Clauses 64
10.2 FC-BB-2_SONET Overview 64
10.3 FC-BB-2_SONET Functional Model 65
10.3.1 Fibre Channel Network Interface. 65
10.3.2 SONET Network Interface 66
10.3.3 Mapping and Encapsulation. 67
10.3.4 FC-BB-2_SONET Forwarding 67
10.3.5 Call Handling. 67
10.3.6 Frame Handling 67

11 Mapping and Message Encapsulation using HDLC-like Framing 68
11.1 Applicability 68
11.2 Overview. 68
11.3 Mapping of BBW messages to HDLC format 68
11.4 Mapping HDLC frames to SONET/SDH 70

12 FC-BB-2_SONET Service Considerations 74
12.1 Applicability 74
12.2 Latency Delay and Timeout Value 74
12.3 Delivery Order 74
12.4 Loss and Flow Control 74

13 FC-BB-2_IP Structure and Concepts. 75
13.1 Applicability and Related Clauses 75
13.2 FC-BB-2_IP Overview 75
13.3 VE_Port Functional Model 76

13.3.1 FC-BB-2_IP Interface Protocol Layers 76
13.3.2 E_Port/F_Port FC Interface 76
13.3.3 FC-BB-2_IP Protocol Interface 76
13.3.3.1 Major Components 76
13.3.3.2 FC Switching Element (SE) with FC Routing 77
13.3.3.3 FC and FCIP Entities 78
13.3.3.4 VE_Port Virtual ISL Exchanges 80
13.3.3.5 Control and Service Module (CSM) 81
13.3.3.6 Platform Management Module (PMM) 82
13.3.4 IP Network Interface 84
13.4 The B_Access Functional Model 84
13.4.1 FC-BB-2_IP Interface Protocol Layers 84
13.4.2 B_Port FC Interface 84
13.4.3 FC-BB-2_IP Protocol Interface 85
13.4.3.1 Major Components 85
13.4.3.2 FC and FCIP Entities 85
13.4.3.3 B_Access Virtual ISL Exchanges 87
13.4.3.4 B_Port Control and Service Module (CSM) 90
13.4.3.5 B_Port Platform Management Module (PMM) 90
13.4.4 IP Network Interface 90
13.5 FC-BB-2_IP Network Topologies 91

14 Mapping and Message Encapsulation using TCP/IP 93
14.1 Applicability 93
14.2 Encapsulated Frame Structures 93
14.2.1 FC frame Encapsulation Structure 93
14.2.2 Encapsulated FCIP Special Frame (FSF) structure 94
14.3 TCP/IP Encapsulation 95

15 The FC-BB-2_IP Protocol Procedures 96
15.1 Applicability 96
15.2 FC-BB-2_IP Protocol Procedures 96
15.3 Procedures for Platform Management 96
15.3.1 Function 96
15.3.2 Procedures for Discovery 96
15.3.3 Procedures for Extending FC-SP Security 96
15.3.3.1 Authentication Mechanisms 96
15.3.3.2 Authenticate Special Frame (ASF) 97
15.4 Procedures for Connection Management 98
15.4.1 Function 98
15.4.2 Procedures for Link Setup 98
15.4.3 Procedures for Data Transfer 99
15.4.4 Procedures for FCIP Link Disconnection 99
15.4.5 Procedures for Multiple Connection Management 99
15.5 Procedures for Error Detection Recovery 100
15.5.1 Procedures for Handling Invalid FC frames 100
15.5.2 Procedures for Error Recovery 100
15.6 List of FC-BB-2_IP System Parameters 101
15.6.1 FC Timers 101
15.6.2 TCP Timers 101
15.6.3 Maximum number of attempts to complete an Encapsulated FC Frame transmission 101
15.6.4 Maximum number of outstanding Encapsulated FC Frames 101

16 FC-BB-2_IP Service Considerations 102
16.1 Applicability 102
16.2 Latency Delay 102
16.3 Throughput 102
16.3.1 How Timeouts affect Throughput 102
16.3.2 How loss affects Throughput 102
16.3.3 Other factors that affect Throughput 102
16.4 Reliability 103
16.4.1 Loss of Connectivity 103
16.4.2 Loss of Synchronization 103
16.4.3 Loss or Corruption of TCP Segments 103
16.4.4 Loss or Corruption of FC frames 103
16.4.5 FCIP Error Reporting 103
16.5 Quality of Service (QoS) 104
16.6 Delivery Order 104
16.7 IP Multicast and Broadcast 104
16.8 Security and Authentication 104

Annex A (normative) **Encoded SOF and EOF Ordered Sets 105**
A.1 Ordered Sets 105
A.2 SOF and EOF OS-Codes 105
A.3 FC-BB-2 SOF OS codes 106
A.4 FC-BB-2 EOF OS codes 106

Annex B (informative) **ATM Traffic Management and Signaling 108**
B.1 ATM Traffic Management 108
B.2 ATM QoS Parameters 108
B.3 ATM Traffic Parameters 111
B.4 ATM Service Categories 112
B.5 ATM Adaptation Layer (AAL) Types 114
B.6 ATM Multiplexing 114
B.7 Summary of ATM Services and Guarantees 115
B.8 ATM Signaling UNI Standard 115

Annex C (informative) **SR Protocol Parameter Guidelines and State Diagram 118**
C.1 Assumptions 118
C.2 Calculated Ack Delay (T2) Timer variable 118
C.3 Calculated Window size 118
C.4 Calculated Ack (T1) Timer variable 118
C.5 SR Protocol State Diagram 119

Bibliography 121

Figure

Figure 1 – Scope and components of FC-BB-2 specification 11
Figure 2 – FC-BB-2_ATM Reference Model 24
Figure 3 – FC-BB-2_SONET Reference Model 25
Figure 4 – FC-BB-2_IP Reference Model. 25
Figure 5 – SR Flow Control Protocol Between two BBWs 41
Figure 6 – FC-BB-2_ATM Network Configuration 54
Figure 7 – FC-BB-2_ATM Functional Block Diagram. 56
Figure 8 – AAL5 Mapping of a BBW message with SFC 59
Figure 9 – AAL5 Mapping of a BBW message with SR. 60
Figure 10 – Recommended ATM Bandwidth Allocation for multiple VCs 61
Figure 11 – FC-BB-2_SONET Network Configuration 64
Figure 12 – FC-BB-2_SONET Functional Block Diagram. 66
Figure 13 – SONET SPE HDLC Mapping Example. 71
Figure 14 – Path Signal label: C2 71
Figure 15 – Encapsulation of BBW message into HDLC frame using SFC 72
Figure 16 – Encapsulation of BBW message into HDLC frame using SR 73
Figure 17 – FC-BB-2_IP Network Configuration 75
Figure 18 – FC-BB-2_IP VE_Port Functional Model 77
Figure 19 – FC-BB-2_IP Protocol Layers 78
Figure 20 – Scope of VE_Port Virtual ISL 80
Figure 21 – Security Layers. 83
Figure 22 – FC-BB-2_IP B_Access Functional Model 86
Figure 23 – Scope of B_Access Virtual ISL 87
Figure 24 – B_Access Initialization State Machine. 90
Figure 25 – FC-BB-2_IP Network Topologies 92
Figure 26 – TCP/IP Encapsulation of an Encapsulated FC Frame 95
Figure B.1 – Cell Transfer Delay Distribution 110
Figure B.2 – SVC Signaling at the UNI and Switched payload. 117
Figure C.1 – SR Protocol State Diagram. 119

Table

Table 1 – FC-BB-2 Organization. 12
Table 2 – ISO and International Conventions 23
Table 3 – Specification and FC Port Types Supported 24
Table 4 – FC-BB-2 SW_ILS Codes. 28
Table 5 – FC-BB-2 ELS Codes 28
Table 6 – BBW message structure. 29
Table 7 – LLC/SNAP Header 29
Table 8 – SNAP PID 30
Table 9 – BBW_Header. 30
Table 10 – Flow Control Protocol Type Encodings 30
Table 11 – BBW message payload structure for SFC 31
Table 12 – BBW message payload structure for SR 31
Table 13 – SR_Header format 32
Table 14 – SS bits encoding. 32
Table 15 – MMMMM bit encoding. 32
Table 16 – SR_BBW messages 33
Table 17 – SR_I message format. 35
Table 18 – SR_SREJ payload format 36
Table 19 – SR_FRMR payload format 38
Table 20 – Mapping of BBW messages to AAL5 CPCS 58
Table 21 – ATM VBR-NRT Service Specification. 62
Table 22 – SONET/SDH Data Rates. 66
Table 23 – Mapping of BBW messages to HDLC format. 69
Table 24 – FC-BB-2_SONET Protocol Stack 71
Table 25 – LKA payload 81
Table 26 – LKA Accept payload 81
Table 27 – EBP Request payload. 87
Table 28 – EBP Accept payload 88
Table 29 – EBP Reject Reason Code Explanation 88
Table 30 – TCP/IP Segment structure carrying Encapsulated FC Frame 93
Table 31 – Encapsulated FC Frame structure 93
Table 32 – TCP/IP Segment structure carrying Encapsulated FSF 94
Table 33 – Encapsulated FSF structure 94
Table 34 – ASF Request Payload 97
Table 35 – ASF Accept Response Payload 98
Table A.1 – Byte-encoded frame delimiter format 105
Table A.2 – OS-Code Definition 105
Table A.3 – FC-BB-2 SOF Codes 106
Table A.4 – FC-BB-2 EOF Codes 106
Table B.1 – I.356 defined QoS Parameters for different Traffic Classes 111
Table B.2 – Service Categories and its Traffic and QoS Attributes 113
Table B.3 – ATM Service Categories and Guarantees 115