ISO/IEC 14165-222 :2005-06 (E)

Information technology_- Fibre Channel_- Part_222: Single-byte command sets-2 mapping protocol (FC-SB-2)

Foreword 9

Introduction 10

1 Scope 12

2 Normative references 13
2.1 General information concerning references 13
2.2 Approved references 13
2.3 References under development 13

3 Definitions and conventions 14
3.1 Definitions 14
3.2 Keywords 15
3.3 Conventions 16
3.3.1 English usage conventions 16
3.3.2 FC-PH 17
3.3.3 Bit numbering 17
3.3.4 Binary notation 17
3.3.5 Hexadecimal notation 17
3.3.6 Abbreviations, acronyms and symbols 17

4 Structure and concepts 19
4.1 Introduction 19
4.2 FC-4 General description 19
4.3 SB-2 overview 19
4.3.1 SB-2 instance 19
4.3.2 SB-2 protocols 19
4.4 Channel-path elements 20
4.4.1 Overview of channel-path elements 20
4.4.2 Channel 20
4.4.3 Channel image 20
4.4.4 Control unit 21
4.4.5 Control-unit image 21
4.4.6 Link 22
4.5 Channel-path configurations 22
4.5.1 Channel-path configuration overview 22
4.5.2 Point-to-point configuration 22
4.5.3 Fabric configuration 23
4.5.4 Physical path 24
4.5.5 Logical path 25
4.5.6 Channel-to-channel communication 25
4.6 Information transfer 26
4.7 Protocols 27
4.7.1 Protocol overview 27
4.7.2 Link level 27
4.7.3 Device level 28
4.7.4 Addressing 28

5 FC-PH Link Control 30
5.1 FC-PH Link control overview 30

5.2 Class of service ---- 30
5.3 Buffer-to-buffer credit reclamation ---- 30
5.4 SB-2 Sequences and exchanges ---- 31
5.4.1 SB-2 sequences ---- 31
5.4.2 SB-2 exchange pairs ---- 31
5.5 FC-PH frame header fields ---- 33
5.5.1 Frame header field overview ---- 33
5.5.2 R_CTL field ---- 33
5.5.3 D_ID and S_ID fields ---- 33
5.5.4 CS_CTL ---- 34
5.5.5 TYPE field ---- 34
5.5.6 F_CTL field ---- 34
5.5.7 SEQ_ID ---- 34
5.5.8 DF_CTL ---- 34
5.5.9 SEQ_CNT ---- 34
5.5.10 OX_ID ---- 34
5.5.11 RX_ID ---- 34
5.5.12 Parameter field ---- 35
5.6 Other FC-PH mechanisms ---- 35

6 Link-Level functions ---- 36
6.1 Link-level function overview ---- 36
6.2 FC-PH Basic-link-services ---- 36
6.2.1 Abort sequence ---- 36
6.3 FC-PH Extended link services ---- 36
6.3.1 F_Port login ---- 36
6.3.2 N_Port login ---- 36
6.3.3 N_Port logout ---- 37
6.3.4 Reinstate recovery qualifier ---- 37
6.3.5 Registered state change notification ---- 37
6.3.6 State-change registration ---- 38
6.3.7 Request Node-Identification Data ---- 39
6.3.8 Registered Link-Incident Record ---- 43
6.3.9 Registered Link-Incident Record requests and responses ---- 43
6.3.10 Link-Incident-Record Registration ---- 47
6.4 SB-2 Link-control functions ---- 47
6.4.1 SB-2 Link-control function overview ---- 47
6.4.2 Establish logical path ---- 49
6.4.3 Remove logical path ---- 52
6.4.4 Logical path established ---- 52
6.4.5 Logical path removed ---- 53
6.4.6 Link-level acknowledgment ---- 54
6.4.7 Test initialization ---- 55
6.4.8 Test initialization result ---- 56
6.4.9 Link-level reject ---- 57
6.4.10 Link-level busy ---- 58

7 N_Port link initialization ---- 60
7.1 N_Port link initialization overview ---- 60
7.2 Link-initialization procedure ---- 61
7.3 Initialization process for a channel ---- 62

7.3.1 Channel initialization overview ---- 62
7.3.2 Channel login ---- 62
7.3.3 Channel Node-Identifier acquisition ---- 63
7.3.4 Channel state-change registration ---- 64
7.3.5 Channel Link-Incident-Record registration ---- 64
7.3.6 Channel Logical-Path establishment ---- 65
7.4 Initialization process for a control unit ---- 66
7.4.1 Control unit initialization overview ---- 66
7.4.2 Control-unit login ---- 66
7.4.3 Control unit node-identifier acquisition ---- 67
7.4.4 Control unit State-Change registration ---- 69
7.4.5 Control unit logical-path establishment ---- 69

8 SB-2 Information units ---- 71
8.1 SB-2 Information unit overview ---- 71
8.2 Rules for sending SB-2 IUs ---- 71
8.2.1 Overview of rules for sending SB-2 information units ---- 71
8.2.2 Rules for device-level functions ---- 72
8.3 SB-2 IU structure ---- 73
8.4 SB-2 header ---- 75
8.4.1 SB-2 header format ---- 75
8.4.2 Channel image ID ---- 75
8.4.3 Control-unit image ID ---- 75
8.4.4 Device address ---- 75
8.5 IU header ---- 76
8.5.1 IU header format ---- 76
8.5.2 Information-unit identifier ---- 76
8.5.3 Device-header flags ---- 78
8.5.4 CCW number ---- 80
8.5.5 Token ---- 82
8.6 Device information block (DIB) structure ---- 83
8.6.1 DIB structure overview ---- 83
8.6.2 DIB header ---- 83
8.6.3 Longitudinal-Redundancy-Check field ---- 84
8.6.4 DIB data field ---- 84
8.6.5 Cyclic-Redundancy-Check field ---- 85
8.7 Command DIB structure ---- 87
8.7.1 Command DIB overview ---- 87
8.7.2 Command header ---- 87
8.8 Command-Data DIB Structure ---- 93
8.9 Data DIB structure ---- 93
8.9.1 Data DIB overview ---- 93
8.9.2 Data Header ---- 94
8.10 Status DIB ---- 94
8.10.1 Status DIB processing ---- 94
8.10.2 Status DIB structure ---- 96
8.10.3 Status header ---- 97
8.10.4 Supplemental Status Field ---- 108
8.11 Control DIB structure ---- 110
8.11.1 Control DIB structure overview ---- 110
8.11.2 Control header ---- 110

8.12 Link-Control DIB structure ---- 121
8.12.1 Link-Control DIB structure overview ---- 121
8.12.2 Link header ---- 122
8.12.3 Link payload ---- 123

9 Device-Level functions and protocols ---- 124
9.1 Device-Level operations ---- 124
9.1.1 Overview of Device-Level operations ---- 124
9.1.2 Channel program execution ---- 124
9.1.3 Initiating an I/O operation ---- 124
9.1.4 Data-Transfer protocol ---- 127
9.1.5 Ending an I/O operation ---- 133
9.1.6 Command chaining ---- 136
9.2 Device-Level controls ---- 137
9.2.1 Overview of Device-Level control functions ---- 137
9.2.2 Stacking Status Function ---- 138
9.2.3 Cancel function ---- 139
9.2.4 System-Reset function ---- 141
9.2.5 Selective-Reset function ---- 142
9.2.6 Request-Status function ---- 144
9.2.7 Device-Level-Exception function ---- 145
9.2.8 Status-Acceptance function ---- 145
9.2.9 Device-Level-Acknowledgment function ---- 146
9.2.10 Control-Unit-Busy condition ---- 146
9.3 Error handling at the device level ---- 146
9.3.1 Purge path function ---- 146
9.3.2 Command retry ---- 147
9.3.3 Channel-Initiated recovery procedures ---- 149
9.3.4 Address-Exception condition ---- 153
9.4 Resetting event ---- 153
9.5 Special functions ---- 155
9.5.1 Path groups ---- 155
9.5.2 Dynamic reconnection ---- 155

10 Link error detection ---- 157
10.1 Link error detection overview ---- 157
10.2 SB-2 Timeouts ---- 157
10.2.1 Overview of SB-2 timeouts ---- 157
10.2.2 SB-2 Protocol time-out value ---- 157
10.2.3 SB-2 time-out value ---- 158
10.2.4 Logical path time-out value ---- 158
10.2.5 Cancel function timeout ---- 159
10.3 SB-2 link failure ---- 159
10.4 Logical path timeout error ---- 159
10.5 SB-2 exchange error ---- 159
10.5.1 SB-2 exchange error overview ---- 159
10.5.2 SB-2 protocol timeout ---- 159
10.5.3 SB-2 IU integrity error ---- 159
10.5.4 SB-2 protocol errors ---- 160
10.5.5 Receive ABTS ---- 161
10.5.6 Cancel function timeout error ---- 161

10.5.7 Abnormal termination of exchange ---- 161
10.6 Logical-Path-Not-Established error ---- 161
10.7 Test initialization result error ---- 161

11 Error recovery actions ---- 163
11.1 Error recovery action overview ---- 163
11.2 Link-Level recovery ---- 164
11.2.1 Link-Level recovery overview ---- 164
11.2.2 Recovery for an SB-2 link failure ---- 165
11.2.3 Logical path timeout error ---- 165
11.2.4 Recovery for an SB-2 offline condition ---- 165
11.2.5 Recovery for an FC-PH link failure condition ---- 166
11.2.6 Recovery for an SB-2 exchange error ---- 166
11.2.7 Recovery for a Logical-Path-Not-Established error ---- 167
11.2.8 Recovery for Link-Level Reject, P_RJT and F_RJT ---- 167
11.2.9 Recovery for a Test-Initialization-Result error ---- 168
11.3 Device-Level recovery ---- 169
11.3.1 Device-Level recovery overview ---- 169
11.3.2 Errors that cause the removal of a logical path ---- 169
11.3.3 Errors that do not cause the removal of a logical path ---- 170

Annex A (informative) Fabric address assignment ... 173
A.1 Background ... 173
A.2 Description ... 173

Annex B (informative) Correlation of exchanges of an exchange pair ... 174
B.1 Correlation of exchanges ... 174

Annex C (normative) LRC calculation ... 175
C.1 LRC calculation procedure ... 175
C.2 LRC calculation example ... 175

Annex D (normative) Status/chaining summary ... 177
D.1 Requirements for sending status and chaining ... 177

Bibliography ... 178

Index ... 179

Tables

Table 1 – Information categories of SB-2 IUs 33
Table 2 – SB-2 specific Link-Incident Record 43
Table 3 – Incident-Specific Information 46
Table 4 – Summary of link-control request and response IUs 49
Table 5 – Logical path field 56
Table 6 – Characteristics of IUs sent by a channel 71
Table 7 – Characteristics of IUs Sent by a Control Unit 72
Table 8 – DIB-type settings 77
Table 9 – EE-bit table 80
Table 10 – Contents of the command field 88
Table 11 – Required Commands 88
Table 12 – LRI and RV bit usage 99
Table 13 – Status byte 100
Table 14 – QTF/QTU relationship 104
Table 15 – DTF/DTU relationship 107
Table 16 – Bits 0 - 5 of Sense-data byte 0 110
Table 17 – Summary of Device-Level control functions 111
Table 18 – Summary of control IUs 113
Table 19 – Interpretation of the RO and RU bits 118
Table 20 – Exception code assignments 119
Table 21 – Permitted responses to a Selective-Reset IU 150
Table C.1 – Headers of IU 175
Table C.2 – LRC Calculation Example 176
Table D.1 – Status/will 177

Figures

Figure 1 – Document relationship . . . 10
Figure 2 – FC-PH and SB-2 bit numbering conventions . . . 17
Figure 3 – Channel images . . . 20
Figure 4 – Control unit images . . . 22
Figure 5 – Point-to-point channel-path configuration (single logical image) . . . 23
Figure 6 – Point-to-point channel-path configuration (multiple logical images) . . . 23
Figure 7 – Fabric channel-path configuration (multiple channel images) . . . 24
Figure 8 – Fabric channel-path configuration (multiple channel images, CTC connection) . . . 26
Figure 9 – Relationships among link level, device level, physical path, and logical path . . . 27
Figure 10 – Contents of the node descriptor . . . 40
Figure 11 – Link-control information field of the LRJ IU . . . 58
Figure 12 – IU payload structures . . . 74
Figure 13 – SB-2 header . . . 75
Figure 14 – IU header . . . 76
Figure 15 – IU identifier . . . 76
Figure 16 – Device-header flags . . . 78
Figure 17 – Basic DIB structure . . . 83
Figure 18 – DIB header structure . . . 83
Figure 19 – DIB data field . . . 84
Figure 20 – Addends of the alternative initialized value of the CRC generator . . . 86
Figure 21 – Command header . . . 87
Figure 22 – CCW control flag field . . . 89
Figure 23 – Command-flag field . . . 91
Figure 24 – Data header . . . 94
Figure 25 – Status header . . . 97
Figure 26 – Status-flag field . . . 97
Figure 27 – Queue-time parameter (QTP) format . . . 104
Figure 28 – Queue-time parameter example . . . 105
Figure 29 – Defer time parameter format . . . 106
Figure 30 – Defer-time parameter example . . . 108
Figure 31 – Control header . . . 110
Figure 32 – Control-parameter field for the selective-reset IU . . . 116
Figure 33 – Control-parameter field for the device-level exception IU . . . 119
Figure 34 – Link header . . . 122
Figure 35 – Link-control field . . . 122
Figure 36 – Link error detection . . . 157
Figure 37 – Recovery actions for the channel and control units . . . 164