

ISO/IEC 14165-222 :2005-06 (E)

Information technology_ - Fibre Channel_ - Part_222: Single-byte command sets-2 mapping protocol (FC-SB-2)

- Foreword 9
- Introduction 10
- 1 Scope** 12
- 2 Normative references** 13
 - 2.1 General information concerning references 13
 - 2.2 Approved references 13
 - 2.3 References under development 13
- 3 Definitions and conventions** 14
 - 3.1 Definitions 14
 - 3.2 Keywords 15
 - 3.3 Conventions 16
 - 3.3.1 English usage conventions 16
 - 3.3.2 FC-PH 17
 - 3.3.3 Bit numbering 17
 - 3.3.4 Binary notation 17
 - 3.3.5 Hexadecimal notation 17
 - 3.3.6 Abbreviations, acronyms and symbols 17
- 4 Structure and concepts** 19
 - 4.1 Introduction 19
 - 4.2 FC-4 General description 19
 - 4.3 SB-2 overview 19
 - 4.3.1 SB-2 instance 19
 - 4.3.2 SB-2 protocols 19
 - 4.4 Channel-path elements 20
 - 4.4.1 Overview of channel-path elements 20
 - 4.4.2 Channel 20
 - 4.4.3 Channel image 20
 - 4.4.4 Control unit 21
 - 4.4.5 Control-unit image 21
 - 4.4.6 Link 22
 - 4.5 Channel-path configurations 22
 - 4.5.1 Channel-path configuration overview 22
 - 4.5.2 Point-to-point configuration 22
 - 4.5.3 Fabric configuration 23
 - 4.5.4 Physical path 24
 - 4.5.5 Logical path 25
 - 4.5.6 Channel-to-channel communication 25
 - 4.6 Information transfer 26
 - 4.7 Protocols 27
 - 4.7.1 Protocol overview 27
 - 4.7.2 Link level 27
 - 4.7.3 Device level 28
 - 4.7.4 Addressing 28
- 5 FC-PH Link Control** 30
 - 5.1 FC-PH Link control overview 30

5.2	Class of service	30
5.3	Buffer-to-buffer credit reclamation	30
5.4	SB-2 Sequences and exchanges	31
5.4.1	SB-2 sequences	31
5.4.2	SB-2 exchange pairs	31
5.5	FC-PH frame header fields	33
5.5.1	Frame header field overview	33
5.5.2	R_CTL field	33
5.5.3	D_ID and S_ID fields	33
5.5.4	CS_CTL	34
5.5.5	TYPE field	34
5.5.6	F_CTL field	34
5.5.7	SEQ_ID	34
5.5.8	DF_CTL	34
5.5.9	SEQ_CNT	34
5.5.10	OX_ID	34
5.5.11	RX_ID	34
5.5.12	Parameter field	35
5.6	Other FC-PH mechanisms	35
6	Link-Level functions	36
6.1	Link-level function overview	36
6.2	FC-PH Basic-link-services	36
6.2.1	Abort sequence	36
6.3	FC-PH Extended link services	36
6.3.1	F_Port login	36
6.3.2	N_Port login	36
6.3.3	N_Port logout	37
6.3.4	Reinstate recovery qualifier	37
6.3.5	Registered state change notification	37
6.3.6	State-change registration	38
6.3.7	Request Node-Identification Data	39
6.3.8	Registered Link-Incident Record	43
6.3.9	Registered Link-Incident Record requests and responses	43
6.3.10	Link-Incident-Record Registration	47
6.4	SB-2 Link-control functions	47
6.4.1	SB-2 Link-control function overview	47
6.4.2	Establish logical path	49
6.4.3	Remove logical path	52
6.4.4	Logical path established	52
6.4.5	Logical path removed	53
6.4.6	Link-level acknowledgment	54
6.4.7	Test initialization	55
6.4.8	Test initialization result	56
6.4.9	Link-level reject	57
6.4.10	Link-level busy	58
7	N_Port link initialization	60
7.1	N_Port link initialization overview	60
7.2	Link-initialization procedure	61
7.3	Initialization process for a channel	62

7.3.1	Channel initialization overview	62
7.3.2	Channel login	62
7.3.3	Channel Node-Identifier acquisition	63
7.3.4	Channel state-change registration	64
7.3.5	Channel Link-Incident-Record registration	64
7.3.6	Channel Logical-Path establishment	65
7.4	Initialization process for a control unit	66
7.4.1	Control unit initialization overview	66
7.4.2	Control-unit login	66
7.4.3	Control unit node-identifier acquisition	67
7.4.4	Control unit State-Change registration	69
7.4.5	Control unit logical-path establishment	69
8	SB-2 Information units	71
8.1	SB-2 Information unit overview	71
8.2	Rules for sending SB-2 IUs	71
8.2.1	Overview of rules for sending SB-2 information units	71
8.2.2	Rules for device-level functions	72
8.3	SB-2 IU structure	73
8.4	SB-2 header	75
8.4.1	SB-2 header format	75
8.4.2	Channel image ID	75
8.4.3	Control-unit image ID	75
8.4.4	Device address	75
8.5	IU header	76
8.5.1	IU header format	76
8.5.2	Information-unit identifier	76
8.5.3	Device-header flags	78
8.5.4	CCW number	80
8.5.5	Token	82
8.6	Device information block (DIB) structure	83
8.6.1	DIB structure overview	83
8.6.2	DIB header	83
8.6.3	Longitudinal-Redundancy-Check field	84
8.6.4	DIB data field	84
8.6.5	Cyclic-Redundancy-Check field	85
8.7	Command DIB structure	87
8.7.1	Command DIB overview	87
8.7.2	Command header	87
8.8	Command-Data DIB Structure	93
8.9	Data DIB structure	93
8.9.1	Data DIB overview	93
8.9.2	Data Header	94
8.10	Status DIB	94
8.10.1	Status DIB processing	94
8.10.2	Status DIB structure	96
8.10.3	Status header	97
8.10.4	Supplemental Status Field	108
8.11	Control DIB structure	110
8.11.1	Control DIB structure overview	110
8.11.2	Control header	110

8.12	Link-Control DIB structure	121
8.12.1	Link-Control DIB structure overview	121
8.12.2	Link header	122
8.12.3	Link payload	123
9	Device-Level functions and protocols	124
9.1	Device-Level operations	124
9.1.1	Overview of Device-Level operations	124
9.1.2	Channel program execution	124
9.1.3	Initiating an I/O operation	124
9.1.4	Data-Transfer protocol	127
9.1.5	Ending an I/O operation	133
9.1.6	Command chaining	136
9.2	Device-Level controls	137
9.2.1	Overview of Device-Level control functions	137
9.2.2	Stacking Status Function	138
9.2.3	Cancel function	139
9.2.4	System-Reset function	141
9.2.5	Selective-Reset function	142
9.2.6	Request-Status function	144
9.2.7	Device-Level-Exception function	145
9.2.8	Status-Acceptance function	145
9.2.9	Device-Level-Acknowledgment function	146
9.2.10	Control-Unit-Busy condition	146
9.3	Error handling at the device level	146
9.3.1	Purge path function	146
9.3.2	Command retry	147
9.3.3	Channel-Initiated recovery procedures	149
9.3.4	Address-Exception condition	153
9.4	Resetting event	153
9.5	Special functions	155
9.5.1	Path groups	155
9.5.2	Dynamic reconnection	155
10	Link error detection	157
10.1	Link error detection overview	157
10.2	SB-2 Timeouts	157
10.2.1	Overview of SB-2 timeouts	157
10.2.2	SB-2 Protocol time-out value	157
10.2.3	SB-2 time-out value	158
10.2.4	Logical path time-out value	158
10.2.5	Cancel function timeout	159
10.3	SB-2 link failure	159
10.4	Logical path timeout error	159
10.5	SB-2 exchange error	159
10.5.1	SB-2 exchange error overview	159
10.5.2	SB-2 protocol timeout	159
10.5.3	SB-2 IU integrity error	159
10.5.4	SB-2 protocol errors	160
10.5.5	Receive ABTS	161
10.5.6	Cancel function timeout error	161

10.5.7	Abnormal termination of exchange	161
10.6	Logical-Path-Not-Established error	161
10.7	Test initialization result error	161
11	Error recovery actions	163
11.1	Error recovery action overview	163
11.2	Link-Level recovery	164
11.2.1	Link-Level recovery overview	164
11.2.2	Recovery for an SB-2 link failure	165
11.2.3	Logical path timeout error	165
11.2.4	Recovery for an SB-2 offline condition	165
11.2.5	Recovery for an FC-PH link failure condition	166
11.2.6	Recovery for an SB-2 exchange error	166
11.2.7	Recovery for a Logical-Path-Not-Established error	167
11.2.8	Recovery for Link-Level Reject, P_RJT and F_RJT	167
11.2.9	Recovery for a Test-Initialization-Result error	168
11.3	Device-Level recovery	169
11.3.1	Device-Level recovery overview	169
11.3.2	Errors that cause the removal of a logical path	169
11.3.3	Errors that do not cause the removal of a logical path	170
Annex A	(informative) Fabric address assignment.....	173
A.1	Background	173
A.2	Description	173
Annex B	(informative) Correlation of exchanges of an exchange pair.....	174
B.1	Correlation of exchanges	174
Annex C	(normative) LRC calculation.....	175
C.1	LRC calculation procedure	175
C.2	LRC calculation example	175
Annex D	(normative) Status/chaining summary.....	177
D.1	Requirements for sending status and chaining	177
Bibliography	178
Index	179

Tables

Table 1 – Information categories of SB-2 IUs	33
Table 2 – SB-2 specific Link-Incident Record	43
Table 3 – Incident-Specific Information	46
Table 4 – Summary of link-control request and response IUs	49
Table 5 – Logical path field	56
Table 6 – Characteristics of IUs sent by a channel	71
Table 7 – Characteristics of IUs Sent by a Control Unit	72
Table 8 – DIB-type settings	77
Table 9 – EE-bit table	80
Table 10 – Contents of the command field	88
Table 11 – Required Commands	88
Table 12 – LRI and RV bit usage	99
Table 13 – Status byte	100
Table 14 – QTF/QTU relationship	104
Table 15 – DTF/DTU relationship	107
Table 16 – Bits 0 - 5 of Sense-data byte 0	110
Table 17 – Summary of Device-Level control functions	111
Table 18 – Summary of control IUs	113
Table 19 – Interpretation of the RO and RU bits	118
Table 20 – Exception code assignments	119
Table 21 – Permitted responses to a Selective-Reset IU	150
Table C.1 – Headers of IU	175
Table C.2 – LRC Calculation Example	176
Table D.1 – Status/will	177

Figures

Figure 1 – Document relationship	10
Figure 2 – FC-PH and SB-2 bit numbering conventions	17
Figure 3 – Channel images	20
Figure 4 – Control unit images	22
Figure 5 – Point-to-point channel-path configuration (single logical image)	23
Figure 6 – Point-to-point channel-path configuration (multiple logical images)	23
Figure 7 – Fabric channel-path configuration (multiple channel images)	24
Figure 8 – Fabric channel-path configuration (multiple channel images, CTC connection)	26
Figure 9 – Relationships among link level, device level, physical path, and logical path	27
Figure 10 – Contents of the node descriptor	40
Figure 11 – Link-control information field of the LRJ IU	58
Figure 12 – IU payload structures	74
Figure 13 – SB-2 header	75
Figure 14 – IU header	76
Figure 15 – IU identifier	76
Figure 16 – Device-header flags	78
Figure 17 – Basic DIB structure	83
Figure 18 – DIB header structure	83
Figure 19 – DIB data field	84
Figure 20 – Addends of the alternative initialized value of the CRC generator	86
Figure 21 – Command header	87
Figure 22 – CCW control flag field	89
Figure 23 – Command-flag field	91
Figure 24 – Data header	94
Figure 25 – Status header	97
Figure 26 – Status-flag field	97
Figure 27 – Queue-time parameter (QTP) format	104
Figure 28 – Queue-time parameter example	105
Figure 29 – Defer time parameter format	106
Figure 30 – Defer-time parameter example	108
Figure 31 – Control header	110
Figure 32 – Control-parameter field for the selective-reset IU	116
Figure 33 – Control-parameter field for the device-level exception IU	119
Figure 34 – Link header	122
Figure 35 – Link-control field	122
Figure 36 – Link error detection	157
Figure 37 – Recovery actions for the channel and control units	164