

ISO/IEC 14165-116 :2005-08 (E)

Information technology_ - Fibre channel_ - Part_116: 10_Gigabit Fibre Channel (10GFC)

Contents

FOREWORD	9
INTRODUCTION	10
1 Scope	11
2 Normative references	11
3 Definitions and conventions	12
3.1 Definitions	12
3.2 Editorial Conventions	12
3.2.1 General	12
3.2.2 Hexadecimal notation	12
3.2.3 Transmission rate abbreviations	13
3.2.4 Acronyms and other abbreviations	14
3.2.5 Special symbols	15
3.3 Keywords	15
3.4 Notation	16
3.4.1 State diagram conventions	16
4 Structure and concepts	19
4.1 Overview	19
4.2 10GFC structure	20
4.2.1 FC-3 general description	20
4.2.2 FC-2 general description	20
4.2.3 FC-1 general description	21
4.2.4 FC-0 general description	22
5 Functional characteristics	23
5.1 General characteristics	23
5.2 10GFC physical variant nomenclature	23
6 Optical interface specification	24
6.1 General	24
6.2 850 nm Parallel (4 lane) PMD, type 1200-MX-SN4P-I	24
6.2.1 Overview	24
6.2.2 PMD MDIO function mapping	24
6.2.3 PMD functional specifications	25
6.2.4 Operating ranges	27
6.2.5 PMD to MDI optical specifications for 1200-MX-SN4P-I	27
6.2.6 Optical measurement requirements	30
6.2.7 Environmental specifications	31
6.2.8 Environment	31
6.2.9 PMD labeling requirements	32
6.3 850 nm Serial PMD, type 1200-MX-SN-I	32
6.3.1 General	32
6.3.2 Optical specifications	32
6.3.3 Jitter, measurement and safety specifications	33
6.4 850 nm CWDM (four wavelength) PMD, type 1200-MX-SN4-I	34
6.4.1 Overview	34
6.4.2 Wavelength-division multiplexed-lane assignments	34
6.4.3 Operating ranges	34
6.4.4 Transmitter optical specifications	34
6.4.5 Receive optical specifications	34
6.4.6 Eye Safety	35

6.5	1 310 nm Serial PMD, type 1200-SM-LL-L	36
6.5.1	General	36
6.5.2	Optical specifications	36
6.5.3	Jitter, measurement and safety specifications	36
6.6	1 310 nm CWDM (four wavelength) PMD, type 1200-X-LC4-L	37
6.6.1	General	37
6.6.2	Optical specifications	37
6.6.3	Jitter, measurement and safety specifications	37
7	Optical interface receptacle specification	38
7.1	General	38
7.2	Optical interface connector	38
7.3	Optical receptacle	38
7.4	Optical plug	38
8	Optical interface cable plant specifications	40
8.1	Overview	40
8.2	Fibre optic cable plant model	40
8.2.1	Optical fibre connection	40
8.2.2	Medium dependent interface (MDI)	40
8.3	Characteristics of the fiber optic cabling	41
8.3.1	General	41
8.3.2	Optical fiber and cable	41
8.3.3	Cable plant optical return loss	41
8.3.4	Connectors and splices	41
9	newFC-1 and 10GFC Levels	44
9.1	Definitions and nomenclature	44
9.2	Overview	44
9.3	Byte lane ordering	44
9.4	XGMII control characters and ordered set translation	46
9.4.1	General	46
9.4.2	FC-1 to XGMII translation tables	46
9.4.3	Unsupported FC-1 ordered sets	47
9.4.4	Reserved codes	48
9.4.5	10GFC error character	48
9.5	XAUI idle characters	48
9.6	Ordered set mapping from XGMII to XAUI interface	49
9.7	10GFC Level functions	49
9.7.1	General	49
9.7.2	Ordered set translation	50
9.7.3	Link fault signalling	50
9.7.4	10GFC primitive sequence qualification state diagram	50
9.7.5	XGMII and FC-1 primitive sequence interaction	52
9.8	FC-1 level rules, requirements and functions	52
9.8.1	General	52
9.8.2	FC-1 link fault and error indications	52
9.8.3	FC_Port state machine	53
9.8.4	Arbitrated loop functions	53
9.8.5	Inter-frame gap (IFG) rules	53
9.8.6	XGMII primitive sequence Q rules	54
9.8.7	XGMII primitive signal P rules	55
9.8.8	EOF handling	55
9.8.9	10GFC Errors (/E/)	56
10	10 gigabit media independent interface (XGMII)	57
10.1	General	57

10.2	Overview	57
10.2.1	General	57
10.2.2	XGMII characteristics	57
10.2.3	Rate of operation	57
10.2.4	Byte lane connections	57
10.3	XGMII data stream	58
10.3.1	General	58
10.3.2	Inter-frame gap (IFG)	58
10.3.3	Preamble and start of frame (SOF)	59
10.3.4	Data frame size	59
10.3.5	Data CRC	59
10.3.6	End of frame EOF	59
10.4	XGMII fault Indications	59
11	XGMII extender sublayer (XGXS) and 10 gigabit attachment unit interface (XAUI)	60
11.1	General	60
11.2	XGXS and XAUI rate of operation	60
12	8B/10B physical coding sublayer (PCS) and physical medium attachment (PMA) sublayers	61
12.1	General	61
12.2	Overview	61
12.3	Rate of operation	61
12.4	Ordered set mapping between XGMII and 8B/10B PCS	61
12.4.1	General	61
12.4.2	8B/10B encoding	61
12.4.3	Data skew and multiple clock domain operation	61
12.5	8B/10B PCS to XGMII mapping	62
12.5.1	Reserved codes	62
12.5.2	Invalid characters	62
12.5.3	Terminate T	62
12.5.4	Error /E/	63
12.6	Transmit and Receive state diagrams	63
13	Physical coding sublayer (PCS) for 64B/66B	65
13.1	General	65
13.2	Single lane 64B/66B bit encoding	65
14	10 gigabit sixteen bit interface (XSBI)	66
15	Port management	67
Annex A	(informative) Cable plant employing cross-connects	68
A.1	Characteristics of fiber optic cabling	68
Annex B	(normative) 10GFC to SONET mapping	70
Annex C	(informative) FC-AL-2 to 10GFC mapping	71
C.1	General	71
C.2	Overview	71
C.3	FC-AL-2 mapping	71
C.3.1	General	71
C.3.2	Unsupported FC-1 ordered sets	71
C.4	Concerns about FC-AL-2 operation	71
C.5	Forcing LPSM to Point-to-Point Mode	72
Annex D	(informative) 8B/10B PCS State Diagrams	74

D.1	General	74
D.2	Overview	74
D.3	Transmit source state diagram	74
D.3.1	General	74
D.3.2	Send data state	74
D.3.3	Transmission errors	75
D.3.4	Primitive signal P transmission	75
D.3.5	Primitive sequence Q transmission	75
D.3.6	Idle pattern I generation	75
D.4	PCS receive state diagram	76
D.4.1	General	76
D.4.2	Reception Error	76
D.4.3	Primitive sequence Q and primitive signal P reception	77
D.4.4	Idle pattern reception	80
Annex E (normative) XAUI and 8B/10B PCS test patterns		81
E.1	general	81
E.2	High frequency test pattern	81
E.3	Low frequency test pattern	81
E.4	Mixed frequency test pattern	81
E.5	Continuous jitter test pattern (CJPAT)	81
BIBLIOGRAPHY		84