

ISO/IEC 14165-116 :2005-08 (E)

Information technology_ - Fibre channel_ - Part_116: 10_Gigabit Fibre Channel (10GFC)

Contents

| | |
|--|-----------|
| FOREWORD | 9 |
| INTRODUCTION | 10 |
| 1 Scope | 11 |
| 2 Normative references | 11 |
| 3 Definitions and conventions | 12 |
| 3.1 Definitions | 12 |
| 3.2 Editorial Conventions | 12 |
| 3.2.1 General | 12 |
| 3.2.2 Hexadecimal notation | 12 |
| 3.2.3 Transmission rate abbreviations | 13 |
| 3.2.4 Acronyms and other abbreviations | 14 |
| 3.2.5 Special symbols | 15 |
| 3.3 Keywords | 15 |
| 3.4 Notation | 16 |
| 3.4.1 State diagram conventions | 16 |
| 4 Structure and concepts | 19 |
| 4.1 Overview | 19 |
| 4.2 10GFC structure | 20 |
| 4.2.1 FC-3 general description | 20 |
| 4.2.2 FC-2 general description | 20 |
| 4.2.3 FC-1 general description | 21 |
| 4.2.4 FC-0 general description | 22 |
| 5 Functional characteristics | 23 |
| 5.1 General characteristics | 23 |
| 5.2 10GFC physical variant nomenclature | 23 |
| 6 Optical interface specification | 24 |
| 6.1 General | 24 |
| 6.2 850 nm Parallel (4 lane) PMD, type 1200-MX-SN4P-I | 24 |
| 6.2.1 Overview | 24 |
| 6.2.2 PMD MDIO function mapping | 24 |
| 6.2.3 PMD functional specifications | 25 |
| 6.2.4 Operating ranges | 27 |
| 6.2.5 PMD to MDI optical specifications for 1200-MX-SN4P-I | 27 |
| 6.2.6 Optical measurement requirements | 30 |
| 6.2.7 Environmental specifications | 31 |
| 6.2.8 Environment | 31 |
| 6.2.9 PMD labeling requirements | 32 |
| 6.3 850 nm Serial PMD, type 1200-MX-SN-I | 32 |
| 6.3.1 General | 32 |
| 6.3.2 Optical specifications | 32 |
| 6.3.3 Jitter, measurement and safety specifications | 33 |
| 6.4 850 nm CWDM (four wavelength) PMD, type 1200-MX-SN4-I | 34 |
| 6.4.1 Overview | 34 |
| 6.4.2 Wavelength-division multiplexed-lane assignments | 34 |
| 6.4.3 Operating ranges | 34 |
| 6.4.4 Transmitter optical specifications | 34 |
| 6.4.5 Receive optical specifications | 34 |
| 6.4.6 Eye Safety | 35 |

| | | |
|-----------|--|-----------|
| 6.5 | 1 310 nm Serial PMD, type 1200-SM-LL-L | 36 |
| 6.5.1 | General | 36 |
| 6.5.2 | Optical specifications | 36 |
| 6.5.3 | Jitter, measurement and safety specifications | 36 |
| 6.6 | 1 310 nm CWDM (four wavelength) PMD, type 1200-X-LC4-L | 37 |
| 6.6.1 | General | 37 |
| 6.6.2 | Optical specifications | 37 |
| 6.6.3 | Jitter, measurement and safety specifications | 37 |
| 7 | Optical interface receptacle specification | 38 |
| 7.1 | General | 38 |
| 7.2 | Optical interface connector | 38 |
| 7.3 | Optical receptacle | 38 |
| 7.4 | Optical plug | 38 |
| 8 | Optical interface cable plant specifications | 40 |
| 8.1 | Overview | 40 |
| 8.2 | Fibre optic cable plant model | 40 |
| 8.2.1 | Optical fibre connection | 40 |
| 8.2.2 | Medium dependent interface (MDI) | 40 |
| 8.3 | Characteristics of the fiber optic cabling | 41 |
| 8.3.1 | General | 41 |
| 8.3.2 | Optical fiber and cable | 41 |
| 8.3.3 | Cable plant optical return loss | 41 |
| 8.3.4 | Connectors and splices | 41 |
| 9 | newFC-1 and 10GFC Levels | 44 |
| 9.1 | Definitions and nomenclature | 44 |
| 9.2 | Overview | 44 |
| 9.3 | Byte lane ordering | 44 |
| 9.4 | XGMII control characters and ordered set translation | 46 |
| 9.4.1 | General | 46 |
| 9.4.2 | FC-1 to XGMII translation tables | 46 |
| 9.4.3 | Unsupported FC-1 ordered sets | 47 |
| 9.4.4 | Reserved codes | 48 |
| 9.4.5 | 10GFC error character | 48 |
| 9.5 | XAUI idle characters | 48 |
| 9.6 | Ordered set mapping from XGMII to XAUI interface | 49 |
| 9.7 | 10GFC Level functions | 49 |
| 9.7.1 | General | 49 |
| 9.7.2 | Ordered set translation | 50 |
| 9.7.3 | Link fault signalling | 50 |
| 9.7.4 | 10GFC primitive sequence qualification state diagram | 50 |
| 9.7.5 | XGMII and FC-1 primitive sequence interaction | 52 |
| 9.8 | FC-1 level rules, requirements and functions | 52 |
| 9.8.1 | General | 52 |
| 9.8.2 | FC-1 link fault and error indications | 52 |
| 9.8.3 | FC_Port state machine | 53 |
| 9.8.4 | Arbitrated loop functions | 53 |
| 9.8.5 | Inter-frame gap (IFG) rules | 53 |
| 9.8.6 | XGMII primitive sequence Q rules | 54 |
| 9.8.7 | XGMII primitive signal P rules | 55 |
| 9.8.8 | EOF handling | 55 |
| 9.8.9 | 10GFC Errors (/E/) | 56 |
| 10 | 10 gigabit media independent interface (XGMII) | 57 |
| 10.1 | General | 57 |

| | | |
|----------------|---|-----------|
| 10.2 | Overview | 57 |
| 10.2.1 | General | 57 |
| 10.2.2 | XGMII characteristics | 57 |
| 10.2.3 | Rate of operation | 57 |
| 10.2.4 | Byte lane connections | 57 |
| 10.3 | XGMII data stream | 58 |
| 10.3.1 | General | 58 |
| 10.3.2 | Inter-frame gap (IFG) | 58 |
| 10.3.3 | Preamble and start of frame (SOF) | 59 |
| 10.3.4 | Data frame size | 59 |
| 10.3.5 | Data CRC | 59 |
| 10.3.6 | End of frame EOF | 59 |
| 10.4 | XGMII fault Indications | 59 |
| 11 | XGMII extender sublayer (XGXS) and 10 gigabit attachment unit interface (XAUI) | 60 |
| 11.1 | General | 60 |
| 11.2 | XGXS and XAUI rate of operation | 60 |
| 12 | 8B/10B physical coding sublayer (PCS) and physical medium attachment (PMA) sublayers | 61 |
| 12.1 | General | 61 |
| 12.2 | Overview | 61 |
| 12.3 | Rate of operation | 61 |
| 12.4 | Ordered set mapping between XGMII and 8B/10B PCS | 61 |
| 12.4.1 | General | 61 |
| 12.4.2 | 8B/10B encoding | 61 |
| 12.4.3 | Data skew and multiple clock domain operation | 61 |
| 12.5 | 8B/10B PCS to XGMII mapping | 62 |
| 12.5.1 | Reserved codes | 62 |
| 12.5.2 | Invalid characters | 62 |
| 12.5.3 | Terminate T | 62 |
| 12.5.4 | Error /E/ | 63 |
| 12.6 | Transmit and Receive state diagrams | 63 |
| 13 | Physical coding sublayer (PCS) for 64B/66B | 65 |
| 13.1 | General | 65 |
| 13.2 | Single lane 64B/66B bit encoding | 65 |
| 14 | 10 gigabit sixteen bit interface (XSBI) | 66 |
| 15 | Port management | 67 |
| Annex A | (informative) Cable plant employing cross-connects | 68 |
| A.1 | Characteristics of fiber optic cabling | 68 |
| Annex B | (normative) 10GFC to SONET mapping | 70 |
| Annex C | (informative) FC-AL-2 to 10GFC mapping | 71 |
| C.1 | General | 71 |
| C.2 | Overview | 71 |
| C.3 | FC-AL-2 mapping | 71 |
| C.3.1 | General | 71 |
| C.3.2 | Unsupported FC-1 ordered sets | 71 |
| C.4 | Concerns about FC-AL-2 operation | 71 |
| C.5 | Forcing LPSM to Point-to-Point Mode | 72 |
| Annex D | (informative) 8B/10B PCS State Diagrams | 74 |

| | | |
|--|---|-----------|
| D.1 | General | 74 |
| D.2 | Overview | 74 |
| D.3 | Transmit source state diagram | 74 |
| D.3.1 | General | 74 |
| D.3.2 | Send data state | 74 |
| D.3.3 | Transmission errors | 75 |
| D.3.4 | Primitive signal P transmission | 75 |
| D.3.5 | Primitive sequence Q transmission | 75 |
| D.3.6 | Idle pattern I generation | 75 |
| D.4 | PCS receive state diagram | 76 |
| D.4.1 | General | 76 |
| D.4.2 | Reception Error | 76 |
| D.4.3 | Primitive sequence Q and primitive signal P reception | 77 |
| D.4.4 | Idle pattern reception | 80 |
| Annex E (normative) XAUI and 8B/10B PCS test patterns | | 81 |
| E.1 | general | 81 |
| E.2 | High frequency test pattern | 81 |
| E.3 | Low frequency test pattern | 81 |
| E.4 | Mixed frequency test pattern | 81 |
| E.5 | Continuous jitter test pattern (CJPAT) | 81 |
| BIBLIOGRAPHY | | 84 |