

# ISO 10893-10:2011-04 (E)

Non-destructive testing of steel tubes - Part 10: Automated full peripheral ultrasonic testing of seamless and welded (except submerged arc-welded) steel tubes for the detection of longitudinal and/or transverse imperfections

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>2</b>
<b>4</b>	<b>General requirements .....</b>	<b>3</b>
<b>5</b>	<b>Test method .....</b>	<b>3</b>
<b>6</b>	<b>Reference tube .....</b>	<b>4</b>
<b>6.1</b>	<b>General .....</b>	<b>4</b>
<b>6.2</b>	<b>Types of reference notches .....</b>	<b>4</b>
<b>6.3</b>	<b>Dimensions of reference notches .....</b>	<b>5</b>
<b>7</b>	<b>Equipment calibration and checking .....</b>	<b>6</b>
<b>7.1</b>	<b>General .....</b>	<b>6</b>
<b>7.2</b>	<b>Adjustment of trigger/alarm level .....</b>	<b>6</b>
<b>7.3</b>	<b>Calibration check and recalibration .....</b>	<b>7</b>
<b>8</b>	<b>Acceptance .....</b>	<b>7</b>
<b>9</b>	<b>Test report .....</b>	<b>8</b>
<b>Annex A (normative) Testing on longitudinal imperfections of tubes with a ratio of the specified outside diameter to the average of the specified thickness range less than 5 .....</b>		<b>9</b>
<b>Annex B (normative) Manual/semi-automated testing of untested ends and suspect areas .....</b>		<b>11</b>