

# DIN EN 10228-3:2016-10 (E)

## Non-destructive testing of steel forgings - Part 3: Ultrasonic testing of ferritic or martensitic steel forgings

---

<b>Contents</b>		<b>Page</b>
European foreword .....		4
1	Scope .....	5
2	Normative references .....	5
3	Terms and definitions .....	5
4	Mandatory information .....	6
5	Test procedure .....	6
5.1	General .....	6
5.2	Form .....	6
5.3	Content .....	7
6	Personnel qualification .....	7
7	Equipment and accessories .....	7
7.1	Instrument .....	7
7.2	Probes .....	7
7.2.1	General .....	7
7.2.2	Contouring .....	8
7.2.3	Nominal frequency .....	8
7.2.4	Normal-beam probes .....	8
7.2.5	Angle-beam probes .....	8
7.2.6	Dual-element probes .....	8
7.3	Calibration blocks .....	8
7.4	Reference blocks .....	8
7.5	Couplant .....	8
8	Routine calibration and checking .....	9
9	Stage of manufacture .....	9
10	Surface condition .....	9
10.1	General .....	9
10.2	Surface finish related to quality class .....	9
10.3	As-forged surface condition .....	9
11	Test sensitivity .....	10
11.1	General .....	10
11.2	Normal-beam probes .....	10
11.3	Angle-beam probes .....	10
11.4	Repeat testing .....	10
12	Scanning .....	10
12.1	General .....	10
12.2	Complex forgings .....	11
12.3	Grid scanning coverage .....	11
12.4	100 % scanning coverage .....	11
12.5	Scanning speed .....	11

<b>13</b>	<b>Classification .....</b>	<b>14</b>
<b>13.1</b>	<b>Classification of indications .....</b>	<b>14</b>
<b>13.2</b>	<b>Classification of discontinuities .....</b>	<b>16</b>
<b>14</b>	<b>Recording levels and acceptance criteria .....</b>	<b>18</b>
<b>15</b>	<b>Sizing .....</b>	<b>20</b>
<b>16</b>	<b>Test report .....</b>	<b>20</b>
<b>Annex A (informative)</b>	<b>Maximum testable depth and corresponding beam path range for circumferential angle beam scans .....</b>	<b>22</b>
<b>Annex B (informative)</b>	<b>Amplitude of indication in dB relative to % DAC .....</b>	<b>23</b>