

DIN EN ISO 15630-1:2019-05 (E)

Steel for the reinforcement and prestressing of concrete - Test methods - Part 1: Reinforcing bars, rods and wire (ISO 15630-1:2019)

| Contents | Page |
|--|------|
| European foreword | 4 |
| Foreword | 5 |
| Introduction | 6 |
| 1 Scope | 7 |
| 2 Normative references | 7 |
| 3 Terms, definitions and symbols | 7 |
| 4 General provisions concerning test pieces | 9 |
| 5 Tensile test at room temperature | 10 |
| 5.1 Test piece | 10 |
| 5.2 Test equipment | 10 |
| 5.3 Test procedure | 10 |
| 6 Bend test | 11 |
| 6.1 Test piece | 11 |
| 6.2 Test equipment | 12 |
| 6.3 Test procedure | 12 |
| 6.4 Interpretation of test results | 12 |
| 7 Rebend test | 13 |
| 7.1 Test piece | 13 |
| 7.2 Test equipment | 13 |
| 7.2.1 Bending device | 13 |
| 7.2.2 Rebending device | 13 |
| 7.3 Test procedure | 13 |
| 7.3.1 General | 13 |
| 7.3.2 Bending | 14 |
| 7.3.3 Artificial ageing | 14 |
| 7.3.4 Rebending | 14 |
| 7.4 Interpretation of test results | 14 |
| 8 Axial force fatigue test | 15 |
| 8.1 Principle of test | 15 |
| 8.2 Test piece | 15 |
| 8.3 Test equipment | 15 |
| 8.4 Test procedure | 16 |
| 8.4.1 Provisions concerning the test piece | 16 |
| 8.4.2 Upper force (F_{up}) and force range (F_r) | 16 |
| 8.4.3 Stability of force and frequency | 16 |
| 8.4.4 Counting of force cycles | 16 |
| 8.4.5 Frequency | 16 |
| 8.4.6 Temperature | 16 |
| 8.4.7 Validity of the test | 16 |
| 9 Chemical analysis | 16 |

| | | |
|---|---|-----------|
| 10 | Measurement of the geometrical characteristics | 17 |
| 10.1 | Test piece | 17 |
| 10.2 | Test equipment | 17 |
| 10.3 | Test procedure | 17 |
| 10.3.1 | Heights of transverse ribs or depths of indentations | 17 |
| 10.3.2 | Height of longitudinal ribs (a') | 18 |
| 10.3.3 | Transverse rib or indentation spacing (c) | 18 |
| 10.3.4 | Pitch (P) | 18 |
| 10.3.5 | Part of the circumference without ribs or indentations (Σe_i) | 18 |
| 10.3.6 | Transverse rib or indentation angle (β) | 18 |
| 10.3.7 | Transverse rib flank inclination (α) | 18 |
| 10.3.8 | Width of transverse rib or width of indentation (b) | 19 |
| 11 | Determination of the relative rib or indentation area (f_R or f_P) | 20 |
| 11.1 | General | 20 |
| 11.2 | Measurements | 20 |
| 11.3 | Calculation of f_R | 20 |
| 11.3.1 | Relative rib area | 20 |
| 11.3.2 | Simplified formulae | 20 |
| 11.3.3 | Formula used for the calculation of f_R | 21 |
| 11.4 | Calculation of f_P | 21 |
| 11.4.1 | Relative indentation area | 21 |
| 11.4.2 | Simplified formulae | 22 |
| 11.4.3 | Formula used for the calculation of f_P | 23 |
| 12 | Determination of deviation from nominal mass per metre | 23 |
| 12.1 | Test piece | 23 |
| 12.2 | Accuracy of measurement | 23 |
| 12.3 | Test procedure | 23 |
| 13 | Specialized tests | 23 |
| 13.1 | Tensile test at elevated temperature | 23 |
| 13.1.1 | General | 23 |
| 13.1.2 | Test piece | 23 |
| 13.1.3 | Test equipment | 23 |
| 13.1.4 | Test procedure | 24 |
| 13.2 | Tensile test at low temperature | 24 |
| 13.2.1 | General | 24 |
| 13.2.2 | Test piece | 24 |
| 13.2.3 | Test equipment | 24 |
| 13.2.4 | Test procedure | 24 |
| 13.3 | Cyclic inelastic load test | 24 |
| 13.3.1 | Principle of the test | 24 |
| 13.3.2 | Test piece | 25 |
| 13.3.3 | Test equipment | 25 |
| 13.3.4 | Test procedure | 25 |
| 14 | Test report | 26 |
| Annex A (informative) Options for agreement between the parties involved | | 27 |
| Bibliography | | 28 |